


GOODSON

Tools and Supplies for Engine Builders



*Celebrating the past and the
future of Goodson*

80 years

CARBIDE CUTTERS

CYLINDER HEAD SUPPLIES



fijntechiek **f**ijnaart b.v.
Machines voor motoren revisie,
honen en ultrasoonreinen

Service makes the difference!

Blaaksedijk 30 | 4793 RN Fijnaart | Nederland
tel. +31 (0)168 46 44 61 info@ftf.nl www.ftfmachines.com

2025

www.goodson.com • 1-800-533-8010

HONING STONES

TEEL STAMPS, LETTERS, NUMERALS

From The President's Desk

The image of the original GOODSON building located in Dallas Texas in the 1940's is displayed on our catalog cover. Our back cover shows our GOODSON team, pictured in front of our current location in Winona Minnesota. A lot has changed over the past 80 years, but as the quote from Alphonse Karr goes, "the more things change, the more they stay the same."

For 80 years GOODSON has continually invested in ways to better serve our valued customers. This includes upgrades to our website and technology to allow you to quickly place an order using your computer, tablet or smartphone. But if you choose to order using "old school" methods, call our toll-free phone number and a real, live person will answer the telephone and assist you with your tool and supply needs!

At **GOODSON**, we won't judge you on how you want to do business, because as employee-owners, we are here to service your engine rebuilding tool and supply needs, no matter the method. That will never change along with our tried-and-true **GOODSON** commitment to our customers:



*Roger Schumacher,
Goodson President*

- Top notch customer service
- Same-day shipping
- Iron-Clad Guarantee
- Goodson Techxperts at your service
- Full Service ... Fast!

GOODSON looks forward to celebrating our 80th anniversary in 2025 with each of you because we know that we couldn't have made it 80 years without you!

Thank you for your business!

Do You Have An Idea For The Next Great Product?

Many of the ideas for our most successful new products come directly from you, the guys in the shop. You work in this industry and have come up with some creative solutions to everyday problems. A great case in point is the Lifter Buddy on page 2.

Contact me, Richard Orlikowski, and give me a call to learn more about how you can have Goodson produce and market your new product idea.



*Richard Orlikowski,
Goodson Product Manager*



GOODSON Ironclad Guarantee

Goodson won't risk losing your business for any reason. If you're not 100% satisfied with

your purchase, we'll fix it, exchange it or credit your account for the purchase price.

To send an item back, just include a note detailing the reason for the return and ship it back, freight pre-paid within 30 days. The only time we can't honor this guarantee is if a tool has been damaged through misuse or modification. All abrasives have a shelf life so we can only guarantee them for one year from the original purchase date.

Contact Us



fijntechniek **f**ijnaart b.v.
Machines voor motoren revisie,
honen en ultrasoonreinigen

Service makes the difference!

Blaaksedijk 30 | 4793 RN Fijnaart | Nederland
tel. +31 (0)168 46 44 61 info@ftf.nl www.ftfmachines.com

Please note that the Goodson offices will be closed in observance of these 2025 holidays: New Year's Day (January 1), Easter (April 18), Memorial Day (May 26), Independence Day (July 4), Labor Day (September 1), Thanksgiving (November 27 & 28), Christmas (December 24 & 25) and New Year's Eve (December 31).

We're always open on the web!


Web: www.goodson.com

Email: orderdesk@goodson.com

New for 2025!

Main Cap Pullers for Coyote, Hemi & LS

new



- Designed to remove main bearing caps quickly and efficiently
- Requires little to no effort!
- Slide the dowels under the caps with one swift downward motion of the handles, now your main cap is loosened for easy removal
- Made using the highest quality materials

Description	Order No.
Main Cap Puller - Coyote	MCP-COYOTE
Main Cap Puller - Hemi	MCP-HEMI
Main Cap Puller - LS	MCP-LS

New Size!



Sunnen SGM Ball Head

- Fits .389 Pilot
- Channel Measures .500"
- For use with the following Tip Holders: SGM-1999, SGM-2000, SGM-2001, SGM-2002
- Tip holders are new for 2025!



Description	Order No.
Sunnen SGM Ball Head .389	3D-BHSGM
3D Tip Holder for Sunnen, Micro	SGM-1999
	SGM-2000
3D Tip Holders, Sunnen Style	SGM-2001
	SGM-2002

Manual Valve Spring Compressor Bench

- Same, great features of the CF-500
- 26"L x 34"W x 35"H footprint
- Locking collar can be used to stop vertical travel or to keep the spring compressed while assembling keepers
- Frame tilts up to 25° in either direction for working on canted valves
- Full cylinder head support is adjustable from 0 to 45°

Order No. CF-700

CYLINDER HEAD REBUILDING
CLEANING, ASSEMBLY & SAFETY
SHORT BLOCK REBUILDING
CRANKSHAFT/ FLYWHEEL GRINDING
MISCELLANEOUS TOOLS & SUPPLIES
BRAKE SERVICE TOOLING
MEASURING TOOLS
V-TWIN & METRIC HARD PARTS

New for 2025!


made in
America

Introducing: The Lifter Buddy!

Assure Quality of Lifters using the Lifter Buddy!

- Lifters have become a quality concern for Engine Builders
- Poor quality or the lifter clogged with dirt and debris could result in the lifter not pumping - leading to the engine needing to be disassembled
- Save time by testing lifters with the Lifter Buddy before final assembly



← Oils the lifter body

← Oils the wheel/roller

- Attach Lifter Buddy to pre-lube tank or other pressurized oiling system
- Requires 10-15 psi to push oil through
- Pumps clean oil into and out of lifter
- Allows for clear monitoring if there is any debris or dirt present
- The Lifter Buddy removes the air and replaces with clean engine oil
- Extricates air and lubricates all in one
- Made of durable, heavy duty material
- Fast and simple to use



**Order No.
LB-GM**

RAPIDEX

A rapid-use index of product categories

Cylinder Head Rebuilding

Pilots.....	4-6
Valve Seat Work.....	7-25
Valve Refacing	26-30
Reamers	31-32
Valve Guide Resizing	33-35
Valve Guide Replacement.....	36-40
Valve Seal Work.....	41
Valve Spring Work.....	42-47
Cylinder Head Resurfacing.....	49-52
Crack Detection & Repair	53-56
Porting & Polishing	58-60

Cleaning, Assembly & Safety

Parts Storage & Organizers.....	61-64
Parts Baskets	64
Wire Wheels & Brushes.....	65-66
Cleaning	67-69
Last Blast Paint & Metal Markers	70
Assembly Lubes	71
Coolants & Lubricants	72-73

Index

Short Block Rebuilding

Boring Bar Tooling & Supplies.....	84-85
Cylinder Honing.....	86-89
Flex-Hones®	90
Rod Honing.....	92
Rod & Piston Work	95-98
Lifter Bore Tooling	100
Camshaft Work.....	101-102

Crankshaft/Flywheel Grinding

Crankshaft Grinding Wheels.....	104-105
Crankshaft Grinding & Polishing.....	108-110
Flywheel Grinding.....	111-113

Miscellaneous Tools

Diamond Dresser Tools.....	114-115
Miscellaneous.....	117

Brake Service Tooling

Brake Tips & Holders.....	118-119
Brake Lathe Silencers	120
Brake Lathe Replacement Parts.....	121-122

Measuring Tools

Straight Edges.....	123
Dial Bore Gauges	125-127
Micrometers.....	126
Calipers & Dial Indicators	129

V-Twin Hard Parts

Valve Springs	130-132
Seats & Seat Inserts.....	133
Valve Guides	134
Replacement Valves.....	135

© Copyright 2025, Goodson Mfg. Co., Inc. All copy and illustrations are copyrighted. Absolutely no mechanical or electronic reproduction or use of any part is allowed without our prior written permission. Goodson reserves the right to correct printing errors. Prices are subject to change without notice.

Policies

See page 82 for more information about these policies.

Pricing:

Prices are subject to change without notice. There is no minimum order. Orders are billed at the prices in effect at the time of shipping. Discounts are not available on select items including Sunnen®, UltraSonic, LLC and QualCast Products.

Shipping:

Goodson typically ships orders the same day they are received. Orders received after 2:00pm (central), on weekends or holidays are shipped the next business day. If your order is lost in shipping, Goodson works with the shipper to provide tracking service. Please inspect all shipments upon receipt and report damage or errors within 48 hours.

Freight:

For orders shipped ground within the USA, you may deduct the freight charges on any **JOBBER** net invoice of \$800 or more if you pay within 30 days of the invoice date. Glass Beads, Steel Shot, Tumbler Media, Machines, Equipment, Bulk Liquids, Cleaning Detergents and Crankwheels are not included. Hazardous Materials, Dangerous Goods & Dimensional Shipping fees may apply on some items.

Terms:

- 1) A 1% discount is given on merchandise if payment is made within 15 days from **invoice** date. This discount applies only to the merchandise amount (not the total amount) on the **invoice** (not a statement). The discount amount is shown in the lower left hand corner of the invoice. This discount does not apply to statement payments and does not apply to credit card orders.
- 2) Balances not paid in full within 30 days are subject to a finance charge of 1.5% per month (18% per year).

Credit & Debit Card Orders:

Goodson accepts MasterCard, Visa, American Express, Discover Card and PayPal. For your security, credit card numbers are **NOT** kept on file. Credit Card and PayPal orders do not qualify for the 1% quick-pay discount.

Check Acceptance:

In the unlikely event that your check is returned for insufficient or held funds, we will debit your checking account electronically for the face amount of the check plus the service fee allowed by your state's law. This allows us to resolve the problem without turning you over to a collection agency and harming your credit rating. The transaction will appear on your bank statement and no one will have to contact you about payment.

Returns:

You may return any item, except special orders, within 60 days. We will do our best to correct any problems or to send a replacement. If an item was damaged through mis-use or modification, Goodson will not accept it as a return. Credits will only be issued after it is determined that the part is resellable or it is deemed defective.

Some Hazardous Materials are Non-returnable due to shipping regulations. See our policies on the last page of the index for more details or call us toll-free at 1-800-533-8010.

ABRASIVES WARRANTY: Abrasives have a shelf life, therefore, all abrasives are warranted against manufacturing defects for 1 year from the date of original purchase.

RESETTING/RESHARPENING SERVICE: Premium Diamonds can be reset and many of our cutting tools, including CBN inserts, FT/VSIA cutters and VN-65C can be resharpened. Send your resets and sharps to **GOODSON Tools & Supplies**, ATTN: Resharps, 156 Galewski Dr. Winona, MN 55987. Be sure to include your customer number.

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING


MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS


V-TWIN & METRIC
HARD PARTS

Solid Tapered Pilots




.297" Solid-Tapered High Speed Steel Pilots

Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.
.1574"	4.00	4.50"	P-1158N	.1779"	4.52	4.50"	P-1178N	.2165"	5.50	4.50"	P-1216N	.2500"	6.35	4.50"	P-1250N	.2810"	7.14	4.50"	P-1281N
.1582"	4.02	4.50"	P-1159N	.1968"	5.00	4.50"	P-1197N	.2362"	6.00	4.50"	P-1236N	.2510"	6.37	4.50"	P-1251N	.3130"	7.95	4.50"	P-1313N
.1771"	4.50	4.50"	P-1177N	.1976"	5.02	4.50"	P-1198N	.2370"	6.02	4.50"	P-1237N	.2598"	6.60	4.50"	P-1260N				




.375" Solid-Tapered High Speed Steel Pilots

Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.
.1771"	4.50	6.00"	P-5177N	.2490"	6.32	6.00"	P-5249N	.2952"	7.50	6.00"	P-5295N	.3417"	8.67	6.50"	P-5341N	.3750"	9.52	7.00"	P-5375N
.1960"	4.98	6.00"	P-5196N	.2500"	6.35	6.00"	P-5250N	.3095"	7.86	6.00"	P-5309N	.3427"	8.70	6.50"	P-5342N	.3760"	9.55	7.00"	P-5376N
.1968"	5.00	6.00"	P-5197N	.2559"	6.50	6.00"	P-5256N	.3105"	7.88	6.00"	P-5310N	.3437"	8.72	6.50"	P-5343N	.3770"	9.57	7.00"	P-5377N
.1976"	5.02	6.00"	P-5198N	.2566"	6.52	6.00"	P-5257N	.3115"	7.91	6.00"	P-5311N	.3447"	8.75	6.50"	P-5344N	.3780"	9.60	7.00"	P-5378N
.2165"	5.50	6.00"	P-5216N	.2598"	6.60	6.00"	P-5260N	.3125"	7.93	6.00"	P-5312N	.3457"	8.78	6.50"	P-5345N	.3790"	9.62	7.00"	P-5379N
.2173"	5.52	6.00"	P-5217N	.2748"	6.98	6.00"	P-5274N	.3135"	7.96	6.00"	P-5313N	.3543"	9.00	6.50"	P-5354N	.3820"	9.70	7.00"	P-5382N
.2185"	5.55	6.00"	P-5218N	.2756"	7.00	6.00"	P-5275N	.3145"	7.98	6.00"	P-5314N	.3551"	9.02	6.50"	P-5355N				
.2354"	5.98	6.00"	P-5235N	.2763"	7.02	6.00"	P-5277N	.3149"	8.00	6.00"	P-5315N	.3587"	9.11	6.50"	P-5358N				
.2362"	6.00	6.00"	P-5236N	.2775"	7.05	6.00"	P-5278N	.3165"	8.03	6.00"	P-5316N	.3730"	9.47	7.00"	P-5373N	Inch	mm	OAL	Order No.
.2370"	6.02	6.00"	P-5237N	.2792"	7.09	6.00"	P-5279N	.3407	8.65	6.50"	P-5340N	.3740"	9.49	7.00"	P-5374N	.5000"	12.70	7.75"	P-5500N



.385" Solid-Tapered High Speed Steel Pilots

Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.
.2165"	5.50	7.50"	P-5216S	.2598"	6.60	7.50"	P-5260S	.3125"	7.94	7.50"	P-5312S	.3420"	8.68	7.50"	P-5342S	.3580"	9.09	7.50"	P-5358S
.2173"	5.52	7.50"	P-5217S	.2744"	6.97	7.50"	P-5274S	.3130"	7.95	7.50"	P-5313S	.3430"	8.71	7.50"	P-5343S	.3730"	9.47	7.50"	P-5373S
.2350"	5.97	7.50"	P-5235S	.2755"	7.00	7.50"	P-5275S	.3141"	7.98	7.50"	P-5314S	.3440"	8.73	7.50"	P-5344S	.3740"	9.50	7.50"	P-5374S
.2362"	6.00	7.50"	P-5236S	.2762"	7.02	7.50"	P-5276S	.3149"	8.00	7.50"	P-5315S	.3450"	8.76	7.50"	P-5345S	.3750"	9.53	7.50"	P-5375S
.2370"	6.02	7.50"	P-5237S	.2771"	7.04	7.50"	P-5277S	.3161"	8.03	7.50"	P-5316S	.3543"	9.00	7.50"	P-5354S	.3760"	9.55	7.50"	P-5376S
.2381"	6.05	7.50"	P-5238S	.2779"	7.06	7.50"	P-5278S	.3170"	8.05	7.50"	P-5317S	.3550"	9.02	7.50"	P-5355S				
.2500"	6.35	7.50"	P-5250S	.3100"	7.87	7.50"	P-5310S	.3410"	8.66	7.50"	P-5341S	.3560"	9.04	7.50"	P-5356S				





.437" Solid-Tapered High Speed Steel Pilots

Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.
.2165"	5.50	6.75"	P-5216K	.2381"	6.05	6.75"	P-5238K	.3115"	7.90	6.75"	P-5311K	.3150"	8.00	6.75"	P-5315K	.3440"	8.74	6.75"	P-5344K
.2185"	5.55	6.75"	P-5218K	.2755"	7.00	6.75"	P-5275K	.3125"	7.94	6.75"	P-5312K	.3157"	8.02	6.75"	P-5316K	.3457"	8.78	6.75"	P-5345K
.2362"	6.00	6.75"	P-5236K	.2763"	7.02	6.75"	P-5276K	.3135"	7.96	6.75"	P-5313K	.3169"	8.05	6.75"	P-5317K	.3587"	9.09	6.75"	P-5358K
.2370"	6.02	6.75"	P-5237K	.2775"	7.05	6.75"	P-5277K	.3145"	7.98	6.75"	P-5314K	.3427"	8.70	6.75"	P-5342K	.3730"	9.47	6.75"	P-5373K
												.3437"	8.73	6.75"	P-5343K	.3750"	9.52	6.75"	P-5375K



Every Expanding Pilot Comes Complete With A Collet & Expander



.375" Top Expanding Pilots

- Includes Collet & Expander • Expand up to .020" (.51mm)
- High Speed Steel


Size	mm	Range	OAL	Pilot	Collet	Expander
.216"	5.50	.213"-.233"	5.875"	P-5.5MMNX	P-216-COLLET	P-1216-EXP
.236"	6.00	.233"-.253"	5.813"	P-6MMNX	P-6MM-COLLET	P-1236-EXP
.256"	6.50	.253"-.273"	5.875"	P-6.5MMNX	P-65MM-COLLET	P-6.5MM-EXP
.275"	7.00	.272"-.292"	6.250"	P-7MMNX	P-7MM-COLLET	P-7MM-EXP
.312"	7.92	.309"-.329"	6.500"	P-312NX	P-312-COLLET	P-343-EXP
.335"	8.50	.330"-.350"	6.500"	P-8.5MMNX	P-343-COLLET	P-343-EXP
.343"	8.70	.340"-.360"	7.063"	P-343NX	P-343-COLLET	P-343-EXP
.375"	9.50	.372"-.392"	7.000"	P-375NX	P-375-COLLET	P-375-EXP
.393"	10.00	.390"-.410"	6.875"	P-10MMNX	P-10MM-COLLET	P-10MM-EXP
.437"	11.00	.430"-.450"			P-11MM-COLLET	P-11MM-EXP
.472"	12.00	.469"-.489"			P-12MM-COLLET	P-12MM-EXP



.437" Top Expanding Pilots


- Includes Collet & Expander • Expand up to .020" (.51mm)
- High Speed Steel

Size	mm	Range	OAL	Pilot	Collet	Expander
.236"	6.00	.233"-.253"	6.750"	P-6MMKX	P-6MM-COLLET	P-1236-EXP
.275"	7.00	.272"-.292"	7.250"	P-7MMKX	P-7MM-COLLET	P-7MM-EXP
.312"	7.92	.309"-.329"	7.500"	P-312KX	P-312-COLLET	P-343-EXP
.343"	8.70	.340"-.360"	7.563"	P-343KX	P-343-COLLET	P-343-EXP
.375"	9.50	.340"-.360"	7.500"	P-375KX	P-375-COLLET	P-375-EXP
.453"	11.50	.450"-.470"	7.875"	P-453KX	P-11.5MM-COLLET	P-11MM-EXP



Extended Length (7 1/4") .375" Top Solid-Tapered High Speed Steel Pilots

Inch	mm	OAL	Order No.	Inch	mm	OAL	Order No.
.2755"	7.00	7.25"	P-5275NL	.3437"	8.73	7.75"	P-5343NL
.2756"	7.01	7.25"	P-5276NL	.3447"	8.75	7.75"	P-5344NL
.3145"	7.98	7.25"	P-5314NL	.3457"	8.78	7.75"	P-5345NL
.3150"	8.00	7.25"	P-5315NL	.3740"	9.50	7.75"	P-5374NL
.3417"	8.68	7.75"	P-5341NL	.3750"	9.52	7.75"	P-5375NL
.3427"	8.70	7.75"	P-5342NL				



Left: The standard length pilot protrudes beyond the head surface very slightly.
Right: The extended length pilot protrudes further from the head giving your tooling more support for cutting or grinding.

.375" Extended Length Expanding Pilots

- Includes Collet & Expander • Expand up to .020" (.51mm)
- High Speed Steel

Size	mm	Range	OAL	Pilot	Collet	Expander
.3120"	7.92	.309"-.329"	7.750"	P-312NXL	P-312L-COL	P-343-EXP
.3430"	8.71	.340"-.360"	7.750"	P-343NXL	P-343L-COL	P-343-EXP
.3750"	9.52	.372"-.392"	7.813"	P-375NXL	P-375L-COL	P-375-EXP




.385" Top Expanding Pilots

- Includes Collet & Expander • Expand up to .020" (.51mm)
- High Speed Steel

Size	mm	Range	OAL	Pilot	Collet	Expander
.236"	6.00	.233"-.253"	7.375"	P-6MMSX	P-6MM-COLLET	P-1236-EXP
.256"	6.50	.253"-.273"			P-65MM-COLLET	P-6.5MM-EXP
.275"	7.00	.272"-.292"	7.750"	P-7MMSX	P-7MM-COLLET	P-7MM-EXP
.312"	7.92	.309"-.329"	8.000"	P-312SX	P-312-COLLET	P-343-EXP
.343"	8.70	.340"-.360"	8.000"	P-343SX	P-343-COLLET	P-343-EXP
.375"	9.50	.372"-.392"	8.000"	P-375SX	P-375-COLLET	P-375-EXP
.393"	10.00	.390"-.410"	7.875"	P-10MMSX	P-10MM-COLLET	P-10MM-EXP
.406"	10.30	.403"-.423"	8.000"	P-406SX	P-10MM-COLLET	P-10MM-EXP
.437"	11.00	.430"-.450"	8.000"	P-11MMSX	P-11MM-COLLET	P-11MM-EXP
.453"	11.50	.450"-.470"	7.875"	P-453SX	P-12MM-COLLET	P-11MM-EXP
.472"	12.00	.469"-.489"	8.500"	P-12MMSX	P-12MM-COLLET	P-12MM-EXP
.500"	12.70	.497"-.517"	8.438"	P-500SX	P-12MM-COLLET	P-12MM-EXP

Setting your expanding pilot

tech tips
from the techxperts™



- 1 Select an expanding pilot that is the same diameter as the valve guide ID.
- 2 Insert the pilot into the valve guide making sure that the expanding section of the pilot (collet) is completely within the valve guide. The pilot will not center properly and may be damaged if the collet extends outside of the valve guide.
- 3 Pilot shoulder should be about 1/8" above the valve guide.
- 4 Hold the pilot while turning the nut at the opposite end. This will expand the collet and secure the pilot into position.

NOTE: DO NOT use Expanding Pilots with multi-angle valve seat cutting systems (ie: 3-D Fast Cut)

CYLINDER HEAD
REBUILDING

ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Carbide, Dresser & Specialty Pilots

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING


CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS


V-TWIN & METRIC
HARD PARTS



.236" Top Tapered Carbide Pilots

- Less deflection under stress • Due to the brittle nature of carbide we can only warranty carbide pilots for size

Inch	mm	Order No.	Inch	mm	Order No.	Inch	mm	Order No.
.1559"	3.96	PCT-1560M	.1759"	4.47	PCT-1760M	.2560"	6.50	PCT-2560M
.1566"	3.98	PCT-1570M	.1771"	4.50	PCT-1770M	.2570"	6.53	PCT-2570M
.1575"	4.00	PCT-1575M	.1968"	5.00	PCT-1970M	.2578"	6.55	PCT-2580M
.1578"	4.01	PCT-1580M	.2161"	5.49	PCT-2160M	.2763"	7.02	PCT-2765M



.375" Top Tapered Carbide Pilots

- Less deflection under stress • Due to the brittle nature of carbide we can only warranty carbide pilots for size

Inch	mm	Order No.	Inch	mm	Order No.	Inch	mm	Order No.
.1968"	5.00	PCT-1970	.2756"	7.00	PCT-2756	.3150"	8.00	PCT-3150
.2165"	5.50	PCT-2165	.2759"	7.01	PCT-2760	.3433"	8.72	PCT-3430
.2173"	5.52	PCT-2170	.2763"	7.02	PCT-2765	.3440"	8.73	PCT-3440
.2362"	6.00	PCT-2362	.2771"	7.04	PCT-2770	.3740"	9.50	PCT-3740
.2370"	6.02	PCT-2370	.3122"	7.93	PCT-3120			




Valve Seat Wheel Dresser Pilots for Universal & Heavy Duty Wheel Dressing Stands

- All pilots have a .625" bottom • Dressing stands, page 24

Dresser Pilots (select based on stone holder type)

Fits Stone Holder Type	OAL	Order No.
A .437" Hex Stone Holder	5 9/16"	031-1102-89
B .437" Hex or Flex Stone Holder	7 1/4"	031-0202-80
C .385" Top Stone Holder	6"	031-0202-55
D .375" Top Stone Holder	6 3/8"	031-0202-47



Sioux-Style Dresser Stand Pilots & Bushings

- Replacement parts for the popular 1716 Seat Wheel Dresser no longer available from Sioux™
- .375" top pilot features a groove to fit Black & Decker holders • .600" bottom size

Description	Order No.
.385" Top Pilot, .600" Bottom Size	1718A
.375" Top Pilot, .600" Bottom Size	1718-BD
Dressing Stand Bushings (2) for .375" & .385" Pilots	SK-9-10
Dressing Stand Bushings (2) for .572" Pilots	SK-11-12

Specialty Pilots



3/16" Shank Pilots for Valve Guide Top Cutters

Size	Order No.
.312" (7.93mm)	GFP-312
.343" (8.73mm)	GFP-343
.375" (9.53mm)	GFP-375
.437" (11.11mm)	GFP-437
.500" (12.70mm)	GFP-500

See page 34 for Valve Guide Top Cutters



Valve Guide Pilots for Seal & Seat Cutting

Hardened & Ground Pilots		
Guide ID		Order No.
.275"	7.0	VP-7MM
.312"	7.9	VP-312
.343"	8.7	VP-343
.375"	9.5	VP-375


See page 37 and 47 for Applications

Replaceable Pilots for Adjustable Valve Guide Driver

Diameter	Order No.
.312"	AVG-312
.343"	AVG-343
.372"	AVG-372
.437"	AVG-437
5.0mm	AVG-5MM
5.5mm	AVG-55MM

See page 37 and 47 for Applications

3-D Fast Cut™



Holders (3DH-1995 & 3DH-1999M) have been modified to provide support to cutters without interfering with the bowl diameter.

Micro Tips FTM-190 and FTM-82R6B-HP only fit Tip Holder 3DH-1995

3-D Fast Cut™ System Micro Ball Head Tooling

- Fits the same 1" ball head driver as the original 3-D Fast Cut tooling
- See page 5 for .236" Top Pilots

Description	Order No.	
Micro Ball Head Starter Kit	3D-236-KIT	▼
3D Ball Head for .236" / 6mm Pilot (2.56"L)	3D-BH236	X
Micro Cutter Tips 45° / 1.0mm	FTM-185	X
See pg. 9 for profiles 45° / 1.0mm	FTM-187	X
45° / 1.0mm	FTM-188	X
90° (For counterboring)	FTM-190	
82° Radius Cutter	FTM-82R6B-HP	
Tip Holders (incl. .550"-.984" Range FT-SCREW)	3DH-1999M	X
.551"-.850" Range	3DH-1995	
Bounce Springs Short 1.050" / 26.7mm	3D-BS1	X
.340"ID Medium 1.540" / 39.2mm	3D-BS3	X
.420"OD Long 2.550" / 64.8mm	3D-BS2	X
Bounce Spring Bushing (1 pair)	3D-BB1	X
Bounce Spring Spacer 22mm long	3D-BB2	X
3-D Fast Cut™ Accessories		
Replacement 2.5mm Hex Key	3D-2.5	X
Replacement Side Screw M5x8MM	3D-58	
Replacement Base Screw M5x5MM	3D-55	
Cutter Blade Mounting Screw	FT-SCREW	
Blade Wrench	FT-WRENCH	X
Tool Setting Fixture	3D-TSFA	X
Bridgeport / DCM Ball Head Driver	3D-3/4SS	

More levels on page 49

Valve Guide Level

- Graduated vials with satin-chromed, brass protective covers that rotate to close tightly
- Base castings are seasoned, then precision machined and finished on a bearing surface • Replaceable vials
- Adjustable for precise calibration
- 1 division equals .0005" per inch
- Fits pilots from 6mm to .437"



VGL-100
(use with your pilot or find a pilot on page 3)

Description	Order No.	Replacement Vial
4" Valve Guide Level (3" vial)	VGL-100	VGL-101

See www.goodson.com for level calibration instructions



Valve Seat Removal Tooling

- Fits most popular 3-angle cutting tools including our popular 3-D Fast Cut™ System, Kwik-Way, Peterson, Rottler, Serdi, T&S, Winona Van Norman, Newen, etc.
- Use to relieve press fit for easier seat removal
- Requires a minimum of 2 cuts
- For precise set up use the MGA-MIC (below)

- Tip Holders include one cutting tip and mounting screw (see chart below) • Replacements sold separately
- Ball Head and Drive Tools sold separately (see page 8)

Description	Replacement Tip	Order No.
Tip Holders	3DB-1999i	3D-1999C
	3DB-250	3D-2000C
	3DB-250	3D-2001C
	3DB-250	3D-2002C
Wide Body Tip Holders	3DB-250	3D-2003C
	3DB-250	3D-2004C
Replacement Tip	fits 3DB-1999C	3DB-1999i
	fits all BUT 3DB-1999C	3DB-250
Replacement Screw	for 3DB-1999i	3DB-1999S
	for 3DB-250	3DS-SCREW

Cutting Range with Pilot Size				
Holder	.236" Top	.375" Top	.385" Top	.437" Top
3D-1999C	0.960"-1.225"	1.095"-1.360"	1.105"-1.360"	1.157"-1.360"
3D-2000C	1.056"-1.480"	1.194"-1.480"	1.206"-1.480"	1.264"-1.480"
3D-2001C	—	1.376"-2.000"	1.386"-2.000"	1.450"-2.000"
3D-2002C	—	1.524"-2.460"	1.544"-2.460"	1.610"-2.460"
3D-2003C	—	1.680"-2.400"	1.680"-2.400"	—
3D-2004C	—	2.280"-3.200"	2.280"-3.200"	—

.375" Precision Drill Bushing for standard or pilot

MGA-MIC-1S
Precision ground and micro polished stabilized tool steel




MGA-MIC

3-D Fast Cut Setting Micrometer

- Direct reading micrometer accurate to .001"
- Uses tapered .375" Pilot to match your ball head (sold separately)
- Use to set cutting diameter of 90° carbide cutters when modifying counterbores
- Use the optional calibration standard to ensure your micrometer is reading correctly

Description	Cutting Range	Order No.
Standard Micrometer	0.800" - 2.800"	MGA-MIC
Calibration Standard		MGA-MIC-1S




3-D Fast Cut™ Starter Kits

- Can be used with your existing solid taper pilots
- Ball heads are available to fit most common seat grinder pilots
- Choose from over 100 3-angle blade profiles on pages 10-13
- Fully compatible with most popular 3-angle cutting systems including Kwik-Way®, Peterson, Rottler, Serdi, Sunnen®, T&S, Winona Van Norman®, Newen®, etc.
- Use between 50 and 100 RPM • Goodson recommends starting at 60 RPM

Description	Fits Pilot	Order No.	Includes	
Complete Starter Kits	.375" / 9.53mm	3D-375-KIT	▼	
(see page 3 & 5 for pilots)	.385" / 9.78mm	3D-385-KIT	▼	
Ball Head Standard 3.346" long	.375" / 9.53mm	Use with 3D tip holders	3D-BH375	X
	.385" / 9.78mm		3D-BH385	X
	.390" / 9.90mm		3D-BH390	
	.375" / 9.53mm	Use with SGM tip holders	3D-BH-SUN375	
Ball Head Extended Length 3.80" long	.375" / 9.53mm	Use with 3D tip holders	3D-BH375L	
Ball Head Wide Body 4.0625" long	.375" / 9.53mm	Use with 3D tip holders	3D-BH375W	
Serdi-Style Tool Bodies 4" long	Use with Serdi-style pilots			
	Standard .375" / 9.53mm	SER-5100		
	Large Body .375" / 9.53mm	SER-5300		
Sunnen Style Drive Adaptor for VGS-20		3D-SUN		
Tip Holders	.709"-1.181" / 18-30mm Range	3D-2000	X	X
(includes	1.02"-1.653" / 26-42mm Range	3D-2001	X	X
FT-SCREW)	1.575"-2.362" / 40-60mm Range	3D-2002	X	X
Tip Holders-Wide Body	1.575"-2.362" / 40-60mm Range	3D-2003		
	2.385"-3.150" / 58-80mm Range	3D-2004		
Cutters	45° / 1.0mm	FT-45039V1	X	X
	45° / 1.3mm	FT-45051V1	X	X
more on	45° / 1.5mm	FT-45059V1	X	X
pages 8-11	45° / 1.9mm	FT-45075V1	X	X
Tool Setting Fixture - All Steel Construction		3D-TSFA	X	X
Cutter Blade Mounting Screw		FT-SCREW		
Blade Wrench		FT-WRENCH	X	X
Automotive Bounce Spring Set (4pc.)		3D-SS4	X	X
Bushing Set (1 pair)	.375"	3D-DB7		X
	.385"	3D-DB6	X	
Ball Head Driver	#3 Morse Taper Driver	3D-CM3		
	Bridgeport & DCM Driver	3D-3/4SS		
3-D Fast Cut™ Accessories				
Lift Clip for Enhanced Control, especially on Spring Pad Cutters (pg. 12)		3D-CLIP		
Replacement 3.0mm Allen Key		3D-3.0	X	X
Replacement 2.5mm Allen Key		3D-2.5	X	X
Replacement Screws for NWN Ball Head Base (5 Pack) - metric		MGA-4X5MM		
Replacement Base Screw for Standard Ball Heads M5x6MM		3D-56		
Replacement Base Screw for Wide Body Ball Heads M6x6MM		3D-66		
Replacement Side Screw for Standard Ball Heads M6x8MM, Brass Tip		3D-68		
Replacement Side Screw for Wide Body Ball Heads M6x16MM, Brass Tip		3D-615		
Adjusting Screw for Tip Holder #3D-2000, OAL: .395" / 10mm		3D-2000-S		
Adjusting Screw for Tip Holder #3D-2001, OAL: .475" / 12mm		3D-2001-S		
Adjusting Screw for Tip Holder #3D-2002, OAL: .625" / 15.9mm		3D-2002-S		


See page 7 for Valve Seat Removal Tooling for the 3-D Fast Cut™ System



Ball Heads



Watch an overview of the 3-D Fast Cut™ System in our Tech Lab Tuesday video. Scan the code below with your smart phone for quick access




tech tips

Use at 50-100 RPM for best control

3-D Fast Cut™ Ball Head for Sunnen® Tool Holders

- Fits .375" Top pilots
- Channel measures .500"
- Use with insert holders SGM-1045, SGM-1055, SGM-1090 and SGM-1115
- 3.350" long x 1.162" diameter
- Order No. 3D-BH-SUN375

**3-D
FAST
CUT™
SYSTEM**



3-D Fast Cut Adjustable Spring Pad Cutters

- No need to change tooling, just change the tool holder and start cutting spring pads
- Works with all popular 3-angle cutting systems
- Square blades are indexable and replaceable
- Tool holder includes one blade



Tool Holders		
Blade Size	Application	Order No.
3/8" / 9.53mm	All except Sunnen®	SPC-375
1/2" / 12.70mm	All except Sunnen®	SPC-500
Replacement Carbide Cutters (for all holder styles above)		
3/8" / 9.53mm		SPCI-375
1/2" / 12.70mm		SPCI-500
Accessories		
Lift Clip for Enhanced Control		3D-CLIP

Valve Spring Seat Cutters on Page 47



Minnesota Fast Freeze

- Instantly chills seats & guides to -50°F (-45.5°C) • Creates interference fit with heated aluminum heads • Finish seat and guide work faster than ever • Aerosol*
- Use on tight bushings, pins, shafts, etc.
- 10 oz. can

Description	Order No.
Minnesota Fast Freeze	MFF-8

**Hazardous Goods Fees Apply When Shipped by Air*

Press Fit Lubricants

- A light coat eases press fit
- Ideal for valve guides, piston pins, cylinder sleeves, etc.
- Eliminates the scoring, gouging and galling of parts during press fitting

Description	Order No.
Goodson Aerosol 6oz. (170g)	PFL-200*
Sunnen® Aerosol 7oz (198g)	B-200*
Sunnen® Brush Applicator 200mL	B-200L*


**Hazardous Goods Fees Apply When Shipped by Air*



**made in
America**



3-D Fast Cut™ Bowl Profiler

- Machine seats & bowls on a pair of V8 heads in about 40 minutes
- Remove material to contour cylinder head bowl areas and unshroud valves in combustion chambers
- Will not work with Sunnen® Ball Heads



Holder Diameter Range	Order No.
1.25"-1.87" / 32-48mm	NBN-1
1.57"-2.13" / 40-54mm	NBN-2

Blades sold separately



Convert your Sunnen® or Mira® brazed cutters to 3-D with this simple holder

This blade holder allows you to mount premium, replaceable carbide cutters on your existing MIRA® and Sunnen® ball-type tool holders. Choose from our wide selection of replaceable cutters, previously only available for 3-D Fast Cut™ or similar seat cutting systems.

Description	Order No.	
Standard Cutter	Mira®	MGA-3DH
Holders	Sunnen® VSC-Series	SUN-3DH
Mini Cutter	Mira®	MGA-3DH-M
Holders	Sunnen®	SUN-3DH-M
Mini Cutters	30° / 45° / 60°	FT-213B-HP
	32° / 45° / 60°	FT-215B-HP
	30° / 45° / 60°	FT-4028B-HP
	45° / 90°	FT-9020B-HP
view profiles on page 9		
Replacement Screw		FT-SCREW

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS



SABER TOOTH SERIES CUTTER BLADES



**Cutter
Key:**



High Performance Cutter Blades



Add 10 to 20 CFM to Cylinder Heads

Designed to increase airflow by as much as 20 CFM, these cutters are intended for certain applications. Generally you should use intake cutters on intakes and exhaust on exhausts, but as with most things, there's always an exception. Experiment to find the right combination for you and your customers.



Increase Flow & Improve Horsepower

Enlarged to show details



3-Pc. Set High Performance Valve Seat Cutters

- Increase flow & improve horsepower with this set
- Machine your intake seat with IFT-4539B-HP then use cutter IFT-75R6B-HP to machine below the seat and blend into the port
- On exhaust, machine with IFT-4524-HD
- Order No. IFT-HP-SET





3-D Radius Profile Seat Cutter Blades



Diamond Hand Files

- Use for fine touch-up on your Seat Cutter Blades
- Set includes 1-360 grit and 1-600 grit file
- Order No. **DFS-2**

3-D Fast Cut Tool Holder

- Use when sharpening cutter blades to keep the cutter in the correct position
- Order No. **3D-HOLDER**




Custom Cutter Blades Are Easy!

- 1 Download the Goodson Custom Formtool Profile Form from our website (scan the code at right with the camera on your smart phone or other smart device) or call to have us send a copy.
 - 2 Complete the form, including a drawing of the cutter you need. Be sure to include all angles, radii, seat widths, etc. Missing information will delay your cutter or result in an incorrect profile.
 - 3 Send the completed form to Goodson.
- Fax: 888-466-3909 or
E-mail: orderdesk@goodson.com. We'll get a blueprint made which you must approve before we start production.




Cutter Key:


- I** Intake
- E** Exhaust
- S** Specialty




I FT-5043A-HD




I FT-4247A-HD




I FT-068B-HP




I FT-069B-HP




I FT-5118A-HP




I FT-5119A-HP




E FT-003B-HP




E FT-004B-HP




E FT-005B-HP




E FT-5120A-HP




S FT-002B-HP




S FT-033B-HP




S FT-077B-HP




S FT-084B-HP




S FT-085B-HP




S FT-5121A-HP




S FT-213B-HP




S FT-215B-HP




S FT-4028B-HP




S FT-9020B-HP




S FTM-185




S FTM-187



S FTM-188



S FTM-190



S FTM-82R6B-HP

Micro Blades
Work with holders
on pages 7 & 8

CYLINDER HEAD REBUILDING
CLEANING, ASSEMBLY & SAFETY
SHORT BLOCK REBUILDING
CRANKSHAFT/ FLYWHEEL GRINDING
MISCELLANEOUS TOOLS & SUPPLIES
BRAKE SERVICE TOOLING
MEASURING TOOLS
V-TWIN & METRIC HARD PARTS



SABER TOOTH
SERIES CUTTER BLADES

3-D Multi-Angle Seat Cutter Blades

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

TOOLING
BRAKE SERVICE

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS


45° Seat Angle Cutter Blades

30° Seat Angle Cutter Blades


 FT-45039U1	 FT-45039U2	 FT-45039V1	 FT-45039W1	 FT-45039W2	 FT-45039W3
 FT-45051V2	 FT-45051V4	 FT-45051V1	 FT-45051V3	 FT-45051X1	 FT-45055V1
 FT-45059V1	 FT-45059V2	 FT-45059V3	 FT-45059X1	 FT-45063U1	 FT-45063U2
 FT-45063V1	 FT-45063V3	 FT-45063V2	 FT-45063W1	 FT-45071V1	 FT-45075V2
 FT-45075V1	 FT-45079U1	 FT-45079U2	 FT-45079V1	 FT-45098U1	 FT-45098U2
 FT-30039T1	 FT-30051S1	 FT-30059S1	 FT-30059S3	 FT-30063S1	 FT-30071S1
 FT-30075S1	 FT-30079S1	 FT-30079S2	 FT-30098S1	 FT-30098S2	resharpening available Have Goodson Resharpen Your Valve Seat Cutter Blades




SABER TOOTH
SERIES CUTTER BLADES




FT-15




FT-20




FT-25




FT-30




FT-35




FT-37




FT-39




FT-45




FT-50




FT-55




FT-60




FT-65




FT-70




FT-75



FT-82




FT-90




FT-R5


sized for
diesel




FT-37063S60




FT-37079S60



FT-37071S52



FT-39570T1



FT-20098S1



- Increase Low Lift Air Flow
- Increase Torque
- Increase Horsepower

Offset Pilot


Indexing Pin

Mounting Fixture




Diesel Relief Tooling


- Use with your seat and guide machine or Bridgeport Mill equipped with a multi-angle seat cutting system • Developed for Goodson by Joe Mondello Racing Engines
- Use for 6.0L & 7.3L Ford, 12 Valve, 5.9L Cummins & 6.6L Duramax diesel engines
- For 2-Valve & 4-Valve heads • Complete kit includes the Mounting Fixture, .375" Top Offset Pilot, Indexing Pin & Radius Cutter
- This tool is only for use with radius cutters BSS-20CC and BSS-45CC




BSS-20CC




BSS-45CC




BSS-3001




BSS-3701




BSS-3002




BSS-3702




BSS-3001



BSS-4501



BSS-4502



IFT-4524-HD

black smoke
series cutters
for High
Performance
Diesel
Engines

Developed for
Goodson by Joe
Mondello Racing
Engines.

These cutters are
designed to be
used with your 3-D
Fast Cut or other
multi-angle tooling.



See How to
Use the Diesel
Relief Tooling on
YouTube! Search
for Diesel Valve
Relief Tool.

Description	Order No.	Incl.
7mm Diesel Relief Tool Kit	DVRT-7MM-KIT	▼
8mm Diesel Relief Tool Kit	DVRT-8MM-KIT	▼
20CC Radius Cutter for 2-Valve Heads	BSS-20CC	X
45CC Radius Cutter for 4-Valve Heads	BSS-45CC	X

Valve Seat Work

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS



Measure
run-out
to .0001"
directly from
valve seat

Precision Valve Seat Run-Out Gauge

- Use with your .375" Top Pilot (sold separately) • Measure run-out to .0001" directly from the seat • Locked to the pilot • Dial indicator remains stationary while rotating contact pointer • .800" - 2.500" dia. range
- Includes 2" dia. dial indicator

Description	Order No.
Gauge Assembly	SCG-375
Replacement Indicator	SCG-IND

Easy-To-Read Gauge



Premium Valve Seat Run-Out Gauges



- Hardened guide bushings & contact pilot
- Quick thumb screw set-up
- Jeweled bearing indicator reads to $\pm .050$ " with .001" precision
- Range: 1.00"-2.50"
- Measures concentricity

Pilot Size	OAL	Order No.
.375"	5"	VSG-375
.385"	5"	VSG-385
Replacement Indicator		VSG-IND



Valve Seat Machining Aid

- Machine valve seats to a mirror-like finish
- Universal - works with any type of cylinder head machining center
- Use full strength
- Safe for metal surfaces
- Works with mineral-based cutting oils, not water based
- Quart (946mL)
- Order No. PF-2020



Valve Seat Scribe Tool

- Tool body fits over .375" Top pilot
- Use valve to set point then scribe seat with inner and outer radii
- We recommend using Layout Fluid so you can see the scribe mark more clearly
- Grind seat top and throat to match face precisely
- Replaces ST-30-BD Scribe Tool
- Order No. SST-375

Layout Fluids

- Choose from blue and red
- Toluene-free • Dries in minutes
- Provides a thin film without cracking or chipping • Prevents glare with a uniform, deep color
- 2 oz. markers feature felt tip applicator
- 4 oz. containers includes brush in cap

Description	Color	Order No.
2 oz. Layout Fluid Markers	Blue	VBF-2
	Red	VRF-2
4 oz. Layout Fluid	Blue	VBF-4
	Red	VRF-4



Cutting & Tapping Fluid

- Cut through even the hardest metals
- Spray clings to the surface of the tool to prolong tool life
- Ideal for stainless steel, high nickel alloys, titanium and more
- Use for reaming, seat cutting and CBN cutting
- Aerosol*
- Order No. CTF-14*

*Hazardous Goods Fees Apply When Shipped by Air
Order 6 or more CTF-14, save 10% off jobber



Spray Bluing Fluid

- Fast drying • Will not rub off
- Good adhesion to all metals and glass
- Non-corrosive • Resists heat
- No flaking or peeling
- Scribes clean lines for precision work
- Eliminates rags, daubers, spilled bottles
- Dries to a smooth level coating
- Aerosol*
- Order No. SBF-16*



*Hazardous Goods Fees Apply When Shipped by Air



Prussian Blue Oil Based Paste

- Aids precision fitting of machined surfaces
- Locates high spots on bearings, valves, gears and other close-tolerance components
- Non-drying, easy clean-up
- Coat parts with a uniform film of Prussian Blue; assemble in working position and turn shaft; improper fit will show up as easy-to-see bright blue streaks
- 0.75 fl. oz. tube
- Order No. PB-75

Neway Valve Seat Cutting System



Many cutter body styles available including single angle and double angle for a variety of cutting applications.

special order

Don't see the cutter you need in the chart below? Goodson can order any Neway Cutter Body and tooling available.

Adjustable Tungsten Carbide cutter blades. Cutters work in a range from 3/8" smaller and 1/4" larger than the cutter body size.

Replaceable cutter blades (see chart for which blades to order for your cutter) are included with body purchase (where applicable).

Cutter body is made of anodized aluminum around a steel hub.

Small Series Cutter Bodies use .297" Top Pilots
Standard Series Cutter Bodies use .375" Top Pilots (pages 4 & 5)

Replacement Blades & Parts

Enlarged For Detail



Description	Order No.		
Small Series Cutter Bodies (Use .297" Top Pilots - page 3)			
Cutter Body	Blade	Qty.	Replacement
Diameter	Angle		Blade
0.975" / 24.8mm	45°	3	NCB-253
1.000" / 25.4mm	60°	3	NCB-252
1.312" / 33.3mm	15°/60°	3/3	NCB-251 / 254
Replacement	Angle	Blade	Lenth
Blades	15-46°	5/16"	7.9mm
		3/8"	9.53mm
Sold Individually		1/2"	12.7mm
	60-75°	1/2"	12.7mm
		3/4"	19.05mm
Non-Serrated	60-75°	1/2"	12.7mm
Correction Blades		3/4"	19.05mm
Hard Seat Blades	15-46°	3/8"	9.53mm
		1/2"	12.7mm
Radius		3/8"	9.53mm
Combustion		1/2"	12.7mm
Chamber Blades		3/4"	19.05mm
Flat Head Screw			NCB-260
Wedge for bodies 1" / 25.4mm and over			NCB-265
Wedge for bodies smaller than 1" / 25.4mm			NCB-266
Tool Kit (includes brush, 2 hex keys and pilot puller)			NKA-246
EZ-Turn Wrench			NTW-EZ
1/2" T-Handle Driver			NTW-505
3/8" T-Handle Driver			NTW-513
Drive Adaptor	1/2" to 3/8"	12.7-9.53mm	NTW-503-1

Description				Order No.
Small Series Cutter Bodies (Use .375" Top Pilots - page 3 & 4)				
Cutter Body	Blade	Qty.	Replacement	
Diameter	Angle		Blade	
1.125" / 28.6mm	30°	3	NCB-250	NCU-278
	45°	3	NCB-250	NCU-268
	60°	3	NCB-252	NCU-269
	37.5°	5	NCB-250	NCU-3731
1.250" / 31.6mm	30° / 45°	3/3	NCB-250	NCU-230
	31° / 46°	3/3	NCB-250	NCU-203
	60°	3	NCB-252	NCU-270
1.375" / 35.0mm	30° / 45°	3/3	NCB-250 / 251	NCU-232
1.500" / 38.0mm	15° / 75°	3/3	NCB-251 / 254	NCU-217
	30° / 45°	3/3	NCB-251	NCU-234
	30° / 45°	5/5	NCB-251	NCU-626
	40°	5	NCB-251	NCU-4038
	60°	3	NCB-254	NCU-205
1.750" / 44.5mm	15° / 60°	5/5	NCB-251 / 254	NCU-643
	30° / 45°	5/5	NCB-251	NCU-645
	55°	5	NCB-251	NCU-17555
2.000" / 50.8mm	15° / 60°	5/5	NCB-251 / 254	NCU-653
	30° / 45°	5/5	NCB-261	NCU-660
	60°	5	NCB-254	NCU-657
2.500" / 63.5mm	30° / 45°	7/7	NCB-251	NCU-677
	50°	7	NCB-251	NCU-25050
	52°	7	NCB-251	NCU-25052
	T-Handle	55°	7	NCB-251



T-Handle

Valve Seat Cutting Fluid

- High silicone content reduces drag on cutters so they last longer
- Promotes smoother cuts
- May be diluted up to 9:1
- Non-aerosol spray

Size	Order No.
16 oz. Spray / 473 mL	SCF-2
1 Gal. / 3.79 L	SCF-10



Neway Easy Turn Wrench

- Turn cutters continuously
- Produces a smooth seat quickly and easily
- Improves material removal control
- Spring loaded
- Includes drive adaptor to convert 1/2" to 3/8"

Description	Order No.
Wrench	NTW-EZ
Drive Adaptor	NTW-503-1



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEAS
TOO

V-TWIN & METRIC
HARD PARTS

Counterboring Tools

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

GOODSON Counterbore Cutters CUT TRUE TO SIZE!

Other cutters may cut as much as .005" smaller

tech tips

from the techxperts™

Goodson recommends using
Indexable Counterbore Cutters
at 40 to 60 RPM.



Indexable Counterbore Cutters

These indexable counterbore cutters eliminate down time from having brazed cutters reset or sharpened. You can service them right in your own shop! Each cutter body includes 2 carbide cutter tips with 4 cutting edges. When one edge wears, simply rotate the tip to a new cutting edge. You'll also get a wrench with every cutter body.



DWI-SERIES

- Fits DCM Tech, Sunnen, and Winona Van Norman
- 9/16" / 14.3mm arbor


Size	mm	Repl. Insert	Order No.
1.062"	26.97	SCI-250-B	DWI-1062
1.125"	28.57	SCI-250-B	DWI-1125
1.187"	30.15	SCI-250-B	DWI-1187
1.250"	31.75	SCI-250-B	DWI-1250
1.312"	33.32	SCI-250-B	DWI-1312
1.375"	34.93	SCI-250-B	DWI-1375
1.437"	36.50	SCI-250-B	DWI-1437
1/4" Replacement Cutting Insert		SCI-250-B	
Replacement Screw for SCI-250-B		SCS-T7	
Allen Wrench for SCS-T7		SCW-T7	

Size	mm	Repl. Insert	Order No.
1.500"	38.10	SCI-375-B	DWI-1500
1.562"	39.67	SCI-375-B	DWI-1562
1.625"	41.28	SCI-375-B	DWI-1625
1.687"	42.85	SCI-375-B	DWI-1687
1.750"	42.85	SCI-375-B	DWI-1750
1.812"	44.45	SCI-375-B	DWI-1812
1.875"	47.63	SCI-375-B	DWI-1875
1.937"	49.20	SCI-375-B	DWI-1937
2.000"	50.80	SCI-375-B	DWI-2000
2.062"	52.37	SCI-375-B	DWI-2062
2.125"	53.98	SCI-375-B	DWI-2125
3/8" Replacement Cutting Insert		SCI-375-B	
Replacement Screw for SCI-375-B		SCS-T15	
Torx Wrench for SCS-T15		SCW-T15	



SABER TOOTH Cutter Inserts

1.25" Precision Ground
Setting Standard




Direct Reading Micrometer
and Indicator makes setting
fast and easy

Kit includes 4
9/16" Arbor Cutters


GOODSON Adjustable Counterbore Cutter Kit

- Cutter assemblies feature positive stop adjusting screws to prevent cutters from changing dimensions when in use
- Direct reading micrometer and dial indicator for fast, accurate set-up • 7 cutter assemblies to choose from, covering a range from 1.25" to 2.75" diameter
- Kit substitutions are available, call to inquire
- Heavy duty billet steel construction



Counterbore Cutter Drive Adaptors

Cutter Drivers	Order No.
#3 MT Driver	CD-MT3
Fits .750" Bridgeport Collet	
9/16" arbor	DCW-60-375
5/8" arbor	DCW-60-385



Wear Sleeves for DWA & DWI Counter Bore Cutters

• Wear sleeves fit CD-MT3 Driver	
Pilot Top Size	Order No.
.375" (9.53mm)	DCW-375
.385" (9.78mm)	DCW-385



SABER TOOTH
SERIES CUTTER BLADES



Scan with your smart
phone or other device
to view



Description	Order No.	Incl.
Complete Kit (9/16" / 14.3mm Arbor)	DWA-300	▼
Cutter Assemblies (in/mm) complete with cutting inserts installed		
9/16" Arbor	1.250"-1.375" / 31.8-34.9	DWA-250 X
	1.375"-1.500" / 34.9-38.1	DWA-375 X
	1.500"-1.750" / 38.1-44.5	DWA-302 X
	1.750"-2.000" / 44.5-50.8	DWA-303 X
	2.000"-2.250" / 50.8-57.2	DWA-304
	2.250"-2.500" / 57.2-63.5	DWA-305
	2.500"-2.750" / 63.5-69.9	DWA-306
Replacement Cutting Insert	DKB-7	
Replacement Insert Screw	DKS-7	
Wrench	FT-WRENCH	X
Hex Keys	5/32"	DWA-5/32 X
	5/64"	DWA-5/64 X
	9/64"	DWA-5/32 X
Wear Sleeves (see note below)		
	For .375" Top Pilot	DCW-375
	For .385" Top Pilot	DCW-385

To use the Counterbore Cutter Kit with Kwik-Way & Peterson Machines you will need to adapt the 9/16" cutter to fit the 5/8" drive. Use a DCW wear sleeve.

Goodson
exclusive

Universal Valve Seat Wheel Dresser Stand

- Infinitely adjustable from 0° to 90°
- Scale marked in 1° increments
- Dress stones up to 4" diameter
- Includes Premium dresser diamond & dresser pilot
- Base has pre-drilled holes for easy mounting to your bench
- Choose dresser pilot from chart below




Includes
Premium Dresser Pilot
Choose From
Chart Below

Description	Order No.	Incl.
Universal Dressing Stand	SWD-UNI	▼
Replacement Premium Dressing Diamond	G-13P	X
Dressing Stand Riser Bushings (.250" & .875" Tall)	SK-9-10	X
Dressing Stand Riser Bushings (For .437" dresser Pilots)	SK-11-12	

See pages 18-23 for valve seat stones, stone holders, air drivers, etc.

Heavy Duty Valve Seat Wheel Dresser Stand

- Ball bearing mounted diamond carrier
- Adjustable in 1° increments from 0° to 90°
- Includes diamond
- Choose dressing pilot from list below
- Designed for maximum accuracy



Includes Premium
Dresser Pilot
Choose From
Chart Below

Description	Order No.
Heavy Duty Dresser	031-1900-02
Replacement Torsion Spring for 031-1900-02	000-1850-78
Replacement Brass Plug	031-1917-00
Replacement Diamond Dresser	G-18




Valve Seat Wheel Dresser Pilots for Universal & Heavy Duty Wheel Dresser Stands

- .437" top pilots include a groove
- All pilots have .625" bottom

Dresser Pilots (select based on stone holder type)

Fits Stone Holder Type	OAL	Order No.
A .437" Hex Stone Holder	5 $\frac{1}{16}$ "	031-1102-89
B .437" Hex or Flex Stone Holder	7 $\frac{1}{4}$ "	031-0202-80
C .385" Top Stone Holder	6"	031-0202-55
D .375" Top Stone Holder	6 $\frac{3}{8}$ "	031-0202-47



Stones and Holders
sold separately



Seat Stone Removal Tool

Once in a while a valve seat stone will be so tight on the stone holder that it's almost impossible to get off. That's why we came up with this tool. Simply fasten it to your bench with screws or bolts (not included) or clamp it in a vise, place the holder onto the fixture and twist the stone off easily.

Description	Order No.
Sioux-Style	SX-SRT
Kwik-Way Style	KW-SRT


Valve Seat Height Gauge

- Adjusts for all popular valve seat diameters • Gauge accurate to .001"
- Seat contact probe aligns on valve seat while gauge rides along the side deck • Pilot aligns in valve guide
- Fully adjustable seat contact probe and gauge positions allow tool to fit popular seat diameters from .750" to 3.00"
- Includes Dial Indicator




Description	Fits Pilot	Order No.
Valve Seat Height Gauge Kit	.375"	VSHG-375
Replacement Dial Indicator		EDI-1

tech tips Goodson recommends using Bounce Springs with your Valve Seat Stones to prevent damage to the stone and the from the techxperts™ seat. This is especially important with the very small stones.



Standard Bounce Spring Set

- Includes 1 each of 3 lengths: 1" / 24.5mm, 1.50" / 38.1mm & 2" / 50.8mm
- ID = .450" / 11.4mm
- OD = .570" / 14.5mm
- Not for use with 3-D Fast Cut
- Order No. **BSS-100**



Small Diameter Bounce Springs

- ID = .406" / 10.3mm
- OD = .500" / 12.7mm

Length / mm	Order No.
1.10" / 27.9	BS-1
1.67" / 42.4	BS-2
3.00" / 76.2	BS-3

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS



Goodson seat wheels are built to grind accurately & outlast the competition

- Brass bushings resist galling or seizing to the holder
- Heat-cured, permanent epoxy bonding prevents loose bushings
- Bushings are set deep to expose the most abrasive for long life
- Each wheel is trued and checked to assure accurate, vibration-free grinding
- Custom sizes and angles are available in-house – Call for more information

GP

General Purpose
Removes material from
cast-iron seats or inserts.

CB

Cool Blue
Pure Aluminum-Oxide
stone. Superior general
purpose stone for high
performance Beryllium
seats. Very sharp.

S

Stellite
Specially formulated to
grind Stellite and other
types of hardened seat.

F

Finish
Final polishing stone
gives an ideal final finish
with minimal stock
removal. Removes
chatter marks.

NC

Nickel Chrome
For aluminum heads
with chrom-alloy seat
inserts. Soft abrasive
stone to grind hard seats.
Speckled.

R

Ruby
The original Black &
Decker composition,
general purpose stone.

KW

Fits Kwik-Way 13/16"x13 thread

Colors may vary due to manufacturing processes

Size		General Purpose (GP) 90 Grit			Cool Blue (CB) 80 Grit		Stellite (S) 90 Grit	
Inch	mm	00°	30°	45°	00°	45°	00°	45°
1¼"	32	KW-1000-GP	KW-1030-GP	KW-1045-GP	KW-1000-CB	KW-1045-CB	KW-1000-S	KW-1045-S
1⅝"	33	KW-1000A-GP		KW-1045A-GP	KW-1000A-CB	KW-1045A-CB		
1⅞"	35	KW-1100-GP	KW-1130-GP	KW-1145-GP	KW-1100-CB	KW-1145-CB	KW-1100-S	KW-1145-S
1⅞"	36	KW-1100A-GP		KW-1145A-GP	KW-1100A-CB	KW-1145A-CB	KW-1100A-S	KW-1145A-S
1½"	38	KW-1200-GP	KW-1230-GP	KW-1245-GP	KW-1200-CB	KW-1245-CB	KW-1200-S	KW-1245-S
1⅞"	39	KW-1200A-GP		KW-1245A-GP		KW-1245A-CB	KW-1200A-S	KW-1245A-S
1⅝"	41	KW-1300-GP	KW-1330-GP	KW-1345-GP	KW-1300-CB	KW-1345-CB	KW-1300-S	KW-1345-S
1⅞"	43	KW-1300A-GP		KW-1345A-GP	KW-1300A-CB	KW-1345A-CB	KW-1300A-S	KW-1345A-S
1¾"	44	KW-1400-GP	KW-1430-GP	KW-1445-GP	KW-1400-CB	KW-1445-CB	KW-1400-S	KW-1445-S
1⅞"	47	KW-1500-GP	KW-1530-GP	KW-1545-GP	KW-1500-CB	KW-1545-CB	KW-1500-S	KW-1545-S
2"	51	KW-1600-GP	KW-1630-GP	KW-1645-GP	KW-1600-CB	KW-1645-CB	KW-1600-S	KW-1645-S
2⅞"	54	KW-1700-GP	KW-1730-GP	KW-1745-GP	KW-1700-CB	KW-1745-CB	KW-1700-S	KW-1745-S
2¼"	57	KW-1800-GP	KW-1830-GP	KW-1845-GP	KW-1800-CB	KW-1845-CB	KW-1800-S	KW-1845-S
2⅝"	60	KW-1900-GP	KW-1930-GP	KW-1945-GP	KW-1900-CB	KW-1945-CB		
Size		Finishing (F) 150 Grit			Nickel Chrome (NC) 60 Grit		Ruby (R) 80 Grit	
Inch	mm	30°	45°		00°	45°	00°	45°
1¼"	32		KW-1045-F		KW-1000-NC	KW-1045-NC	KW-1000-R	KW-1045-R
1⅞"	35	KW-1130-F	KW-1145-F		KW-1100-NC	KW-1145-NC	KW-1100-R	KW-1145-R
1⅞"	36		KW-1145A-F		KW-1100A-NC	KW-1145A-NC		
1½"	38	KW-1230-F	KW-1245-F		KW-1200-NC	KW-1245-NC	KW-1200-R	KW-1245-R
1⅞"	39		KW-1245A-F		KW-1200A-NC	KW-1245A-NC		
1⅞"	41	KW-1330-F	KW-1345-F		KW-1300-NC	KW-1345-NC	KW-1300-R	KW-1345-R
1⅞"	43		KW-1345A-F		KW-1300A-NC	KW-1345A-NC		
1¾"	44	KW-1430-F	KW-1445-F		KW-1400-NC	KW-1445-NC	KW-1400-R	KW-1445-R
1⅞"	47	KW-1530-F	KW-1545-F		KW-1500-NC	KW-1545-NC	KW-1500-R	KW-1545-R
2"	51	KW-1630-F	KW-1645-F		KW-1600-NC	KW-1645-NC	KW-1600-R	KW-1645-R
2⅞"	54	KW-1730-F	KW-1745-F		KW-1700-NC	KW-1745-NC		
2¼"	57		KW-1845-F		KW-1800-NC	KW-1845-NC		
2⅞"	60				KW-1900-NC	KW-1945-NC		

Ordering is easy!

- 1 - Find the diameter (valve head diameter + 1/16" to 1/8").
- 2 - Find the angle you need (you can modify angles with our Valve Seat Wheel Dresser Stand, page 24).
- 3 - Select the abrasive to match your job.

tech tips
from the techxperts™

Keep your stones grinding at
their best with a
Seat Wheel Dresser Stand!

See Page 17 for details



Hex Drive Seat Grinding Kit includes everything listed below. Everything comes packed in a handy storage case.

Valve Seat Grinding Sets

Order the set as-is or modify a set to meet your specific needs. Set contents include:

Description	OE Number		Order No.	Includes		
45° Hex Drive Motor Seat Grinding Set (110V, 50/60 Hz)			SGH-110-KIT	▼		
45° Hex Drive Motor Seat Grinding Set (220V, 50/60 Hz)			SGH-220-KIT	▼		
Hex Drive Seat Grinder - 45° 110V, 50/60 Hz	031-3100-20		031-3100-20		1	
Hex Drive Seat Grinder - 45° 220V, 50/60 Hz	031-3100-27		031-3100-27	1		
Universal Valve Seat Wheel Dresser w/G-13P Diamond			SWD-UNI	1	1	
Replacement Dressing Stand Diamond			G-13P			
Dressing Stand Pilot with .437" Top	031-1102-89		031-1102-89	1	1	
Stone Holder - ¹ / ₁₆ " x 13 Thread w/Plunger	031-0300-30		031-0300-30	2	2	
Heavy Duty Plastic Case (21 ¹ / ₁₆ " x 12 ¹ / ₂ " x 13 ¹ / ₂ ")	001-1000-25		SG-CASE	1	1	
Seat Stone Removal Tool			KW-SRT	1	1	
Leather Vibration Reducer (3 Pc.)			KHW-3	1	1	
.437" Top Pilots	Dia./mm					
	.2755" / 7.00mm	030-0237-30	P-5275K	1	1	
	.2763" / 7.02mm	030-0237-49	P-5276K	1	1	
	.2765" / 7.05mm	030-0237-40	P-5277K	1	1	
	.3125" / 7.93mm	030-0239-35	P-5312K	1	1	
	.3135" / 7.96mm	030-0239-51	P-5313K	1	1	
	.3145" / 7.98mm	030-0239-78	P-5314K	1	1	
	.3150" / 8.00mm	030-0239-94	P-5315K	1	1	
	.3437" / 8.72mm	030-0242-73	P-5343K	1	1	
	.3440" / 8.74mm	030-0243-03	P-5344K	1	1	
	.3457" / 8.78mm	030-0243-11	P-5345K	1	1	
	.3730" / 9.47mm	030-0247-45	P-5373K	1	1	
	.3750" / 9.52mm	030-0247-70	P-5375K	1	1	
General Purpose Valve Seat Grinding Stones (¹ / ₁₆ " x 13)		30°		45°		
1.375" / 35mm	KW-1130-GP	1	1	KW-1145-GP	1	1
1.500" / 38mm	KW-1230-GP	1	1	KW-1245-GP	1	1
1.615" / 41mm	KW-1330-GP	1	1	KW-1345-GP	1	1
1.750" / 44mm	KW-1430-GP	1	1	KW-1445-GP	1	1
1.785" / 47mm	KW-1530-GP	1	1	KW-1545-GP	1	1
2.000" / 51mm	KW-1630-GP	1	1	KW-1645-GP	1	1
2.125" / 54mm	KW-1730-GP	1	1	KW-1745-GP	1	1
Finishing Valve Seat Grinding Stones (¹ / ₁₆ " x 13)		30°		45°		
1.375" / 35mm	KW-1130-F	1	1	KW-1145-F	1	1
1.500" / 38mm	KW-1230-F	1	1	KW-1245-F	1	1
1.625" / 41mm	KW-1330-F	1	1	KW-1345-F	1	1
1.750" / 44mm	KW-1430-F	1	1	KW-1445-F	1	1
1.785" / 47mm	KW-1530-F	1	1	KW-1545-F	1	1
2.000" / 51mm	KW-1630-F	1	1	KW-1645-F	1	1
2.125" / 54mm	KW-1730-F	1	1	KW-1745-F	1	1



45° Kwik-Way Hex Drive (SGH) Electric Motor Unit

- Heavy duty electric motor
- 11,500 RPM • Weighs 9 lbs.
- 3/5 HP, 7.5 Amps

Description	Order No.
110V, 50/60Hz	031-3100-20
220V, 50/60Hz	031-3100-27
Nose Assembly	031-3105-12
Hex Drive Assembly	031-3112-17
Replacement Leather Pad	031-1009-41
2 Pc. Brush Set	003-0072-43
Trigger Switch	000-1201-20



Hex Drive Replacement Adaptors

- Adapt your Seat Grinder Motor to fit various Kwik-Way Seat Grinders

Description	Order No.
.500" Bore	031-0412-36
Fit SGA Motor Units with Serial No. 0 to 2000	
.650" Bore	031-0426-10
Fit SGA Motor Units with Serial No. 4000 & up	
3/8" x 24 Thread	031-1011-00
Fit SGAll Hex Motor Units	
5/16" x 18 Thread	031-2012-09
Fit SSG Hex Motor Units	

Same Day Shipping

full service
...fast



"If you need a custom angle or size in a Valve Seat Stone, Goodson can do it. We grind seat stones in-house to standard and custom dimensions. Give Goodson a call today."
- Tim, Goodson Production - 10 years of service



SX

Fits Sioux™, KO Lee, US, Thor, Skil, Winona 11/16"x16 thread
Colors may vary due to manufacturing processes

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Size		General Purpose (GP) 70 Grit					Cool Blue (CB) 80 Grit		Ruby (R) 80 Grit		
Inch	mm	Jobber	00°	30°	45°	60°	00°	45°	00°	45°	
7⁄8"	22								SX-500-R	SX-545-R	
15⁄16"	24								SX-600-R	SX-645-R	
1"	25								SX-700-R	SX-745-R	
1 1⁄16"	27								SX-800-R	SX-845-R	
1 1⁄8"	28		SX-900-GP	SX-930-GP	SX-945-GP				SX-900-R	SX-945-R	
1 3⁄16"	30		SX-900A-GP		SX-945A-GP						
1 1⁄4"	32		SX-1000-GP	SX-1030-GP	SX-1045-GP	SX-1060-GP	SX-1000-CB	SX-1045-CB	SX-1000-R	SX-1045-R	
1 5⁄16"	33		SX-1000A-GP		SX-1045A-GP		SX-1000A-CB	SX-1045A-CB			
1 3⁄8"	35		SX-1100-GP	SX-1130-GP	SX-1145-GP	SX-1160-GP	SX-1100-CB	SX-1145-CB	SX-1100-R	SX-1145-R	
1 7⁄16"	36		SX-1100A-GP		SX-1145A-GP		SX-1100A-CB	SX-1145A-CB			
1 1⁄2"	38		SX-1200-GP	SX-1230-GP	SX-1245-G	SX-1260-GP	SX-1200-CB	SX-1245-CB	SX-1200-R	SX-1245-R	
1 9⁄16"	39		SX-1200A-GP		SX-1245A-GP		SX-1200A-CB	SX-1245A-CB			
1 5⁄8"	41		SX-1300-GP	SX-1330-GP	SX-1345-GP	SX-1360-GP	SX-1300-CB	SX-1345-CB	SX-1300-R	SX-1345-R	
1 11⁄16"	43		SX-1300A-GP		SX-1345A-GP		SX-1300A-CB	SX-1345A-CB			
1 3⁄4"	44		SX-1400-GP	SX-1430-GP	SX-1445-GP	SX-1460-GP	SX-1400-CB	SX-1445-CB	SX-1400-R	SX-1445-R	
1 7⁄8"	47		SX-1500-GP	SX-1530-GP	SX-1545-GP	SX-1560-GP	SX-1500-CB	SX-1545-CB	SX-1500-R	SX-1545-R	
2"	51		SX-1600-GP	SX-1630-GP	SX-1645-GP	SX-1660-GP	SX-1600-CB	SX-1645-CB	SX-1600-R	SX-1645-R	
2 1⁄8"	54		SX-1700-GP	SX-1730-GP	SX-1745-GP		SX-1700-CB	SX-1745-CB	SX-1700-R	SX-1745-R	
2 1⁄4"	57		SX-1800-GP	SX-1830-GP	SX-1845-GP	SX-1860-GP	SX-1800-CB	SX-1845-CB	SX-1800-R	SX-1845-R	
2 3⁄8"	60		SX-1900-GP	SX-1930-GP	SX-1945-GP	SX-1960-GP	SX-1900-CB	SX-1945-CB	SX-1900-R	SX-1945-R	
2 1⁄2"	63		SX-2000-GP	SX-2030-GP	SX-2045-GP		SX-2000-CB	SX-2045-CB	SX-2000-R	SX-2045-R	
2 5⁄8"	66		SX-2100-GP	SX-2130-GP	SX-2145-GP		SX-2100-CB	SX-2145-CB			
Size		Stellite (S) 100 Grit					Finishing (F) 150 Grit		Nickel Chrome (NC) 60 Grit		
Inch	mm	Jobber	00°	30°	45°	00°	30°	45°	00°	30°	45°
7⁄8"	22					SX-500-F		SX-545-F	SX-500-NC		SX-545-NC
15⁄16"	24					SX-600-F		SX-645-F	SX-600-NC		SX-645-NC
1"	25					SX-700-F		SX-745-F	SX-700-NC		SX-745-NC
1 1⁄16"	27					SX-800-F		SX-845-F	SX-800-NC		SX-800-NC
1 1⁄8"	28		SX-900-S	SX-930-S	SX-945-S	SX-900-F	SX-930-F	SX-945-F	SX-900-NC	SX-930-NC	SX-945-NC
1 3⁄16"	30		SX-900A-S		SX-945A-S	SX-900A-F		SX-945A-F	SX-900A-NC		SX-945A-NC
1 1⁄4"	32		SX-1000-S	SX-1030-S	SX-1045-S	SX-1000-F	SX-1030-F	SX-1045-F	SX-1000-NC	SX-1030-NC	SX-1045-NC
1 5⁄16"	33		SX-1000A-S		SX-1045A-S	SX-1000A-F		SX-1045A-F	SX-1000A-NC		SX-1045A-NC
1 3⁄8"	35		SX-1100-S	SX-1130-S	SX-1145-S	SX-1100-F	SX-1130-F	SX-1145-F	SX-1100-NC	SX-1130-NC	SX-1145-NC
1 7⁄16"	36		SX-1100A-S		SX-1145A-S	SX-1100A-F		SX-1145A-F	SX-1100A-NC		SX-1145A-NC
1 1⁄2"	38		SX-1200-S	SX-1230-S	SX-1245-S	SX-1200-F	SX-1230-F	SX-1245-F	SX-1200-NC	SX-1230-NC	SX-1245-NC
1 9⁄16"	39		SX-1200A-S		SX-1245A-S	SX-1200A-F		SX-1245A-F	SX-1200A-NC		SX-1245A-NC
1 5⁄8"	41		SX-1300-S	SX-1330-S	SX-1345-S	SX-1300-F	SX-1330-F	SX-1345-F	SX-1300-NC	SX-1330-NC	SX-1345-NC
1 11⁄16"	43		SX-1300A-S		SX-1345A-S	SX-1300A-F		SX-1345A-F	SX-1300A-NC		SX-1345A-NC
1 3⁄4"	44		SX-1400-S	SX-1430-S	SX-1445-S	SX-1400-F	SX-1430-F	SX-1445-F	SX-1400-NC	SX-1430-NC	SX-1445-NC
1 7⁄8"	47		SX-1500-S	SX-1530-S	SX-1545-S	SX-1500-F	SX-1530-F	SX-1545-F	SX-1500-NC	SX-1530-NC	SX-1545-NC
2"	51		SX-1600-S	SX-1630-S	SX-1645-S	SX-1600-F	SX-1630-F	SX-1645-F	SX-1600-NC	SX-1630-NC	SX-1645-NC
2 1⁄8"	54		SX-1700-S	SX-1730-S	SX-1745-S	SX-1700-F	SX-1730-F	SX-1745-F	SX-1700-NC	SX-1730-NC	SX-1745-NC
2 1⁄4"	57		SX-1800-S	SX-1830-S	SX-1845-S	SX-1800-F	SX-1830-F	SX-1845-F	SX-1800-NC	SX-1830-NC	SX-1845-NC
2 3⁄8"	60		SX-1900-S	SX-1930-S	SX-1945-S	SX-1900-F	SX-1930-F	SX-1945-F	SX-1900-NC	SX-1930-NC	SX-1945-NC
2 1⁄2"	63		SX-2000-S	SX-2030-S	SX-2045-S	SX-2000-F	SX-2030-F	SX-2045-F	SX-2000-NC	SX-2030-NC	SX-2045-NC
2 5⁄8"	66								SX-2100-NC	SX-2130-NC	SX-2145-NC

All Valve Seat Wheels are guaranteed against manufacturing defects for 1 year from original purchase date



2 Angle Valve Seat Wheels

- Use with SX-HOLDER & SX-78 adaptor (page 22)
- 30° one side, 45° on the other side

General Purpose		
Inch	mm	Order No.
2 5/8"	66.0	SXL-2145-GP
3"	76.2	SXL-2345-GP
3 1/2"	88.9	SXL-2545-GP
3 3/4"	92.3	SXL-2645-GP
4"	101.6	SXL-2745-GP

SX-HOLDER



SX-78



KWIK-WAY
Seat Grinding Equipment & Supplies

MFG BY

GOODSON
Tools and Supplies for Engine Builders



Sioux-Style Valve Seat Grinding Kits

These kits include everything you need to get started in seat grinding. Choose between kits including 110V and 220V Star Drive Electric Grinders. After that, everything else in the kit is identical.

We started with the most common sizes of pilots and valve seat stones, but you can customize one of these kits to meet your specific needs. Call 1-800-533-8010 for additional information.

Description	OE Number	Order No.	Includes	
45° Star Drive Motor Seat Grinding Set (110V, 50/60Hz)		SGK-110-KIT	▼	
45° Star Drive Motor Seat Grinding Set (220V, 50/60Hz)		SGK-220-KIT	▼	
Star Drive Seat Grinder - 45° 110V, 50/60Hz	031-3100-21	031-3100-21	1	
Star Drive Seat Grinder - 45° 220V, 50/60Hz	031-3100-28	031-3100-28	1	
Universal Valve Seat Wheel Dresser w/G-13P Diamond		SWD-UNI	1	1
Replacement Dressing Diamond		G-13P		
Dressing Stand Pilot	031-0202-55	031-0202-55	1	1
Stone Holder - 11/16" x 16 Thread	1702	SX-HOLDER	2	2
Heavy Duty Plastic Storage Box (21 5/16" x 12 1/2" x 13 1/2")	001-1000-25	SG-CASE	1	1
Seat Stone Removal Tool		SX-SRT	1	1
Bounce Spring Set (3 Pc.)		BSS-100	1	1
Leather Vibration Reducer (3pc.)		SHW-3	1	1

.385" Top Pilots Dia./mm

.2755" / 7.00mm		P-5275S	1	1
.2763" / 7.02mm		P-5277S	1	1
.2779" / 7.05mm		P-5278S	1	1
.3125" / 7.94mm		P-5312S	1	1
.3130" / 7.95mm		P-5313S	1	1
.3141" / 7.98mm		P-5314S	1	1
.3149" / 8.00mm		P-5315S	1	1
.3430" / 8.71mm		P-5343S	1	1
.3440" / 8.73mm		P-5344S	1	1
.3450" / 8.76mm		P-5345S	1	1
.3750" / 9.53mm		P-5375S	1	1
.3760" / 9.55mm		P-5376S	1	1

General Purpose Seat Grinding Stones (11/16" x 16)

General Purpose Seat Grinding Stones (11/16" x 16)			30°		45°	
1.375" / 35mm	SX-1130-GP	1	1	SX-1145-GP	1	1
1.500" / 38mm	SX-1230-GP	1	1	SX-1245-GP	1	1
1.625" / 41mm	SX-1330-GP	1	1	SX-1345-GP	1	1
1.750" / 44mm	SX-1430-GP	1	1	SX-1445-GP	1	1
1.785" / 47mm	SX-1530-GP	1	1	SX-1545-GP	1	1
2.000" / 51mm	SX-1630-GP	1	1	SX-1645-GP	1	1
2.125" / 54mm	SX-1730-GP	1	1	SX-1745-GP	1	1

Finishing Valve Seat Grinding Stones (11/16" x 16)

Finishing Valve Seat Grinding Stones (1/4" - 1/2")		30°	45°
1.375" / 35mm	SX-1130-F	1	1
1.500" / 38mm	SX-1230-F	1	1
1.625" / 41mm	SX-1330-F	1	1
1.750" / 44mm	SX-1430-F	1	1
1.785" / 47mm	SX-1530-F	1	1
2.000" / 51mm	SX-1630-F	1	1
2.125" / 54mm	SX-1730-F	1	1



45° Sioux-Style (SGK) Star Drive Electric Motor Unit

- Heavy duty electric motor
- 11,500 RPM
- Weighs 9 lbs.
- 3/5 HP • 7.5 Amps

Description	Order No.
110V, 50/60Hz	031-3100-21
220V, 50/60Hz	031-3100-28
Nose Assembly	034-3105-00
2 Pc. Brush Set	003-0072-43
Trigger Switch	001-1201-20



Enlarged to
show detail

034-3112-00

Replacement Drive Assemblies

- 1/2" x 20 thread
- Easy to install
- Always keep one on hand for emergencies

Description	Order No.
Star Drive (SGH)	034-3112-00

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

full service
...fast



"We replenish our warehouse locations daily so that items are readily available to fill your orders without delay."

— Tracy, Goodson Receiving - 4 years of service

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Rebuildable

$\frac{13}{16}$ "x13 Thread Hex Drive

Kwik-Way Stone Holder

- Use to replace worn-out holders or save time by having several holders set up with different sizes, compositions or angles of seat stones • Ball-bearing construction
- Without spring plunger
- Use rebuild kit 034-0002-00 (below)
- $\frac{13}{16}$ " x 13 thread
- .437" Pilot Size
- Supersedes KW-3056
- Order No. 031-0300-56



Rebuildable

$\frac{13}{16}$ "x13 Thread Hex Drive

Kwik-Way Stone Holder

- Use to replace worn-out holders or save time by having several holders set up with different sizes, compositions or angles of seat stones • Ball-bearing construction
- With spring plunger
- Use rebuild kit 034-0002-15 (below)
- $\frac{13}{16}$ " x 13 thread
- .437" Pilot Size
- Order No. 031-0300-30



New-Generation Hex Drive Stone Holder For .375" Top Pilot

- Use to replace worn-out holders or save time by having several holders set up with different sizes, compositions or angles of seat stones • Ball-bearing construction
- Without spring plunger
- $\frac{13}{16}$ " x 13 thread
- .375" Pilot Size
- Order No. KW-375E



New-Generation Hex Drive Stone Holder For .437" Top Pilot

- Use to replace worn-out holders or save time by having several holders set up with different sizes, compositions or angles of seat stones • Ball-bearing construction
- Without spring plunger
- $\frac{13}{16}$ " x 13 thread
- .437" Pilot Size
- Order No. KW-437



Accessories	Order No.
Heavy-Duty Twisted Cable Steel Coupling	031-0304-10
Replacement Hex Drive Body Cap	031-0302-95
Stabilizer Assembly with Bronze Bushing	031-0126-60
Valve Seat Stone Removal Tool	KW-SRT
Leather Vibration Reducer (3 pc.) for KW-Holders	KHW-3
Replacement Spring Plunger Assembly	031-0313-97

Accessories	Order No.
Black & Decker $\frac{5}{8}$ " Hexball $\frac{7}{16}$ "x24 Thread	BD-58
Sioux-Style Conversion Bushings $\frac{1}{16}$ "x16 to $\frac{7}{16}$ "x14	SX-78
$\frac{9}{16}$ "-16 to $\frac{1}{16}$ "-16 Adaptor for Sioux Style	BD-60



Stone Holder Rebuild Kits

For Hex Drive Stone Holder without Spring Plunger Includes 2 Bearings, Bearing Sleeve, Bearing Lock Nut, Sleeve Key, Hex Cap & Garter Spring
Fits OE & Goodson models
Order No. 034-0002-00



For Hex Drive Stone Holder with Spring Plunger

Includes 2 Bearings, Bearing Sleeve, Bearing Lock Nut, Sleeve Key, Hex Cap & Spring Plunger. Fits OE & Goodson models
Order No. 034-0002-15



For Flex Drive Stone Holder

Includes 2 Bearings, Bearing Sleeve, Heavy Duty Flex Coupling, Inner Sleeve Key & Set Screw
Order No. 034-0003-25



Rebuild kit components are not available individually

Grinding Wheel Adaptors

Description	Order No.
$\frac{13}{16}$ "-13 (KW) Threaded Stones to $\frac{1}{16}$ "-16 Threaded Holders (Sioux™, KO Lee)	031-0390-02
$\frac{13}{16}$ "-13 (KW) Threaded Stones to $\frac{7}{16}$ "-16 Threaded Holders (Black & Decker)	031-0391-00
$\frac{13}{16}$ "-13 (KW) Threaded Stones to $\frac{2}{32}$ "-18 Threaded Holders (Kwik-Way)	031-0393-04



031-0390-02



031-0391-00



031-0393-04

¹¹/₁₆"x16 Thread Star Drive Stone Holder For .385" Top Pilot

- Use to replace worn-out holders or save time by having several holders set up with different sizes, compositions or angles of seat stones
- Ball-bearing construction
- .385" Top Pilot Size



Description	OAL	OE#	Order No.
Short Body	3½"	1672	SX-1672
Standard Body	4¾"		SX-HOLDER

¹¹/₁₆"x16 Thread Hex Drive Stone Holder For .385" Top Pilot

- Use to replace worn-out holders or save time by having several holders set up with different sizes, compositions or angles of seat stones
- Ball-bearing construction
- OAL: 5³/₁₆"
- OE# 1702BB
- .385" Top Pilot Size
- Order No. **SX-1702BB**



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

¹¹/₁₆"x16 Thread Star Drive Stone Holder For .375" Top Pilot

- Use to replace worn-out holders or save time by having several holders set up with different sizes, compositions or angles of seat stones
- Ball-bearing construction
- OAL: 4³/₄"
- .375" Top Pilot Size
- Order No. **SX-375**



⁹/₁₆"x16 Thread Black & Decker Style Stone Holder For .375" Top Pilot

- Use to replace worn-out holders or save time by having several holders set up with different sizes, compositions or angles of seat stones
- Ball-bearing construction • OE # BD-HOLDER
- .375" Top Pilot Size
- Includes BD-60 Adaptor to convert to ¹¹/₁₆"x16 thread
- Order No. **BDS-HOLDER**



¹¹/₁₆"x16 Thread Star Drive Stone Holder For .389" Top Pilot

- Use to replace worn-out holders or save time by having several holders set up with different sizes, compositions or angles of seat stones
- Ball-bearing construction
- OAL: 4³/₄"
- OE# 1702
- .389" Top Pilot Size
- Order No. **SUN-HOLDER**



90° Angle High-Speed Air Drivers

- 2 models available - Star or hex drive
- 11,000 RPM motor
- 5/8" - 11 spindle
- 1/4" air inlet • 6 CFM • Rear exhaust
- Weighs 2.25 lbs. • Measures 8.75" long
- Composite grip and trigger are designed for user comfort


Description	Order No.
Star Drive (SGK) 5/8"-11 spindle	AG-SX90
Hex Drive (SGH) 5/8"-11 spindle	AG-KW90
Replacement Drive Adaptors (1½" OAL)	
Star Drive (SGK) Adaptor	SW-SX
Hex Socket (SGH) Adaptor	SW-KW

Air Drive Adaptors

- 1/4" shank
- Adaptors available for a variety of stone holders
- Use with bounce springs (page 24) for best results

Description		Order No.
Hexball Driver	5/8" SAE Thread	ADA-BDS
Kwik-Way Drive Adaptor	1½"x20 Thread	ADA-KW
Sioux-Style Drive Adaptor	Welded Style Adaptor	ADA-SX-HD





Small: 8 1/8" | Large: 8 3/8"

Traditional Valve Lapping Sticks

- Oil resistant polyethylene handles
- Locking tabs eliminate cup slippage

Description	Cup ID	Order No.
Small Lapping Stick	81/8" Long	VLS-15
Replacement Cups	15.9mm / 0.625" dia. .156"	VLS-5/8
	20.6mm / 0.813" dia. .230"	VLS-13/16
Large Lapping Stick	85/8" Long	VLS-30
Replacement Cups	28.6mm / 1.125" dia. .380"	VLS-1 1/8
	34.9mm / 1.375" dia. .380"	VLS-1 3/8



Valve Seat Inserts

- For Harley-Davidson®
- Easy to machine
- Effectively dissipate heat for consistent valve sealing
- Hardness increases during engine break-in
- Radiused for easy installation



Replacement Valve Seats For Shovel Head 1200 & 1340

Application	OD	ID	Thick	MSRP	Order No.	Supersedes
Exhaust	1.944"	1.575"	.400"	\$ 14.47	10-HC493	HVS-1944
Intake	2.135"	1.750"	.400"	14.47	10-HC542	HVS-2135

Oversize Seats for Shovel, Evolution, Twin Cam & M8 - machining required

	OD	ID	Thick	MSRP	Order No.	Supersedes
	1.630"	1.180"	.385"	\$ 14.47	10-HC414	HVS-1630
	1.757"	1.410"	.430"	14.47	10-HC447	HVS-1757
	1.882"	1.520"	.410"	14.47	10-HC478	HVS-1882
Fits M8	2.008"	1.610"	.440"	14.47	10-HC510	HVS-2008
	2.040"	1.700"	.425"	14.47	10-HC518	HVS-2040
	2.070"	1.610"	.460"	14.47	10-HC526	HVS-2070
	2.132"	1.800"	.460"	14.47	10-HC541	HVS-2132
	2.163"	1.750"	.455"	14.47	10-HC549	HVS-2163

For Iron Head Sportster

Application	OD	ID	Thick	MSRP	Order No.	Supersedes
Exhaust	1.757"	1.371"	.315"	\$ 14.47	10-HC446	HVS-1757S
Intake	2.068"	1.750"	.315"	14.47	10-HC525	HVS-2068

Universal Repair Seat

	OD	ID	Thick	MSRP	Order No.	Supersedes
	1.339"	1.024"	.375"	\$ 8.98	10-SC340	MVS-42
Powdered	1.693"	1.299"	.434"	10.55	10-SC430	MVS-58
Metal	1.820"	1.375"	.450"	14.47	10-HC462	HVS-1820
	1.945"	1.375"	.440"	14.47	10-HC494	HVS-1945
	2.257"	1.550"	.500"	14.47	10-HC573	HVS-2257




When installing seats preheat head to 400° and freeze the seat for easier installation. Press fit .006" to .008".



Vacuum Style Lapping Stick

- Press the spring-loaded vacuum pump for a firm hold – stays on until you release the vacuum
- Includes 3 cup sizes (also sold separately)

Description	Cup ID	Order No.
Vacuum Lapping Stick 91/4" Long		VLV-50
Replacement Cups	19.1mm / 0.750" dia. .415"	VLV-3/4
	25.4mm / 1.000" dia. .415"	VLV-1
	31.8mm / 1.250" dia. .415"	VLV-1 1/4



"The Plunger" Hand Valve Lapping Stick

- Large diameter for sure grip
- For 2" and larger valves


Description	Cup ID	Order No.
Hand Valve Lapping Stick 8 1/4" Long		VLS-75
Replacement Cup 44.5mm / 1.750" dia. .313"		VLS-1 3/4



Nickel-Chrome Valve Seats

WARNING: This product can expose you to chemicals, including Nickel which are known to the state of California to cause cancer

OD	ID	Depth	Order No.	OD	ID	Depth	Order No.
1.250"	0.812"	1/4"	VS-1250	1.625"	1.375"	7/32"	VS-1625A
1.312"	1.000"	1/4"	VS-1312	1.687"	1.375"	1/4"	VS-1687
1.375"	1.062"	1/4"	VS-1375	1.750"	1.500"	1/4"	VS-1750
1.437"	1.125"	1/4"	VS-1437	1.812"	1.500"	1/4"	VS-1812
1.500"	1.187"	1/4"	VS-1500	1.875"	1.562"	1/4"	VS-1875
1.562"	1.250"	1/4"	VS-1562	1.937"	1.625"	1/4"	VS-1937
1.562"	1.312"	7/32"	VS-1562A	2.000"	1.625"	1/4"	VS-2000
1.625"	1.312"	1/4"	VS-1625				



See page 7 for valve seat removal tools that fit 3-D Fast Cut

Valve Seat Removers

- Use to pry out valve seat inserts or stubborn grease seals
- Choose from 90°, 100° and 120°, or buy the set
- Not recommended for use on aluminum heads
- Set includes one of each angle
- 13 7/8" overall length

Description	Order No.
3-Pc. Set	VSP-SET ▼
90°	VSP-90 X
100°	VSP-100 X
120°	VSP-120 X

Petroleum Based Valve Lapping Compound

- Silicon-carbide, grease-based compound
- Petroleum based valve lapping compound facilitates precise mating between valve seats and valves
- Use with any powered or manual valve lapping tools • The higher the number the finer the grit

Size	Grit	Order No.
2 oz. / 56.7g	400 Grit	VLC-2-400
	600 Grit	VLC-2-600
	800 Grit	VLC-2-800
	1200 Grit	VLC-2-1200
2 oz. / 56.7g ea. Combo	120 Grit & 280 Grit	VLC-4
1 lb. / 453.6g	120 Grit	VLC-120
	180 Grit	VLC-180
	280 Grit	VLC-280



Manual



Pneumatic



Valve Seat Drivers For Fast Seat Installation

- Pneumatic Drivers install seats faster, easier and without galling • Driver Head ID is .75" / 19.05mm

VSD-HD



Description	Order No.
Manual Drivers	
.375" / 9.53mm & .385" / 9.78mm ID	VSD-202-G
Driver Heads (Blackened for Rust Resistance)	
1.000" to 1.125" Seats / 25.4 - 28.6mm	VSD-203-G
1.250" to 1.375" Seats / 31.8 - 34.9mm	VSD-204-G
1.500" to 1.625" Seats / 38.1 - 41.3mm	VSD-205-G
1.750" to 1.875" Seats / 44.5 - 47.6mm	VSD-206-G
2.000" to 2.125" Seats / 50.8 - 54.0mm	VSD-207-G
Driver Heads (Not Blackened)	
1.750" to 2.000" Seats / 44.5 - 50.8mm	VSD-HD
Pneumatic Drivers	
.375" / 9.53mm & .385" / 9.78mm ID	PSD-385
.437" / 11.10mm ID	PSD-437

Watch an overview of Valve Lapping Tools including live demonstrations in our Tech Lab Tuesday Video Library. Scan the code below with your smart phone or other device for instant access.



Air Powered Valve Lapping Tool

- Operates on 90psi
- Includes air tool and 3 replacement cups • Air actuated ... no electricity needed • Cups also sold separately
- Air supply pressure: 89 psi
- Sound pressure: 77dB
- Sound power: 88 dB
- Hand/arm weighted vibration: 5.43 m/s²
- Use a light touch when operating - no pressure required!

Replacement Cups Also Available

Description	Cup ID	Order No.
Air Powered Valve Lapping Tool		AVLP-300
Replacement Cups	21mm / 0.827" dia.	AVLP-301
	33mm / 1.299" dia.	AVLP-302
	38mm / 1.496" dia.	AVLP-303

Powered Lapping Tool

- Change rotary action into an effective oscillating motion
- Drive with a power drill
- Makes lapping faster and easier
- Includes 2 cup sizes



Description	Cup ID	Order No.
Complete Tool		VLP-100
Replacement Cups	22.2mm / 0.875" dia	VLP-10
	25.4mm / 1.000" dia.	VLP-20



Minnesota Fast Freeze

- Instantly chills seats & guides to -50°F (-45.5°C) • Creates interference fit with heated aluminum heads • Finish seat and guide work faster than ever • 10 oz. Aerosol*
- Use on tight bushings, pins, shafts, etc.
- Order No. MFF-8*

*Hazardous Goods Fees Apply When Shipped by Air

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Precision made wheels = superior performance

We stock more than 40 individual valve refacer wheels, each one designed for a specific machine. Our 4" general purpose wheel for Black & Decker is different from our 4" general purpose wheel for Sioux™. We won't compromise on performance just to simplify our inventory. Your valve refacer requires a certain type of grit, grade and bond and Goodson delivers. All Goodson Valve Refacing Wheels are designed to be used with mineral based grinding oils such as VGO-10 or VGO-SD10. Goodson guarantees all valve refacing wheels against manufacturing defects for 1 year from original purchase date.

Choose from these types: **GP** = for general purpose grinding **S** = for grinding Stellite, **T** = for grinding Titanium, and **CB** = for general purpose grinding of harder materials. Stone color may vary due to manufacturing process.

To Fit	Use	Dia x Ht x Arb	Shape	Type	Color	Fits Models	OE No.	Order No.
Black & Decker	Valve	4" x 1" x 5/8"	Offset	CB	Blue	A, B, C, LW, M, MW, N, NW, NWB	Goodson Spec	GV-146-CB
		4" x 1" x 5/8"	Offset	S	Ruby	A, B, C, LW, M, MW, N, NW, NWB	16371	GV-144
		4" x 1" x 5/8"	Offset	GP	Gray	All but 680, 682, 285, 956		GV-147
		4" x 1" x 5/8"	Offset	GP	Black	All but 680, 682, 285, 956		GV-148
		4" x 1" x 5/8"	Offset	T	Green	All but 680, 682, 285, 956	Goodson Spec	GV-150
		5" x 1" x 5/8"	Offset/20°	GP	Pink	P, PC, PCB, T, TD, TG	34131	GV-156
Comec	Valve	4" x 1 1/4" x 1/2"	Cup	GP	Ruby	All models	20939	GV-145
		215 x 35 x 76mm	Flared	GP	Gray	VR416, RV-516	7604	GV-925
	Stem	215 x 35 x 76mm	Flared	S	Brown	VR416, RV-516	Goodson Spec	GV-980
IDL	Valve	100 x 50 x 20mm	Cup	GP	White	VR416, RV-516	7606	GV-928
		8" x 1 1/4" x 1 1/2"	Flared	GP	White	CG-50, -80, -82, V-90, VR-7000	8230	GV-823
	Stem	8" x 1 1/4" x 1 1/2"	Flared	GP	Gray	CG-50, -80, -82, V-90, VR-7000	VR1703	GV-825
Sunnen®	Valve	8" x 1 1/4" x 1 1/2"	Flared	S	White	CG-50, -80, -82, V-90, VR-7000	Goodson Spec	GV-821
		8" x 1 1/4" x 1 1/2"	Flared	T	Green	CG-50, -80, -82, V-90, VR-7000	VR1704	GV-827
	Stem	8" x 1 1/4" x 1 1/2"	Flared	GP	Ruby	CG-50, -80, -82, V-90, VR-7000	VR1701	GV-824
Kwik-Way	Valve	4 1/2" x 7/8" x 7/8"	Offset	GP	Black	CV, SK, KK, VC, SM, SV, XC	010-0450-10	GV-257
		4 1/2" x 7/8" x 7/8"	Offset	S	Gray	CV, SK, KK, VC, SM, SV, XC	010-0457-03	GV-259
		5" x 7/8" x 7/8"	Offset	GP	White	EVS, VS	Goodson Spec	GV-251
		5" x 7/8" x 7/8"	Offset	GP	Gray	EVS, VS	010-0509-01	GV-252
		7" x 1" x 7/8"	Offset	T	Green	EVS, VS	010-0508-04	GV-255
		7" x 1" x 7/8"	Offset	GP	Gray	SVS, SVS-2	010-0709-00	GV-280
		7" x 1" x 7/8"	Offset	CB	Blue	SVS, SVS-2	Goodson Spec	GV-280-CB
		7" x 1" x 7/8"	Offset	S	White	SVS, SVS-2	010-0707-50	GV-281
		7" x 1" x 7/8"	Offset	T	Green	SVS, SVS-2	010-0708-05	GV-282
		7" x 1" x 7/8"	Offset	T	Green	SVS, SVS-2	Goodson Spec	GV-282A
		7" x 1" x 7/8"	Offset	GP	Orange	SVS, SVS-2	Radiac Spec	F372239 <small>Radiac</small>
		7" x 1" x 7/8"	Offset	GP	Ruby	SVS, SVS-2	Radiac Spec	F377419 <small>Radiac</small>
		8" x 1 3/8" x 1 1/2"	Offset	GP	Gray	VL	010-0819-04	GV-260
		3" x 1 1/4" x 5/8"	Cup	GP	Gray	All models except VL	Radiac Spec	F336036 <small>Radiac</small>
		3" x 1 1/4" x 5/8"	Cup	GP	Gray	All models except VL	010-0300-05	GV-237
KO Lee	Valve	3" x 1 1/4" x 5/8"	Cup	CB	Blue	All models except VL	Goodson Spec	GV-237-CB
		5" x 3/4" x 5/8"	Offset	GP	Gray	All models	OV5GH60	GV-658
	Stem	5" x 3/4" x 5/8"	Offset	S	White	All models	OV5GH80S	GV-659
Rottler	Valve	4" x 1" x 5/8"	Cup	GP	Gray	K500(C) & K403(C)	RV4KH60	GV-345
		4" x 1" x 5/8"	Cup	CB	Blue	All	Goodson Spec	GV-345-CB
		7" x 1" x 7/8"	Offset	GP	Gray	VR-7, VR-10	VTRW-8	GV-280
		7" x 1" x 7/8"	Offset	CB	Blue	VR-7, VR-10	Goodson Spec	GV-280-CB
		7" x 1" x 7/8"	Offset	T	Green	VR-7, VR-10	VTRW-7	GV-282
		7" x 1" x 7/8"	Offset	S	White	VR-7, VR-10		GV-281
		7" x 1" x 7/8"	Offset	T	Green	VR-7, VR-10	Goodson Spec	GV-282A
		7" x 1" x 7/8"	Offset	GP	Orange	VR-7, VR-10	Radiac Spec	F372239 <small>Radiac</small>
		7" x 1" x 7/8"	Offset	GP	Ruby	VR-7, VR-10	Radiac Spec	F377419 <small>Radiac</small>
		9" x 1 1/4" x 1 1/2"	Offset	GP	Orange	VR-9, VR-12		GV-725
		9" x 1 1/4" x 1 1/2"	Offset	S	Pink	VR-9, VR-12		GV-726
		9" x 1 1/4" x 1 1/2"	Offset	T	Green	VR-9, VR-12		GV-727
		9" x 1 1/4" x 1 1/2"	Offset	S	Ruby	VR-9, VR-12	Nitrite Coated Diesel	GV-728
		3" x 1 1/4" x 5/8"	Cup	GP	Gray	VR-7, VR-10	VTRW-9	GV-237
		3" x 1 1/4" x 5/8"	Cup	CB	Blue	All models except VL	Goodson Spec	GV-237-CB
100 x 50 x 20mm	Stem	3" x 1 1/4" x 5/8"	Cup	GP	Gray	VR-7, VR-10	Radiac Spec	F336036 <small>Radiac</small>
		100 x 50 x 20mm	Cup	GP	White	VR416, VR-516, VTRW-3	7606	GV-928

Colors may vary due to manufacturing process. All valve refacing wheels are guaranteed for 1 year from original purchase date.



Valve Refacing Wheels

Colors may vary due to manufacturing processes. All valve refacing wheels are guaranteed for 1 year from original purchase date.



video available

Scan the code with your smart phone or other smart device camera.



To Fit	Use	Dia x Ht x Arb	Shape	Type	Color	Fits Models	OE No.	Order No.
Skil Snap-On	Valve	5" x 3/4" x 5/8"	Offset	GP	Gray	All models	7556/VW80	GV-658
		5" x 3/4" x 5/8"	Offset	S	White	All models	VW80S	GV-659
	Stem	4" x 1" x 5/8"	Cup	GP	Gray	All but Skil 491	7557/VR2M89	GV-345
Sioux™	Valve	4" x 1" x 5/8"	Cup	CB	Blue	All but Skil 491	Goodson Spec	GV-345-CB
		4" x 1" x 5/8"	Offset	CB	Blue	All but 680, 682, 285, 956	Goodson Spec	GV-146-CB
		4" x 1" x 5/8"	Offset	GP	Gray	All but 680, 682, 285, 956	78SP	GV-147
		4" x 1" x 5/8"	Offset	GP	Black	All but 680, 682, 285, 956	78E	GV-148
		4" x 1" x 5/8"	Offset	S	Ruby	All but 680, 682, 285, 956	Goodson Spec	GV-144
		4" x 1" x 5/8"	Offset	T	Green	All but 680, 682, 285, 956	Goodson Spec	GV-150
		5" x 1" x 5/8"	Offset/20°	GP	Pink	Thor 299 & 300	Goodson Spec	GV-156
		7" x 1 1/16" x 1 3/4"	Str./15°	GP	Orange	680, 956, 2001 & 2075	Goodson Spec	GV-270
		7" x 1 1/16" x 1 3/4"	Str./15°	CB	Blue	680, 956, 2001 & 2075	Goodson Spec	GV-270-CB
		7" x 1 1/16" x 1 3/4"	Str./15°	S	White	680, 956, 2001 & 2075	177	GV-271
		7" x 1 1/16" x 1 3/4"	Str./15°	T	Green	680, 956, 2001 & 2075	174	GV-272
		7" x 1 1/16" x 1 3/4"	Str./15°	GP	Ruby	2001, 2075, 680 & 956	Radiac Spec	A379613 <small>Rediac</small>
		7" x 1 1/16" x 1 3/4"	Str./15°	T	Green	2001, 2075, 680 & 956	Radiac Spec	A340229 <small>Rediac</small>
	Stem	4" x 1" x 5/8"	Cup	GP	Gray	All but 682 & 685	81 (73533)	GV-345
		4" x 1" x 5/8"	Cup	CB	Blue	All but 682 & 685	Goodson Spec	GV-345-CB
		4" x 1" x 5/8"	Offset	GP	Gray	All but 682 & 685	Radiac Spec	F336037 <small>Rediac</small>
Sunnen® (TA) S&D	Valve	6" x 1 1/16" x 3/4"	Flared	GP	Black	VR6500, all S&D	Sunnen Spec	VR602
		6" x 1 1/16" x 3/4"	Flared	GP	Black	VR6500, all S&D	VR602	GV-766
		6" x 1 3/8" x 3/4"	Flared	T	Black	VR6500, all S&D	Sunnen Spec	VR603
		6" x 1 3/8" x 3/4"	Flared	S	Black	VR6500, all S&D	Sunnen Spec	VR604
		6" x 1 3/8" x 3/4"	Flared		Black	VR6500, all S&D	Sunnen Spec	VR605
		6" x 1 3/8" x 3/4"	Cup		Black	TR6700 Tappet Grinder	Sunnen Spec	VR606
		6" x 1 3/8" x 3/4"	Flared	GP	Black	TR6700	Sunnen Spec	VR607
		6" x 1 3/8" x 3/4"	Flared	GP	Gray	VR6500	Radiac Spec	F345291 <small>Rediac</small>
		6" x 1 3/8" x 3/4"	Flared	GP	Black	VR7000, VR8000	Sunnen Spec	VR1702
		6" x 1 3/8" x 3/4"	Flared		Black	VR7000, VR8000	Sunnen Spec	VR1703
		6" x 1 3/8" x 3/4"	Flared	T	Gray	VR7000, VR8000	Sunnen Spec	VR1704
	Stem	5" x 1 3/8" x 3/4"	Cup	S	White	VR6500, all S&D	Sunnen Spec	VR601
		6" x 1 3/8" x 3/4"	Cup	GP	Black	VR7000, VR8000	Sunnen Spec	VR1701
Winona	Valve	5" x 3/4" x 5/8"	Off./Bev.	GP	Gray	E, Y, YW, X, XA	75399	GV-658
Van		5" x 3/4" x 5/8"	Off./Bev.	S	White	K500HM, K403CM	75400	GV-659
Norman	Stem	4" x 1" x 5/8"	Cup	GP	Gray	All but 500 & CRW	40352	GV-345
		4" x 1" x 5/8"	Cup	CB	Blue	All but 500 & CRW	Goodson Spec	GV-345-CB

Colors may vary due to manufacturing process. All valve refacing wheels are guaranteed for 1 year from original purchase date.

Mineral Based Valve Grinding Oil

- Long-lasting
- Cools while grinding
- Removes particles for a better finish
- Inhibits rust
- Prevents rancidity, foaming & deposits



Size	Order No.
1 gallon / 3.79 L	VGO-10
5 gallons / 18.93 L	VGO-50

Severe Duty Mineral Based Valve Refacer Oil For Titanium, Inconel®, Stainless Steel & Stellite

- Mineral Based
- Includes additives to improve cutting performance under high pressure



Size	Order No.
1 gallon / 3.79 L	VGO-SD10
5 gallons / 18.93 L	VGO-SD50

Valve Refacing

CYLINDER HEAD REBUILDING

CLEANING, ASSEMBLY & SAFETY

SHORT BLOCK REBUILDING


CRANKSHAFT/ FLYWHEEL GRINDING

MISCELLANEOUS TOOLS & SUPPLIES

BRAKE SERVICE TOOLING

MEASURING TOOLS


V-TWIN & METRIC HARD PARTS



Use VG-STOP for extra long stemmed valves


Adaptor for 1/2" Chucks

- For small diameter valves
- Collet cover range from 2.8mm to 6.5mm
- Hardened steel collet holder fits any machine with a 1/2" chuck
- Collet seats in retainer nut for fast, easy removal
- Internal stop adjusts, allowing you to reface an entire set of valves to identical specs quickly
- Start with the set then replace collets as needed (collets will not work without the holder)
- Use the Adaptor Stop to machine longer valve stems

Description	Range	Order No.	Incl.
Full Set		UVRC-46	▼
Steel Collet Holder (collets MUST be used)		UVRC-46R	X
	Collets 3.5 to 4.0mm (.138" to .158")	UVRC-4.0MM	X
	4.5 to 5.0mm (.177" to .196")	UVRC-5MM	X
	5.0 to 5.5mm (.196" to .216")	UVRC-5.5MM	X
	5.5mm to 6.0mm (.216" to .236")	UVRC-6.0MM	X
	6.0mm to 6.5mm (.236" to .256")	UVRC-6.5MM	X
Adaptor Stop		VG-STOP	X



Find out how to expand the capacity of your valve refacer to accept smaller valves. Scan the code at right with your smart phone or other smart device for instant access.



Valve Stem to Valve Face Concentricity Gauge

- Accurate to .001"
- Features a rugged, positive stop – set it once and do an entire set of valves • Use before grinding to eliminate needless cleaning & machine time • Use after refacing to ensure stem concentricity • Also check pilots and other small parts for concentricity
- For stems as small as 4mm
- Order No. VCG-16



GMC-VST

GMC-AG300



GMC-RIMAC



GMC-PRF

Sun-Dura® Canvas Machine Covers

- Heavy-weight, breathable black Sun-Dura® fabric won't hold in moisture
- Several sizes to fit a variety of machines
- All covers will fit other machines, just match your machine's dimensions to the cover dimensions
- Covers are opaque, pictures for demonstration only

Fits Machine	Dimensions	Order No.
Ring Filer	13"L x 7 1/2"D x 7 1/2"H	GMC-PRF
VST-2000 Spring Tester	10"L x 14"D x 18"H	GMC-VST
AG-Series Precision Gauge	8"L x 8"W x 4"D	GMC-AG300
Rimac Spring Tester	32"dia. x 18 1/2"H (tapers)	GMC-RIMAC



Mix 1 part grinding aid to 4 parts refacer oil

Valve Grinding Aid For Titanium, Stainless & Stellite Valves

- Not water soluble - add to your mineral based Valve Grinding Oil for better finish on titanium, stainless steel and stellite valves
- Mix ratio: 1:4 • Won't hinder your regular valve grinding process
- Seeks out, and bonds to hot metals
- Ideal for grinding hard metal racing valves • 32 oz. / 946 mL
- Order No. VGA-T32

Replacement Parts

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS



Replacement V-Belts for Sunnen® VGS-20 Seat & Guide Machine


- Poly V-Belts
- Milled construction
- Shippable worldwide

Application	Length	Replaces OE#	Order No.
Drive	22"	PDB-310A/ST-467X	VGS-20-22
Countershaft	30"	PDB-309A/ST-467W	VGS-20-30



Valve Refacer Steady Rest Shoes for Sunnen® VR-7000 & VR-8000

- Sold by the pair
- Order No. **SUN-1202A**




Replacement Parts for CV-616 Honing Machine

Replacement Belts	Order No.
Timing Belt (45"L x 1"W)	CK-252
Flat Belt (51 $\frac{1}{2}$ " x 3/4"W)	CK-192A
Replacement Fiber Planetary Gear Set	CK-234A

Sunnen VR-6500 Valve Refacer Replacement Belts

- 2 sizes available
- Shippable worldwide



Belt Type	Length	OE Number	Order No.
Drive Belt	11"	PDB-305A	VR-6500-11
Jack Shaft Belt	17"	PDB-306A	VR-6500-17
Spindle Belt	23"		VR-6500-23

Diamond dressers shown at approximately actual size



Diamond Dresser Tools for Common Valve Refacers

- Select from Standard or Premium Grade • See the complete assortment of diamond dresser tools on pages 114 and 115.

	Machine	Description	Carat	Standard	Premium
Valve Refacers	B&D, Skil, Sioux™, Thor, VanDom, WVN	$\frac{3}{8}$ " x $1\frac{1}{2}$ "	$\frac{1}{8}$	G-1	G-1P
	Kwik-Way, Tobin Arp (S&D)	$\frac{5}{16}$ " x $2\frac{1}{2}$ "	$\frac{1}{8}$	G-3	
	Kwik-Way, Valve Master (1714)	$\frac{1}{2}$ " x $3\frac{1}{4}$ " 20NF	$\frac{1}{8}$	G-4	
	Sioux™ (1713, 1715), IDL, WVN (CG50, CG80)	$\frac{3}{8}$ " x $2\frac{3}{4}$ " 24NF	$\frac{1}{8}$	G-5	G-5P
	IDL, WVN (CG50, CG80)	$\frac{3}{8}$ " x $3\frac{1}{4}$ " 24NF	$\frac{1}{8}$	G-80	
	US	$\frac{7}{16}$ " x 2"	$\frac{1}{8}$	G-6	
	Skil (Talent)	$\frac{5}{16}$ " x $2\frac{1}{4}$ " 18NC	$\frac{1}{8}$	G-9	
	Kwik-Way	$\frac{7}{16}$ " x $2\frac{3}{4}$ " 20NF	$\frac{1}{8}$	G-17	G-17P

full service ...fast



"In addition to the wide selection of tools and supplies found in this catalog, we have access to hundreds more hard-to-find tools. If you're looking for a special tool, call us and we'll help you find it."

- Cheryl, Goodson Purchasing, 3 years of service

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS



Replacement Belts For Kwik-Way Valve Refacers

Application	Machine	Order No.
1 Spindle Belt 14.5"L "O" Ring - 1 Pr.	SVS II	000-2303-62
2 Chuck Belt 10" Cog, 50 tooth	SVS II	001-1899-90
3 Spindle Belt 18" Serpentine	SVS	001-1905-20
4 Chuck Belt 12" Cog, 60 tooth	SVS or VS	001-1899-99
5 Spindle Belt 16" V-Belt	VS	001-1900-67
6 Chuck Belt 19" 120 tooth	VS	001-1900-75

Replacement Chuck Balls For Kwik-Way Valve Refacers

- Measure chuck ball diameter before ordering to ensure correct replacement • 6 per set




enlarged
to show
detail

Diameter	Order No.
1/2"	010-2101-27
17/32"	010-2101-35



Replacement Bearing Cap for Sioux™ 1710 Electric Driver

- Order No. SX-23694



Replacement Brush Set for Sioux™ 1710 Electric Driver

- Carbon brushes for armature
- Measure 3/8" x 1/4"
- Order No. SX-18004



Replacement Switch for Sioux™ 1710 Electric Driver With Plastic Handle

- 125/250 VAC or 125VDC
- 2 Pole • Measures 1.87"L x 0.875"W x 1.07"H
- Order No. SX-18204



Replacement Bearing Cap for Sioux™ 1792 Pneumatic Driver

- Order No. SX-33970















◀ Collet is
unavailable
from OE



◀ Replace with
two-piece set

Collet for Black & Decker™ Valve Refacers

- Two-piece set replaces the Black & Decker Twin Grip collet (no longer available)
- Remove the damaged, worn or broken collet and replace with this set
- Accommodates 1/4" (6.35mm) to 3/8" (9.53mm) valve stems
- Order No. BVR-38



Replacement Parts for Sioux™ Valve Refacers

Description	Fits Model No.	Order No.
A- Chuck Balls (3pc.)	680, 2075	24185
B- Chuck Springs (9pc.)	680, 2075	SX-53615
C- Spindle Belt 28 5/16" x 1 1/2" 5 groove	2075	SX-65117
D- Serpentine 29 3/8" x 1 1/2" 5 groove	680	SX-14471
E- Cog Style 24" x 1 1/2" 120 teeth	680	SX-14467
F- Chuck Belt 23 3/8" x 3/8" 115 teeth	2075	SX-14473
G- Replacement Belt for Grinding Head Fits Serial #s up to 34999 (2 belts)	645	SX-14400
H- Chuck Belt Fits Serial #s 34999 & up (also coolant pump belt for #s 35217 & up)	645	SX-14401
J- Belt for Motor Shaft; Fits Serial #s up to 34999	645	SX-14402
K- Coolant Pump Belt; Fits Serial #s 34999-35216	645	SX-14403
L- Replacement Belt for Grinding Head; Fits Serial #s 35000-58700	645	SX-14453
M- Replacement Belt for Grinding Head; Fits Serial #s 58701 & up	645	SX-14461
N- Belt for Motor Shaft; Fits Serial #s 35000 & up	645	SX-14445
O- Replacement Switch (1100V, AC)	2001, 2075	SX-18221

tech tips

from the techxperts™
For best results,
limit speed to
175 RPM

High Speed Steel Core Drill/Reamers

- Save time — drill and ream in a single pass
- Top-quality, high speed steel
- Prepares the guide bore for standard OD valve guide inserts
- Several shank designs to fit most Seat & Guide machines
- For best results limit speed to 175 RPM

High Speed
Steel Core Drill/
Reamers are
62 to 64 Rc

Steam-Oxide
Coating for Chip
Lubricity

Fits	Size	mm	Order No.
Peterson and K.I. ½" round shank	.375" x .500"	9.5x12.7	CDR-6197G
Serdi ¾" with flat	.275" x .437"	7.0x11.1	CDR-7192G
	.275" x .500"	7.0x12.7	CDR-7193G
	.312" x .437"	7.9x11.1	CDR-7194G
	.312" x .500"	7.9x12.7	CDR-7195G
	.343" x .500"	8.7x12.7	CDR-7196G
	.375" x .500"	9.5x12.7	CDR-7197G
Cobalt Core Drills/ Reamers ½" round shank	.275" x .437"	7.00x11.1	CDR-274-CB
	.275" x .500"	7.00x12.7	CDR-275-CB
	.311" x .5628"	7.90x14.3	CDR-563-CB
	.312" x .500"	7.92x12.7	CDR-312-CB
	.343" x .500"	8.71x12.7	CDR-343-CB
	.373" x .625"	9.47x16.5	CDR-625-CB
	.375" x .500"	9.53x12.7	CDR-375-CB

sized for diesel



Valve Guide Tooling For 5.9 L, 24 Valve, 7mm Cummins

- To replace integral guides used in this diesel cylinder head
- Replacement guides are .502/.511" stepped to use with OE or replacement seals below

Description	Order No.	Includes	
Complete Kit	CVG-KIT	▼	
Tooling Kit Only	CVG-59KIT	▼	
A Core Reamer (.426" pilot, .485" shank)	CCR-59	1	1
B Core Drill (7mm pilot, .429" shank)	CCD-59	1	1
C Guide Driver (7.0mm)	PHL-2235-G	1	1
D Cast Iron Valve Guide (Exhaust)	CIG-3022		12
E Cast Iron Valve Guide (Intake)	CIG-3021		12
F Exhaust Seals (12 pk.)	CVS-59E		1
G Intake Seals (12 pk.)	CVS-59i		1

tech tips

from the techxperts™ This application requires you to perform all machining and guide installation from the spring side of the head.



Piloted Core Drills and Reamers

- CNC-machined to .0003" T.I.R. or less
- Ideal for any Bridgeport-type (collet driven) machine
- Use dry at 175 to 225 RPM

Piloted Core Drills

- Center accurately in the guide
- Cutting angle prevents the bit from wandering due to irregular guide wear
- Flutes are designed to enlarge bores quickly

Precision Reamers

- Pilot size is carefully matched to the OD of the related core drill
- Assures accurate location of the reamer for smooth, vibration free operation
- Gives proper interference fit to match manufacturer specifications



Find out more about Piloted Core Drills & Reamers. Scan the code at right with your smart phone or other smart device for instant access



High Speed
Steel Core Drill/
Reamers are
65 to 67 Rc

Bronze-Oxide
Coating for
Chip Lubricity

Core Drills				Core Reamers		
	OD	Pilot	OE No.	Order No.	OD	OE No.
DCM Tech, Peterson / K.I. 1/2" Round	.4687"	.312"	DP-1550	DPP-1511B	.500"	66-02147, RR-115
Sunnen® / Tobin-Arp 1/2" with Flat	.490"	.312"	VGS-156A	DTA-2082B	.500"	VGS-162A
	.490"	.343"	VGS-152A	DTA-2082	.500"	VGS-162A
	.490"	.371"	VGS-153A	DTA-2083	.500"	VGS-162A
Universal .429" Round Shank	.429"	7mm	sized for diesel	CCD-59	.4365"	Use for Ford 6.0L Diesel
	.429"	7mm		CCD-59	.4375"	Use for Ford 6.0L Diesel
	.429"	7mm		CCD-59	.5000"-.5003"	Use for 24V Cummins
			Use Core Drill/Reamers (CDR) in chart above for sizing		.562"	.500" pilot
	.541"	8mm		CCD-550	.550"	Use for 12V, 5.9 Cummins
						CCR-550

Note: For the best performance, Core Drills and Reamers should be used in matched pairs. If you order a drill slightly smaller or larger than the OE specification to fit your machine, please order the matching reamer listed immediately to the right of the drill in the table.

Bronze Reaming Oil

- Prevents build-up • Extends reamer life • Improves valve guide finish

Size	Order No.
1 Pint / 473.2mL	BW-303-G
1 Quart / 946.4mL	BW-303A-G
1 Gallon / 1.893L	BW-305-G



tech tips
from the techxperts™

For best results always use Carbide Reamers with Bronze Reaming Oil (BW-303A-G)

Extended non-cutting pilot section for easier alignment with the guide

Pilot portion of reamer features 4 flutes to deliver more cutting oil to the work piece

Reamer body features 8 flutes to cut bronze valve guides quickly, accurately and repeatably

1.750"

2.365"

1.935"

tech tips
from the techxperts™

Once used on cast iron, do NOT use on bronze.

Small Reamers for Cast Iron or Bronze

- Premium quality reamers with tough cobalt flutes for long life in cast iron or bronze • Square drive shank
- Use at 200 to 300 RPM
- OAL is 4.50" (nominally)

Inch	mm	Shank Dia.	Drive Dia.	Order No.
.1575"	4.00	.152"	.112"	MR-4MM
.1771"	4.50	.173"	.112"	MR-4.5MM
.1968"	5.00	.187"	.138"	MR-5.0MM
.1980"	5.03	.187"	.136"	MR-198
.2165"	5.50	.206"	.162"	MR-5.5MM
.2360"	6.00	.224"	.160"	MR-6.0MM
.2755"	7.00	.246"	.182"	MR-7.0MM

Solid Carbide Valve Guide Reamers Specifically Designed For Use Only With Bronze Guides

- Unique 8-flute body design with 4-flute pilot for longer tool life
- Cutting geometry requires less torque to drive the reamer
- More rigid tool construction
- Faster feeds than conventional design
- Non-cutting pilot allows easier alignment with guide
- Simply the best bronze valve guide reamer we've created!
- Use at 300 to 400 RPM • OAL: 6.00" (nominal)
- Pilot measures approximately .005" smaller than cutting diameter

Inch	mm	Order No.	Inch	mm	Order No.
.1771"	4.50	HGR-4.5MM*	.3115"	7.91	HGR-3115
.1968"	5.00	HGR-5.0MM*	.3120"	7.92	HGR-3120
.2165"	5.50	HGR-5.5MM*	.3141"	7.98	HGR-3140
.2362"	6.00	HGR-6MM	.3150"	8.00	HGR-8MM
.2750"	7.00	HGR-7MM	.3410"	8.66	HGR-3410
.2766"	7.03	HGR-2766	.3420"	8.69	HGR-3420
.2770"	7.04	HGR-2770	.3425"	8.70	HGR-3425
.3110"	7.90	HGR-3110	.3430"	8.71	HGR-3430
*Pilot, Flute & Shank Dimensions slightly smaller; call for specific details			.3435"	8.72	HGR-3435
			.3440"	8.74	HGR-3440

High Speed Steel Finish Reamers Exclusively for Cast Iron

Precision size cast iron guides. Piloted and made from the finest tempered steel. With proper care, these reamers will accurately size multiple guides without losing their efficient cutting action. **NOT for hardened or bronze guides.** Use at 400 to 500 RPM. Pilot area measures .012" smaller than cutting diameter.

3/16" Square Drive		
Inch	mm	Order No.
.2165"	5.50	WR-5.5MM-G
.217"	5.51	WR-217-G
.218"	5.54	WR-218-G
.236"	6.00	WR-6MM-G
.250"	6.35	WR-250-G
.256"	6.50	WR-6.5MM-G
.260"	6.60	WR-260-G
.273"	6.93	WR-273-G
.274"	6.96	WR-274-G
.275"	6.99	WR-275-G
.2755"	7.00	WR-7MM-G
.276"	7.01	WR-276-G
.277"	7.03	WR-277-G
.278"	7.06	WR-278-G
.281"	7.14	WR-281-G

1/4" Square Drive		
Inch	mm	Order No.
.310"	7.87	WR-310-G
.311"	7.90	WR-311-G
.312"	7.92	WR-312-G
.313"	7.95	WR-313-G
.314"	7.98	WR-314-G
.315"	8.00	WR-8MM-G
.316"	8.03	WR-316-G
.317"	8.05	WR-317-G
.341"	8.66	WR-341-G
.342"	8.69	WR-342-G
.343"	8.71	WR-343-G
.3435"	8.72	WR-3435-G
.344"	8.74	WR-344-G
.345"	8.76	WR-345-G
.346"	8.79	WR-346-G
.354"	9.00	WR-9MM-G
.355"	9.02	WR-355-G
.356"	9.04	WR-356-G
.358"	9.09	WR-358-G

1/4" Square Drive		
Inch	mm	Order No.
.372"	9.45	WR-372-G
.373"	9.47	WR-373-G
.374"	9.50	WR-374-G
.375"	9.52	WR-375-G
.376"	9.55	WR-376-G
.377"	9.58	WR-377-G
.378"	9.60	WR-378-G
.379"	9.63	WR-379-G
.380"	9.65	WR-380-G
.386"	9.80	WR-386-G
.394"	10.00	WR-10MM-G
.395"	10.03	WR-395-G
.405"	10.29	WR-405-G
.433"	11.00	WR-11MM-G
.436"	11.07	WR-436-G
.437"	11.10	WR-437-G
.453"	11.51	WR-453-G
.472"	12.00	WR-12MM-G
.499"	12.67	WR-499-G
.500"	12.70	WR-500-G

tech tips
from the techxperts™

For best results, use high speed steel finish reamers exclusively on cast iron. Ream without oil.

See page 37 for Drive Adaptors

... another
satisfied
customer

"I have been using the Goodson Hyper-Finish Diamond Valve Guide Hone for years. It makes quick and easy work for valve guide sizing. It will not load up, keeps the guide straight and true and gives great results every time. Best money I've spent on a tool."

- Wes Brown, Cycle-Rama, Inc., Pinellas Park, Florida, Goodson customer since 1999



Introduced to the World Market in 2010!

Black Diamond Hyper-Finish™ Valve Guide Sizing System

The **NEW** Black Diamond Hyper-Finish Diamond Valve Guide Sizing System is better than ever. CNC manufactured tooling now has greater accuracy, more durability and better quality. Mandrels are made of black anodized hard plated steel. Not for use on Aluminum Heads.

With this easy-to-use system you can size guides from .193" to .389" (5.00 to 9.90mm) just by switching out mandrels. Mandrels also sold individually. The Drive Head (**HF-100**) fits every size mandrel assembly shown in the chart below, features a quick change set-up and now has an extended reach for more flexibility. Hyper-Finish Tooling is NOT interchangeable with the Sunnen® Valve Guide Hone Set (p. 35). Use at 200 RPMs max. **NOTE: BHFS-040 & BHFS-050 are the only replacement abrasives that will fit old style mandrels.**

Size	Range		Mandrel Assembly	Abrasive	Replacement	Replacement	Drive	Guide
	Inch	mm	(abrasive & mandrel)	Length	Abrasive	Mandrel	Head	Brush
5.0mm	.193"-.203"	4.90 - 5.15mm	BHFM-193C	40mm	BHFS-010	BHFM-193	HF-100	GVP-9N
5.5mm	.212"-.232"	5.40 - 5.90mm	BHFM-212C	40mm	BHFS-020	BHFM-212	HF-100	GVP-10N
6.0mm	.232"-.253"	5.90 - 6.40mm	BHFM-232C	40mm	BHFS-020	BHFM-232	HF-100	GVP-10N
6.5mm	.251"-.271"	6.40 - 6.90mm	BHFM-251C	40mm	BHFS-020	BHFM-251	HF-100	GVP-11N
7.0mm	.271"-.311"	6.90 - 7.90mm	BHFM-271C	80mm	BHFS-040*	BHFM-271	HF-100	GVP-11N
.312"	.311"-.350"	7.90 - 8.90mm	BHFM-307C	80mm	BHFS-050*	BHFM-307	HF-100	GVP-1N
.343"	.334"-.374"	8.50 - 9.50mm	BHFM-344C	80mm	BHFS-050*	BHFM-344	HF-100	GVP-2N
.375"	.350"-.389"	8.90 - 9.90mm	BHFM-350C	80mm	BHFS-050*	BHFM-350	HF-100	GVP-3N


Included in
Master Kit

*Only these replacement abrasives will fit old style mandrels

Choose from the Standard Master Kit or Build Your Own!

Standard Master Kit includes: Driver Head, 4-Mandrel Assemblies (see chart above), 4-Nylon Valve Guide Brushes (7mm to 3/8") and 8 oz. Diamond Honing Oil.
Order No. BHF-KIT

Custom Kit includes: Driver Head, 4-Mandrel Assemblies (select from chart above), 4-Nylon Valve Guide Brushes (you pick the sizes - see chart above) and 8 oz. Diamond Honing Oil.
Order No. BHF-KIT-CUSTOM



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS



Adjustable hose lets you
direct coolant right where
you need it

Perforated steel grate lets oil through
and can be removed for cleaning


Rolled front edge directs splashed
coolant back into the sump

½" diameter holes (18) and
1" diameter holes (2) drilled
in the top plate provide ample
tool storage

Benchtop Valve Guide Finishing Station

This Goodson designed valve guide finishing station incorporates the features you requested such as:

- Large 5-gallon capacity coolant sump
 - Integral high output pump - 1/150 HP oil filled submersible pump, 115V 60 cycle, single phase heavy-duty motor
 - Aluminum construction for durability and easy cleaning
 - Perforated steel grate allowing used coolant through to recirculate
 - Removable steel grate for easy maintenance
 - Built-in, easy-to-reach storage for tools
- Buy the complete kit and save!**



Description	Order No.	Incl.
Complete 110V Valve Guide Finishing Station Kit	HF-1000KIT	▼
Honing Station Only - 110V	HF-1000	x
Universal Head Holders	HH-200	x
Pump 110V	HF-PUMP	x
5 Gallons Diamond Honing Oil	DHO-50	x


Export voltage available, contact Goodson for additional information

⅜" diameter shank pilot

Carbide or High Speed Steel Valve Guide Top Cutters

- Matches Seat & Guide machine pilots

Description	Shank	Order No.
Cutters ⅜" High-Speed Steel	.500"	GFH-100
⅜" Carbide	.500"	GFC-200
⅜" High-Speed Steel	.486"	GFH-300
¾" (.1875")	.312" (7.93mm)	GFP-312
Shank Pilots .343" (8.73mm)		GFP-343
.375" (9.53mm)		GFP-375
.437" (11.11mm)		GFP-437
.500" (12.70mm)		GFP-500



Cutter



Valve Guide Top Collar

- Supports guide top during machining
- Protects against damage or breakage
- Ideal for high-performance work, and for installing thin-wall liners (pages 38-39)

Size	Range	Order No.
.500"	.496" -.504"	VGC-502
.530"	.526" -.534"	VGC-530
.566"	.562" -.570"	VGC-566



**Goodson
exclusive**

Diamond Honing Oil

- For high pressure honing
- Recommended for use with Black Diamond Valve Guide Sizing System



Size	Order No.
8 oz./237mL	DHO-8
1 Gallon/3.79L	DHO-10
5 Gallons/18.93L	DHO-50



Valve Guide OD Chamfer Tool

- Improve oil deflection
- Universal cutter chamfers any OD from ¼" to ⅝" (6.35-15.9mm)
- Most precise when used in a Seat and Guide Machine
- Order No. GCT-35



full service
...fast



"We take our job of getting your order to you quickly very seriously. We use several different carriers allowing us to get your products to you when you need them at a price you can afford."

- Ashley, Goodson Shipping Department, 4 years of service



Valve Guide Hone Set

- Sets-up fast • Easy to use!
- Produces straight, round holes for top-quality work
- Ideal for high-performance applications
- Use a low RPM, 1/2" drill for driving power (200 RPM max.)
- Silicon-Carbide Roughing & Finishing Stones
- Sunnen® tooling is NOT interchangeable with Goodson Black Diamond Hyper-Finish (page 33)

Truing Sleeve

Adaptor

P-180 Hone Head

Silicon-Carbide Honing Stone

Wedge (included with Mandrel)

Mandrel



Description	Order No.
Sunnen Honall® Valve Guide Hone Set	P-190
Includes: Head & Driver, Mandrels & Sleeves (1 of ea. for sizes - 5/16", 11/32", 3/8", & 7/16")	
Adaptors: (1) PK10-A & (1) PK12-A, Stones L10-J69 & L12-J67, Case & instructions	
Sunnen Honall® Valve Guide Hone Head & Driver only	P-180
BL Mandrels (Order Mandrel, Sleeve, Stones, Adaptor & Stone Retainer Separately)	

Range			Mandrel	Sleeve	Roughing Stones	Finishing Stones	Adaptor	Stone Retainer
Size	Inch	mm	Order No.	Order No.	Order No.	Order No.	Order No.	Order No.
3.8mm	.150"-.156"	3.8-3.9	BL5150CS	S150	L5J67 (12)	L5J95 (12)	PSK6-A ‡	LN3025C
4.5mm	.175"-.180"	4.4-4.6	BL5175CS	S175	L5J67 (12)	L5J95 (12)	PSK6-A ‡	LN3025C
5mm	.195"-.200"	4.9-5.1	BL6-195CS	S-195	L6-J47 (12)	L6-J67 (12)	PSK6-A ‡	LN-3087C
5.5mm	.210"-.215"	5.3-5.5	BL6-210CS	S-210	L6-J47 (12)	L6-J67 (12)	PSK6-A ‡	LN-3087C
	.215"-.220"	5.5-5.6	BL6-215CS	S-215	L6-J47 (12)	L6-J67 (12)	PSK6-A ‡	LN-3087C
	.225"-.230"	5.7-5.8	BL6-225CS	S-225	L6-J47 (12)	L6-J67 (12)	PSK6-A ‡	LN-3087C
6mm	.230"-.235"	5.8-6.0	BL6-230CS	S-230	L6-J47 (12)	L6-J67 (12)	PSK6-A ‡	LN-3087C
	.235"-.240"	6.0-6.1	BL6-235CS	S-235	L6-J47 (12)	L6-J67 (12)	PSK6-A ‡	LN-3087C
1/4"	.245"-.250"	6.2-6.4	BL8-245AS	S-245	L8-J47 (6)	L8-J67 (6)	PK8-A	-----
	.250"-.255"	6.4-6.5	BL8-250AS	S-250	L8-J47 (6)	L8-J67 (6)	PK8-A	-----
6.6mm	.255"-.260"	6.5-6.6	BL8-255AS	S-255	L8-J47 (6)	L8-J67 (6)	PK8-A	-----
7mm	.270"-.275"	6.8-7.0	BL8-270AS	S-270	L8-J47 (6)	L8-J67 (6)	PK8-A	-----
	.275"-.280"	7.0-7.1	BL8-275AS	S-275	L8-J47 (6)	L8-J67 (6)	PK8-A	-----
5/16" ♦	.308"-.316"	7.8-8.0	BL10-308AS	S-308	L10-J47 (6)	L10-J69 (6)	PK10-A	-----
11/32" ♦	.339"-.347"	8.6-8.8	BL10-339AS	S-339	L10-J47 (6)	L10-J69 (6)	PK10-A	-----
23/64"	.354"-.362"	9.0-9.2	BL10-354AS	S-354	L10-J47 (6)	L10-J69 (6)	PK10-A	-----
3/8" ♦	.370"-.385"	9.4-9.8	BL12-370AS	S-370	L12-J47 (6)	L12-J67 (6)	PK12-A	-----
7/16" ♦	.432"-.447"	11.0-11.4	BL12-432AS	S-432	L12-J47 (6)	L12-J67 (6)	PK12-A	-----


♦ Included in set Order No. P-190 ‡NOTE: Remove the stone retainer included with the PSK6-A and replace with LN-3087C for valve guide honing

tech tips
from the techxperts™

Ordering Information: The head and driver are interchangeable with the adaptors. Only one head and driver is required. Mandrels are available to cover all popular sizes. Please select from the parts in the photo above and order per size range desired. We suggest you have an adaptor for each mandrel to save change-over time between sizes.

5 Piece Nylon Bristle Valve Guide Brush Set

- Complete kit includes five popular nylon bristle brush sizes
- Brushes measure from 5/16" to 1 1/2" diameter x 2 1/2" L
- Overall Length: 12"
- For more sizes see page 66
- Order No. GVP-SET



6 Piece Valve Guide Flex-Hone® Set

- Kit includes the most popular sizes for valve guide work • 240 Grit Silicon-Carbide

			Order No.	Incl.
6 Pc. Valve Guide Kit			VGF-KIT	▼
Size	mm	OAL		
1/4"	6.4	8"	VGF-6.4MM	x
9/32"	7.0	8"	VGF-7MM	x
5/16"	8.0	8"	VGF-8MM	x
11/32"	9.0	8"	VGF-9MM	x
3/8"	10.0	8"	VGF-10MM	x
7/16"	11.0	8"	VGF-11MM	x

More Valve Guide Flex-Hones® on page 90



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING


CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS



Valve Guide Replacement

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Valve Guide Drivers

- Corrosion-resistant finish 1° negative angle prevents guides from spreading • Rockwell hardness of 45-50
- Pilots are slightly smaller than guide ID for easy removal



Powered Drivers

Standard Sizes			Order No.	Incl.
4-piece Kit			PH-2226-G	▼
Guide ID /mm	Driver OD	Pilot		
.312" / 7.92	.487" / 12.4	.300" / 7.62	PH-2228A-G	
.312" / 7.92	.423" / 10.7	.304" / 7.72	PH-2228-G	x
.343" / 8.71	.422" / 10.7	.336" / 8.53	PH-2229A-G	
.343" / 8.71	.487" / 12.4	.337" / 8.56	PH-2229-G	x
.372" / 9.47	.487" / 12.4	.367" / 9.32	PH-2231-G	x
.437" / 11.10	.612" / 15.5	.429" / 10.90	PH-2230-G	x
Metric Sizes			Order No.	Incl.
6-piece Kit			PH-2600-G	▼
Guide ID /in.	Driver OD	Pilot		
5.0mm / .196"	9.0 / .355"	4.75 / .187"	PH-2250-G	x
5.5mm / .217"	10.5 / .412"	5.21 / .205"	PH-2255-G	x
6.0mm / .236"	10.5 / .412"	5.72 / .225"	PH-2260-G	x
6.6mm / .260"	11.8 / .463"	6.30 / .248"	PH-2234-G	x
7.0mm / .275"	11.0 / .432"	6.60 / .260"	PH-2235-G	x
8.0mm / .315"	11.7 / .462"	7.80 / .307"	PH-2236-G	x
9.0mm / .353"	12.4 / .487"	8.81 / .347"	PH-2237-G	
10mm / .393"	15.5 / .612"	9.82 / .387"	PH-2238-G	
11mm / .433"	15.5 / .612"	10.85 / .427"	PH-2239-G	



Manual Drivers

Standard Sizes			Order No.	Incl.
4-piece Kit			GP-500A-G	▼
Guide ID /mm	Driver OD	Pilot		
.312" / 7.92	.422" / 10.7	.305" / 7.75	GP-431-G	x
.312" / 7.92	.487" / 12.4	.302" / 7.67	GP-531-G	x
.343" / 8.71	.422" / 10.7	.336" / 8.53	GP-533-G	
.343" / 8.71	.487" / 12.4	.336" / 8.53	GP-534-G	x
.372" / 9.47	.487" / 12.4	.367" / 9.32	GP-537-G	x
.437" / 11.10	.611" / 15.5	.428" / 10.87	GP-743-G	x
Metric Sizes			Order No.	Incl.
6-piece Kit			GP-600M-G	▼
Guide ID /in.	Driver OD	Pilot		
6.6mm / .260"	11.7 / .462"	6.22 / .245"	GP-6.6MM-G	x
7mm / .275"	10.7 / .422"	6.78 / .267"	GP-7MM-G	x
8mm / .315"	12.3 / .484"	7.77 / .306"	GP-8MM-G	x
9mm / .353"	12.3 / .484"	8.84 / .348"	GP-9MM-G	x
10mm / .393"	15.5 / .611"	9.82 / .387"	GP-10MM-G	x
11mm / .433"	15.5 / .611"	10.82 / .426"	GP-11MM-G	x




Air Hammer

- Delivers 3500 blows per minute
- Weighs 3 lbs.
- .401" tool opening

Description	Order No.
Air Hammer	AH-335
Replacement Retainer Spring	AH-5RS

Universal Driver Tool

- Will fit Diesel Guide Drivers at right to increase your reach
- 4.75" OAL
- .401" ID
- Order No. CL-7333



Extra-Long Powered Valve Guide Drivers

- For use with overhead cam heads
- 1° negative angle to prevent guide mushrooming
- Pilots are slightly smaller than guide ID • 7.5" long

Guide ID / in.	Driver OD	Pilot	Order No.
4.0mm / .157"	9.0 / .355"	3.80 / .150"	PHL-2240-G
4.5mm / .177"	9.0 / .355"	4.30 / .170"	PHL-2245-G
5.0mm / .196"	9.0 / .355"	4.75 / .187"	PHL-2250-G
5.5mm / .217"	10.5 / .412"	5.21 / .205"	PHL-2255-G
6.0mm / .236"	9.1 / .358"	5.72 / .225"	PHL-2258-G
6.0mm / .236"	10.5 / .412"	5.72 / .225"	PHL-2260-G
6.6mm / .260"	11.8 / .463"	6.29 / .248"	PHL-2234-G
7.0mm / .275"	11.0 / .432"	6.60 / .260"	PHL-2235-G
7.9mm / .312"	10.7 / .423"	7.72 / .304"	PHL-2228-G
8.0mm / .315"	11.7 / .462"	7.80 / .307"	PHL-2236-G
8.7mm / .343"	12.4 / .487"	8.56 / .337"	PHL-2229-G
9.5mm / .375"	12.4 / .487"	9.32 / .367"	PHL-2231-G



Extra Long Manual Valve Guide Drivers

- 8" OAL • Pilot approximately 1" long
- NOTE:** Due to the nature of these valve guide drivers, they cannot be warranted against breakage, but are guaranteed for dimensional accuracy.

Guide ID / in.	Driver OD	Pilot	Order No.
4.0mm / .157"	9.0 / .355"	3.80 / .150"	GPL-2240-G
4.5mm / .177"	9.0 / .355"	4.30 / .170"	GPL-2245-G
5.0mm / .196"	9.0 / .355"	4.75 / .187"	GPL-2250-G
5.5mm / .217"	10.5 / .412"	5.21 / .205"	GPL-2255-G
6.0mm / .230"	9.1 / .358"	5.72 / .225"	GPL-2258-G
6.0mm / .236"	10.5 / .412"	5.72 / .225"	GPL-2260-G

sized for
diesel



Air-Powered Valve Guide Drivers for Diesel Engines

- Drive guides in from the shoulder instead of from the top
- Installing drivers have the proper recess to drive guides in for the correct installed height
- Remove / Install guides faster – no measuring necessary
- For most standard pneumatic tools

	Installer	Order No.	Remover	Order No.
Application	Major/ Counter Bore ID		Shank/Pilot OD	
Cummins	.752" / .503"	DVG-Ci	.595" / .450"	DVG-CR
Cummins 8.3, 6CT	.552" / —	DVG-8.3	.491" / .304"	DVG-71R
Caterpillar 3116	.515" / .475"	DVG-3116	.491" / .304"	DVG-71R
Caterpillar 3126	—	—	.595" / .354"	DVG-3468R
Caterpillar 3406-3408	.709" / —	DVG-3468i	.595" / .354"	DVG-3468R
Detroit GMC 53	.502" / .421"	DVG-53i	—	—
Detroit GMC 71/92	—	—	.491" / .304"	DVG-71R
International DT 466	—	—	.595" / .354"	DVG-3468R

full service
...fast



"We work hard to have the right stock at the right price at the right time so you get your orders on time."

- Nancy, Goodson Inventory Fulfillment Manager, 30 years of service



tech tips
from the techxperts™

Install guides to same height every time!



Adjustable Powered Valve Guide Driver With Replaceable Pilots

- 4140 CRS heat treated to 40-45 Rc
- Standardize the correct installed height on one guide then repeat it on all others
- Screw-in pilots with $\frac{5}{16}$ " - 18 threads • $\frac{6}{16}$ " overall length

Description	Order No.	Includes	
Standard Valve Guide Driver Kit	AVG-STD	▼	
Metric Valve Guide Driver Kit	AVG-MM	▼	
Pneumatic Body Only 5/8"-18 thread	AVG-1	x	x
Installation Sleeve	AVG-3	x	x
Locking Nut	AVG-2	x	x
Replaceable Pilots	Diameter		
	.312"	AVG-312	x
	.343"	AVG-343	x
	.372"	AVG-372	x
	.437"	AVG-437	x
	5.0mm	AVG-5MM	x
	5.5mm	AVG-55MM	x
Use thread locker on pilot to resist loosening while in use.	6.0mm	AVG-6MM	x
	7.0mm	AVG-7MM	x
	8.0mm	AVG-8MM	x
	9.0mm	AVG-9MM	




Watch for the Made In America symbol throughout the catalog

This symbol indicates products manufactured within the United States. We are proud to feature products made by US manufacturers, including many right in our own back yard of Winona, Minnesota.

Valve Guide OD Machining Tool

- Faces the guide top to the correct size
- Sizes the guide OD for press-on seals
- Chamfers the top to prevent seal damage
- Cutters & pilots are interchangeable and chuck into any drill press, portable drill or seat & guide machine



Individual Cutters		
Guide OD		Order No.
.415"	10.5	VSC-415
.428"	10.8	VSC-428
.475"	12.1	VSC-475
.495"	12.6	VSC-495
.500"	12.7	VSC-500
.530"	13.5	VSC-530
.562"	14.3	VSC-562
.625"	15.9	VSC-625

Pilots		
Guide ID		Order No.
.275"	7.0	VP-7MM
.312"	7.9	VP-312
.343"	8.7	VP-343
.375"	9.5	VP-375

Cutter and Pilot Assemblies				
Guide OD		Pilot Size		Order No.
.415"	10.5	.312"	7.9	VSC-415312
.420"	10.7	.312"	7.9	VSC-420312
.428"	10.9	.312"	7.9	VSC-428312
.475"	12.1	.312"	7.9	VSC-475312
.475"	12.1	.343"	8.7	VSC-475343
.500"	12.7	.275"	7.0	VSC-500275
.500"	12.7	.312"	7.9	VSC-500312
.500"	12.7	.343"	8.7	VSC-500343
.500"	12.7	.375"	9.5	VSC-500375
.530"	13.5	.312"	7.9	VSC-530312
.530"	13.5	.343"	8.7	VSC-530343
.530"	13.5	.375"	9.5	VSC-530375
.562"	14.3	.343"	8.7	VSC-562343
.562"	14.3	.375"	9.5	VSC-562375
.625"	15.9	.375"	9.5	VSC-625375

tech tips
from the techxperts™

Right Hand Rotation Only.

For best results, keep your RPM about the same as your hone RPM, use the same rate of speed and number of strokes per minute.

Ultra-Finish Plateau Valve Guide Soft Hones

- Use AFTER guide honing to remove microscopic peaks and scuffs without enlarging the guide ID
- Abrasive impregnated nylon bristles
- Use with liberal amounts of honing oil
- Not interchangeable with Flex-Hones®
- Use with your portable drill or seat and guide machine

Hole in.	Diameter mm	Hone Dia.	Head Length	Overall Length	Order No.
.2187"	5.5	.241"	1.00"	4.00"	UF-5.5MM
.2500"	6.4	.275"	1.25"	4.50"	UF-6.4MM
.2813"	7.0	.309"	1.25"	4.50"	UF-7MM
.3125"	8.0	.343"	1.25"	4.50"	UF-8MM
.3437"	9.0	.378"	1.25"	4.50"	UF-9MM
.3750"	10.0	.413"	1.25"	4.50"	UF-10MM

NOTE: Larger size Ultra-Finish hones on page 92



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

... another
satisfied
customer

"I have been using your products for over 30 years and have never had an issue. Your phone staff is friendly and helpful; my parts are packaged perfectly and the quality of your products is excellent. Keep up the good work."

— Brad Mattei, Mattei's Cycle Supply, New Orleans, LA, Goodson Customer Since 1990

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

tech tips
from the techxperts™
Use with Knurlube

Knurling Arbors

- Piloted for positive centering
- Use by hand or with electric drill & speed reducer
- **Not for use on chilled, hardened or bronze guides**

Inch	mm	Drive	Order No.
.236"	6.00	.1875"	WKA-6MM-G
.275"	7.00	.1875"	WKA-7MM-G
.312"	7.92	.2500"	WKA-312-G
.343"	8.71	.2500"	WKA-343-G
.375"	9.53	.2500"	WKA-375-G
1 Quart Knurlube (946.6mL)			WLB-47-G

Electric Drill Drive Adaptors For Knurling Arbors and/or Reamers

Use **WSR-41-3-G** (¼" sq.) and **WSR-41-4-G** (⅜" sq.) include the **WSR-41-7-G** (⅝" drill adaptor). Clamp ⅜" drive in drill to drive reamers directly.

Description	Order No.
A Drill Adaptor for 3/8" drill	WSR-41-7-G
B ¼" Adaptor for arbors/reamers larger than .281"	WSR-41-3-G
C ⅜" Adaptor for arbors/reamers .281" or smaller	WSR-41-4-G
D Slip on Adaptor (converts WSR-41-3-G to .1875")	WSR-41-5-G

Knurlube

- High pressure lube prevents tool damage
- Extends knurler life by reducing friction and arbor wear

Size	Order No.
8 oz. / 236.6mL	WLB-46-G
32 oz. / 946.4mL	WLB-47-G

Bronze Reaming Oil

- Prevents build-up
- Extends reamer life
- Improves valve guide finish

Size	Order No.
16 oz. / 473.2mL	BW-303-G
32 oz. / 946.4mL	BW-303A-G
1 Gal. / 1.893L	BW-305-G

Valve Guide OD Knurling Tool

- Enlarge guides to fit bore
- Ideal for rare metric sizes and aluminum heads with damaged guide bores
- Works on most materials, **except** chilled or hardened guides

Description	Order No.
Complete Tool	VGK-25
Replacement Knurling Wheel	VGK-25W
Replacement Knurling Rollers (2)	VGK-25R

tech tips
from the techxperts™

Hold guide firmly in Vise, Drill Press or Seat & Guide machine; tighten the knurler and turn it around the guide **by hand**. Increase OD up to .002".

Harley valve guides on page 134

Cast Iron False Valve Guides

Universal Applications

ID	OD	Length	Order No.
.312"	.439"	2.281"	CIG-312
.342"	.502"	3.062"	CIG-342
.372"	.502"	2.750"	CIG-372
.343"	.564"	2.750"	OG-343
.373"	.564"	2.750"	OG-373

24 Valve 7mm Cummins Diesel (.511" seal surface) see tooling, page 31

ID	OD	Length	Order No.
Intake .275"	.502"	1.940"	CIG-3021
Exhaust .275"	.502"	2.020"	CIG-3022
Ford 6.0L (.513" x .659" seal surface) see tooling, page 31			
.275"	.4395"	2.332"	CIG-3055

7.3 Powerstroke Use with Core Drill Reamer CDR-563-CB, page 31

.3146"	.5652"	2.440"	CIG-8476
--------	--------	--------	----------

Manganese Bronze False Valve Guides

Universal Applications

ID	OD	Length	Order No.
.311"	.439"	3.062"	BVG-311
.343"	.502"	2.375"	BVG-343
.372"	.502"	2.375"	BVG-372

Cast Iron and Manganese Bronze Valve Guides for Harley-Davidson on page 134

Universal Repair Guides

- Unfinished ID ready to be reamed with Goodson's exclusive carbide reamers (page 31)
- Manganese bronze

ID	OD	Length	Order No.
7.0mm	.740"	2.700"	UVBG-7MM
.308"	.740"	2.700"	UVBG-308
.341"	.740"	2.700"	UVBG-341
.372"	.740"	2.700"	UVBG-372



Get QualCast Valve Guides from your friends at Goodson

Goodson offers the complete line of QualCast Products for High Performance, Standard Duty and Heavy Duty vehicle engines. Visit the QualCast section of the Goodson website for listings.

Scan the code below with your smart phone or other device for fast access to the QualCast Valve Guide listings on the Goodson website



sized for
diesel



Bronze-Liners & Tooling

Carbide Sizing Balls

- Finished to .00008" roundness
- Within the 90 Rockwell range
- The finished ID of the Bronze-Liner will be .001" smaller than the ball used

Size	Order No.
6.0mm	.2360" CL-5236
	.2370" CL-5237
	.2380" CL-5238
7.0mm	.2760" CL-5276
	.2770" CL-5277
	.2780" CL-5278
5/16"	.3125" CL-53125
	.3130" CL-5313
	.3140" CL-5314

Size	Order No.
8.0mm	.3150" CL-5315
	.3160" CL-5316
	.3170" CL-5317
11/32"	.3430" CL-5343
	.3435" CL-53435
	.3440" CL-5344
	.3445" CL-53445
	.3450" CL-5345
	.3460" CL-5346
3/8"	.3730" CL-5373
	.3740" CL-5374
	.3745" CL-53745
	.3750" CL-5375
	.3755" CL-53755
	.3760" CL-5376

tech tips

from the techxperts™

Always be sure to hold your hand under the cylinder head to catch the carbide ball as it comes out of the guide.



Thin-Wall .030" Bronze-Liners

- Outlast original guides
- Dimples promotes oil retention
- Rounded nose design makes installation quick and easy
- Stripe helps you identify rounded end
- Phosphor-bronze

tech tips

from the techxperts™

Phosphor-Bronze liners outlast original guides and are easy to replace

Stripe helps you quickly identify the round nose end

Rounded nose design makes installation fast and easy

Dimples inside promote oil retention

NOTE: 5.0 & 5.5mm Guides do NOT interchange with competitors' guides. You MUST use our tooling with these guides.

Liner Size	Guide Size	OD	Length	Box of 16 Order No.	Box of 100 Order No.
5.0mm	.030"	2.00"		CL-500	CL-500A
5.5mm	.030"	2.50"		CL-550	CL-550A
6.0mm	.030"	2.50"		CL-600	CL-600A
7.0mm	.030"	2.50"		CL-700	CL-700A
.312"	.030"	2.50"		CL-1220	CL-1220A
8.0mm	.030"	2.50"		CL-1420	CL-1420A
.343"	.030"	3.00"		CL-1640	CL-1640A
.375"	.030"	3.00"		CL-1830	CL-1830A
Overize OD Bronze Liners					
.343" +.002"	.032"	2.50"		CL-1640-2	CL-1640-2A
.375" +.002"	.032"	3.00"		CL-1820-2	CL-1820-2A
.375" +.004"	.034"	3.00"		CL-1820-4	CL-1820-4A

Removal Tool

Remove bronze liners without damaging the bore using the driver tool at right

Description	Order No.
6.0mm	CL-7352
7.0mm	CL-7344
5/16"	CL-7310
8.0mm	CL-7320
11/32"	CL-7330
3/8"	CL-7340

Universal Driver Tool

- Fits all removal tools at left and is designed to work with your air hammer
- .401" ID • 4.75 OAL
- Order No. **CL-7333**



Chamfer Tool & T-Wrench

Use these optional accessories to remove any burrs that may be created when trimming the liner to length

Description	Order No.
Chamfer Tool	CL-5800
T-Wrench	CL-5870



CL-5800

Small Hole Gauge Set

- See if rebuilding or replacing is needed by checking guide wear
- Check guide bosses for proper interference fit during replacement
- Check and maintain correct stem-to-guide ID clearance
- 4-piece set has combined range of .125" to .500"
- Order No. **SHG-4**



Mitutoyo

Split Ball Bore Gauge

- Dial gauge with large contact area
- Measures quickly & accurately to .0001" (.0025mm)
- Works in threaded or knurled guide IDs
- Range: .280" to .400"
- Easy to change contacts
- Includes molded plastic storage case
- Order No. **MVG-34**



premium grade

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS


V-TWIN & METRIC
HARD PARTS

full service
...fast



"If any of our products aren't satisfactory, we want you to send it back. We have a no hassle return policy. Just send it back, freight pre-paid within 60 days and we'll exchange it, fix it or credit your account for the amount of the purchase."

- Kayla, Goodson Customer Service, 3 years of service



6.0mm to 3/8" Bronze-Liner Installation Tool Kits

Phosphor-Bronze is an ideal valve guide material – it's more durable than cast iron, conducts heat away faster and retains lubrication better to reduce wear. Install rugged, thin-wall (.030") Bronze-Liners in cast iron or aluminum heads to repair guides and deliver performance better than new! Plus, Bronze-Liners install quickly with simple tools. If a Bronze-Liner ever wears out, you can quickly and easily replace it with a new one to restore performance. **Removal Tools, page 39.**

Kits include ▼	6.0mm Guides	7.0mm Guides	5/16" Guides
Master Tool Kits	CL-6MM	CL-7MM	CL-312
Carbide Boring Tool	CL-2024C	CL-2007C	CL-2005C
Bushing Kit	CL-2003	CL-2001	CL-2000
Ball Driver	CL-4452P	CL-4446P	CL-4444P
Carbide Sizing Balls	.2370" CL-5237 .2380" CL-5238	.2770" CL-5277 .2780" CL-5278	.3125" CL-53125 .3130" CL-5313
Auto-Driver	CL-3600	CL-3507	CL-3500
Trim Tool	.402" OD CL-5602	.500" OD CL-5600	.500" OD CL-5600
Trim Tool Pilot	CL-5634	CL-5626	CL-5620
Guide Brush	GVP-10N	WCB-44	WCB-44

When Working By Hand, Kits Require Seat Centering Cones - See Chart Below

Kits include ▼	8.0mm Guides	11/32" Guides	3/8" Guides
Master Tool Kits	CL-8MM	CL-343	CL-375
Carbide Boring Tool	CL-2008C	CL-2012C	CL-2014C
Bushing Kit	CL-2000	CL-2000	CL-2000
Ball Driver	CL-4444P	CL-4444P	CL-4444P
Carbide Sizing Balls	.3160" CL-5316 .3170" CL-5317	.3440" CL-5344 .3445" CL-53445	.3750" CL-5375 .3760" CL-5376
Auto-Driver	CL-3500	CL-3504	CL-3506
Trim Tool	.500" OD CL-5600	.500" OD CL-5600	.500" OD CL-5600
Trim Tool Pilot	CL-5620	CL-5622	CL-5624
Guide Brush	WCB-44	WCB-44	WCB-44

tech tips
from the techxperts™

The centering cone must fit the valve seat properly so using the correct size is essential.

This is NOT a one-size-fits-all tool. If you have a cone that is too small for the seat it could slip through the opening. If you have one that's too large, the side of the combustion chamber could interfere or you won't have enough of the cone in the seat area for it to be stable and centered.

60° Seat Centering Cones

- Center firmly in the valve seat
- Cones feature a .625" ID
- Steel construction
- Use the Seat Centering Cones with the Master Tool Kits (above) for proper alignment of the reamer and guide bore

Description	Order No.
7 Piece Kit	CL-6500 ▼
Nominal	Range
1"	0.970"-0.730" CL-6310 x
1 1/4"	1.230"-0.740" CL-6308 x
1 1/2"	1.475"-0.805" CL-6306 x
1 3/4"	1.730"-0.860" CL-6304 x
2"	1.950"-0.875" CL-6302 x
2 1/4"	2.230"-1.000" CL-6300 x
2 1/2"	2.550"-1.875" CL-6312 x


Valve Spring Testing

Rimac® Valve Spring Testers

Rimac® Valve Spring Testers

- Specifically designed for quick, easy testing of multiple valve springs
- High-torque, lever-actuated compression is key to repeatable precision
- The vertical design ensures stability on the workbench
- Ideal for use in the shop, but portable enough to take to the racetrack
- Calibrated spring set includes two springs with different ranges that can be combined for a range of 10 to 640 lbs.

Description	Order No.
0-500 lb. Tester (reads in 5 lb. increments)	VST-69
0 to 1000 lb. Tester (reads in 2 lb. increments)	VST-70
Calibrated Test Spring Set (2 pc.set)	VST-SPRINGS



Positive stop for checking repeatability

Adjustable multi-position lever

VST-70

Ram travels 4⁵/₈"

Upper Platform measures 2¹/₄" dia.

Lower Platform measures 3¹/₄" dia.

Spring scale divisions: 1/16" and 1mm

Easy to read dial shows both pounds and kilograms

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS




Easy-to-use Travel Stop with adjustable set screws lets you set an exact position, allowing repeated testing at a desired height. Two set screws allow you to adjust for installed spring height and max lift (near coil bind).

Arbor style handle makes compressing springs fast and easy

5.0" travel capacity will fit almost any spring on the market today

Integral digital travel readout

2.0" diameter plates will handle virtually any spring on the market



Protect Your Valuable Valve Spring Tester with a Machine Cover!

Fits Machine	Order No.
VST-2000 Spring Tester	GMC-VST
Rimac Spring Tester	GMC-RIMAC

More Machine Covers on page 28

Intercomp® Digital Arbor Valve Spring Tester

- 1,500 lb / 680.4 kg load cell in 1 lb. increments
- Force units switchable from pounds to kilograms
- Billet 6061 T-6 Aluminum construction
- Digital travel readout at .001"/inch or .01/mm
- 5" travel capacity • 2.0" diameter spring pads
- Easy to read backlit screen
- Operates on 9V battery (included)
- Adjustable stop to repeatedly check springs at the same heights
- Order No. VST-2000

For routine calibration of spring testers, return tester to Goodson. Call for details, 1-800-533-8010.

... another
satisfied
customer

"Everyone at Goodson has been and is always great help! Quality products at great prices.
A must to build high quality engines"

- Wayne Brown, Brunswick, GA, Goodson customer since 2023

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Valve Seal Puller

- .810" tool dia.
- Fits Multi-Valve Engines
- Lifts from the bottom of the seal
- Works within the confines of lifter bucket bores
- Fingers grip seal for fast, easy removal
- Works on most domestic and import vehicles
- New and improved seal puller with stronger 3 jaw pulling action

Description	Order No.
Valve Seal Puller	VSP-323
Replacement Shaft	VSP-323-4
Replacement O-Ring	VSP-323-5
Replacement Jaw Set (3 Pc.)	VSP-323-3
Replacement Jaw Sleeve	VSP-323-1
Black Split Sleeve	VSP-323-2

Parts are interchangeable with VSP-320



made in
America



Universal Seal Pliers

- Works on OHC and in-line engines with recessed springs
- Long, serrated jaws reach into confined areas and grip seals firmly
- Heat-treated steel with easy-grip handles
- Order No. VSP-823



Intake & Exhaust Valve Stem Seals for 24 Valve, 7mm Cummins Diesel

- Fit 7mm valve stems
- OD measures .511"
- Sold in packs of 12



Application	Order No.
Intake	CVS-59I
Exhaust	CVS-59E



Goodson now offers the full line of QualCast Products.

Whatever you're looking for, you can find it online at www.goodson.com!

- Valves
- Valve Guides
- Valve Spring Inserts
- Valve Lifters
- Rocker Components
- Push Rods
- And a whole lot more!
- Valve Seat Inserts
- Valve Springs
- Valve Keepers (cotters, keys)
- Valve Stem Seals
- Injector Components
- Freeze Plugs

You'll find products for High Performance, Light Duty, Standard Duty and Heavy Duty. Products ship directly from QualCast's Nashville location to your door. Visit the QualCast section on the Goodson website today or Call 1-800-533-8010.

Height Indicator

- Measure compressed spring height when testing pressure
- Ideal for high performance and checking identical springs
- For Rimac® and other spring testers
- Height Scale displays inches and metric
- Includes Dial Indicator, and Mounting Kit (additional dial indicators on page 127)
- Order No. VST-25



Minnesota Fast Freeze

- Instantly chills seats & guides to -50°F (-45.5°C)
- Creates interference fit with heated aluminum heads
- Finish seat and guide work faster than ever
- Finish work faster than ever • Aerosol*
- Use on tight bushings, pins, shafts, etc.
- 10 oz. can

Description	Order No.
Minnesota Fast Freeze	MFF-8



Pneumatic Head:
Adjustable to 25° in either direction for cant valves



Head Support:
Table adjusts 45° to the front and 30° to the rear



Positive Stops: Adjusts front and rear angles



Speed Knobs:
Allows quick positioning of workpiece



Foot Pedal:
Easy, hands-free operation



Quick Release Knob:
Allows fast positioning to opposite cam bank

Goodson exclusive


Slide Hammer:
A quick tap loosens keepers for fast removal

To watch how-to set-up and use the Pneumatic Valve Spring Bench, scan the code below with your smart phone or other smart device.



Pneumatic Valve Spring Press


- Pneumatic valve support holds valve closed as you compress the spring
- Produces 432 lbs. of force at 100 PSI
- Adjustable stainless steel plate won't damage the head
- 28mm Valve Spring Adaptor (CF-502) is standard with unit (other sizes are available) • Measures 28"L x 24"W x 26"H
- Ideal for use on heads with recessed springs • For aluminum and cast iron heads
- Ships fully assembled • Replacement Parts Available
- Order No. **PSB-5000**



Adjustable Pneumatic Valve Spring Compressor

- Develops up to 325 lbs. of force with 130 PSI
- For springs from 3/4" to 1 3/4" dia.
- CNC-machined 6061 T6 aircraft-quality aluminum frame is adjustable in 1/4" increments
- Includes adjustable jaws (CF-44)
- Stainless steel cylinder with viton grade seals
- 2" cylinder travel • Fingertip controls • Full 1 year warranty

Description	Jobber	Order No.
Valve Spring Compressor		CF-2002
Replacement Parts and Accessories		
Valve Spring Adaptor Jaw Set		CF-44
1/4" Green Air Line (lin. ft.)		CF-2001-AL
Air Control Needle Valve		CF-2001-NV
Intake / Exhaust Cartridge		CF-2003-C
Air Cylinder 2" Travel		CF-2001-AC
1/8" NPT L-Fitting		CF-2003-L



Diesel Adjustable Pneumatic Valve Spring Compressor

- Develops up to 325 lbs. of force with 130 PSI
- For springs from 3/4" to 1 3/4" dia.
- CNC-machined 6061 T6 aircraft-quality aluminum frame is adjustable in 1/4" increments
- Includes adjustable jaws (CF-44)
- Stainless steel cylinder with viton grade seals
- 2" cylinder travel • Fingertip controls • Full 1 year warranty

Description	Jobber	Order No.
Valve Spring Compressor		CF-2008
Replacement Parts and Accessories		
Valve Spring Adaptor Jaw Set		CF-44
1/4" Green Air Line (lin. ft.)		CF-2001-AL
Air Control Needle Valve		CF-2001-NV
Intake / Exhaust Cartridge		CF-2003-C
Air Cylinder 2" Travel		CF-2001-AC
1/8" NPT L-Fitting		CF-2003-L

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILD

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

full service
...fast

Valve Spring Compressors

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

TOOLING
BRAKE SERVICE

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

**Goodson
exclusive**

Locking Arm:
Holds the C-frame
securely in position
at the desired angle

Lock Collar:
Can be used to stop
vertical travel or to hold
spring compressed
while assembling
keepers



To watch how to use the Manual Valve Spring Bench, scan the code at right with the camera on your smart phone or other smart device.



Manual Valve Spring Bench

- Remove and install valve springs on heads with recessed springs
- Creates 550 lbs. force with 45 lbs. exertion
- Includes 28mm diameter spring adaptor (CF-502), other size spring adaptors also available (see chart below)
- Frame tilts up to 25° in either direction for canting valves
- Full cylinder head support is adjustable from 0 to 45°
- Integral slide hammer easily releases stuck keepers
- Replacement parts available
- Order No. CF-500

Spring Adaptors

- Fit both manual (CF-500) and pneumatic (PSB-5000) spring benches
- 1/2" pin diameter
- Solid steel construction with replaceable nylon wear insert



OD	Reach	Adaptor	Insert
18mm	4 1/2"	CF-518	CF-518-1
23mm	4 1/2"	CF-501	CF-501-1
28mm	3 1/2"	CF-502	CF-502-1
35mm	2 1/2"	CF-503	insert not required




Dual Stage 1000 Lb. Pneumatic Valve Spring Compressor

- Lightweight — built of 6061 / 7075 T-6 Aluminum
- 1 1/2" Screw Adjustment — 7" to 8 1/2" Throat
- Certified to 1000 lbs of force
- Dual stage air pump develops up to 1000 lbs. of force on as little as 70 psi air supply — **Do NOT exceed 120 psi**
- Includes 1.600" ID Jaw adaptor, 1.740" ID jaw sold separately

Description	Order No
Spring Compressor with 1.600" ID Jaw	GSC-1000
Replacement Standard Jaw, 1.600" ID	GSC-3002
Adaptor Jaw, 1.740" ID	GSC-3003
LS1 Jaw Adaptor (1.740 OD) use with GSC-3002	GSC-3000-LS1
Rebuild Seal Kit (with Intake Button Return Spring)	GSC-3000SK
Replacement Intake Button Return Spring	GSC-3004
Intake Trigger Assembly	GSC-20004A
Exhaust Trigger Assembly	GSC-20004B
Delrin Pressure Cap (included)	B-10005C

Not interchangeable with our CF-3000B Spring Compressor



full service
...fast



"I make sure all Goodson products are packaged properly and include instructions and other important information for you."
- Craig, Goodson Receiving - 10 years of service

Manual Valve Spring Compressor


- Weighs only 6 lbs
- High leverage allows for easy, one-hand operation
- Covers a range from 10"H to 8"D
- Works with most L-head and valve-in-head engines
- Fits truck & tractor engines
- Jaws adjust for different spring sizes

Description	Order No.
Spring Compressor	CF-140
Replacement Jaw set	CF-44
HD Replacement Jaw Set	CF-44HD



Manual Valve Spring Compressors

- Handle valve springs from a range of applications
- Welded, gusseted all-steel construction takes plenty of abuse
- Plenty of leverage to compress valve springs
- Order No. **CF-1500**




CYLINDER HEAD
REBUILDING
CLEANING,
ASSEMBLY & SAFETY

small engine
powersports

Manual Valve Spring Compressor For Small Engines

- Steel construction
- 20lb. max. spring pressure
- Once you lock the compressor in position, your hands are free to work
- Includes 2 jaw sets – small, for springs up to 7/8" (22.2mm) and large, for springs up to 1 1/16" (27.0mm)
- Order No. **CF-600** While Supplies Last



Valve Spring Compressor Adaptor

- Fits seat and guide machines or drill press
- Puts collet or drill press chuck behind adaptor
- Allows more room to remove or re-install valve keepers and associated components
- Fits 1/2" collet or Jacobs chuck (not included)

OD (mm)	Reach (mm)	Order No.
3/4" (19.1)	3 3/4" (95.3)	CF-6
1 1/16" (20.6)	3 3/4" (95.3)	CF-8
1" (25.4)	3 3/4" (95.3)	CF-10
1 1/4" (31.7)	3 3/4" (95.3)	CF-12
1 1/2" (38.1)	3 3/4" (95.3)	CF-15



SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

Keeper Installation Tools

- Spring-loaded plunger
- For single & multi-groove keepers
- Reaches keeper grooves located farther from the valve tip • Ideal for use with **CF-500** (p. 43) and **PSB-5000** (p. 42)

Best Keeper Tool
on the Market!

Size	Order No.
5mm / .2031"	VKI-5
6mm / .2344"	VKI-6
7mm / .2812"	VKI-7
8mm / .3125"	VKI-8
Replacement Rubber Sleeve	VKI-56



One of the
handiest keeper
tools you'll ever
find!

Keeper Magnet

- 6 5/16" long holder fits easily into deep bores
- Powerful .170" diameter earth magnet holds keepers securely when removing or installing
- Order No. **VKM-17**



Adaptors for Deeply Recessed Springs

- Open top design gives easy access to keepers
- Durable, non-marring material
- Fit on Split-Jaw Spring Adaptors such as our **CF-44** (below)

Description	OD	Height	Order No.
Small Metal Adaptor	26mm	4" (101.6mm)	CF-32
Medium Nylon Adaptor	27mm	3" (76.2mm)	CF-24-G
Large Nylon Adaptor	32mm	3" (76.2mm)	CF-25-G



MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

CF-44

CF-44HD

Valve Spring Adaptor Jaws

- Fit frames with double locking screws to secure jaws such as Goodson **CF-2002**, **CF-2008** and **CF-140**
- Heavy duty jaws are non-adjustable (has a 1 5/8" max spring diameter)

Description	Order No.
Standard Duty 1.000"-1.875" (25.4-47.6mm) Range	CF-44
Heavy Duty (non-adjustable)	CF-44HD



MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Same Day Shipping

Air Powered Grinder
uses standard shop air

DESIGNED BY AN ENGINE BUILDER FOR ENGINE BUILDERS!

Bucket Lifter Grinder Assembly with FREE Grinder

- Machine just the bucket lifter!
- Fast and accurate
- Save time — measure once, then remove the material from inside the Bucket Lifter instead of machining the stem height and finding the right VAD thickness or grinding the seat to meet your specs
- Micrometer feed shows how much material is being removed
- Confirm with dial indicator and bridge (included)
- Use right at your assembly station
- Works with most Bucket Style Lifters, including those with VADs
- Complete Assembly includes Air Driver, CBN Cutter, Micrometer Feed Body, Dial Indicator and Indicator Base
- **US Patent Number US 10456887**

Description	Order No.
Complete Bucket Lifter Grinder Assembly	BLG-1000
Replacement CBN Cutter	BLG-1001
Replacement Dial Indicator	EDI-1
CBN Dressing Stick 1/2" x 1/2" x 6"	DS-CBN


Micrometer Feed shows
how much material you are
removing

CBN Cutter makes
quick work of
virtually any
bucket lifter

Use the Dial Indicator and Base
to measure the valve contact point.
Once determined, remove necessary
material to set lash.

video
available

View our Tech Lab Tuesday
video to see how easily you can
adjust valve lash by machining
the bucket lifters with the Bucket
Lifter Grinder. Scan the code
at left with the camera on your
smart phone or other smart
device for instant access.




CF-1300LF included
with purchase

Heavy Duty Manual Valve Spring Compressor

- Drop forged steel frame
- Open receiver design allows for quick access to keepers
- Accommodates springs up to 1 3/4" diameter
- 8 1/2" throat • 6" deep
- Compresses springs up to 1000 pounds

Description	Jobber	Order No.
Manual Valve Spring Compressor	\$424.99	CF-1300
Small Receiver (OD: 1.625", ID: 1", Height: 2.156")	89.99	CF-1300SF
Large Receiver (OD: 2.0", ID: 1.197", Height: 2.25")	99.99	CF-1300LF

**made in
America**



V-Twin On-the-Engine Valve Spring Compressor


Replace broken valve springs, install high performance valve springs, remove and replace valve guide seals all without disassembling the bike. Just remove the gas tank and get to work. Use on Sportster, Evolution, Twin-Cam and most aftermarket V-Twins. Kit includes valve spring compressor, adaptor for compressing beehive springs, valve seal driver/installer and head pressurizing hose. Order No. **CF-HDIF**

**made in
America**

full service
...**fast**



"We work hard to get the right products in the right boxes and ship them to the right address every single time."
- Shawn, Goodson Shipping, 7 years of service



Small Chamfering Cones & Mandrels Make Deburring and Chamfering Easy In Tight Spaces

These mandrels are available in two diameters – $\frac{3}{4}$ " and $1\frac{1}{2}$ " diameters with a $\frac{1}{2}$ " shank to fit most portable drills. The small diameter fits easily into tight spaces such as Beehive Valve Springs (see page 132) or bolt holes. The mandrel is designed to support a 60° abrasive cone which is held securely by the retaining ring. One 80-grit cone is included with initial purchase.

Description	Order No.
$\frac{3}{4}$ " Dia. Mandrel	CC-34
$\frac{3}{4}$ " Dia. Abrasive Cones 80 grit	CC-35
120 grit	CC-36
$1\frac{1}{2}$ " Dia. Mandrel	CC-60
$1\frac{1}{2}$ " Dia. Abrasive Cones 80 grit	CC-61
120 grit	CC-62



3-D Fast Cut™
Adjustable Spring Pad
Cutters on page 12

Valve Spring Seat Cutters

- Resize valve spring seats to maintain spring-to-valve concentricity or use to enlarge seats for over-size dual springs
- Requires special pilot – see chart below

Carbide Tipped Cutter Bodies
(use VP pilots below)

OD	ID	Order No.
1.320"	.630"	VSS-1320
1.350"	.625"	VSS-1350
1.500"	.625"	VSS-1500
1.550"	.625"	VSS-1550
1.625"	.625"	VSS-1625
1.680"	.750"	VSS-1680HD
1.750"	.625"	VSS-1750

Hardened & Ground Pilots

Guide ID	Order No.
.275"	7.0 VP-7MM
.312"	7.9 VP-312
.343"	8.7 VP-343
.375"	9.5 VP-375

tech tips
from the techxperts™

You must use these pilots with the VSS and VSC cutters. The flat sides are necessary for a proper fit.

Universal Gel Lube

- Sprays on as a liquid and forms into a gel within seconds
- Penetrating formula blends freely with motor oil
- Multiple uses, including cams, lifters, rocker arms, bearings, pistons/wrist pins, cylinders, etc.
- Provides lubrication for engines subjected to prolonged storage before initial start-up
- 8 oz. Aerosol* Can
- Order No. **GL-8U**



*Hazardous Goods Fees Will Apply if Shipped By Air

8 Piece Valve Train Checking Spring Set

- 1.250" OD
- Spring Steel construction
- Essential for high-performance engine building and engine blueprinting
- Maintain a positive valve train position while checking valve to piston clearance
- Order No. **VTS-8**



**Buy the
Kit and
SAVE!**

Dial Indicated Valve Stem Height Gauges

- 5 sizes to choose from
- Small diameter extended measuring body allows extra height for dial indicator clearance
- Use with our large-faced Dial Indicator to check valve tip height



Description	Jobber	Order No.	Incl.
Valve Stem Height Gauge Kit w/Stand		VSH-KIT	▼
Dial Indicator (2" travel, .001" graduations)		MDI-2	x
Dial Indicator (1" travel, .001" graduations)		EDI-1	
Measuring Bodies	OD	ID	OAL
	.750"	.625"	3.830"
	.900"	.770"	2.840"
	.900"	.770"	3.840"
	1.060"	.812"	2.840"
	1.250"	1.090"	3.300"
5-Post Tool Stand		TS-5	x
1" Checking Standard		MCS-1	

More dial indicators on page 128

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS


V-TWIN & METRIC
HARD PARTS

Non-Serrated Valve Spring Booster Shims

- Won't compress
- Shims meet or exceed OE specifications
- Maintain pressure and protect head from spring abrasion
- Made of prime quality cold rolled steel
- Support valve springs better than serrated shims
- Won't damage spring pad area on aluminum heads or cause lateral loads or harmonics

Special Orders are available.

Size		50 count High Performance			100 count		
OD	ID	.060"	.030"	.015"	.060"	.030"	.015"
1.000"	0.688"				A-101	B-101	C-101
	0.765"				A-104	B-104	
1.100"	0.719"					B-106	
1.218"	0.875"				A-105	B-105	
1.250"	0.625"	A-107-HP	B-107-HP	C-107-HP	A-107	B-107	C-107
	0.812"	A-203-HP	B-203-HP	C-203-HP	A-203	B-203	C-203
	0.875"				A-201	B-201	
1.360"	1.000"	A-102-HP	B-102-HP	C-102-HP	A-102	B-102	
1.375"	0.765"	A-301-HP	B-301-HP	C-301-HP		B-301	
1.438"	0.645"	A-306-HP	B-306-HP	C-306-HP			
1.439"	0.765"	A-305-HP	B-305-HP	C-305-HP			
1.480"	0.703"	A-303-HP	B-303-HP	C-303-HP	A-303	B-303	
1.500"	0.645"	A-306S-HP	B-306S-HP	C-306S-HP			
	1.031"	A-103-HP	B-103-HP	C-103-HP	A-103	B-103	
1.634"	0.643"	A-601-HP	B-601-HP	C-601-HP			



Magnetic Head Bolt Washer & Valve Spring Shim Removal Tools

- Hollow design allows easy access over studs or head castings
- Powerful earth magnets grab firmly, letting you lift the washer or shim easily


Description			Order No.	Incl.
Magnetic Remover Set			MWR-SET	▼
Washer Removers	ID	OD		
	0.250"	0.625"	MWR-14	x
	0.500"	0.865"	MWR-12	x
	0.450"	0.812"	MWR-716	x
Shim Remover	0.708"	1.355"	MVSR-2	x



View "CCing Heads — How To Measure Your Combustion Chamber Volume." Scan the code at right with the camera on your smart phone or other smart device for quick access.



Clear acrylic plate lets you see when the chamber is full



Positive fluid control




100cc Glass Buret allows use with alcohol or solvent with high-visibility red markings

Clamp gives you ability to fully adjust the height of the buret in relation to your cylinder head

Cylinder Head CC-ing Equipment

- Use glass buret with alcohol or solvent
- Positive on/off fluid control valve
- Clear acrylic plate lets you see when the combustion chamber is full
- Mix Measuring Concentrate with water to make 1 gallon

Description	Order No.	Incl.
CC-Measurement Kit	CCB-KIT	▼
100cc Glass Buret	CCB-100	x
5" x 5" x 3/8" Acrylic Plate	GCB-3	x
Buret Cleaning Brush - 35 1/2" OAL	GCB-BRUSH	x
Buret Stand	GCB-1	x
Buret Clamp	GCB-2	x
Funnel - 2 oz. Capacity	CCB-FUNNEL	x
Blue Measuring Liquid Concentrate (Yields 1 Gal.)	GCB-LIQUID	
4" Precision Cylinder Head Level	LEV-4	
Replacement Vial for 4" level	VGL-101	
100cc Graduated Glass Beaker	GC-100	
Universal Cylinder Head Holders (pair)	HH-200	



full service
...fast



"Goodson accepts major credit cards, debit cards, bank drafts and personal checks. Call us for more information."
- Bev, Goodson Accounting Manager - 42 years of service

resharpening
available



PCD Inserts for Aluminum

- A must for shops committed to meeting today's strict surface finish requirements
- Fits machines with $\frac{3}{8}$ " & $\frac{1}{2}$ " CBN holder
- $\frac{1}{2}$ " diameter inserts require shim*
- Use with Resurfacing Spray (HPS-16) for best results (below)

Titanium-Nitride Coated			Goodson	Radiac
Dia.	Thick.	Sided	Order No.	Order No.
$\frac{3}{8}$ "	$\frac{1}{8}$ "	Single	PCDS-375	-----
	$\frac{1}{8}$ "	Single	GPCD-375	-----
$\frac{1}{2}$ "	$\frac{1}{8}$ "	Single	-----	2379264*
	$\frac{1}{8}$ "	Single	GPCD-500*	-----
$\frac{1}{2}$ "	$\frac{3}{16}$ "	Single	PCDS-500	-----
$\frac{1}{2}$ "	$\frac{3}{16}$ "	Single	-----	2379265
$\frac{1}{2}$ "	$\frac{3}{16}$ "	Single w/screw hole	-----	2X6145
$\frac{1}{16}$ "	Thick Carbide Shim*		CBN-500SHIM	

CBN Cutter Inserts for Cast Iron

- Faster and cleaner than segments and wheels



Uncoated			Goodson	Uncoated Radiac
Dia.	Thick.	Sided	Order No.	Order No.
$\frac{3}{8}$ "	$\frac{1}{8}$ "	Single	GCBN-375	-----
$\frac{1}{2}$ "	$\frac{1}{8}$ "	Single	GCBN-500*	-----
Titanium-Nitride Coated				
$\frac{1}{2}$ "	$\frac{1}{8}$ "	Double	CBN-500D*	2X5299*
	$\frac{3}{16}$ "	Single	CBN-500S	2359233
	$\frac{3}{16}$ "	Solid	-----	2359234
	$\frac{3}{16}$ "	Single Sided with Screw Hole	-----	2X6144
	$\frac{3}{16}$ "	Special Edge Prep for Diesel	-----	2379268
$\frac{3}{8}$ "	$\frac{1}{8}$ "	Double	CBN-375D	-----
	$\frac{1}{8}$ "	Single	CBN-375S	-----
Sharp Uncoated				
$\frac{3}{8}$ "	$\frac{1}{8}$ "	Single	CBNS-38	-----
$\frac{1}{2}$ "	$\frac{3}{16}$ "	Single	CBNS-12	-----
$\frac{1}{16}$ "	Thick Carbide Shim*		CBN-500SHIM	

*Shim required on DCM machine

resharpening
available

CBN Super Abrasive For Cast Iron Diesel Heads

- Designed for cast diesel heads with hardened pre-cups • Won't chip
- Fits all overhead surfacers with $\frac{1}{2}$ " diameter insert capacity
- Will **NOT** work on standard cast heads

Cut using the dull
finished side



Standard Grade Cutters


Dia.	Thick.	Sides	Order No.
$\frac{3}{8}$ "	$\frac{1}{8}$ "	Single	GCBN-D375
$\frac{1}{2}$ "	$\frac{1}{8}$ "	Single	GCBN-D500

Premium Grade Cutters

Dia.	Thick.	Sides	Order No.
$\frac{1}{2}$ "	$\frac{1}{8}$ "	Single	DRD-500
$\frac{1}{16}$ "	Thick Carbide Shim		CBN-500SHIM

*NOTE: A $\frac{1}{16}$ " thick carbide shim must be used on DCM machines

Measure here for
replacement vial



Starrett Precision Levels & Vials

- Graduated vials with satin-chromed, brass protective covers that rotate to close tightly
- Base castings are seasoned, then precision machined and finished on a bearing surface • Replaceable vials
- Adjustable for precise calibration
- 1 division equals .0005" per inch
- Fits pilots from 6mm to .437"
- Use replacement vial to right of level for correct fit



tech tips
from the technicians™
Confirm level calibration
before every use

VGL-100
(use with
your pilot
or find on
page 3)

Description	Order No.	Replacement Vial
4" Valve Guide Level (3" vial)	VGL-100	VGL-101
4" Level (3" vial - nominal)	LEV-4	VGL-101
8" Level (6" vial - nominal)	LEV-8	LEV-8-1
12" Level (8" vial - nominal)	LEV-12	LEV-12-1

See goodson.com for level calibration instructions

High Performance Resurfacing Fluid

- Prolongs cutter life
- Enhances surface finish
- Refreshing scent



Description	Order No.
11 oz. Aerosol*	HPS-16
4 oz. Bottle	HPS-4

* Hazardous Goods Fees Apply When Shipped By Air

resharpening
available



Tool Bits For Van Norman 530, 570 Rotary Broaches

- Can be resharpened
- Order No. **VN-65C**

Enlarged for clarity



Carbide Cutter Replacement Tips For Storm Vulcan Broach Style Surfacers

- Fits Storm Mill 85, 85B, 85BE, 85C, 85N and 280
- Order No. **SV-85BE**

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

full service
...**fast**



"We are committed to maintaining your privacy. Information about you and your business is never sold, rented or given to anyone outside of our company."

- Sue, Goodson Office Manager - 40 years of service

tech tips

from the techxperts™

4 Keys to Resurfacing Aluminum Heads

1 - Choose the correct abrasive

Use a speckled wheel segment to grind aluminum heads.

2 - Lubricate, Lubricate, Lubricate

Put a light coat of Grind Aid (GRA-10) on the abrasive to reduce aluminum build up. Speed up the traverse and reduce the cut to .0005" to .0010" per pass.

3 - Dress for Success

Keep grains open by dressing often. Don't dress before the last pass, but be sure to apply Grind Aid liberally so the stone yields a finer surface finish.

4 - Keep heat build-up to a minimum

The greatest danger is heat build up that can cause scoring as aluminum transfers to the stone. Take shallow cuts and use plenty of lubrication to prevent this.

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Silicon-Carbide
Abrasive



Silicon-Carbide
Abrasive



Aluminum Oxide &
Silicon-Carbide
Abrasive



Aluminum
Oxide
Abrasive



Resurfacing Wheel Segments

Segments are available in a variety of compositions.

Match the abrasive to the material for best results and longest life. Order segments in 8, 10, or 12 piece sets.


Width	Thickness	Length	Application	Abrasive	Color	Order No.
2.56"/65mm	0.98"/25mm	3.94"/100mm	Cast Iron & Aluminum	Silicon-Carbide	Black	GS-PBS
			Steel & Hardened Metals	Aluminum Oxide	White	GS-PBS-1
			Aluminum, Cast Iron, Hardened Iron, & Steel	Aluminum Oxide and Silicon-Carbide	Speckled	GS-PBS-2
			Steel & Hardened Metals	Aluminum Oxide	Ruby	GS-PBS-3
			For Peterson/Peterson Berco 1055 AWL, RSC950 (std.), SYP320, -360, -1000, -1300, RSC1200, -1550, RPYS1500 models. For Winona Van Norman SM-2000, SM-4000/5000, MG-4000, SM-6000C/6000A and MG-3000/3850 models. For Storm Vulcan RT7Y Late (Serial No. 103152 and up) and RT 17Y Late (Serial No. 128697 and up) models.			
3.13"/79mm	0.81"/21mm	3.13"/79mm	Aluminum, Cast Iron, Hardened Iron & Steel	Aluminum-Oxide and Silicon-Carbide	Speckled	GS-SVS-2
For Peterson/Person Berco RG-32, RTY, RG-35, RG-300/900 models. For Storm Vulcan RT 7Y Early (Serial No. up to 103151 and RT 17Y Early (Serial No. up to 128696)						
2.56"/65mm	0.79"/20mm	3.94"/100mm	Steel & Hardened Metals	Silicon-Carbide	Black	GS-KWS
			Aluminum, Cast Iron, Hardened Iron & Steel	Aluminum-Oxide and Silicon-Carbide	Speckled	GS-KWS-2
			For Kwik-Way 858 and 862 models			

tech tips

from the techxperts™

To maintain proper cutting action, Goodson strongly recommends that you replace your cylinder head resurfacing segments in full sets. See your user's manual for wheel diameter and number of segments required. Due to manufacturing process colors may vary. Need help choosing the abrasive? Call the Goodson Techxperts™


Resurfacing Segments are guaranteed for 1 year from original purchase date



Import / Metric Cylinder Head Stud Stretchers

- Save time, don't remove the studs from a head for resurfacing • Put stud stretchers on two studs and leave the rest • Sold in pairs

Length	Thread	Order No.
3"	8mm x 1.25	SS-20
3 3/4"	8mm x 1.25	SS-30
3 3/4"	10mm x 1.25	SS-40



Surface Grinding Coolant for Segments and Single-Piece Wheels

- Synthetic
- Water soluble
- Non-foaming • Dilute 20:1

Size	Order No.
1 Gallon / 3.78 L	SGC-10
5 Gallons / 18.93 L	SGC-50



Cylinder Head Resurfacing

24 Grit Blanchard Grinder Wheels

- Includes gasket pad for mounting onto a Blanchard Grinder
- Also ideal for resurfacing clutch plates
- Wheel measures 11" x 5" x 9"
- Tape wound for added safety
- Excellent grade for most grinding conditions and metals
- Order No. **U69755**



Radiac
Abrasives
A TYROLIT Company

The most complete abrasives program in the industry ...

1. Consistent high quality abrasives

Each Goodson resurfacer wheel is made to the highest standards of roundness, balance and strength. Extensive quality control, start-to-finish, lets us back our abrasives with our Iron-Clad Guarantee of total satisfaction.

2. Full inventory

Since we specialize in the distribution of abrasives to machine shops world wide we always carry an extensive inventory. Call Goodson, we have what you need on our shelves.

3. Same day shipping

We usually ship your order the same day that we receive it. Along with our huge inventory, our shipping speed ensures consistently faster delivery when you order from Goodson.

Single-piece Resurfacer Wheels

- Meet or exceed OE standards established for general purpose grinding applications
- Silicon-Carbide abrasive • Banding will wear off to expose more abrasive



U342040



GS-48

Peterson			
Machine Model(s)	Size: dia. x height x face width	Grit	Order No.
All 14" Dry Grinders	14" x 1 1/2" x 4" Plate	24	U342040
All 14" Dry Grinders	14" x 1 1/2" x 4" Plate	36	GS-48

Radiac
Abrasives

Grinding Wheels are guaranteed for 1 year from original purchase date



GS-545B



GS-545BL

NOTE: Plates are no longer painted, resulting in less warpage

Kwik-Way			
Machine Model(s)	Size: dia. x height x face width	Grit	Order No.
545B, 856, 855-5, 860	14" x 3" x 1 1/2" (Serrated) Plate	24	GS-545B
545BL, 860A, L & T	16" x 3" x 1 1/2" (Serrated) Plate	24	GS-545BL

Grinding Wheels are guaranteed for 1 year from original purchase date



FG-1165-G



FG-1070A-G



FG-1045-G



GS-17



GS-00



GS-0

Grinding Wheel Dressers & Replacement Cutters

Diamond Dresser Tools are available on pages 114-115

Cutter Assemblies				Replacement Cutters					
Applications	OD	W	Order No.	Pieces	Washers	OD	ID	Thick	Order No.
Peterson (12mm shaft)				8 stars	3	2.375"	1.500"	.093"	GS-17
WVN SM2000, 4000, 5000, 6000C, 6000A, MG3000, 3850	1.250"	0.978"	FG-1165-G		1 w/locking tangs	1.750"	1.500"	.060"	
				7 stars	none	1.250"	0.313"	.095"	FG-1161-G
Peterson & DCM	2.375"	2.262"	FG-1070A-G	5 stars		2.375"	1.132"	.1375"	FG-1070-G
Hand Held			FG-1045-G	1 stone	none	1.500"	0.313"	.6250"	FG-1044-G
Desmond Dresser for wheels to 10"			GS-0	4 blades, 2 spacers			0.250"		GS-00
				4 blades, 2 spacers			0.500"		GS-11



Cylinder Head Resurfacing

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Abrasive Industrial Supplies

Need a Different Size or Grit or Material?

We can make the size you need. Specify grit, grain and size and we'll take it from there. Call 1-800-533-8010 for info!

Cylinder Head Resurfacing Belts

A belt has three important parts: abrasive, bond and backing. Goodson belts are made for top performance and long life. Our belts also feature a unique splice that permits use in both directions for even longer wear; when worn one way, turn belt around to resurface more heads.

Abrasive: Match the abrasive to the workpiece (aluminum, cast iron or steel) and to your machine for the longest belt life.

Bond: Double-layer, heat-resistant resin holds abrasive firmly. Bond is so strong that grains wear out instead of loosening.

Selection Guide: which abrasive works best on what materials...

ALUMINUM	CAST IRON	STEEL	Zirconia-Alumina (40g)
			Silicon-Carbide (40g)
			Silicon-Carbide (80g)



Resin Backing: Waterproof, poly-back belt won't tear or fray. It's the toughest backing of any resurfacing belt.

See list of machines and belt sizes below to determine which belt(s) you need.

Silicon-Carbide 40-grit:

- Good-quality • Black
- Primarily for cast iron but can resurface aluminum if extra care is used
- Down-pressure optional

Silicon-Carbide 60-grit:

- Good-quality • Black
- Primarily for cast iron but can resurface aluminum if extra care is used
- Down-pressure optional

Silicon-Carbide 80-grit:

- Good-quality • Black
- Designed especially to resurface aluminum
- Down-pressure not recommended

Zirconia-Alumina 40-grit:

- Better-quality
- Blue
- Grains fracture under pressure to stay sharp
- For cast iron or steel
- Down-pressure recommended

Zirconia Alumina With Grind Aid - 40-grit:

- Premium-quality belt with pre-applied Grind Aid • Blue/Green
- Excels on severe applications
- Grains fracture under pressure to stay sharp
- For stainless steel, alloy
- Down-pressure required

Belts with * are made to order. Please allow 5 to 7 working days for delivery.

*** made to order**

Belt Size	Order No.	Order No.	Order No.	Order No.	Order No.
10" x 87"	SGS-10-87	SGS-10-87-60*	SGA-10-87*	SGB-10-87*	SGZ-10-87*
10" x 103"	SGS-10-103	SGS-10-103-60	SGA-10-103*	SGB-10-103	SGZ-10-103*
11 $\frac{7}{8}$ " x 76"	SGS-11-76	SGS-11-76-60*	SGA-11-76	SGB-11-76	SGZ-11-76*
11 $\frac{7}{8}$ " x 79"	SGS-11-79	SGS-11-79-60	SGA-11-79	SGB-11-79	SGZ-11-79
11 $\frac{7}{8}$ " x 89"	SGS-11-89	SGS-11-89-60	SGA-11-89	SGB-11-89	SGZ-11-89
11 $\frac{7}{8}$ " x 91"	SGS-11-91	SGS-11-91-60	SGA-11-91	SGB-11-91	SGZ-11-91*
11 $\frac{7}{8}$ " x 101"	SGS-11-101	SGS-11-101-60*	SGA-11-101	SGB-11-101	SGZ-11-101*
14" x 86"	SGS-14-86	SGS-14-86-60	SGA-14-86	SGB-14-86	SGZ-14-86
14" x 103"	SGS-14-103	SGS-14-103-60	SGA-14-103	SGB-14-103	SGZ-14-103
14" x 107 $\frac{1}{2}$ "	SGS-14-107	SGS-14-107-60	SGA-14-107	SGB-14-107	SGZ-14-107
14" x 113 $\frac{1}{2}$ "	SGS-14-113	SGS-14-113-60	SGA-14-113	SGB-14-113	SGZ-14-113*
15" x 127 $\frac{1}{2}$ "	SGS-15-127	SGS-15-127-60*	SGA-15-127	SGB-15-127	SGZ-15-127

Colors may vary due to manufacturing process. Guaranteed for 1 year from original purchase date.

Belt/Machine Compatibility **tech tips**

Belt Size	Machine(s)
10" x 87"	Rogers SB-1028, SF-1028, T&S Machine, Master Tool 1029
10" x 103"	Rogers SF-1036, T&S Machine, Master Tool PS1036
11 $\frac{7}{8}$ " x 76"	Winona Van Norman BG-600
11 $\frac{7}{8}$ " x 79"	RMC, Peterson RG-1203
11 $\frac{7}{8}$ " x 89"	RMC-800, Serv-Equip PG-1229
11 $\frac{7}{8}$ " x 91"	Peterson RG-1234, Kansas Instruments
14" x 86"	Automotive Craftsman
14" x 103"	Master Tool
14" x 107"	Kwik-Way 870 Master Surfer
14" x 113 $\frac{1}{2}$ "	Storm Vulcan/Anderson AB-1000A, Peterson PG-1400
15" x 127 $\frac{1}{2}$ "	Storm Vulcan/Anderson AB-1540A, Anderson AB-1560, IDL HS-4350, Peterson PG-1500, Winona Van Norman BR-1500, BG-1515 & BG-1520



Semi-Synthetic Belt Resurfacer Coolant

- Rust-inhibiting
- For **ALL** belt resurfacers with a coolant sump
- Dilute 30 parts water to 1 part coolant

Size	Order No.
1 Gallon (3.79L)	SGB-10
5 Gallons (18.39L)	SGB-50

full service
...fast

"When you call Goodson, you speak to a person first - not a machine. We work hard to make sure we answer your calls promptly and avoid keeping you on hold."

- Ashley, Goodson Receptionist, 3 years of service



Scan the code at right with your smart phone or other smart device to watch Magnetic Particle Inspection on the Goodson website.



Ergonomic handle design for less operator fatigue.



MMP-210

Articulating legs adjust to a wide range of angles, allowing you to test uneven surfaces with ease



Magnetic Crack Detection Units

- Articulating legs conform to virtually any surface configuration
- Designed for one-person operation • Lightweight • No transformer box to drag around • 230V units feature a pigtail on the cord • Easy to access switches • Full 1-Year Manufacturer's Warranty for Repair • 50% duty cycle (example: 2 minutes on, 2 minutes off) • Produce a strong AC magnetic field

Description	Order No.
115V Electronic Crack Detector with 10# Pull	MMP-100
115V Heavy Duty Electronic Crack Detector with 22# Pull	MMP-210
230V Electronic Crack Detector with 10# Pull (subject to stock on hand)	MMP-100S



Small Parts Demagnetizer

- Easy to use table demagnetizer
- Ensures that all residual magnetism is eliminated, fast

Description	Order No.
Small Parts Demagnetizer	SPD-46



Maxxeon® WorkStar® 364 USB Rechargeable UV Leak Detection Pen/Inspection Light

- 3.7V 570mAh, 2.1 Wh Lithium battery with USB charger
- Run time: 35 min. continuous, 2 hr. intermittent operation
- Use with Goodson Glow for crack detection
- Easily adjustable beam to suit application
- Drop tested to 6 feet
- Order No. DFL-364

Specifications



MMP-100 / MMP-100S

Physical: 7 3/8" x 9 1/4" x 2 1/8"
187 x 235 x 54mm
Max. Span: 12" (304.8mm)
across poles
Voltage: 115V (MMP-100)
230V (MMP-100S)
Line Current: 4 amp (MMP-100)
3 amp (MMP-100S)
Weight: 6.5 lb (2.95 kg)
Cord: 10' L, 3-wire



MMP-210

Physical: 10 1/2" x 11" x 2 3/4"
266 x 280 x 70mm
Max. Span: 18" (457mm) across
poles
Voltage: 115V (MMP-210)
230V (MMP-210S)
Line Current: 8 amp (MMP-210)
3 amp (MMP-210S)
Weight: 13 lb (5.9 kg)
Cord: 10' L, 3-wire



Magnetic Powder Applicators

- A quick & easy method for distributing magnetic powder

Description	Order No.
Atomizer Assembly for small areas (1 oz.)	MM-301
Applicator Bulb for large areas	WCD-266-G
Replacement Bulb for Atomizer Jar	MM-301-1

Non-Fluorescent Magnetic Powder for Dry Method Particle Inspection

- Works with all dry magnets including Magnaflux® and Parker
- Store in a moisture free environment



Color/Size	1 lb.	5 lb.	25 lb.
White/Gray	WCD-100-G	WCD-500-G	WCD-2500-G
Yellow	WCD-101-G	WCD-501-G	WCD-2501-G
Red	WCD-103-G	WCD-503-G	WCD-2503-G

Crack Detection



Scan the code below with your smart phone or other smart device to view our **Chemical Crack Detection Video** on the Goodson website.



Alumni-Chek

- Find surface cracks on aluminum & cast iron without electricity or special lights
- Ideal for aluminum, but also works on brass, cast-iron, steel, carbide, and Stellite • Even the tiniest cracks show as bright red • Complete kit includes Cleaner, Penetrant, Developer and Shop Towels (also available separately)

Description	Order No.	Incl.
Complete Kit	AC-KIT*	▼
Cleaner Aerosol*	AC-1*	x
Penetrant Aerosol*	AC-2*	x
Developer Aerosol*	AC-3*	x
5 Towels	WST-5	x

*Hazardous Goods Fees Apply When Shipped By Air



Magnetic Crack Detection Spray

- Use with your magnetic crack inspection unit
- Applies quickly and easily — just spray it on the area you want to check
- Glows brightly under black-light
- 32 oz. non-aerosol spray
- Order No. **MFA-32**

tech tips ?

from the techxperts™

You can find more tips, general information, product instructions and SDS all online.

www.goodson.com



tech tips

from the techxperts™

- Step 1:** Spray cleaner evenly on the surface and allow it to dry completely.
- Step 2:** Spray on Penetrant. Allow to saturate for 5 minutes. Wipe off excess to avoid false readings.
- Step 3:** Spray on thin layers of developer to build up a uniform powdery film.
- Step 4:** Flaws and cracks will glow brightly when viewed under the black light (Applies only to Goodson Glow).



GOODSON Glow Crack Detection Sprays

- Easily detect surface cracks that could be missed with just visual inspection
- Cracks & flaws glow brightly under black light after treatment with Cleaner, Penetrant and Developer

Description	Order No.
Goodson Glo Cleaner Aerosol*	GLO-1*
Goodson Glo Penetrant Aerosol*	GLO-2*
Goodson Glo Developer Aerosol*	GLO-3*

*Hazardous Goods Fees Apply When Shipped By Air

Crack Detection Powder & Oil Carrier

- For wet method crack detection
- Mix powder with oil carrier
- Use with Ultra Violet Inspection Light to view results

	Size	Order No.
Powder	4 oz. / 113.4g	GCR-14A-4
	1 lb. / 453.6g	GCR-14A
Oil Carrier	5 Gallons / 18.93L	GCR-50



Magnetic Crack Detection Oil

- Oil impregnated with magnetic powder (GCR-14A, GCR-14A-4) to glow under black-light
- Low viscosity oil flows into small cracks • Oil clarity makes cracks easier to see • Aerosol Spray is pre-mixed oil and carrier
- Order No. **MFA-50**

**Goodson
exclusive**



Scan the code at left with your smart phone or other device to view the product video.

Pistol Grip Vacuum Tester

- Lightweight - only 1.9 lbs. without the plate
- Pulls and holds up to 24" vacuum on as little as 90 PSI • Quick coupling Robinair fittings
- Easy to reach controls for single-handed operation • Hard-anodized billet aluminum
- Tester includes one 4.75" vacuum plate and hose kit with filter

Description	Order No.	Incl.	
Pistol Grip Vacuum Tester Kit	DVC-2011		▼
Optional Vacuum Plates			
Robinair Fitting Replacement Plate Set	DVC-7KIT		▼
2.00" (50.8mm dia.)	DVC-2	x	
3.00" (76.2mm dia.)	DVC-3	x	
4.75" (120.7mm dia.)	DVC-475	x	x
6.00" (152.4mm dia.)	DVC-6	x	
2"x3" (50.8x76.2mm)	DVC-23	x	
3"x4" (76.2x101.6mm)	DVC-34	x	
Plate Lube 8 oz. (236.6 mL)	DVC-PL	x	
Parts & Accessories			
Pressure Gauge	DVC-GAUGE		
Flexible Hose Kit w/3' Air Line (optional)	DVC-2011-HK		▼
1/8" NPT "L" Fitting	CF-2003-L	x	x
1/8" NPT Female Coupling	LDP-AR-6	x	x
Inline Air Filter	DVC-FILTER	x	x
1/8" x 1/4" Straight Fitting	DVC-SF	x	x
Nipple Coupling	DVC-1N	x	x
Air Line	CF-2001-AL	x	x
Robinair Fitting	DVC-SN		
1/8" NPT Male Coupling	DVC-1M		
6 Pc. Replacement Foam Set (1 of each size)	FOAM-KIT		
Replacement Foam Mat - 11" x 31" x 3/8"	DVC-1131		



Sioux-Style Replacement Vacuum Tester Parts

- For Sioux™ 1630K Tester no longer made
- Closed cell foam for an exceptional seal

Sioux-Style Replacement Plates for the 1630K Tester		
Size	OE No.	Order No.
2" / 50.8mm dia.	1630-2	SVT-2
3" / 76.2mm dia.	1630-3	SVT-3
4.75" / 120.7mm dia.	1630-4	SVT-475
6" / 152.4mm dia.	1630-6	SVT-6
2"x3" / 50.8 x76.2mm		SVT-23
3x4" / 76.2 x101.6mm		SVT-34
Replacement Parts for the 1630K Tester		
Replacement Fitting		DVC-SX
Replacement Gauge		1630-GAUGE

Heavy Duty Manual Vacuum Tester

- A steady reading of 25" (63.5cm) indicates proper valve seating
- All metal construction
- 4 3/4" plate, fittings and plate lube included
- DVC Plates (above) will fit this tester



Description	Order No.
Manual Vacuum Tester	DVC-101-HD
Replacement 4.75" Plate	DVC-475
Plate Lube - 8 oz. (236.6 mL)	DVC-PL

Vacuum Testing

tech tips


Vacuum testing is the fastest method for from the techxperts™ testing valve to seat integrity. Simply assemble your machined cylinder head and install the spark plugs. Use a reliable vacuum source producing approximately 24" HG on the vacuum gauge and a closed cell foam test plate with a through fitting to draw down or evacuate the combustion chamber.

Once you've reached 24" HG on the gauge and close the vacuum to the chamber. Watch the gauge for a drop in vacuum. It should hold steady confirming that you have achieved valve to seat mating.

Coat the face of your closed cell foam test plate with Plate Lube (DVC-PL) to condition the foam. This produces a soft, yielding material that will fill minor head surface blemishes or imperfections.



Handy toggle switch turns the unit on and off.



Inline filter keeps debris out of the unit for longer life and more power.



Vacuum control knob has 3 settings — continuous, hold and release

Trego Electric Vacuum Tester

- Check valve to seat seal right on the bench or in the engine compartment — no special set up is required
- This unit is equipped with a vacuum piston pump and generates up to 850 Mbar of vacuum • Reads in PSI
- A built-in pressure control knob allows you to control vacuum settings accurately • 115V, 60Hz, 67W motor
- Dimensions: 9⁷/₈"L x 6³/₄"W x 4¹/₂"H

Description	Order No.	Incl.
Electric Vacuum Tester	VT-KIT	▼
2.00" (50.8mm dia.)	DVC-2	x
3.00" (76.2mm dia.)	DVC-3	x
4.75" (120.7mm dia.)	DVC-475	x
6.00" (152.4mm dia.)	DVC-6	x
2"x3" (50.8x76.2mm)	DVC-23	x
3"x4" (76.2x101.6mm)	DVC-34	x
Plate Lube 8 oz. (236.6 mL)	DVC-PL	x
1/4" Air Line (6')	CF-2001-AL	x
Inline Air Filter	DVC-FILTER	x
1/8" NPT Female Coupling	LDP-AR-6	x

Jet Valve Eliminator Kit

- Some Mitsubishi/Chrysler 2.6L heads had jet valves while some didn't
- This kit lets you use a jet valve equipped head in place of one without
- 11mm diameter, 1.0 pitch threaded plugs replace entire valve body assembly
- Easier than welding the holes closed
- Package of 4 converts one 2.6L head
- Order No. **JVE-26**



.235" Crack Repair Kit

- Complete kit includes everything you need to repair cracked cast iron heads using the cold repair process • Download the Goodson Crack Repair Manual by scanning the code at right with the camera on your smart phone or other smart device



Description	Order No.	Incl.
Complete Repair Kit:	CRK-150	▼
.235" x 15/16" Threaded Iron Plugs (100 Pk.)	CRP-235	1
High Speed Steel Drill	CRD-235	1
High Speed Steel Tapered Reamer	CRR-235	1
High Speed Steel Tapered Taps	CRT-235	2
Cut-Off Saw with Blade	CR-SAW	1
Replacement Saw Blade	CR-BLADE	1
Cutting & Tapping Fluid*	CTF-14	1
All Weather Seal (16 oz.)	AWS-16	1
Ceramic Motor Seal (16 oz.)	CRS-16	1

*Hazardous Goods Fees Apply When Shipped By Air

Threaded Crack Repair Plugs

- Iron • Tapered • Threaded plugs
- Cast to rigid specifications

Plug Size	Qty.	Order No.
.200" x 1 ⁵ / ₁₆ "	100	CRP-200
.200" x 1/2"	100	CRP-201
.235" x 1 ⁵ / ₁₆ "	100	CRP-235
.327" x 1 ³ / ₈ "	50	CRP-327



High Speed Steel Drills

- 118° points for fast chip removal

Plug Size	Order No.
.200"	CRD-200
.235"	CRD-235
.327"	CRD-327



Tapered Reamers

- High Speed Steel

Plug Size	Order No.
.200"	—
.235"	CRR-235
.327"	CRR-327



Tapered Taps

- High strength steel machined to match plug taper & thread

Plug Size	Order No.
.200"	CRT-200
.235"	CRT-235
.327"	CRT-327





"At Goodson, we're always on the lookout for new or improved tools that make engine rebuilding easier. If you have a tool you think we'd be interested in, give us a call."
- Richard, Goodson Product Manager, 26 years of service

shown actual size



melted center
reveals
overheating

Heat Tabs

- Provides visual evidence of engine overheating
- Special heat sensitive metal centers melt and fall out when engine exceeds the melting point of the tab
- 100 Heat Tabs per package
- Attach to heads with Heat Tab Adhesive (below)

Description	Melting Point	Order No.
Round Heat Tabs	255-260° F / 124-127° C	RHT-100
Round Ironite Heat Tabs	255-260° F / 124-127° C	HT-100RD
Round Diesel Heat Tabs	225-235° F / 107-110° C	DHT-100
Heat Tab Adhesive (3 oz./88.7mL tube)		HTA-3

Leak Detection Mat

- Commercial-grade Neoprene
- Resists petroleum products, abrasion, swelling, sunlight and aging
- Repair worn mats or make custom leak detection plates
- Measures 3' x 4' x 3/16" thick
- Order No. **LDP-34MAT**



Rust Inhibitor for Pressure Testing

- Clear fluid inhibits rust and does not discolor or cloud the test tank solution
- Lets you see better to pressure test
- Biocide and anti-rust additives extend tank solution life while preventing corrosion
- Synthetic formula
- Mix 20:1 with water
- Yields 20 gallons
- Order No. **PRI-10**



Seal-All™

- Seals pin holes, porosity and small cracks in heads & blocks
- Penetrates and seals
- Out-performs ceramics
- Bonds with existing rust & corrosion to prevent spread
- Heat at 175°-200°F (79.4°-93.3°C) for 4 hours to cure
- Not for use on assembled engines
- 32 oz. (946 mL)
- Order No. **CPS-32**



Fluid Weld®

- For cast iron or aluminum heads and blocks
- Use as a sealant for threaded or press-fit parts like valve guides and seats, threaded crack repair plugs, replacement studs, etc.
- Seals small cracks • Non-toxic
- Non-flammable
- **NOT** for use on assembled engines
- Withstands temperatures to 3000°F



Size	Order No.
2 oz. (59 mL)	FW-2
8.8 oz. (260 mL)	FW-88

All Weather Seal

- Seals intakes & head gasket leaks
- Seals cracks in cylinder heads & engine blocks
- Prevents anti-freeze from seeping through gaskets and hoses
- Lubricates water pump seals
- Mixes with all anti-freeze and coolant
- Works in less than 5 minutes
- Fast-acting, non-corrosive, non-clogging
- Can be used with coolant or anti-freeze
- 16 oz./455 mL • Order No. **AWS-16**



Ceramic Motor Seal

- Permanently seals leaking head gaskets, cracked heads and blocks (aluminum or cast iron)
- Coats the engine to inhibit rust formation and salt water corrosion during normal operation
- Seals porous castings in the cooling system
- Stops coolant leaks
- Not compatible with any anti-freeze or coolant, follow instructions on package
- Promotes heat dissipation for added power
- 16 oz./455 mL
- Order No. **CRS-16**



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

full service ...fast



"We pride ourselves on getting orders to you quickly. We stock a wide variety of products in our warehouse and we use most shipping carriers so you can receive your order in 3 days or less."

- Shawn K. Goodson Shipping, 5 years of service

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES


BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

43 Piece Deluxe Porting Kit

- Professional grade porting supplies
- Packed in a clear plastic storage case



Description	Order No.	Incl.
43 Pc. Kit	DPK-100	▼
Replacement Abrasives	Grit	Kit Qty.
Flap Wheels - 1" x 1" x 1/4"	120	2
	AFW-1-120	X
Cross Buffs 3 Ply, 1 1/2"	Med	2
	CB-15M-HD	X
	Very Fine	2
	CB-15VF-HD	X
Cross Buff/Flapwheel Mandrel		1
	CB-MANDREL	X
1/4" Dia. Straight	40	2
	SCR-250-40	X
Cartridge Rolls	80	5
	SCR-250-80	X
3/8" Dia. Straight	40	2
	SCR-375-40	X
Cartridge Rolls	80	5
	SCR-375-80	X
1/4" Dia. Straight	40	2
	SCR-750-40	X
Cartridge Rolls	80	2
	SCR-750-80	X
1/2" Dia. Half Tapered	40	2
	HTR-500-40	X
Cartridge Rolls	80	5
	HTR-500-80	X
3/8" Dia. Full Tapered	40	2
	FTR-625-40	X
Cartridge Rolls	80	5
	FTR-625-80	X
Cartridge Roll Mandrel	2 3/4" Long	1
	CR-275	X
	4" Long	1
	CR-40	X
Mounted Points - 3/8" x 3/4"	60	1
	GM-B52	X
1 1/16" x 1 1/4"	60	1
	GM-12	X

See next page for replacement abrasives

small engine powersports 40 Piece Small Engine Porting Kit

- Professional grade porting supplies
- Packed in a clear plastic storage case



Description	Order No.	Incl.
40 Pc. Kit	SEPK-5	▼
Replacement Abrasives	Grit	Kit Qty.
Flap Wheels - 1" x 1" x 1/4"	120	2
	AFW-1-120	X
Cross Buffs 2 Ply, 3/4"	Very Fine	2
	CB-75VF	X
	1" Medium	2
	CB-1M	X
	1 1/2" Very Fine	2
	CB-1VF	X
	Very Fine	2
	CB-15VF	X
Cross Buff/Flapwheel Mandrel		1
	CB-MANDREL	X
3/8" Dia. Straight	80	4
	SCR-375-80	X
Cartridge Rolls	120	4
	SCR-375-120	X
	320	4
	SCR-375-320	X
3/8" Dia. Half Tapered	80	4
	HTR-375-80	X
Cartridge Rolls		
3/8" Dia. Full Tapered	80	4
	FTR-375-80	X
Cartridge Rolls	120	4
	FTR-375-120	X
1" X 2 Yds. Abrasive Roll	120	1
	UR-1-120	X
	320	1
	UR-1-320	X
Cartridge Roll Mandrel	2 3/4" Long	1
	CR-275	X
	4" Long	1
	CR-40	X

See next page for replacement abrasives

Intake Port Reshaping Kit

- Superior formula uses 2-part epoxy
- Won't shrink when dry
- Mix ratio is 1:1 by weight
- Mix and knead the parts together by hand until the yellow and black colors have combined to make a uniform olive green color
- Working time at 70°F: Golf ball size mix: 40 minutes max.; Baseball size mix: 30 minutes max.
- Cure time at 70°F: full hardness in 6 to 8 hours
- Once cured, forms a hard coating resistant to abrasion, impact, water, chemicals and solvents
- **NOT** for use in contact with potable water or exhaust ports
- Can be milled or machined
- Withstands temperatures up to 500°F/ 260°C
- Kit includes epoxy, gloves and mixing sticks
- Yields 16 oz./453.6g of material
- 24 month shelf-life
- Order No. **PRK-99**



tech tips

Adhesion of PRK-99 will be only as good as the cleanliness and soundness of the substrate. Remove all dirt, oil and grease. Soda blasting is acceptable. Scraping, wire brushing and other manual cleaning methods may also work. Do NOT use a petroleum-based cleaner before using PRK-99, it will prohibit adhesion.

NOTE: Extreme caution must be used when porting & polishing. Be sure to wear safety glasses.

Quick Change Mandrels & Abrasive Sleeves

- 5 sleeves per pack • 1" x 1"
- Mandrel has 1/4" shaft



Description	Grit	Order No.
Mandrel		GMS-101
Sleeves	40	GMS-140
5 Pack	60	GMS-160

Variable Speed Control

- Vary tool speed from 200 to 25,000 RPM
- Control switch with 3 settings - Variable Speed, OFF and Full Speed
- Speed control dial
- 31 1/2" long grounded cord with standard US plug • Fuse protected
- Built in grounded control outlet
- Not compatible with brushless motors
- Order No. **GEO-SC**



Professional Porting & Polishing Tools

Aluminum Oxide Cloth Utility Shop Rolls

- 1" x 50 yards
- Easy to use ... just unroll and tear to length
- Use with butterfly mandrels at right



Grit	Order No.
60	UR-1-60
80	UR-1-80
100	UR-1-100
120	UR-1-120
180	UR-1-180
320	UR-1-320

Crocus Cloth

- Must be used with Lapping Oil
- Great for final touch-ups on cranks, rod pins, valve stems, cams, etc.
- Use with slotted mandrels at right



Description	Order No.
1" x 50 yd. Roll	UR-1-CROCUS
8 oz. Lapping Oil	LP-LO-8




Slotted Butterfly Mandrels

- Use with roll abrasives such as those at left • Several lengths available

Length	Order No.
3"	BM-3
6"	BM-6
8"	BM-8

Want a different abrasive? We can make it in-house. Contact us for more information!

Replacement Abrasive Packs and Mandrels



Replaceable Roll Lock Discs

10 per pack

Dia.	Order No.
2" Medium	RSCD-2M
Coarse	RSCD-2C
3" Medium	RSCD-3M
Coarse	RSCD-3C
Disc Holder	Order No.
2" Dia.	RLH-2
3" Dia.	RLH-3



Aluminum Machining Aid

- Designed for aluminum
- For porting & polishing with cartridge rolls, rotary files, emery cloth or Cross Buffs® • Safe for cast iron
- 32 oz./946.4mL
- Order No. PF-32

HazMat shipping charges apply when shipped by air

Straight Cartridge Rolls

- 1½" long, ⅛" hole
- Fully glued • Box of 50

Dia.	Grit	Order No.
¼"	40	SCR-250-40
	80	SCR-250-80
	120	SCR-250-120
⅜"	40	SCR-375-40
	80	SCR-375-80
	120	SCR-375-120
½"	320	SCR-375-320
½"	40	SCR-500-40
	60	SCR-500-60
	80	SCR-500-80
	100	SCR-500-100
	120	SCR-500-120
¾"	40	SCR-750-40
	80	SCR-750-80
	120	SCR-750-120

Roll Mandrels

Use with straight and tapered cartridge rolls • 1/8" pilot x 1/4" dia.

OAL	Order No.
2¾"	CR-275
4"	CR-40
6"	CR-60
8"	CRM-8H
10"	CRM-10H
12"	CRM-12H

Mirrored Safety Glasses

- Wrap-around design • Tinted lenses provide sun glare protection • Universal bridge • Polycarbonate lenses
- Do not use as welders helpers • Great for protecting your eyes when riding your motorcycle too
- Order No. PGL-21



Half-Tapered Cartridge Rolls

- 1½" long, ⅛" hole
- Fully glued • Box of 50

Dia.	Grit	Order No.
⅜"	40	HTR-375-40
	80	HTR-375-80
½"	40	HTR-500-40
	80	HTR-500-80

Full-Tapered Cartridge Rolls

- 1½" long, ⅛" hole
- Fully glued • Box of 50

Dia.	Grit	Order No.
⅜"	40	FTR-375-40
	80	FTR-375-80
	120	FTR-375-120
	320	FTR-375-320
½"	40	FTR-500-40
	60	FTR-500-60
	80	FTR-500-80
	120	FTR-500-120
¾"	40	FTR-625-40
	80	FTR-625-80

3M® Cross Buffs®

Premium Quality

- Aluminum-Oxide
- Box of 10

Dia.	Grit	Order No.
2-Ply		
¾"	V. Fine	CB-75VF
	Med.	CB-75M
1"	V. Fine	CB-1VF
	Med.	CB-1M
1½"	V. Fine	CB-15VF
	Med.	CB-15M
3-Ply		
1¼"	Med.	CB-125M-HD
1½"	V. Fine	CB-15VF-HD
	Med.	CB-15M-HD



Abrasive Flapwheels

- 1" wide, ¼" x 20 threaded
- Aluminum-Oxide • 1 each

Dia.	Grit	Jobber	Order No.
1½"	80	\$15.99	APK-7
1"	120	10.99	AFW-1-120
2"	120	12.49	AFW-2-120
3"	120	14.49	AFW-3-120



- Cross Buff® / Flap Wheel Mandrel
- Use with Cross Buffs & Flap Wheels above

Description	Order No.
4" Mandrel	CB-MANDREL
Set Screw (3)	CB-SCREW

NOTE: Extreme caution must be used when porting & polishing. Be sure to wear safety glasses.

Iron-Clad Guarantee



"We unload, check and store inventory as efficiently & accurately as possible and we make sure all inventory is accounted for."

— Shane, Goodson Receiving Supervisor, 8 years of service

tech tips

from the techxperts™

Stay Safe:

Always ensure your burr shank is well inserted into your collet and clamped down tightly.

Keep pressure light and keep the burr moving focusing on the highest material first.

Ensure your work is secured tightly to your work bench.

Don't snag or jam your burr into your work.

Wear eye protection as a minimum, but better still, use a full shield for your face.



Double Cut Carbide Rotary Files

• ¼" dia. shank

Dia.	Length	Shank	Order No.
½"	1½"	1.1"	FR-34-C
¾"	1"	1.0"	FR-45-C




FR-45-C



¼" Shank Mounted Points

• Aluminum-Oxide abrasive is ideal for roughing cast iron • 1½" shank length


Dia.	Length	Grit	Order No.
A ¾"	2½"	60	GM-1
B ¾"	2¾"	60	GM-3
C ¾"	1"	60	GM-11
D 1½"	1¼"	60	GM-12
E ¾"	1½"	60	GM-5
F ¾"	1½"	60	GM-15
G ¾"	1"	60	GM-23
H 1"	1"	60	GM-25
I 5/8"	5/8"	60	GM-26
J 13/8"	1"	60	GM-31
K 1"	1"	60	GM-38
L ¾"	¾"	40	GM-40
M ¾"	¾"	60	GM-B52
N 1½"	1½"	60	GM-236



6" Long ¼" Dia. Shank Open Fluted Rotary Files for Aluminum

- Carbide burrs
- Open flute design gives better chip discharge

	Dia.	Length	Order No.
A	½"	1"	LAFR-34
B	¾"	¾"	LAFR-45
C	½"	7/16"	LAFR-55
D	½"	7/8"	LAFR-70
E	½"	1"	LAFR-93
F	¾"	1½"	LAFR-121



6" Long Shank Double Cut Carbide Rotary Files

• ¼" diameter shank

Dia.	Length	Order No.	Incl.
Complete 5 Pc. Kit		LFR-KIT	▼
A ½"	1½"	LFR-34C	x
B ¼"	½"	LFR-45C	x
C ½"	½"	LFR-55C	x
D ½"	1½"	LFR-46C	x
E ½"	1½"	LFR-141C	x

Save when you buy the kit!



¼" Carbide Rotary Files

- Nose design reduces back-gouging
- ¼" shank • Shanks 4" long except MRT-56C at 6" long

Dia.	Length	Order No.
A ¾"	1"	MSH-34C
B 1½"	7/8"	MSE-44C
C ½"	3½"	MRT-54C
D ½"	1"	MRT-56C

Dia.	Length	Order No.
E ½"	7/8"	MSE-54C
F ½"	1"	MSF-54C
G ½"	1½"	MSH-54C



Bifocal Magnifying Safety Glasses

- Safety glasses and cheaters all in one • Anti-fog lenses
- Do not use as welders helpers

Diopter	Order No.
1.00	BSG-100
1.25	BSG-125
1.50	BSG-150



Mirrored Safety Glasses

- Wrap-around design
- Tinted lenses provide sun glare protection
- Universal bridge
- Polycarbonate lenses
- Do not use as welders helpers
- Great motorcycle shades
- Order No. PGL-21

Misc. Cylinder Head

Rocker Arm Stud Conversion Kit

- Convert pressed-in rocker arm studs to threaded studs
- Remove stud, face stud boss, then drill and tap the stud hole
- Use with a seat and guide machine

Description	Order No.	Incl.
Conversion Kit	S-450-KIT	▼
Stud Boss Facer	S-450-F	x
3/8" Drill Bit	S-373D	x
7/16" x 14 Thread Tap	S-437T	x
3/8" Pilot	S-373P	
2 Pc. Tap Guide	S-350G	

S-373P
Pilot shown installed

S-450-F

S-373D

S-437T

S-350G



Economy Cylinder Head Holder

- Holds head with either side up
- Tapered pins fit virtually any size head bolt hole and loosen with a twist
- Ideal for guide sizing with ample clearance to remove arbors and reamers
- Two piece set • Order No. HH-100-G



Manual Rocker Arm Stud Puller

- Heavy-duty ball bearing action
- Creates less stress and friction
- Fits 5/16" (7.9mm) and 3/8" (9.53mm) threaded studs
- Not recommended for use on thermally cleaned heads

Description	Order No.
Complete Stud Puller	SP-600
Drive Nut	SP-601
Puller Body	SP-602
5/16" and 3/8" Mandrel	SP-603
Thrust Bearing	SP-604

SP-603 •

SP-601 •


SP-604 •

SP-602 •



Ultra-Sturdy Cylinder Head Holder

- 360° stand holds head securely in position
- Tie-rod to prevent tipping
- Slip-resistant neoprene covered rails
- Fits domestic, foreign, truck & motorcycle heads
- 3-piece set
- Order No. HH-450



Set screws hold the two pieces firmly in place

Universal Threaded Stud Extractor

- Use with your pneumatic impact tools & sockets (15/16" socket removes, 17/16" installs)
- Requires only 3/4" clearance to adjacent studs
- For threaded studs only • Fits 3/8" socket
- Hardened 3-jaw clamping system
- Internal taper support • Hollow body allows long studs to extend through the tool
- 1 1/2" dia. x 2 7/8" long • 1/4" - 1/2" range



Description	Order No.
Universal Stud Extractor	PSR-375
Replacement Parts	
Jaws	PSR-JAWS
Spring Set (3 Piece)	PSR-3S
Snap Ring	PSR-SR



Universal Cylinder Head Holder

- Accommodates all types of cylinder heads
- Sturdy, durable, lightweight aluminum construction
- Slip-resistant neoprene covered rails
- Place heads quickly into any position and rotate them easily through 360°
- Requires no bolts, clamps or adaptors
- 2 piece set • Order No. HH-200



Torque-Angle Indicator

- When torque is given as degrees of turn past a certain ft./lb., use this gauge to show degrees
- Hold metal base with one hand
- Plastic dial turns as you tighten
- Fits between a socket-driven extension and the socket
- 1/2" square drive
- Order No. TQR-4554



Professional Measuring & Inspection Stand

- Length adjusts up to 23"
- Rotate work to view or measure
- Solid aluminum frame with self lubricating, corrosion and chemical-resistant wear surfaces
- Order No. PMIS-30



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

... another
satisfied
customer

"Outstanding customer service; always. Goodson has gone above and beyond to assure we have the tooling we need."

— Jimmy Stray, Metro Motor Center, Houston, TX, Goodson customer since 1990

CYLINDER HEAD
REBUILDING

Brass or Steel Shim Stock Assortment Packs

- A handy assortment • 4" x 6" each (120 sq. in.)
- One each of .001", .002", .003", .005", .010" thick

Description	Order No.
Brass	SSB-50
Steel	SSS-51

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING



Smog Plugs

- Fit Ford 302 & 351
- Replace smog plugs damaged during head cleaning
- 5/8" x 11 thread outside, 7/16" x 14 thread inside
- Order No. **EMP-34**

CRANKSHAFT/
FLYWHEEL GRINDING

Premium Tapered Reamer

- Use by hand or with a powered driver to deburr or enlarge tapered holes for valve guides, bolt hole chamfering and more • Use in 1/2" chuck at approximately 40 RPM for best results • OAL: 5 3/4"
- Flute length: 3 3/4" • Small End: 1/8" dia. • Large End: 1/2" dia.
- Degree of Taper: 2.86° • Hardened and tempered steel with precision ground cutting edges • For steel, brass, aluminum, plastic, wood and more
- Order No. **TR-216-1**

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS


V-TWIN & METRIC
HARD PARTS

14mm Spark Plug Thread Chaser/Burnisher

- Ideal for cleaning spark plug holes
- Reforms the original material by burnishing, not cutting so no chips are created to be cleaned out
- Order No. **SPB-14**

Two Blade Spot Facer

- 1 1/4" OD Spot Facer located on 3/8" stud
- Removes unneeded material for easier removal and installation of screw-in studs
- Replaceable carbide blades



Description	Order No.	Incl.
Stud Boss Facer	SBF-5587	▼
Stud Boss Facer Tip (each) for SBF-5587 only	SBF-5587T	x
Stud Boss Facer Screw (each)	SBF-5587S	x
Replacement Stud Boss Facer 3/8" Pilot (optional)	SBF-5587P	



Head Bolt Spot Facer

- Spot face head bolt seat parallel to new deck surface after angle milling
- Allows proper head bolt torquing
- Cutting tip radius matches OE design to avoid stress points and cracks • .468" shank with flat
- Use with 7/16" Pilot below
- High Speed Steel construction



Description	Order No.
Spot Facer	HBF-15
7/16" Pilot	GFP-437

GM Vortec Adaptor Plate Set For Van Norman & Storm-Vulcan Rotary Broaches

- Required when using the Van Norman VN 530 / 570 or Storm-Vulcan 850 Storm-Mill Rotary Broaches
- Two plate set • Includes fasteners
- Order No. **VN-VOR**



Chevy Conversion Plate Set



- Convert early model, 6-bolt heads for late model, 7-bolt applications
- Works with stock exhaust systems
- Use the standard exhaust manifold gasket or seal with High-Temp Silicone
- Order No. **CHC-10**



Parts Storage

Dual Overhead Cam Cylinder Head Organizer Tray

- Store valves, springs, retainers, keepers, valve lash adjusters & camshafts • Keep valve lash adjusters from getting mixed up and changing valve adjustment
- Heavy duty construction
- Oil and solvent resistant
- Measures: 23 $\frac{1}{4}$ " x 26 $\frac{1}{2}$ " x 2"H
- Order No. **DOHC-1**



Stackable Cylinder Head Organizer Trays

- Store valves, springs, retainers and keepers in order of assembly • Impervious to oil and most solvents
- Measures 28" x 12 $\frac{1}{2}$ " x 3"H
- Order No. **SHO-8**


Valve Train Tray For 4, 6 or 8-Cylinder OHV Engines

- Heavy duty construction
- Keeps push rods, rockers, lifters, etc. in order
- 64 compartments
- Measures: 11 $\frac{7}{8}$ "W x 23 $\frac{1}{4}$ "L x 1 $\frac{3}{4}$ " H
- Order No. **VTO-80**



Ford/Chevy Small Block Organizer Tray

- Store pistons, rods, lifters, push rods & camshafts
- Formed compartments keep engine components securely in place
- Measures: 24 $\frac{1}{4}$ " x 25 $\frac{1}{2}$ " x 1 $\frac{1}{2}$ "D
- Order No. **iEO-80**




Top tray features 1" deep lip to keep parts from rolling off

Solid steel hangers hold piston rods and crankshafts
Heavy duty casters make moving the engine and cart easy

Engine Storage Cart

- An efficient space-saver
- Heavy-duty casters
- Holds all engine parts off the floor from tear-down to reassembly in less than 4 square feet
- Move the whole engine easily
- Some assembly required
- Order No. **EC-200**



dimensional shipping



Organizer Safety Pins Keep Part Sets Together

Parts Safety Pin • Organize valve springs, rods, etc., from disassembly to cleaning to reassembly
Rod & Cap Mini Pin • Keep connecting rods & rod caps together to prevent mix-ups

Description	Order No.
Parts Safety Pin (3 $\frac{3}{4}$ " x 12")	PSP-20
Rod & Cap Mini Pin (3 $\frac{1}{4}$ " x 4")	RSP-10
Mix or match to make quantity break	

Parts Tags & Marker

- Won't tear or wash off
- Heavy wire ties
- Tough enough to go through a jet wash or hot tank
- Includes 2 Super-Permanent markers with specially formulated ink to withstand most chemicals and extreme heat and steam up to 500°F
- Tag dimensions: 3 $\frac{1}{2}$ "L x 5 $\frac{1}{8}$ "W with 5 $\frac{1}{32}$ " hole for wire tie

Description	Order No.
1000 Parts tags, with 2 markers	IDT-1000
Super-Permanent Marker only	IDT-MARKER



Parts Storage & Cleaning

dimensional
shipping

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS


Organize, Clean And Store Small Parts With GOODSON Small Parts Baskets

- Galvanized, welded 1/4" mesh
- Can be used with caustics
- Not for use with alkaline or acidic solutions, parts tumblers or shot blasters



Small Basket with Lid

- 2 1/4" dia. x 7" L
- Order No. **PWB-2**



Medium Basket with Lid

- 4 1/2" dia. x 7" L
- Order No. **PWB-4**



Single Basket with Handle

- 8.75" OD x 8.5" H
- Lid & clip sold separately
- Order No. **PWB-10**



Single Basket with Lid, Clip & Handle

- 8.75" OD x 8.5" H
- Order No. **PWB-15**



Double Basket with Clip

- 8.75" OD
- 17" H
- Hinged on one side
- Order No. **PWB-25**




Lid & Clip


- For PWB-10
- Order No. **PWB-10L**

Clip Only

- Order No. **PWB-15C**



Six
baskets
fit in 24"
diameter



Jet Wash Parts Baskets

- Triangle-shaped • Sit side by side on Jet Wash table
- 6 baskets make a 24" circle
- Fit more baskets in the machine to clean faster
- Order No. **JWB-6**



BC-17



BC-15



BE-20

Engine & Parts Storage Bags

- Rugged, 3-mil thickness resists tearing
- Engine bags feature 4-mil thickness for extra strength
- Protects your professional work
- Waterproof • Protect finished work from damage
- Jumbo engine bags are extra-strong and big enough to fit complete engines
- Jumbo head bags fit the largest heads
- Ideal for storing heads, cranks, blocks, etc.

Description	Size	Thickness	Qty.	Order No.
Heads, Cranks	16" x 37"	3-mil	100	BC-15
			10	BC-15-10PK
Jumbo Head	17" x 44"	3-mil	100	BC-17
			10	BC-17-10PK
Box-Style	27"x18"x36"	3-mil	50	BE-20
			10	BE-20-10PK
Jumbo Engine	44" x 52"	4-mil	50	BE-44
			10	BE-44-10PK
(Imprinted)				

Shrink Wrap

- Easy-to-use
- High-clarity film
- Keep machined surfaces clean
- Protects from dirt, dust and moisture
- No need to stock several bag sizes

Size	Order No.
5" x 1000' w/ Extended Core	SW-5
18" x 1500' with 3" core	SW-18



Flock Lined Nitrile Parts Gloves

- Nitrile exterior with diamond grip pattern
- Flock lined • Won't swell • 13" long
- Safe for solvents • Sold as pairs

Size	Order No.
Large	PWG-SOL-L
X-Large	PWG-SOL-XL
XX-Large	PWG-SOL-XXL



Radial Wire Brushes

- American made oil tempered high carbon steel wire
- High density for faster cleaning and longer life
- Excellent balance • ½" - ¾" arbor

Size	Wire	Duty	Order No.
6" x 1 3/16"	.014" Crimped	Std.	ADA-6
7" x 7/8"	.014" Crimped	Heavy	DA-7
6" x 9/16"	.016" Twisted	Super	TS-6
8" x 3/4"	.016" Twisted	Super	TS-8
6" x 7/16"	.023" Knotted	Ultra	QTC-6



Super Heavy Duty Double-Fill Cylinder Block Washing Brushes

- Highly aggressive
- Long lasting
- .050" Nylon bristles

Diameter	Order No.
4" (101.6mm)	CWB-40DF
4 1/2" (114.3mm)	CWB-45DF



3M™ Roloc™ Bristle Discs

- Effective on cast iron, yet safe for aluminum
- Less aggressive than wire wheels
- Abrasive grains embedded in flexible plastic bristles that break down exposing new grain
- Bristles flex to maintain contact with contoured surfaces for faster, more thorough cleaning
- Use with holders below

Size	Color	Grit	Max. RPM	Order No.
2"	Green	50	25,000	RBD-2G
	Yellow	80	25,000	RBD-2Y
	White	120	25,000	RBD-2W
3"	Green	50	18,000	RBD-3G
	Yellow	80	18,000	RBD-3Y



Surface Conditioning Discs

- Use with holders at right
- 10 per box

Dia.	Order No.
2"	Medium RSCD-2M
	Coarse RSCD-2C
3"	Medium RSCD-3M
	Coarse RSCD-3C

Roloc-Type Holders

- Use with Surface Conditioning Discs (left) and Bristle Discs (above)
- Threaded

Size	Order No.
2"	RLH-2
3"	RLH-3



Super Scraper™

- Remove gaskets, carbon, rust, paint, etc.
- Precision-ground solid carbide-tipped, double-edged blade lasts longer than plain steel
- Nickel-chrome 1/8" thick steel shank • For all metals including aluminum

Width	Order No.	Incl.
3 Pc. Set	SS-SET	▼
5/8"	SS-4U625	x
1 1/4"	SS-4U	x
2"	SS-4U2	x

Buy the Kit,
SAVE!



Engine Rebuild Brush Kit

- Includes the brushes you'll need for an average engine job
- A great starting place, then add more brushes as you need them • Replacement brushes available

Description	Order No.
Standard Brush Kit - 10 Pc. Kit	BG-KIT ▼
4" Nylon Cylinder Washing Brush	CWB-40 x
1 1/32" Nylon Valve Guide Brush	GVP-2N x
3/8" Nylon Valve Guide Brush	GVP-3N x
Lifter Bore Brush	LBB-100 x
Small Nylon Feed Hole Brush	OB-1 x
Block Oil Return Line Brush	OB-2 x
3/8" Oil Gallery Brush	OGB-38 x
1/2" Oil Gallery Brush	OGB-42 x
5/8" Oil Gallery Brush	OGB-5 x
Round Fiber Parts Brush	PCB-348 x

Low Lint Disposable Assembly Wipes

- Blue, low lint wipes
- Pop-up box
- Hard-wearing
- Tear-resistant
- Ideal for a multitude of uses at the shop, at the track, even at home! • 100 per box
- Order No. **AW-100B**



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Steel End Brushes


Dia. / Wire gauge / Type	Order No.
Standard Duty	
1/2" .020" crimped	GBC-4
3/4" .020" crimped	GBC-6
1" .020" crimped	GBC-10
1 1/2" .020" crimped	GBC-14
1 3/4" .012" crimped	NH-16
2 3/4" .012" crimped	NH-26
1 3/4" .014" galv. for alum.	ANH-16
2 3/4" .014" galv. for alum.	ANH-26
Ultra Duty (listed left to right)	
1/2" .014" crimped	GBC-4A
1 1/8" .020" knotted, 11/4"L	GBC-12
1 1/8" .020" knotted, 7/8"L	GBC-12HD
3/4" .020" knotted	NH-6

GBC-4 GBC-6 GBC-10 GBC-14



Engine Prep Brushes

Application	Order No.
For small feed hole in block 1/4" x 2" x 10", nylon	OB-1
For Block Oil Return Line 5/16" x 2 1/2" x 12", nylon	OB-2
For Cam & Crank Work 5/16" x 2 1/2" x 12", nylon	OB-2A
For Block Oil Return Lines 3/8" x 2 1/2" x 12", nylon	OB-3
For diesel injector 1 3/4" brush, stainless	DIB-1
For lifter bores 1" x 3" x 14", nylon	LBB-100

Nylon Bristle
Oil Gallery BrushesSteel Wire
Oil Gallery Brushes


Desc.	Order No.	
3-pc. Kit	OGB-SK	▼
1/4" x 3" x 24"	OGB-1	x
3/8" x 3" x 24"	OGB-2	x
5/8" x 3" x 24"	OGB-3	x
Desc.	Order No.	
5-pc. Kit	OGB-KIT	▼
3/8" x 3" x 34"	OGB-38	x
1/2" x 2 1/2" x 34"	OGB-42	x
5/8" x 3" x 34"	OGB-5	x
3/4" x 3" x 34"	OGB-7	x
3/4" x 3" x 40"	OGB-8	x

Nylon
Pushrod Brush

- Clean the inside diameter of your pushrods with this brush
- Fits pushrods as small as .080" ID
- 12" overall length
- Order No. **PRB-80**

5 Pc.
Nylon
Valve
Guide
Brush Set


- Complete set includes 5 popular nylon brush sizes
- From 5/16" to 1/2" dia.
- Order No. **GVP-SET**




1/4" Shank Steel Brushes

Deep Well End Brush as brush wears cut back to expose new wire

Dia.	Wire Gauge	Grade	Order No.
1/4"	.012", 6" long	Economy	DEB-1
3/8"	.017", 6" long	Economy	DEB-2
Flare Brush use to remove carbon from engine ports			
1/2" ball, 5/16" cable		Ultra-duty	DEB-3
Port Brush as brush wears cut back spring for new wire			
3/8"	.014", 4" long	Standard	DEB-4
1/2"	.020", 2 1/2" long	Ultra-duty	DEB-5
Cup Brush 5/8"-11 NC - fits standard 4 1/2" angle grinder			
3"	.014" twisted	Ultra-duty	WCB-30
4"	.014" twisted	Ultra-duty	WCB-40

Manual
Guide
Cleaning
Brush


- 1/2" Dia. Nylon bristles
- OAL: 8 3/4"
- Order No. **WCB-44**

Round Fiber
Parts Brush

- 11" long • Nylon bristles
- Plastic Handle
- Order No. **PCB-348**

Nylon
Lifter Bore
Brushes

Dia.	Order No.
7/8"	LBB-875
1"	LBB-100
1 1/8"	LBB-1125



Nylon Bore Washing Brushes

Dia.	Length	Order No.
2"	36"	CBB-200
2 1/4"	36"	CBB-225
2 1/2"	36"	CBB-250
2 3/4"	12"	CWB-27W
3 1/2"	18 1/2"	CWB-35
4"	18 1/2"	CWB-40
4 1/2"	18 1/2"	CWB-45
5"	18 1/2"	CWB-50


Flow
Through
Parts
Washing
Brush

- 24" long hose slides over discharge nozzle on parts washer
- Order No. **PWB-FLO-1**



Valve Guide Brushes

Size	Steel Brushes		Nylon Brushes	
	OAL	Order No.	OAL	Order No.
5/16" x 2 1/2"	9 1/2"	GVP-1	12"	GVP-1N
1 1/32" x 2 1/2"	9 1/2"	GVP-2	12"	GVP-2N
3/8" x 2 1/2"	9 1/2"	GVP-3	12"	GVP-3N
7/16" x 2 1/2"	9 1/2"	GVP-4	12"	GVP-4N
1/2" x 2 1/2"	-----	-----	10 1/2"	GVP-5N
9/16" x 2 1/2"	-----	-----	10 1/2"	GVP-6N
3mm x 1 1/4"	-----	-----	8"	GVP-7N
4mm x 1 1/4"	-----	-----	8"	GVP-8N
5mm x 1 1/4"	-----	-----	8"	GVP-9N
6mm x 1 1/4"	8"	GVP-10S	8"	GVP-10N
7mm x 1 1/4"	8"	GVP-11S	8"	GVP-11N



Parts Cleaning



Concentrated Defoaming Agent Stops Foaming In Coolants

- For jet washers, air-agitated hot tanks and coolant sumps
- Highly concentrated – start with 1 ounce in 50 gallons

Size	Order No.
8 oz. / 236.6mL	D-FOAM-10
1 gallon / 3.78L	D-FOAM-128



Concentrated Hot Tank Detergent Powders For Cast Iron

- Strong alkaline • pH 12.8
- Removes dirt, heavy oil, grease, carbon, light rust and paint
- Mix ratio 1/2 lb. powder to 1 gal. of water
- 25 lbs.
- Order No. D-Ci25

Hazardous Goods Fees Apply – Non-Returnable*

pH Test Strips

- Easy to use • 100 tests per package
- Use the handy guide on the box to determine pH between 0 and 14
- Order No. HT-PH
- Jobber \$56.99



tech tips

from the techxperts™

Pay attention to the mix ratio on cleaning products!

It's important that you start mixing on the weak side and work your way up. An overly strong concentration is just as ineffective as an overly weak mixture. Use pH Test Strips to check the concentration.

Nozzle

Hydro-Air Gun

- Hold by the air supply hose
- Use with hot or cold water
- The grip stays cool even when spraying hot water
- Maintenance free design
- Compact for reaching into tight areas
- Replacement parts available



Description	Order No.
Hydro-Air Gun Assembly	BG-150
Replacement Water Shut-off	BG-150W
Replacement Nozzle	BG-150A

Pro Jet Spray Cleaning Powder

- Heavy-duty • Non-caustic
- Penetrates to emulsify encrusted dirt, grease and oil on cast iron & aluminum
- Won't foam excessively
- Additives prevent scale build-up in jet spray components
- Use to maximum 165° F / 73.9° C
- Mix ratio: 4 oz. powder to 1 gallon of water • pH: 12
- 40 lb. / 18.14 kg pail
- Order No. PJS-50

With Rust Inhibitor



Concentrated Hot Tank Detergent Powders For Non-Ferrous Parts

- Safe on aluminum & sensitive metals, rubber & plastic parts
- Removes heavy grease and oil
- 50 lb. pail • pH: 12.85
- Mix ratio: 1/4 lb. powder to 1 gallon of water
- Order No. D-AL50

Hazardous Goods Fees Apply – Non-Returnable*

Hot Tank Gloves

- One size fits most
- Sold in pairs
- Neoprene fully coated with knit lining and textured grip
- Shoulder length features eyelets & strings at tops to prevent slipping



Description	Order No.
Gauntlet Length (14" long)	HTG-200
Elbow Length (17 1/2" long)	HTG-200E
Shoulder Length (34 1/2" long)	HTG-200L

Full Length Neoprene Shop Apron

- Protects from caustics, steam, grease and oil
- Bib-style • 35" x 45"
- Order No. HTA-300

Shown with Shoulder Length Hot Tank Gloves (above)



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS




"Our easy-to-use catalog features more than 8,000 tools and supplies. Feel free to call if you're not sure what to order or if you have questions. We'll do everything we can to help you get what you need."

-Becky, Goodson Inventory Control, 11 years of service

Glass Bead Gun for Smaller Machines

- Solid brass body
- Fits Trinco, Econoline, etc.
- Includes Gun Body, Nozzle and Air Jet Assembly
- Replacement parts available

Description	Order No.
Complete Gun For Smaller Machines	GB-113
Replacement Parts	
Gun body only	GB-111
Carbide nozzle 19.05mm OD, 7.94mm ID	GB-204
Air jet assembly 3.97mm ID, 25 CFM	GB-330



Glass Bead Cabinet Window Film

- Protects the inside of glass bead cabinet windows
- Save time and money – replace the film rather than the glass • 24" x 10' roll
- Order No. **GB-FILM**




tech tips

from the techxperts™
For best results, attach film to cabinet window with ordinary double-faced tape (not included).

Glass Beads

- Clean parts thoroughly without removing material
- 50 lb. bag • Size #8
- Safe for ferrous & non-ferrous materials
- Order No. **GB-CM**



ARMEX®

Maintenance XL Formula Soda Blast Cleaning Media

- 270 micron / 70 Grit Formula
- Use to strip clean almost any car surface including, steel, aluminum, Fiberglas® and plastics
- Ideal for blocks, heads and intake manifolds
- Dissolves in warm water, minimizing particle ingestion that can block fuel lines and passageways
- Won't damage the surface you're cleaning
- Non-toxic and non-hazardous with a pH of 8.2
- 50 lb. / 22.7 kg bags
- Order No. **SMB-170**




Glass Bead Gun for Large Machines

- Aluminum body
- Fits Zero, Blast-It-All, Winona Van Norman, etc.
- Includes .313" ID ceramic nozzle

Description	Order No.
Complete Gun For Larger Machines	GB-100
Replacement Parts	
Gun body only	GB-101
Barbed Brass fitting	GB-04
Nozzle holding nut (not included in rebuild kit)	GB-54

Rebuild Kits	Order No.	Includes
.250" ID	GB-4-OK	▼
.313" ID	GB-5-OK	▼
.375" ID	GB-6-OK	▼
.437" ID	GB-7-OK	▼
Ceramic Nozzles	.250" ID GB-74	x
7/8" OD x 138"	.313" ID GB-75	x
	.375" ID GB-76	x
	.437" ID GB-77	x
Replacement Orifices	#4 GB-64	x
	#5 GB-65	x
	#6 GB-66	x
	#7 GB-67	x
Orifice Lock Nut	GB-52	x x x x
O-Ring	GB-53	x x x x



Glass Bead Gloves

- 30" overall length
- For ports up to 10" diameter
- Durable cloth-lined Neoprene glove with nylon sleeve
- Sleeve design makes attaching glove to your machine, faster and easier • Clamp sold separately

Port Size	Description	Order No.
Up to 8"	Single: left-hand glove	GB-654-G
(20.32 cm)	Single: right-hand glove	GB-655-G
	Pair: one right-hand & one left-hand	GB-660-G
	Pair+: one right-hand, two left-hand	GB-663-G
Up to 10"	Single: left-hand glove	GB-754-G
(25.4 cm)	Single: right-hand glove	GB-755-G
	Pair: one right-hand & one left-hand	GB-770-G
8" and 10"	Replacement Clamp: fits both port sizes	GB-CLAMP

SAFETY TIP: NEVER point the Glass Bead Gun at the cabinet window or your co-workers!



Tumbler Media & Parts

Cleaning Media

For Parts Tumblers



20 LB.


Ceramic Diagonals (20 lb.)
For soft materials such as brass and aluminum. $\frac{5}{16}$ " dia., $\frac{5}{8}$ " long
Order No. **PTM-20CR**



20 LB.


Steel Diagonals (20 lb.)
Ideal for valves. $\frac{5}{16}$ " dia., $\frac{5}{8}$ " long
Order No. **PTM-20D**

For Airless Blasters




55 LB.

Steel Shot, 170 grade (55 lb.)
Ideal for cleaning cast iron heads.
Diameter varies from .017" to .024".
Order No. **SS-CM**



Now in 10 LB.

Stainless Steel Shot, Conditioned.
Clean aluminum heads to look like new. Restores bright aluminum finish. Lasts longer than plain carbon steel shot. Diameter varies from .006" to .016". 10 lb.
Order No. **SS-CS10**




Now in 10 LB.

Stainless Steel Cut Wire Shot
Unconditioned. Clean cast iron or aluminum heads before and normalize after welding. Helps prevent surface corrosion after blasting. .020" Diameter. 10 lb.
Order No. **SS-CW10**



Parts Tumbler Solution

- Dilute 30:1 with water
- For best results, dry parts with compressed air • 1 gallon / 3.78L
- Order No. **PT-SOL**



Replacement Gears For Sioux™ 710 Parts Tumbler

- Replaces discontinued Sioux™ parts

Description	Order No.
Steel Gear	271
Fiber Gear	19275



Steel Parts Tumbler Basket

- Fits Goodson, K.I., Axe, RMC, and Peterson
- 8" x 12" x 12"
- Order No. **PT-BASKET**



Gauntlet Style Heat & Flame Resistant Gloves

- Heavy lined red terrycloth
- 13 $\frac{1}{2}$ " Long
- Safe to 450°F / 232.2°C
- Order No. **HFR-300**



Keeper-Keeper

- Screws tightly closed
- $\frac{1}{4}$ " holes
- Ideal for tumbling keepers
- Solvent resistant PVC
- Order No. **VK-15**

See Page 135 for Valve Stems

Valve Stem Protectors

- Protects against parts tumbler damage
- Slips on and off easily
- 16 per package
- Order No. **VSP-16**



Cloth Shop Apron

- Bib-style apron
- Heavy duty black fabric
- Several handy pockets
- Embroidered Goodson Racing logo
- Machine Washable
- Order No. **CA-100**



Stay Up-To-Date With Your Friends At Goodson!

We're On Social Media Are You?



Facebook



Instagram



YouTube



Blog

Made-To-Order Crankwheels



"To improve speed and accuracy we scan every item when pulling and packing orders. Every order is checked first by a person, then by computer before it's shipped to you."
-Tanya, Goodson Shipping, 2 year of service

Last Blast Spray Paint

- Quick-dry formula lets you handle parts in minutes
- Pigment won't smudge AND resist abrasion, corrosion and most solvents
- Paint heads, blocks and parts just like OE
- Withstands heat up to 250°F/121.1°C
- 12 oz. cans
- **Last Blast** restores original look to all types of cast iron
- **Aluminum Last Blast** makes aluminum heads and parts look new
- **Color Last Blast** paint heads and parts in popular, factory colors
- **Hi-Temp Last Blast** Withstands continuous heat up to 1200°F. Heat at 450°F for 1 hour to create a professional, durable finish

Color	Order No.
Cast Iron Gray	LB-1*
Aluminum Gray	ALB-1*
GM Black (Gloss)	CLB-58*
Chevy Orange	CLB-61*
Ford Blue	CLB-60*
Hi-Temp Cast Iron Gray	LB-1-HT*
Hi-Temp Aluminum Gray	ALB-1-HT*
Hi-Temp Black (Matte)	CLB-58-HT*

*Aerosol — Hazardous Goods Fees Apply When Shipped By Air



Industrial Metal Markers

- No shaking needed • Quick dry
- Withstands oil, grease & surface contact • Won't lose its brilliance or legibility
- Medium point

Color	Order No.
Orange	MM-STD
Black	MM-010
Yellow	MM-030
White	MM-050
Green	MM-060
Red	MM-070
Blue	MM-080




2" Dispensing Pliers for Flexible Tubes

- Maximizes the use of all the material in the tube due to its effective means of application
- Dispenses the thickest sealant through a very small opening, permitting better application control
- Reduces both cleanup time and the possibility of skin contact or other problems caused by excess material squeeze-out
- Order No. **EB-416**



Universal Gel Lube

- Sprays on as a liquid and forms into a gel within seconds
- Penetrating formula blends with motor oil
- Multiple uses, including cams, lifters, rocker arms, bearings, pistons/wrist pins, cylinders, valve springs, etc.
- Provides lubrication for engines subjected to prolonged storage before initial start-up
- 8 oz. Aerosol* can
- Order No. **GL-8U**



*Hazardous Goods Fees Will Apply if Shipped By Air

High-Performance Hylomar® Gasket Maker & Thread Sealer

- Maintains seal integrity up to 600°F / 315.5°C
- Polyol-based compound turns from a gel into flexible putty within minutes of application
- Non-hardening formula is impervious to oil, gasoline, glycol and other engine fluids
- Oxygen-sensor safe
- Seals gaps .01" or less
- 100 gram tube
- Order No. **HBS-1**



Assembly & Break-In

Press Fit Lube

- A light coat eases press fit
- Ideal for valve guides, piston pins, cylinder sleeves, etc.
- Eliminates the scoring, gouging and galling of parts during press fitting
- 6 oz. / 177.4mL • Aerosol*
- Order No. **PFL-200**

**Hazardous Goods Fees Apply When Shipped By Air*



Press Fit Lubricant

- A light coat eases press fit
- Multiple applications
- Eliminates scoring, gouging and galling of parts during press fitting

Description	Order No.
Aerosol 7 oz. / 207 mL	B-200*
Brush Applicator 200 mL	B-200L

** Hazardous Goods Fees Apply When Shipping By Air*



Extreme Pressure Lube

- Withstands pressures up to 50,000 PSI
- Highly refined petroleum product
- Contains no lead, graphite or minerals
- Won't corrode fine surfaces or emulsify with cooling liquids
- Surfaces stay lubed and protected
- In a grease form • 4 fl. oz. / 118.29mL
- Order No. **EPL-4**

Spray Assembly Lube

- Ideal for lubricating parts to ease assembly
- Eliminates critical initial run-in of new and rebuilt high-performance engine components
- Spray on bearings, crankshafts, pistons, rings, etc.
- 11 oz. Aerosol* can • Order No. **SAL-11**

** Hazardous Goods Fees Apply If Shipped By Air*



First Lube Engine Assembly Lube

- Prevent dry engine start-ups after long-term storage
- Contains Zinc and Moly
- Clings and forms a slick wall between moving parts
- Withstands start-up pressure
- Compatible with all motor oils

Size	Order No.
8 oz. / 236.6mL	FL-10
1 gallon / 3.78L	FL-128



Blood Friction Master® Engine Assembly Lube

- Contains a low friction additive (PTFE) for dry start-ups
- Ideal for long-term storage
- Forms a slick wall between moving parts
- Clings until dissolved by oil
- Withstands start-up pressure
- Compatible with all motor oils
- Ideal for high performance

Size	Order No.
8 oz./236.6 mL w/brush	AL-22-8
1 gal./3.78 L w/pump	AL-22-10



Need Zinc?

Cam-Shield® Camshaft Assembly Paste

- Provides anti-wear protection for camshafts during break-in
- 2500 parts per million of Zinc
- Use with mechanical and hydraulic camshafts & lifters
- For racing, street, classic, agricultural, diesel & marine camshafts
- 4 oz. / 118.29 mL Brush Top Jar
- Order No. **CSAP-4**



Mr. Race Oil® Engine Assembly Gel

- For all 4-stroke engines!
- An advanced engine assembly gel designed to stay in place for engine protection during storage, shipping and start-up time
- Petroleum based, oil soluble product
- Colored blue so you can see where it's applied
- 8 ounce jar • Order No. **EAG-8**



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Rust Shield Spray

- 2 formulas to choose from
- Short Term (Indoor)**
 - Non-sticky • Lasts several weeks
 - Wipes off with just a towel
- Long-Term (Outdoor)**
 - Thicker than short term
 - Protects longer
 - Requires a solvent to remove



Formula	Order No.
Short Term	RS-16*
Long Term	RS-16-OD*

*Hazardous Goods Fees Apply When Shipped By Air

Rust Proofing Oil

- 1 Gallon / 3.78 L
- Apply full strength
- Creates a protective film
- Washes off with standard solvents
- Ideal for use with sprayers or can be applied with a brush
- Order No. **RPO-10**



Petroleum Based Rust Inhibitor

- Brush directly from can onto freshly-machined engine components
- Protects iron, steel and aluminum
- Soften with mineral oil to dip small parts
- Order No. **RPC-2A**



Snap Together Adjustable Coolant Hoses


- Hoses hold any shape • Chemical Resistant
- Ideal for most common shop machines



Size: 1/4" Hose Kit	Size: 1/2" Hose Kit
Includes: 18" hose, 1/4" & 1/8" NPT fittings, 1/16", 1/8" & 1/4" round nozzles	Includes: 16 1/2" hose, 3/8" & 1/2" NPT fittings, 1/4", 3/8" & 1/2" round nozzles
Application: Most parts washers, wet-type seat grinders, valve refacers	Application: Most cylinder hones and flywheel grinders
Order No.: ACH-400	Order No.: ACH-600

Universal Coolant Magnet

- Ideal for Honing Tanks, Flywheel Grinders, Crankshaft Grinders, Head Surfacers and more
- Prevents metal swarf from passing into the coolant tank
- Cut or shape to fit machine bases and return ways
- Measures 3"x48" • Can be trimmed to any size needed
- Order No. **UCM-348**



Size: 1" Flare Nozzle for 1/4" Hose	Size: 1 1/4" Flare Nozzle for 1/2" Hose	Size: 2 1/2" Flare Nozzle for 3/4" Hose
Order No.: ACH-407	Order No.: ACH-807	Order No.: ACH-809



Coolant & Solvent Pumps

Ideal for Parts Washers

170 Gal. Per Hour Pump

- HP: 1/125
- Capacity: 170 gal/hr. at 1" depth • Hi-temp Seals
- Voltage: 115
- Size: 4" x 3 1/2" x 2 3/4"
- Order No. **COP-166**



Ideal for Flywheel Grinders

1200 Gal. Per Hour Pump

- HP: 1/6
- Capacity: 1200 gal/hr. at 1" depth
- Voltage: 115
- Size: 7 3/4" x 6 1/2" x 4 5/16"
- Order No. **COP-1833**



NPT	Hose ID	Order No.	Hose ID	Lng.	Order No.
1/4"	1/4"	ACH-406	1/4"	11"	ACH-401
3/8"	1/2"	ACH-804	1/2"	11"	ACH-801
1/2"	1/2"	ACH-805			

Sludge Filter Bag

- Fits any machine with a coolant sump
- Replace costly OE filters with this economical, universal sock
- Adds filtration to machines that don't have enough • 8" x 24" polyester knit sock
- Order No. **SB-1**



Machine Lubricants, Etc.

Rust Shield for Shop Equipment

- Stops rust without causing rancidity
- Apply to machine parts
- Mixes with coolant – no need to remove before machining
- 1 Gallon / 3.78 L
- Order No. **RS-128**



Way Oil

- Adhesive oil
- Formulated to provide extended lubrication and rust protection for machine-tool ways
- 1 Gallon / 3.78 L
- Order No. **WO-50**

CYLINDER HEAD
REBUILDING
CLEANING,
ASSEMBLY & SAFETY




Flywheel Grinder Table Lubricant

- Helps extend flywheel grinder life
- High-pressure oil designed to lubricate table bearings and ways
- For all makes of flywheel grinders
- 1 Gallon / 3.78 L
- Order No. **FG-1131-G**

EPL-LS1



EPL-14



EPL-18



10 Quart Engine Pre-Lube Tank Replacement Parts

Description	Order No.
Replacement 8' Hose	EPL-HOSE
LS1 Fitting	EPL-LS1
1/4" Replacement Fitting	EPL-14
1/2" Replacement Fitting	EPL-18
Replacement Gauge	EPL-CG
Mini Ball Valve	EPL-MBV

SHORT BLOCK
REBUILDING
FLYWHEEL GRINDING
CRANKSHAFT/
GRINDING



Replacement PF Filter Cartridges

- Cartridges remove grit, metal and dirt from honing oil
- Fit Sunnen® CK-10, CV-616, LBB-1810, PF-150 and CH-100 honing machines



Description	Application	Qty.	Order No.
Extra Fine	Oil Only	4 Pk.	PF-105-4
Fine	Oil Only	4 Pk.	PF-110-4
Extra Fine	Water Only	1 Pk.	PF-104
Fine (Fiberglass)	Water Only	1 Pk.	PF-160


tech tips Use this handy table of machines and capacities to help ensure that the filter you purchase will work it's best!

Mfr.	Machine	Capacity	Mfr.	Machine	Capacity
Sunnen	LBB-1699	15 Gal.	Rottler	H85AXY	70 Gal.
	LBB-1660	15 Gal.		H85A	70 Gal.
	LBB-1810	25 Gal.		H85AX	70 Gal.
	LBB-1803	25 Gal.		H86A	70 Gal.
	EC-3500	32 Gal.		H86AX	70 Gal.
	ML-3500	32 Gal.		H86AXY	70 Gal.
	ML-5000	32 Gal.			
	ML-2000	28 Gal.			
	CK-10	55 Gal.			
	CV-616	55 Gal.			
	SV-10	55 Gal.			
	CK-21	63.5 Gal.			

1" Thick Rod Hone Filter Mat

- Synthetic material
- Traps abrasive particles & metal filings BEFORE they enter the storage tank
- Cushions parts to prevent damage
- Replace when clogged
- 1" (25.4mm) thick

Inches	Metric	Order No.
18" x 25"	45.7 x 63.5 cm	RH-MAT
26" x 40"	66.0 x 101.6 cm	RH-MAT-2
33" x 48"	83.8 x 121.9 cm	RH-MAT-3



Hone Cabinet Filter Paper

- Reduce sump and filter clean-up
- Extend oil life
- Filter paper in the bottom of hone machine removes debris before oil enters the sump
- When full, dispose of properly
- 2 – 60" x 60" sheets (trim to fit)
- Order No. **HN-FP**



MISCELLANEOUS
TOOLS & SUPPLIES
BRAKE SERVICE
TOOLING
MEASURING
TOOLS
V-TWIN & METRIC
HARD PARTS

full service
...fast



"As a small business and employee owner, we wear many hats here at Goodson. Call me for your accounting questions but I'm also trained and knowledgeable to help you with your order!"

- Wendy, Goodson Accounting, 38 years of service

Most Powerful



Heavy-Duty UltraSonic Cleaning Detergent

Use **Ultra 1 Cleaner** for: cast aluminum, cast iron, iron, wrought iron, carbon steel, stainless steel, tool steel, carbide, tin, nickel, zinc, cobalt, titanium. Ideal for brackets, clutch housings, axles, engine blocks (cast), nuts, screws

Quantity	Order No
1 gal.	S-U1-1G
2.5 gal.	S-U1-2.5G
5 gal.	S-U1-5G

Moderate-Duty UltraSonic Cleaning Detergent

Use **Ultra 2 Moderate-Duty Cleaner** for: aluminum, billet aluminum, polished aluminum, cast aluminum, cast iron, iron, wrought iron, carbon steel, stainless steel, tool steel, carbide, tin, nickel, zinc, cobalt, titanium, magnesium, gold, silver, copper (requires additive), brass (requires additive), plastic. Ideal for pistons, wheels, brakes, bearings, connectors, crankshafts, valves, connecting rods, shock mounts and cylinder heads

Quantity	Order No
1 gal.	S-U2-1G
2.5 gal.	S-U2-2.5G
5 gal.	S-U2-5G



Least Powerful



Multi-Purpose UltraSonic Cleaning Detergent

Use **Ultra 3 Moderate-Duty Cleaner** for: gold, silver, aluminum, billet aluminum, titanium, platinum, tin, nickel, zinc, cobalt, copper (requires additive), brass (requires additive), plastic. Ideal for pistons, wheels, brakes, bearings, connectors, crankshafts, valves, shock mounts, connecting rods and cylinder heads

Quantity	Order No
1 gal.	S-U3-1G
2.5 gal.	S-U3-2.5G
5 gal.	S-U3-5G



The full line of ULTRASONIC, LLC machines, parts, filters and supplies are available on the Goodson website!

Visit Goodson.com to see the full selection today. All ULTRASONIC, LLC items ships directly from the manufacturer. Use your smart phone or smart device to scan the QR code for instant access.

Index

3-D Fast Cut™

3-D Fast Cut™ Starter Kits	7, 8
Ball Head Drive Adaptors	7, 8
Bounce Springs	7, 8
Bowl Profiler	9
Lift Clip	8, 9
Micro Ball Head Tooling	7, 8
Pilots	4 - 6
Setting Micrometer	7
Tool Setting Fixture	7, 8
Universal Spring Pad Cutters	9
Valve Seat Cutter Blades	10 - 13
Valve Seat Cutter Tool Holder	7, 8
Valve Seat Removal Tooling	7

A

Abrasive Belt Dresser	108
Abrasives	

Aluminum Oxide Cloth Shop Rolls	59
Belts	52, 109, 110
Bench Grinder Wheels	117
Blanchard Grinder Wheels	51
Brake Drum Grinding Wheels	122
Brake Shoe Grinding Sleeves	118
Cam Grinding Wheels	102
Cartridge Rolls	58, 59
CBN Inserts for Cast Iron	49
Chamfering Cones	47, 89
Crankshaft Grinding Wheels	104, 105
Crankshaft Polishing Belts	109, 110
Crocus Cloth	59
Cross Buffs®	59, 60
Cylinder Head Resurfacing	50 - 52
Cylinder Honing	86 - 89, 91 - 93
Diamond Honing	33
Diesel Super Abrasive Insert	49
Discs	59, 65
Flapwheels	58, 59
Flex-Hones®	35, 89, 90, 102, 122
Flywheel	112 - 113
Grinding Discs	59, 65
Grinding Wheels	26, 27, 51, 93, 102, 104, 105, 117
Grinding Stones	18 - 23, 112, 113
Honing	33, 35, 86 - 93
Hyper-Finish Diamond Honing	33
Lifter Bore Honing	100
Mounted Points	58, 60
PCD Inserts for Aluminum	49
Rod & Cap Grinding Wheels	93
Rod Honing / Pin Fitting	91 - 93
Sleeves	58, 118
Ultra-Finish Plateau Honing	37, 88, 92
Valve Guide Honing	33, 35
Valve Refacing	26 - 28
Valve Seat	18 - 23

Accu-Turn	
Replacement Cutting Tips	119
Replacement Parts	122
Adjustable Coolant Hoses	72
Adjustable Counterbore Cutter Kit	15

Air Tools	25, 36, 37, 43, 44, 46
Align Hone Mandrels & Stones	92
All Tool Brake Lathe Replacement Tips	119
Aluminum Last Blast	70
Alumni-Chek	54
Ammco	
Belts, Drive	121
Brake Lathe Arbor	120
Brake Lathe Cutting Tips	119
Replacement Parts	120 - 122
Aprons	67, 69
Assembly Lubes	70, 71
Assembly Wipes	65

B

Bags	64
Balancing Scales	97
Ball Head Seat Cutter Driver	7, 8
Ball Hones	35, 90, 102, 122
Band Ring Compressors	96
Baskets	64, 69
Beehive Springs	130, 132
Beeswax	99
Bean Brake Lathe Replacement Tips	119
Bearing Scraper	101
Bell Clamps	121
Belt Dressers	108
Belts	
Crankshaft Polishing	109, 110
Cylinder Head Resurfacing	51
Kwik-Way Valve Refacer Belts	30
Made-to-Order	106
Oil Pump Belts	29, 91
Rod Honing Belts (for Sunnen)	29, 91
Sioux Replacement Belts	28
Sunnen® Honing Machine Belts	29, 91
Surface Grinding Belts	52
Bench Grinder Wheels	117
Bifocal Safety Glasses	60
Black & Decker	
Adaptor for Sioux Stones	22
Replacement Collet	30
Stone Holders & Accessories	22
Valve Refacer Wheels	27
Black Diamond Valves	135
Black Diamond Valve Guide Sizing	33
Black Light	53, 117
Black Smoke Series Cutters	13
Blanchard Grinder Wheel	51
Block Bags	64
Blood Friction Master® Assembly Lube	71
Bluing Fluid	14
Bore Gauges & Setting Fixtures	125, 126
Boring Bar Cutters/Accessories	84, 85
Bounce Springs	7, 8, 17
Bowl Profiler Tooling & Blades	10
Brake Drum Grinding Wheels	122
Brake Flex-Hones®	122
Brake Lathe	
Bits	119
Brake Lathe (cont.)	
Cross Feed Shear Gear	121

Cutting Tips	119
Drum Feed Screws & Bushings	121
Feed Motor	121
Flexible Arbor Spacers	121
Lead Screw Bushing	118, 121
Locking Knob	121
Mounting Adaptors	121
Replacement Parts	121 - 122
Rotor Feed Screws	121 - 122
Seals	121
Serpentine Drive Belts	120
Silencer Bands	120
Spindle Boots	122
Switches	121
Tip Holders	118
Tips	119
Wear Inserts, Brass	121
Brake Lubes	121
Brake Shoe Grinding Sleeves	118
Brass Shim Stock	62
Brass Wear Inserts	121
Brazed Carbide Cutting Tools	118
Break-In Lubes	71
Bronze Liners & Tooling	39, 40
Bronze Reaming Oil	32, 38
Brushes	33, 35, 37, 48, 65, 66, 99, 100, 102
Bucket Lifter Grinder	46
Burets and Stands	48
Burr Buster	117
Burrs, Carbide	60
Bushing Press Kit, Tapered Pin	94

C

Calipers	126, 127
Cam-Shield®	71
Camshaft Work	
Cam Bearing Tools	101, 102
Cam Bore Washing Brushes	66, 102
Cam Wheels	102
Flex-Hones®	90, 102
Carbide	
Brake Tips	84, 119
Burrs (Rotary Files)	60
Cutters	9 - 13, 16, 34, 49, 62, 84, 85
Glass Bead Nozzles	68
Pilots	4 - 6
Reamers	31
Resurfacing Tips	52
Rotary Files	60
Sizing Balls	39, 40
Spot Facers / Top Cutters	34
Valve Spring Seat Cutters	47
Cap Grinding Wheels	93
Cartridge Rolls	58, 59
CBN Cutter Inserts	49
CBN Dressing Stick	113
CBN Flywheel Stones	113
CC-ing Equipment	48
CC-ing Liquid Concentrate	48
Centering Cones, 60°	40
Ceramlub™	121
Chamfer Tools	34, 40

Index

- Chamfering Cones 47, 89
- Chevrolet
 - Block Organizer Tray 63
 - Conversion Plate 62
- Clamp-On Brake Lathe Silencers 120
- Cleaning Supplies
 - Aprons 67, 69
 - Baskets 64, 69
 - Brushes . 33, 35, 37, 48, 65, 66, 99, 100, 102
 - Cleaning Media 69
 - De-foaming Agent 67
 - Detergents 67
 - Glass Beads 68
 - Gloves 64, 67 - 69
 - Parts Tumbler Solution 69
 - Pro-Jet Spray Cleaning Powder 67
 - Roloc Bristle Discs 65
 - Safety Gear 59, 60, 64, 67, 69
 - Scrapers 65, 100
 - Shop Towels 65
 - Sludge Filter Bag 72
 - Soda Blast 68
 - Ultrasonic Detergents & Filters 74
- Clover Lapping Compound 25, 116
- Collets
 - Black & Decker 30
 - Dowel Puller 116
 - Expanding Pilots 5
 - Valve Grinding 28
- Combustion Chamber Measuring 48
- Compression Release Valves 130
- Concentricity Gauges 14, 28
- Connecting Rod Heaters 96
- Cold Chisel 103
- Coolant Filters 73
- Coolant Hoses 72
- Coolants, Lubricants & Oils
 - All-Purpose Grinding Coolant 83
 - Aluminum Machining Aid 59
 - Belt Resurfacers Coolant 49, 83
 - Blood Friction Master 71
 - Brake Lubes 121
 - Bronze Reaming Oil 32, 38
 - Cam-Shield® Assembly Lube 71
 - Crank & Cam Grinding Coolant 83, 102
 - Cutting and Tapping Fluid 14, 56
 - Cylinder Honing Oil 83, 85
 - Diamond Honing Oil 34, 83, 85
 - Engine Assembly Gel 71
 - Extreme Pressure Lube 71
 - First Lube 71
 - Flywheel Grinding Coolant 83, 111
 - Flywheel Grinder Table Lubricant 83, 111
 - Gasket Maker / Thread Sealer 70
 - Gel Lube 47, 70
 - High Performance Resurfacing Spray 49
 - High Performance Valve Grinding Aid 27, 83
 - Honing Oil Concentrate 83
- Coolants, Lubricants & Oils (cont.)
 - Hylomar® 70
 - Knurlube 38
 - Lapping Oil 59, 85
 - Magnetic Crack Detection Oil 54
 - Mineral Based Honing Oil 83, 85
 - Minnesota Fast Freeze 9, 25
 - Multi-Duty Grinding Coolant 83
 - Petroleum Based Rust Prevention 73
 - Porting & Polishing Machining Aid 59
 - Plate Lube 55
 - Press Fit Lubricant 9, 71, 94
 - Rod Honing Oil 83, 88, 91
 - Rust Inhibitor for Pressure Tester 57
 - Rust Proofing Oil 72
 - Rust Shield 72, 73
 - Seat Cutting Fluid 15
 - Spray Assembly Lube 71
 - Surface Grinding Coolant 50, 83
 - Titanium Valve Grinding Aid 25, 83
 - Universal Gel Lube 47, 70
 - Valve Grinding Oil 27, 83
 - Valve Seat Machining Aid 14
 - Water Based Diamond Coolant 83, 85
 - Way Oil 73
- Coolant Magnet 72
- Coolant Pumps 72
- Core Drills / Reamers 31
- Counterbore Cutters 10-13, 15
- Crack Detection and Repair
 - Additives 57
 - Alumini-Chek 54
 - Applicators 53
 - Ceramic Motor Seal 57
 - Fluid Weld® 57
 - Goodson Glow 54
 - Heat Tabs 57
 - Magnetic Crack Detection Oil 54
 - Magnetic Field Indicator 53
 - Magnetic Powder 53
 - Parker Magnetic Crack Detection Unit 53
 - Powder 53
 - Repair Kit 56
 - Seal-All™ 57
 - Small Parts Demagnetizer 53
 - Threaded Plugs, Irontite® 56
 - UV Inspection Light 53, 117
- Crankshaft
 - Bearing Scraper 101
 - Crank Grinding Wheels 104, 105
 - Crank Welding Plug Rods 106
 - Dial Indicator, Starrett 103, 128
 - Diamond Dresser Tools 115
 - Display Inspection Stand 61, 102
 - Eliptibur Tool 107
 - Grinding Coolant 83, 101
 - Journal Radius Gauge 103
 - Peening Tool 103
 - Plastigage 106
 - Polishers 108
 - Polishing Accessories 108
- Crankshaft (cont.)
 - Polishing Belts 109, 110
 - Polisher Motor 108
 - Reluctor Ring Installation Tool 107
 - Steady Rest Shoes 107
 - Steel Stamps 106
 - Stroke Checker 106
 - Stroker Mimic™ 105
- Crocus Cloth 59
- Cross-Buffs® 58, 59
- Cross Feed Dust Boots 122
- Cross Feed Shear Gear 120
- CSS Ultra Grinding Wheels 104, 105
- Cummins Tooling 13, 31, 36, 42
- Cutter Drivers & Adaptors 15
- Cutting & Tapping Fluid 14, 56
- Cylinder Block Work
 - Automotive Dowel Puller & Collets 116
 - Bore Washing Brushes 65, 66, 102
 - Deck Bridge Combination Tool 128
 - Lifting Sling 100
 - Oil Gallery Brushes 66, 99
 - Oil Gallery Plugs & Tools 99
- Cylinder Head CC-ing Equipment 48
- Cylinder Head Resurfacing
 - Belt Resurfacers Coolant 60, 83
 - CBN Cutter Inserts 49
 - Dressers 51
 - Grind Aid 108
 - High Performance Resurfacing Spray 49
 - PCD Inserts for Aluminum 49
 - Rotary Broach Tool Bit 49
 - Segments 50
 - Surfacing Belts 52
 - Surfacing Wheels 51
- Cylinder Honing
 - Chamfering Cones and Mandrels 89
 - Goodson 86 - 88
 - Honing Oil 83, 85
 - Keyway Honing Stones 88
 - Lisle® 89
 - Nicasil 89
 - Plateau Honing 88, 92
 - Portable Cylinder Hones 86
 - Stones 86 - 93
 - Sunnen® 86 - 89, 91 - 93
- D
 - D-Foam 67
 - Deburring Tools 94, 117
 - Deck Stand 128
 - Degree Wheel 101
 - Demagnetizer 53
 - Depth Gauge, Flywheel 111
 - Desmond Style Dressers 51, 111, 117
 - Detergents 67
 - Dial Bore Gauge Setting Fixtures 125
 - Dial Bore Gauges 125, 127
 - Dial Calipers 126, 127
 - Dial Indicators 103, 128
 - Diamond Dresser Tools 29, 93, 114, 115
 - Diamond Hand Files 11
 - Diamond Flex-Hones® 90
 - Diamond Guide Hone Tools 33
 - Diamond Honing Oil 33, 83, 85
 - Die Grinding Stones 58, 60
 - Diesel

Index

Core Drills & Reamers	31
Guide Tooling	31 - 40
Heat Tabs	57
Relief Tooling.....	13
Seat Installers	25
Spring Compressor	43 - 46
Super Abrasive	49
Valve Guide Tooling	31 - 36, 38 - 40, 42
Valve Guides	31, 38
Valve Seals	31, 42
Valve Seat Cutter Blades	10 - 13
Dingleberry Hones	35, 83, 90, 102, 122
Disposable Assembly Wipes	65
Distributor Depth Gauge	124
DOHC Organizer Tray	63
Double Angle Valve Seat Wheels	20
Dowel Puller & Collets	116
Dressers	
Abrasive Belt Dresser	108
CBN Dressing Stick	113
Cutter Assemblies	51, 111
Desmond-Style Dressers	51, 111, 117
Diamond Stone Dresser	93
Flywheel Stone Dressers	111, 115
Hand-Held Dressing Sticks	103
Premium Diamond Dressers	29, 114, 115
Refacing Grinding Wheel Dressers	29
Star Dressers	51, 111
Valve Seat Wheel Dressing Stands.....	17
Dressing Stand Pilots	6, 17
Drive Adaptors	7, 16
Dykem® Layout Fluid	14

E

Eliptibur Tool	107
Engine Assembly Gel	71
Engine Brush Kit	65
Engine Cart	63
Engine Pre-Lube Supplies	70 - 73
Electric Rod Heater	96
Epoxy, Porting	58
Expanding Pilots	5
Extended Length Pilots (.375" Top)	5
Extreme Pressure Lube	71

F

False Guides	38, 134
Fast Freeze	9, 25
Feeler Gauges	123
File, Diamond	11
Filter Bag	72
Filter Inspection Tool	99
Filter Paper & Mats	73

Filters

Hone	73
Inline Air Filter.....	55, 56

First Lube

.....	71
-------	----

Flapwheels

.....	58, 59
-------	--------

Flex-Hones®

.....	35, 89, 90, 102, 122
-------	----------------------

Fluid Weld®

.....	57
-------	----

Flywheel Grinding

Bolt Adaptors	111
CBN Flywheel Stones	113
Coolant	83, 111
Dowel Puller & Collets	116
Depth Gauge	111
Dressers	111
Grinding Stones	112, 113
Mounting Adaptors	112

Flywheel Step Gauge

.....	111
-------	-----

FMC

Brake Lathe Replacement Parts.....	122
Brake Lathe Replacement Tips	119

Ford

Core Drills & Reamers	31
Diesel Seat Cutter Blades	13
Smog Plugs	62
Valve Guides	38

Formula One Boring Tools

.....	85
-------	----

G

Gas Porting Tools

.....	94
-------	----

Gasket Maker

.....	70
-------	----

Gauges

Concentricity Gauge	28
Crankshaft Journal Radius Gauge	103
Distributor Depth Gauge	124
Dial Bore Gauges	125, 127
Feeler Gauges	123
Flywheel Depth Gauge	111
Magnetic Field Gauge	53
Rod Bolt Stretch Gauge.....	98, 123
Small Hole Gauge Set	39, 123
Split Ball Bore Gauge	39, 123
Spring Tester Height Indicator	42
Sunnens AG-Gauge	124
Telescoping Gauge Set.....	123
Torque Angle Indicator	61
Vacuum Tester Gauge	55
Valve Guide Gauge Set.....	124
Valve Seat Height Gauge	17, 127
Valve Seat Run-Out Gauges	14
Valve Stem Height Gauges	48
Warp Gauges	123

Gel Lube

.....	47, 70
-------	--------

General Motors (GM)

Oil Pickup Tube Driver	99
Reluctor Ring Installation Tool.....	107
Vortec Adaptor Plate Set	62

Glass Beading Supplies

.....	68
-------	----

Glasses, Safety

.....	59, 60, 116
-------	-------------

Gloves

Glass Bead	68
Heat & Flame Resistant.....	69, 96
Hot Tank Gloves	67
Nitrile	64
Parts Washing Gloves	64

Grind Aid

.....	108
-------	-----

Grinding Stones & Wheels (see Abrasives)

Guide Installers (Drivers)

.....	36
-------	----

Guide Knurling

Knurling Arbors	38
Knurlube	38
OD Knurling Tool	38

Guide Liners

.....	39
-------	----

Guide Shoes

.....	88 - 89, 91 - 93
-------	------------------

Guide Tooling, Diesel

.....	31 - 40
-------	---------

Guides

.....	31, 38, 134
-------	-------------

H

Harley-Davidson® (see V-Twin)

Head Bags

.....	64
-------	----

Head Bolt Spot Facer

.....	62
-------	----

Head Holders

.....	48, 61
-------	--------

Head Organizer Trays

.....	63
-------	----

Heat Tabs

.....	57
-------	----

Heavy Metal

.....	116
-------	-----

Height Gauges

.....	17, 47, 127
-------	-------------

High Performance

Cam Wheels	101
CC-ing Equipment	48
Gasket Maker & Thread Sealer	70

Resurfacing Spray

.....	48
-------	----

Valve Grinding Aid

.....	28, 83
-------	--------

Valve Seat Cutter Blades

.....	10 - 11
-------	---------

Valve Spring Booster Shims

.....	48
-------	----

Valve Spring Compressors

.....	42 - 44, 129
-------	--------------

Valve Spring Testers

.....	41
-------	----

Valve Train Checking Springs

.....	47
-------	----

High Pressure Cleaning System

.....	66
-------	----

Hi-Temp Last Blast Paint

.....	70
-------	----

Honing Oil

.....	83, 85
-------	--------

Honing Stones

Cylinder Honing	86 - 89, 91 - 93
Lifter Bore	100
Pin Fitting.....	93
Rod Honing.....	91, 92
Valve Guide	33, 35

Hoses

.....	43, 55, 72, 73
-------	----------------

Hot Tank Detergents

.....	67
-------	----

Hylomar® Gasket Maker & Solvent

.....	70
-------	----

Hyper Finish Diamond Guide Sizing

.....	33, 34
-------	--------

I

ID Tags

.....	63
-------	----

IDL Valve Refacer Wheels

.....	26, 27
-------	--------

Import Head Stud Stretchers

.....	50
-------	----

Inspection Lights

.....	53, 117
-------	---------

Inspection Stand

.....	61, 102
-------	---------

Indicators

.....	17, 42, 46, 47, 55, 61, 104, 111, 128
-------	---------------------------------------

Infinite Flow Cutting Tips (IFT)

.....	10
-------	----

Index

Intake Port Reshaping Kit..... 58
Iron-tite 56, 57

J

Jet Spray Cleaning Powder 67
Jet Valve Eliminator Kit 55
Jet Washer Parts Baskets..... 64

K

Keeper-Keeper 69
Keeper Tools 45, 129
Keyway Honing Stones 88
Knurling 38
Knurlube 38
KO Lee Valve Refacer Wheels 26
Kwik-Way
Belts..... 29, 52
Boring Bar Cutters 84, 85
Brake Lathe Tips 119
Drive Adaptor 19, 22
Expanding Pilots 5
Heavy Duty Dressing Stand 17
Rebuild Kit for KW Holders 22
Resurfacer Wheel Segments 50
Single-piece Resurfacer Wheels 51
Solid Tapered Pilots 4
Stone Holders 22
Valve Refacer Replacement Parts 30
Valve Refacer Wheels 27
Valve Seat Grinder Motors 19
Valve Seat Stones 18

L

Lapping Compound 25, 116
Lapping Oil 59, 85
Lapping Tools & Compound 24, 25, 116
Last Blast Paint 70
Layout Fluids..... 14
Letter Stamps 106
Levels & Vials 7, 49
Lifter Bore Tools 100
Lifting Sling 101
Lights
Inspection Lights..... 53, 117
LED Lights 117
Work Lights..... 117, 121
Liners, Guide 39
Lisle® Honing Stone Sets 89
Litmus Paper 73
Low-Lint Wipes 65
Lubricants
Blood Friction Master® 71
Brake Lubes 121
Cam-Shield® Assembly Lube 71
Extreme Pressure Lube 71
First Lube..... 71
Flywheel Grinder Table Lubricant..... 73, 111

Lubricants (cont.)

Press Fit Lube 9, 71, 94
Spray Assembly Lube..... 71
Universal Gel Lube 47, 70
Way Oil 73

M

Machine Covers..... 28, 41, 124
Magnetic Bolt Washer Removers 48
Magnetic Crack Detection..... 53 - 54
Magnetic Strap Silencer..... 120
Magnetic Valve Spring Shim Removers..... 48
Main Cap Pullers..... 1
Mallory (Heavy Metal)..... 116
Mandrels
Butterfly Mandrels 59
Chamfering Cone Mandrels 47, 89
Cross Buff / Flap Wheel Mandrel 59
Diamond Sizing System 32
Honing 86 - 89, 91 - 93
Lifter Bore Honing Mandrel..... 100
Quick Change 58
Roll Mandrels 59
Valve Guide Hone 35
Manual Ring Grinders 97
Manual Spring Compressors..... 43 - 45
Manual Vacuum Testers 55
Manual Valve Guide Drivers 36
Markers 63, 70
Maxxeon Work Lights 53, 117
Measuring Liquid Concentrate 48
Measuring Tools
Bore Gauges 125, 127
Calipers 126, 128
Crankshaft Dial Indicator 103, 128
Dial Indicators 103, 128
Distributor Depth Gauge 124
Feeler Gauges 123
Flywheel Depth Gauge 111
Micrometers 126
Rod Bolt Stretch Gauges 98, 123
Small Hole Gauge Set 39, 123
Straight Edges 123
Stroke Checker 107
Telescoping Gauge Set..... 123
Torque Angle Indicator 61
Valve Seat Height Gauge 17, 127
Valve Seat Run-Out Gauge..... 14
Valve Stem Concentricity Gauge..... 28
Valve Stem Height Gauges 47
Warp Alignment Gauge 123
Metal Markers 70
Micrometers 126
Micro Ball Head Tooling..... 8
Micro Valve Seat Stones 20
Milwaukee-Eight™ Parts..... 132 - 135
Minnesota Fast Freeze 9, 25, 42
Mitutoyo® Split Ball Bore Gauge 39, 123
Mondello Seat Cutter Blades..... 10

Motors

Brake Lathe 121
Crankshaft Polisher 108
Seat Grinding..... 19, 21, 23
Mounted Points 58, 60
Mr. Race Oil Engine Assembly Gel 71

N

Neway

Easy Turn Wrench 15
Pilots..... 4 - 6
Replacement Cutter Blades & Screws 15
Valve Seat Cutters..... 15
Nicasil Honing Stones 89
Number Stamps..... 106

O

O-Ring Wire 85
OHC Bucket Grinder 46
Oil Filter Tools 99
Oil Gallery Brushes 66, 99
Oil Gallery Cleaning System..... 66
Oil Gallery Tools 99
Oil Gallery Wax..... 99
Oil Pump Belts 91
Oil Pump Tools 99
On-The-Engine Spring Compressor... 46, 129
Organizers 63
Oversize Bronze-Liners 39
Oversize Valve Guides 39, 134
Oversize Valve Seat Inserts 24, 133

P

Paint

Last Blast Spray Paint 70
Markers..... 70
Paper Shop Towels 65

Parts Cleaning

Airless Blaster Media..... 69
Baskets 64, 69
Brushes .33, 35, 37, 48, 65, 66, 98, 99, 100, 102
Detergent Powders..... 67
Glass Bead Tools & Supplies..... 69
Gloves 64, 68, 69, 96
Keeper-Keeper 69
Parts Tumbler Solution..... 69
Pro-Jet Spray Cleaning Powder 67
Roloc Bristle Discs 65
Soda Blast Media 68
Super Scraper™ 65
Surface Conditioning Discs 59, 65
Tumbler Cleaning Media 69
Ultrasonic Detergents & Filters..... 67

Parts Storage & Organizers

Valve Stem Protectors 69
Baskets 64
DOHC Cylinder Head Tray 63
Engine Cart..... 61
Keeper-Keeper 69
Organizer Trays..... 63

Index

Parts Storage & Organizers (cont.)

Parts Tags & Marker	63
Plastic Bags.....	64
Safety Pins	63
Shrink Wrap.....	64

Parts Tumbler Media

Pastelub™ Hi-Temp Brake Lube	121
------------------------------------	-----

Peening Tool	103
--------------------	-----

Performance Brake Lathe Tips	119
------------------------------------	-----

Peterson

Boring Bar Cutters	84
Core Drills & Reamers	31
Crankshaft Grinding Wheels	104, 105
Cylinder Head Resurfacing Belts.....	52
Resurfacer Abrasives	50 - 52

pH Test Strips.....	67
---------------------	----

Pilots

Expanding	5
Extended Length Top Solid-Tapered	5
Micro	4, 6
Seat Dresser.....	6, 17
Solid-Tapered Steel.....	4
Specialty	6, 37, 47
Tapered Carbide	6

Pin Bushing Press Kit.....	94
----------------------------	----

Piston Installing Tools

Deadblow Hammer	98
Electric Rod Heater	96
Piston Pin Installing Fixture	96, 98
Ring Compressing Pliers.....	96
Rod Clamping Vise	98

Piston Pin Removal Fixture	93
----------------------------------	----

Piston Ring Filers.....	97
-------------------------	----

Plastigage	106
------------------	-----

Plateau Hones	37, 88, 92
---------------------	------------

Plugs

Crack Repair.....	56
Oil Gallery.....	99
Smog Plugs.....	62

Pneumatic Tools

Air Hammer	36
Lapping Tool.....	25
Valve Guide Drivers.....	36
Valve Spring Compressors	43 - 45

Polishing Belts	109, 110
-----------------------	----------

Polishing Rouge	108
-----------------------	-----

Portable Cylinder Hones	86
-------------------------------	----

Porting & Polishing

Aluminum Oxide Cloth Shop Rolls	59
Butterfly Mandrels	59
Crocus Cloth	59
Cross-Buffs®.....	58, 59
Epoxy.....	58
Flapwheels	58, 59
Mandrels	58, 59
Mounted Points	58, 60
Port Reshaping Kit.....	58
Porting Abrasives Kits	58
Porting & Polishing Machining Aid	59
Replacement Abrasives and Mandrels	59
Rotary Files	60

Powered Ring Filer.....	97
-------------------------	----

Premium Tapered Reamers	62, 117
-------------------------------	---------

Press Fit Lubricant.....	9, 71, 94
--------------------------	-----------

Press Kit, Tapered Pin	94
------------------------------	----

Pressure Lube	71
---------------------	----

Pressure Tester Rust Inhibitor	56
--------------------------------------	----

Pro Jet Spray Cleaning Powder	67
-------------------------------------	----

Prussian Blue	14
---------------------	----

Pullers.....	24, 42, 61, 116
--------------	-----------------

Pumps.....	34, 72
------------	--------

Q

QualCast Products	38, 42
-------------------------	--------

R

Radiac Abrasives

Blanchard Grinder Wheels	51
Cam Grinding Wheels	102
CBN Cutters	49
CBN Flywheel Grinding Wheels	113
Crankshaft Grinding Wheels.....	104, 105
Flywheel Grinding Wheels.....	113
PCD Cutters	49
Resurfacing Segments	50
Resurfacing Wheels	51
Rod & Cap Grinding Wheel.....	93
Valve Refacing Wheels	26 - 27

Radial Wire Brushes	65
---------------------------	----

Reamers

Bronze	32
Carbide Valve Guide	32
Core	31
Diesel.....	31
High Speed Steel for Cast Iron	32
Piloted Core Reamers	31
Small Diameter	32
Tapered	62, 117

Reaming Oil	32, 38
-------------------	--------

Rebuilding Kits

Stone Holder.....	22
-------------------	----

Reluctor Ring Installation Tool	107
---------------------------------------	-----

Removers

Booster Shim	48
Bronze Liners	39
Cam Bearings.....	101
Dowel Pin Pullers	116
Keeper	45, 129
Liner Removal Tool Driver	39
Oil Gallery Plugs.....	99
Piston Pin	95
Piston Rings	96, 98
Stud	61
Tapered Pin Bushings	94
Valve Guide.....	36
Valve Seat	7, 24
Valve Seat Stone.....	19 - 23
Valve Stem Seal	42
Washer	48

Resurfacing Belts.....	52
------------------------	----

Resurfacing Coolant	50, 53, 83
---------------------------	------------

Resurfacing Dressers	51
----------------------------	----

Resurfacing Spray.....	49
------------------------	----

Resurfacing Wheel Segments	50
----------------------------------	----

Resurfacing Wheels	51
--------------------------	----

Right Angle Air Driver	23
------------------------------	----

Rimac Spring Testers	41
----------------------------	----

Ring Band Compressors	96
-----------------------------	----

Ring Expanders.....	98
---------------------	----

Ring Grinders	97
---------------------	----

Rocker Arm Tools	61
------------------------	----

Rod and Cap Grinding Wheels	93
-----------------------------------	----

Rod Balancing Supplies	97
------------------------------	----

Rod Bolt Boots	98
----------------------	----

Rod Bolt Installing Block	98
---------------------------------	----

Rod Bolt Stretch Gauge	98, 123
------------------------------	---------

Rod Clamping Vise.....	98
------------------------	----

Rod Heaters.....	96
------------------	----

Rod Hone Filter Mat	73
---------------------------	----

Rod Honing	90, 91
------------------	--------

Rod Honing Oil	83, 88, 91, 100
----------------------	-----------------

Roloc Bristle Discs	65
---------------------------	----

Rotary Broach Tool Bits	49, 110
-------------------------------	---------

Rotary Files	60
--------------------	----

Rotor Adaptors.....	121
---------------------	-----

Rotor Silencers.....	120
----------------------	-----

Rottler

Boring Bar Cutters	84, 85
Sleeve Cutters	84
Valve Refacer Wheels	26, 27

Round Brake Lathe Tips	119
------------------------------	-----

RTI Brake Lathe Tips.....	119
---------------------------	-----

Rubber Abrasive Belt Dresser	108
------------------------------------	-----

Rust Protection	57, 72, 73
-----------------------	------------

S

Saber Tooth Seat Cutter Blades.....	10 - 13
-------------------------------------	---------

Safety Glasses.....	59, 60, 116
---------------------	-------------

Safety Pins	63
-------------------	----

Scales, Balancing.....	97
------------------------	----

Scrapers	65, 101
----------------	---------

Screws

Ball Head	7, 8
Boring Bar.....	85
Carbide Cutter	6, 7, 15, 16
Catspaw.....	84
Cross Buff Mandrel.....	59
Feed Screws.....	118, 120 - 122
Neway.....	15

Scribe Tool	14
-------------------	----

Seal-All™	57
-----------------	----

Seals	31, 42, 133
-------------	-------------

Seal Cutters	37, 129
--------------------	---------

Seal Pullers.....	42
-------------------	----

Seal Setters	133
--------------------	-----

Seats	24, 133
-------------	---------

Seat Cutters.....	9 - 13, 15 - 16, 47
-------------------	---------------------

Seat Cutting Fluid.....	15
-------------------------	----

Seat Drivers	25
--------------------	----

Seat Grinding (see Valve Seat Grinding)	
---	--

Seat Removers	8, 24
---------------------	-------

Segments.....	50
---------------	----

Serdi-Style Bodies & Drivers	7
------------------------------------	---

Shim Remover	48
--------------------	----

Index

Shim Stock	62
Shims	48, 62
Shot	
Ceramic & Steel.....	69
Glass	68
Shop Towels, Low Lint	65
Shrink Wrap	64
Silencer Bands, Brake Lathe	120
Sioux™ Replacement Parts	
Belts.....	29
Driver Parts.....	19, 21, 22, 29
Parts Tumbler Rebuild Parts	69
Vacuum Tester Gauge	55
Valve Grinder Parts	30
Valve Refacer Parts.....	29, 30
Wheel Dresser Parts	19
Sioux-Style	
Drive Adaptor	21
Drivers	21
Pilots	4 - 6
Stone Holders	22
Vacuum Plates	55
Valve Refacer Wheels	27
Valve Seat Grinding Kit	21, 23
Valve Seat Stone Removers	17, 21
Valve Seat Wheels	20, 21, 23
Sizing Balls	39, 40
Sling, Lifting	101
Sludge Filter Bag (Sock)	72
Smog Plugs	62
Snap-on	
Replacement Brake Lathe Cutting Tips... 119	
Valve Refacer Wheels	27
Spark Plug Thread Chaser/Burnisher 62, 117	
Spindle Boots	122
Split Ball Bore Gauge	39, 123
Spot Facers	62
Spray Assembly Lube	71
Spray Bluing Fluid	14
Spring Compressors	43 - 46, 129
Spring Pad Cutters	9, 47
Spring Testers	41
Stamps, Steel	106
Steady Rest Shoes	29, 107
Steel Shim Stock	62
Step Gauge	111
Stone Holders	19 - 23
Stones	
Camshaft	102
Crankwheel.....	104, 105
Flywheel	112, 113
Honing	86 - 89, 91 - 93
Porting & Polishing	58, 60
Refacing	26, 27
Resurfacing	50, 51
Rod Honing.....	91, 93
Valve Seat	18 - 23
Storage Bags	64
Storage Cart	63
Storm-Vulcan	
Crankshaft Grinding Wheels	105

Resurfer Belts	52
Resurfer Wheel Segments	50
Resurfacing Carbide Cutter Tips	49
Straight Edges	123
Stroke Checker	106
Stroker Mimic™	107
Stud Extractor	61
Stud Stretchers	50
Sunnen®	
Adjustment Pinion.....	86
AG-Series Precision Gauge	124
Align Hone Stones.....	92
Belts for Rod Honing Machines	91
Cap Grinding Wheels	93
Coolants & Oils.....	83
Core Drills & Reamers	31
CV-616 Honing Machine Parts.....	29, 91
Cylinder Honing Stones	86 - 89, 91 - 93
Dial Bore Gauges	125
Guide Shoes.....	88, 91, 93
Lifter Bore Hones	100
Mandrel Drivers	91, 93
Master Holder & Stone Supports.....	87
Oil Pump Belts	91
Plateau Honing Tools, Ultra-Finish	88
Portable Cylinder Hones	86
Press-Fit Lubricant	9, 71
Replacement Parts for CV-616	29, 91
Rod Honing Machine Belts.....	91
Rod Honing Stones & Guide Shoes .. 91, 93	
Silicon Compound (AN-30).....	92
Truing Sleeves.....	35, 100
Valve Guide Gauge Set	124
Valve Guide Hone Set	35
Valve Refacer Steady Rest Shoes	29
Valve Refacer Wheels	26, 27
Super Scraper™	65
Surfacing	
Belts.....	52
CBN Inserts	49
Coolants	50, 52, 83
PCD Inserts	49
Segments	50
Wheels.....	51
Swedge Cutting Tool	118
Switches	19, 21, 29, 121

T

Tapered Pin Bushing Kit	94
Tapered Reamers	62, 117
Tapping Fluid	14, 56
Taps	
Crack Repair.....	56
Telescoping Gauge Set	123
Temperature Indicator Crayons	96, 105
Thin Wall Bronze Liners	39
Thread Chaser	62, 117
Timing Chain Tensioner	85
Tip Holders, Brake Lathe	118
Titanium Coated Cutting Tips	119
Tooling Stands	47

Top Cutters	34, 62
Torque-Angle Indicator	61
Trays, Organizing	63
Trizact™ Crank Polishing Belts	109
Tumbling Media	69

U

Ultra-Finish Plateau Honing Tools ..37, 88, 92	
Ultrasonic Detergents & Filters	74
Universal Checking Standards	126
Universal Dressing Stand	17
Universal Gel Lube	47, 70
Universal Head Holder	48, 61
Universal Spring Pad Cutter	9
Utility Rolls	59
UV Inspection Light	53, 117

V

V-Twin

Compression Release Valves	130
Hard Parts	130 - 135
On-the-Engine Spring Compressor ... 46, 129	
Valve Guides	134
Valve Seals.....	133
Valve Seat Inserts	24, 133
Valve Spring Compressors.....	46, 129
Valve Springs	130 - 132
Valves	132, 135
Vacuum Plates	55, 56
Vacuum Testers	55, 56
Valve Grinding	
Adaptor for ½" Chucks	28
Black & Decker Valve Refacer Collets	30
Diamond Dresser Tools.....	29, 114
Dresser Pilots	6, 17
Machine Covers.....	28
Machine Parts.....	29, 30
Valve Grinding Aid	28, 83
Valve Grinding Oil	27, 83
Valve Refacer Wheels	26, 27
Valve Stem Concentricity Gauge	28
Valve Guide	
Bronze-Liners	38, 39
Brushes	33, 35, 40, 66
Core Drill / Reamer	31
Diamond Hone Set	33
Drivers	36, 37
Flex-Hones®	35, 90
Gauge Sets.....	39, 123, 127
Guides	38, 134
Hone Set	33, 35
Knurling Tools.....	38
OD Chamfer Tool	34
OD Knurling Tool	38
Plateau Hones	37
Reamers	32
Small Hole Gauge Set	39, 123
Spot Facer	62

Valve Guide (cont.)	
Top Collars	34
Top Cutters	34, 62
Valve Guide Brushes	33, 40, 66
Valve Guides	38, 134
Valve Lapping Tools & Supplies	24, 25
Valve Refacing Wheels	26, 27
Valve Seal Drivers	133
Valve Seal Pullers	42
Valve Seal Setter	133
Valve Seals	31, 42, 133
Valve Seat	
Basic Valve Seat Grinding Kits	19, 21
Bounce Springs	7, 8, 17, 21
Cutter Blades	10 - 13, 15, 24
Cutter Drivers	7, 8, 15, 24
Cutting Fluid	14
Cutting System	7, 8, 15, 24
Dressers	17, 19, 21
Drivers	17, 19, 21
Inserts	24, 133
Layout Fluids	14
Machining Aid	14
Minnesota Fast Freeze	9, 25
Neway Seat Cutting System	15
Nickel-Chrome Valve Seats	24
Removers	7, 24
Run-Out Gauges	14
Stone Holders	22, 23
Valve & Seat Scribe	14
Valve Seat Cutter Blades	10 - 13, 15, 16
Valve Seat Counterbore Cutters	16
Valve Seat Grinding	17 - 23
Valve Seat Insert Driver	25
Valve Seat Wheels	18 - 21
Valve Spring	
Adaptors	43, 44
Booster Shims	48
Calibrated Springs	41
Compressors	43 - 46, 129
Height Indicator	42
Inserts	48
Keeper Installation Tools	45, 129
Manual Valve Spring Bench	45
Pneumatic Valve Spring Press	43
Seat Cutters	47
Spring & Retainer Kits	130 - 132
Testers	41
Valve Spring Inserts	48
Valve Spring Shim Remover	48
Valve Spring Testers	41
Valve Stem	
Concentricity Gauge	28
Dial Indicated Valve Stem Height Gauge ...	47
Protectors	69
Valve Stem Oil Seals	31, 42, 133
Valves	132, 135
Van Norman	
Boring Bar Cutters & Parts	84, 85
Core Drills & Reamers	31
Crankshaft Grinding Wheels	104
Flywheel Cutter	111
Resurfacer Segments	50
Single-piece Resurfacer Wheels	51
Valve Refacer Wheels	27
Vials, Level	7, 49
Vortec Tools	62

W

Warp Gauge	123
Water Based Honing Coolant	83, 85
Way Oil	73
Wear Inserts, Ammco	121
Wear Sleeves	16
Welding Rods	106
Wipes	65
Wire Wheels & Brushes	65, 66
Wrist Pin Bushing Press Kit	94

California Proposition 65



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

"Proposition 65 requires businesses to provide warnings to Californians about significant exposures to chemicals that cause cancer, birth defects or other reproductive harm."

Due to recent regulatory changes in California, we must now warn you that many of the materials commonly used to manufacture our products contain chemicals known to the state of California to cause cancer and reproductive harm.

A complete list of materials requiring the Prop 65 warning can be found at <https://www.p65warnings.ca.gov>.

WARNING: Operating, servicing and maintaining a passenger vehicle or off-road vehicle can expose you to chemicals including engine exhaust, carbon monoxide, phthalates, and lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. To minimize exposure, avoid breathing exhaust, do not idle the engine except as necessary, service your vehicle in a well-ventilated area and wear gloves or wash your hands frequently when servicing your vehicle. For more information go to www.P65Warnings.ca.gov/products/passenger-vehicle.

If you need additional information about any specific products sold by Goodson, please check our website or contact the Goodson Techxperts for details. Call 1-800-533-8010.

Your Shortcuts

Use the space below to record your most frequently ordered items.

Policies

Pricing:

Prices are subject to change without notice. There is no minimum order. Orders are billed at the prices in effect at the time of shipping. Discounts are not available on Sunnen® QualCast or ULTRASONIC, LLC products.

Shipping:

Goodson makes every effort to ship orders the same day they are received. Due to carrier cut-off times, orders received after 2:00 pm (central time), on weekends or holidays may not ship until the next business day.

You have several choices of shipping methods. Cost of shipping is based on total weight or package dimensions and the distance from our warehouse. **Goodson is not responsible for weather related shipping delays.**

- **STANDARD:** Unless otherwise requested, we ship items up to 100 pounds and up to 130" in combined width, length and height by US Postal Service, UPS or FedEx services. Items over the weight or size limit must go by common carrier.
- **EXPRESS:** We can ship most items by air to arrive in your choice of 1, 2 or 3 days. Aerosol products, however, require a HazMat fee when shipped by air.

Upon receipt of your order, please inspect all cartons immediately for damaged or missing products BEFORE signing for the merchandise. Any packages received in a damaged condition should be rejected and/or noted at the time of delivery. If items are missing or damaged, please contact Goodson within 3 business days.

Freight Allowance:

For open account orders shipped ground within the USA, you may deduct the freight charges on any **JOBBER** net invoice of **\$800** or more if you pay within 30 days (including Internet orders). However, Glass Beads, Steel Shot, Tumbler Media, Machines, Equipment, Bulk Liquids, Cleaning Detergents and Crankwheels are not included (shipped F.O.B. Winona, MN). Hazardous Materials, Dangerous Goods and Dimensional Shipping fees may apply on certain items. Please call to inquire.

Open Account Terms:

- 1) A 1% discount is given on merchandise if payment is made within 15 days from invoice date. This discount applies to the merchandise amount, before shipping, taxes & fees on the **invoice**. The discount amount is shown in the lower left hand corner of the invoice. This discount does not apply to statement payments and does not apply to credit card or PayPal orders.
- 2) Balances not paid in full within 30 days are subject to a finance charge of 1.5% per month (18% per year).

Credit & Debit Card Orders:

Goodson accepts MasterCard, Visa, American Express, Discover Card and PayPal. For your security, credit card numbers are NOT kept on file. Credit card and PayPal orders do not qualify for the 1% quick-pay discount.

Check Acceptance:

In the unlikely event that your check is returned for insufficient or held funds, we will debit your checking account electronically for the face amount of the check plus the service fee allowed by your state's law. This allows us to resolve the problem without turning you over to a collection agency and harming your credit rating. The transaction will appear on your bank statement and no one will have to contact you about payment.

Returns:

You may return any item, **except special orders and HazMat* items**, within 60 days. We will do our best to correct any problems or to send a replacement. If an item was damaged through mis-use or modification, Goodson will not accept it as a return. Credits will only be issued after it is determined that the part is resellable or it is deemed defective.

To return an item, please follow these easy steps:

1. Enclose a note explaining why you're returning the product. For faster processing, be sure to include your name and account number (you'll find this on your invoice)
2. Ship the item freight prepaid within 60 days from invoice date to

Goodson Tools & Supplies for Engine Builders

ATTN: Returns

156 Galewski Drive

Winona, MN 55987

For best results, please ship return merchandise by a trackable shipping method. Keep your shipping receipt as it may be necessary to track the package if it is lost in transit. A 10% restocking fee may apply on returns unless the problem was the fault of Goodson. If so, the restocking fee is waived and shipping costs are reimbursed.

ABRASIVES WARRANTY: Abrasives have a shelf-life, therefore, all abrasives are warranted against manufacturing defects for 1 year from the date of original purchase.

***HAZMAT ITEMS:** Only businesses certified to ship Hazardous Goods can ship such items. To return a HazMat item to Goodson, please call us at **1-800-533-8010** for shipping recommendations.

Privacy Policy:

All information that Goodson collects from its customers through purchases, credit applications or other transactions is kept private and is not disclosed to anyone except as permitted or required by law. Goodson will not sell or trade this information to anyone. Goodson will limit employee access to customers' private information to only those employees who need to know the information to provide products and services to you. Goodson maintains internal safeguards to protect our customer's non-public information. Please visit our website to read our privacy policy at <https://goodson.com/pages/privacy-policy> or scan the code at right to be directed to the page.



International Sales:

All items shipped F.O.B. Winona, MN, USA. To find a distributor near you, visit www.goodson.com.

Goodson currently has distributors in:

- Austria • Australia • Belgium
- Canada • Chile • Colombia
- Costa Rica • Ecuador
- El Salvador • Finland
- France • Germany
- Guatemala • Honduras • Italy • Luxembourg • Mexico • Netherlands
- New Zealand • Norway • Poland • Portugal • Spain • Suriname
- Sweden • Switzerland • United Kingdom • Venezuela



Resharpener & Resetting:

Goodson offers Resetting & Resharpener services for the following:

- Diamond Dressers • CBN & PCD Resurfacing Cutters
 - Valve Seat Cutter Blades • Rotary Broach Tool Bits for Van Norman
- Get more information and pricing by calling **1-800-533-8010**.



Coolants and Lubricants

We don't stock one type of coolant and claim that it suits all types of grinding, nor do we carry one type of oil and try to sell it for every application. Each of our coolants, lubricants and oils is formulated to deliver better results and longevity in its specific use. All of our coolants prolong the life of grinding wheels, retard corrosion and rancidity. Colors may vary. **Note: Dilution ratio is water to coolant.**



Grinding Coolants

All-Purpose Grinding Coolant

A synthetic water soluble coolant that "Licks Rust". Dilute 30:1

Size	Yield	Order No.
1 gal.(3.78L)	30 gallons	CGC-1288

Crank & Cam Grinding Coolant

Synthetic, non-nitrate, high lubricity coolant. Dilute 20:1

Size	Yield	Order No.
1 gal.(3.78L)	20 gallons	CGC-10
5 gal.(18.9L)	100 gallons	CGC-50

Multi-Duty Grinding Coolant

Medium-duty, low foaming, synthetic coolant with rust inhibitors. Safe for ferrous and non-ferrous metals alike. No nitrates, phenols, chlorine or sulfur. Dilute 30:1

Size	Yield	Order No.
1 gal.(3.78L)	30 gallons	GPC-10
5 gal.(18.9L)	150 gallons	GPC-50

Belt-Resurfacing Coolant

For all belt-type resurfacers with or without down-pressure. Dilute 30:1

Size	Yield	Order No.
1 gal.(3.78L)	30 gallons	SGB-10
5 gal.(18.9L)	150 gallons	SGB-50

Surface Grinding Coolant

Non-foaming, non-nitrate coolant for single-piece resurfacing wheels or segments. Dilute 20:1

Size	Yield	Order No.
1 gal.(3.78L)	20 gallons	SGC-10
5 gal.(18.9L)	100 gallons	SGC-50

Flywheel Grinding Coolant

Includes a synthetic rust inhibitor that prevents rancidity. For all flywheel grinders. Dilute 30:1

Size	Yield	Jobber	Order No.
1 gal.(3.78L)	30 gallons	\$50.99	FG-1101-G
5 gal.(18.9L)	150 gallons	194.99	FG-1102-G

Grinding & Honing Oils (Not Water Soluble)

Cylinder Honing Oil (Clear)

Ideal for portable hones and all makes of automotive honing machines. Mixes readily with other brands (including Sunnen®).

Size	Order No.
1 gal.(3.78L)	HO-10
5 gal.(18.9L)	HO-50



Sunnen® Mineral Based Honing Oil

Formulated for general purpose automotive machine shop honing. Compatible with most popular honing machines.

Size	Order No.
5 gal. (18.9L)	MAN-845



Valve Grinding Oil (Light Yellow)

Universal valve grinding oil extends wheel life. Mineral based. Prevents rancidity, foaming & deposits.

Size	Order No.
1 gal.(3.78L)	VGO-10
5 gal.(18.9L)	VGO-50



Rod Honing Oil (Dark Brown)

Keeps stones clean & free-cutting during rod reconditioning, pin fitting and other honing jobs. Will mix with other brands (including Sunnen®).

Size	Order No.
1 gal.(3.78L)	RHO-10
5 gal.(18.9L)	RHO-50



Sunnen® Honing Oil Concentrate

Formulated for general purpose automotive machine shop honing. Compatible with most popular honing machines. Add your own Mineral Oil. Mix Ratio: 10:1 for MAN-845 or 2:1 for MB-30

NOTE: Cannot be shipped to California

Size	Order No.
5 gal. (18.9L)	MAN-C



Severe Duty Valve Grinding Oil (Brown)

For grinding titanium, Inconel®, stainless steel and stellite valves. Includes additives to improve cutting performance under pressure.

Size	Order No.
1 gal.(3.78L)	VGO-SD10
5 gal.(18.9L)	VGO-SD50



Diamond Honing Oil (Brown)

Specially formulated to withstand the cutting pressures created when using our Diamond Valve Guide Honing System.

Size	Order No.
8 oz.(236.6mL)	DHO-8
1 gal.(3.78L)	DHO-10
5 gal.(18.9L)	DHO-50



Sunnen® Mineral Based Multi-Purpose Honing Oil

High performance lubricity agents with sulfur extreme-pressure additives. Won't weld or tear the work-piece. For metals from aluminum to zirconium

Size	Order No.
5 gal. (18.9L)	MB-30



Titanium Valve Grinding Aid

Mix ratio of 1:4. Add to mineral based valve grinding oils. Improves finish on titanium, stainless steel and stellite valves.

Size	Order No.
32 oz.(946.6mL)	VGA-T32



Water Based

Diamond Honing Coolant

Suitable for diamond honing on cast iron blocks. Greatly reduces heat build-up in the block. Reduces amount of block cleaning needed after honing

Size	Order No.
5 gal.(18.9L)	DHC-50



Sunnen® Water Based

Honing Coolant Concentrate for Cast Iron

Meets the demands of Single-Stroke and metal-bond Superabrasive honing. Ideal for honing aluminum or with diamond plated tools. Can be used as a general grinding coolant. 5 gallons makes up to 55 gallons of coolant. Mix ratio: 10:1.

Size	Order No.
5 gal.(18.9L)	SCC750005



Need a Safety Data Sheet or Product Instructions?

Look on the Goodson website for SDS and Product Instructions. If you can't find what you need, give us a call.

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

... another
satisfied
customer

"Very happy with both products and service."

- Alliance Diesel, Charlotte, NC, Goodson customer since 2014

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING


CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS



WINONA VAN NORMAN, VAN NORMAN, PETERSON, KANSAS INSTRUMENTS

1-EDGE CUTTER BIT

Fits Model Numbers	Type	Bit Dia.	Order No.
777, 900, 905, 944, 965	General	1/4"	VN-1
777S, 777S4, 944S, CB11, BC22XL, PK447S	General	3/8"	VGS-1
	Hard Sleeves	3/8"	VGS-2
	Sleeve Cutter	3/8"	VGS-3
888, 999	General	1/16"	VN-360

Original Van Norman

Fits Model Numbers	Type	Bit Dia.	Order No.
777S, 944S	Hard Sleeves	3/8"	777-179

HOLDERS FOR 6-EDGE TIPS - Use RT-6B and RT-6BT (each holder includes one tip)

Fits Model Numbers	Length	Height	Order No.
777, 900, 905, 944, 965	1 1/8"	3/4"	VN-135
777S, 777S4, 944S	2"	1 3/16"	VN-122
Bore Range: 2.65" to 4.50"	VN-122 Adjustment Set Screw		LW-1138
Standard Carbide Replacement Cutter Tip			RT-6B
Titanium Coated Carbide Replacement Tip			RT-6BT enlarged

MISCELLANEOUS PARTS

Fits 6-Edge Holders Above	Bit Screw	Order No.
		VN-130

tech tips VN-130 will also fit KWL-116
from the techxperts™



KWIK-WAY

1-EDGE CUTTER BIT FOR OE HOLDERS

Fits Model Numbers	Type	Bit Dia.	Order No.
F, FT, FL, FN, FR, FS,	Rough	9/16"	KWL-R
FW, FWS, FWSII, FX	Finish	9/16"	KWL-F
Models After 1770	Sleeve Cutter	9/16"	KWL-C

HOLDER FOR 6-EDGE TIPS - Uses RT-6B or RT-6BT Tips (each holder includes one tip)

Fits Model Numbers	Length	Height	Order No.
FL, FN, FR, FS, FT, FW	2 9/16"	5/8"	KWL-116
Standard Carbide Replacement Cutter Tip			RT-6B
Titanium Coated Carbide Replacement Cutter Tip			RT-6BT

PETERSON-BERCO

1-EDGE CUTTER BIT FOR OE HOLDERS

Fits Model Numbers	Length	Bit Dia.	Order No.
ACP-151-A, ACP-151-BL, SCP-151-P	1 3/4"	10mm	PB-151

ROTTLER

1-EDGE CUTTER BIT FOR OE HOLDERS

Fits Model Numbers	Length	Bit Dia.	Order No.
All Bars	1 3/4"	1 1/32"	RL-1
Sleeve Cutter for All Bars	1 3/4"	1 1/32"	RL-1C

HOLDER WITH 3-EDGE TIP - Includes one RL-2T Tip

Fits Model Numbers	Length	Bit Dia.	Order No.
All Bars (holder includes one tip)	1 3/4"	1 1/32"	RL-2H
Replacement Screw for RL-2H			RL-2S
Replacement Cutter Tip			RL-2T

STORM-VULCAN


1-EDGE CUTTER BIT FOR OE HOLDERS

Fits Model Numbers	Length	Bit Dia.	Order No.
NS, BCG, BCT, 220, 260	3/4"	5/16"	S-1



1-Edge Replaceable Type

Tool holder with separate bit. Excellent cutting yet economical. Resharpener the cutter bit many times. When no longer usable, replace only the bit.




6-Edge Replaceable Type

Lowest-cost choice. Holders take 6-edge, replaceable tips. When one edge wears, turn to new surface. Never need to resharpen - just replace the tip.

Looking for Something Not Listed? Contact Goodson For Special Order Boring Bar Holders or Other Tooling
1-800-533-8010

Cutters enlarged for detail



Replacement Tips & Parts

• Fit most boring bar holders

A	B	C	Edges	Order No.
Standard Carbide				
.358"	.097"	.108"	3	SEQ-1
.345"	.094"	.140"	6	RT-6B
.360"	.094"	.124"	3	FG-3B
.327"	.094"	.140"	3	RL-2T
Titanium Coated				
.345"	.094"	.140"	6	RT-6BT

Van Norman, Peterson or Kansas Instruments OE Catspaw Screws For 777S or PK-447S & 944S

Description	Order No.
Catspaw Screws (1 each)	
For #1 Shoe (0.625"L)	800-114
For #2 Shoe (0.740"L)	800-115
For #3, 4 & 5 Shoe (0.940"L)	800-116

Fine Lapping Oil

- A light lap oil coat cools and lubricates
- Use with a variety of applications including diamond laps (below) and crocus cloth (p. 59)



Description	Order No.
Very Fine Lap Oil (8 fl. oz.)	LP-LO-8
Dressing Stick	LP-DS

1 lb. Roll Copper or Stainless Steel O-Ring Wire

- Copper wire is .0403" diameter
- Stainless steel wire is .0410" diameter
- Each roll contains about 200 feet of wire



Description	Order No.
Copper	OWC-0403
Stainless Steel	OWS-041



Boring Bar O-Ring Cutter Replaceable Tool Bits

- Cut grooves for O-rings to enhance gasket sealing for high-performance engines
- Machines a groove .037" wide • 1/4" Shank
- Fit Winona Van Norman, VN, Peterson, KI, Kwik-Way & Rottler Holders (available by special order)

Description	Application	Order No.
Tool Bits	Standard	KWVN-57
	Premium	KWVN-57C6

tech tips
from the techxperts™


To avoid breakage, use the standard cutter on cast iron blocks only and the Premium cutter on hard blocks. **CAUTION:** Avoid column drop as this will break the tips as well.

Conversion Calculator

We've tried to convert as many SAE measurements to Metric (and vise versa) as possible. In some cases there hasn't been enough room.

If you need to convert a measurement, here are the formulas:

Starting Measurement	Conversion Formula	Converted Measurement
Inches (in)	Inches x 25.4	Millimeters (mm)
Feet (ft)	Feet x .3048	Meters (m)
Millimeters (mm)	Millimeters ÷ 25.4	Inches (in)
Fahrenheit (F)	(5÷9) x (F - 32)	Celsius (C)
Celsius (C)	(9/5 x C) + 32	Fahrenheit (F)



Solid Carbide Formula One Single Pass Boring Tools

- Greater fracture resistance than most carbide bits
- Ideal for hard alloys or interrupted cuts in automotive, high performance, marine, motorcycle and diesel engines

Description	Order No.
Kwik-Way 5/16" x 1.274"L	KWL-1071
Van Norman 3/8" x 7/8"L	VGS-1071
Rottler 1 1/32" x 1 1/16"L	RL-1071

Water Based Diamond Honing Coolant

- Suitable for diamond honing on cast iron blocks
- Greatly reduces heat buildup in the block during honing
- Reduces amount of block cleaning after honing
- Disposal of used coolant is easy and more environmentally friendly than conventional honing oils
- 5 gallons makes up to 55 gallons of coolant
- Order No. **DHC-50**



Clear Mineral Based Honing Oil

- Helps keep stones clean and free-cutting
- Ideal for portable hones and all makes of automotive honing machines
- Mixes easily with other brands, including Sunnen®
- **Not** water soluble

Size	Order No.
1 Gal./3.78L	HO-10
5 Gal./18.9L	HO-50



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

tech tips
from the techxperts™

- 1 - Extend the range of your hone with the Master Holder and Stone Supports on the bottom of page 87
- 2 - Use with 1/2" non-pistol grip drill (5/8" drill for AN-815 & GH-2555)
- 3 - Heavy Duty units can also be used in manual hone cabinets


Goodson
exclusive

	Junior Midget	Midget	Junior	Standard	Heavy-Duty	Heavy-Duty
Brand	Sunnen®	Sunnen®	Sunnen®	Sunnen®	Sunnen®	Goodson
Honing Range	1.25" - 1.75"	1.75" - 2.00"	2.00" - 2.60"	2.50" - 5.50"	2.50" - 5.50"	2.50" - 5.50"
Drive Shank	2.00" (incl.)	2.00" (incl.)	2.00" (incl.)	2.00" (incl.)	6.00" (incl.)	6.00" (incl.)
Drive Extension	12.00" (incl.)	12.00" (incl.)	12.00" (incl.)	12.00" (incl.)	12.00" (incl.)	12.00" (incl.)
Thread	7/16" - 14	7/16" - 14	7/16" - 14	7/16" - 14	5/8" - 11	5/8" - 11
Order No.	SNJ-10	SN-75	JN-95	AN-112	AN-815	GH-2555

NOTE: Goodson is authorized to ship Sunnen® products only within North and South America



WorldwideShipping

Cylinder Hone Center Adjustment Pinion

- Every Sunnen® AN-112, AN-815 and Goodson GH-2555 include the AN-16 Center Adjustment Pinion at purchase
- Use to adjust the stone honing diameter
- The Adjustment Pinion will wear over time so must be replaced
- Order No. **AN-16**



Scan this code with the camera on your smart phone or other smart device for quick access to our Tech Lab Tuesday video showing how important the AN-16 is for cylinder honing success.

Honing Stones

- Ideal for Cast Iron

Grit	Range	mm	Finish	Supersedes	Order No.
For Sunnen® Junior Midget Hone (SNJ-10) 3 Stones & No Wipers					
150 Grit	1.25" - 1.44"	31.8-36.6	45 Ra	—	SNJ1-J45
	1.42" - 1.60"	36.1-40.6	45 Ra	—	SNJ2-J45
	1.58" - 1.77"	40.1-44.9	45 Ra	—	SNJ3-J45
400 Grit	1.25" - 1.44"	31.8-36.6	8 Ra	—	SNJ1-J87
	1.42" - 1.60"	36.1-40.6	8 Ra	—	SNJ2-J87
	1.58" - 1.77"	40.1-44.9	8 Ra	—	SNJ3-J87
For Sunnen® Midget Hone (SN-75) 2 Stones & 2 Wipers					
70 Grit	1.75" - 2.00"	44.5-50.8	120 Ra	SN-100	S18-J17
150 Grit	1.75" - 2.00"	44.5-50.8	45 Ra	SN-200	S18-J45
220 Grit	1.75" - 2.00"	44.5-50.8	32 Ra	SN-300	S18-J55
280 Grit	1.75" - 2.00"	44.5-50.8	20 Ra	SN-500	S18-J65
400 Grit	1.75" - 2.00"	44.5-50.8	8 Ra	—	S18-J87
For Sunnen® Junior Hone (JN-95) 2 Stones & 2 Wipers					
70 Grit	2.00" - 2.20"	50.8-55.9	120 Ra	JN-100	T20-J17
	2.20" - 2.40"	55.9-60.9	120 Ra	JN-101	U22-J17
	2.40" - 2.60"	60.9-66.0	120 Ra	JN-102	V24-J17
150 Grit	2.00" - 2.20"	50.8-55.9	45 Ra	JN-200	T20-J45
	2.20" - 2.40"	55.9-60.9	45 Ra	JN-201	U22-J45
	2.40" - 2.60"	60.9-66.0	45 Ra	JN-202	V24-J45
220 Grit	2.00" - 2.20"	50.8-55.9	32 Ra	JN-300	T20-J55
	2.20" - 2.40"	55.9-60.9	32 Ra	JN-301	U22-J55
280 Grit	2.00" - 2.20"	50.8-55.9	20 Ra	JN-500	T20-J65
	2.20" - 2.40"	55.9-60.9	20 Ra	JN-501	U22-J65
	2.40" - 2.60"	60.9-66.0	20 Ra	JN-502	V24-J65
400 Grit	2.00" - 2.20"	50.8-55.9	8 Ra	—	T20-J87
	2.20" - 2.40"	55.9-60.9	8 Ra	—	U22-J87
	2.40" - 2.60"	60.9-66.0	8 Ra	—	V24-J87



Goodson and Sunnen® Cylinder Honing Stones For all popular AN-style Hones and Hone Bodies

- Integral holder type Honing stone sets have 4 pieces: 2 holders with stones and 2 holders with aluminum wipers • Fit Sunnen® AN Standard, AN Heavy-Duty and Goodson **GH-2555** hones • Use with honing oil
- Stones for Short or Blind Holes are 2 $\frac{13}{16}$ " long; all other stones are 4" long

Bore Range					SUNNEN®		GOODSON
Grit	in	mm	Usage	Finish	Old Order No.	New Order No.	Order No.
70 Grit	2.5"-2.7"	63.5-68.6	Cast Iron	120 Ra	AN-115	G25-J17	HN-115S
Roughing	2.7"-4.1"	68.6-104.1	Cast Iron	120 Ra	AN-100	M27-J17	HN-100S
			Cast Iron	120 Ra	-----	-----	HN-100R1
			Short/Blind	120 Ra	AN-100-71	M27-J17-71	HN-102S
			Harley / VW	120 Ra	AN-100F	AN-100F	HN-100F
	3.5"-5.5"	88.9-139.7	Cast Iron	120 Ra	AN-101	N37-J17	HN-101S
			Cast Iron	120 Ra	-----	-----	HN-101R1
			Short/Blind	120 Ra	AN-101-71	N37-J17-71	HN-104S
			Hard Sleeves	55 Ra	AN-131	N37-J11	HN-131S
Use Master Holder & Sleeve Support	4.7"-15.0"	119.4-381	Cast Iron	120 Ra	AN-106	W47-J17	HN-106S
			Hard Sleeves	55 Ra	AN-136	W47-J11	HN-136S
150 Grit	2.5"-2.7"	63.5-68.6	Cast Iron	45 Ra	AN-215	G25-J45	HN-215S
Medium	2.7"-4.1"	68.6-104.1	Cast Iron	45 Ra	AN-200	M27-J45	HN-200S
			Short/Blind	45 Ra	AN-200-71	M27-J45-71	HN-202S
			Hard Sleeves	30 Ra	-----	-----	HN-230S
			Cast Iron	45 Ra	AN-201	N37-J45	HN-201S
	3.5"-5.5"	88.9-139.7	Short/Blind	45 Ra	AN-201-71	N37-J45-71	HN-204S
			Hard Sleeves	30 Ra	AN-231	N37-J43	HN-231S
	4.7"-15.0"	119.4-381.0	Cast Iron	45 Ra	AN-206	W47-J45	HN-206S
			Hard Sleeves	30 Ra	AN-236	W47-J43	HN-236S
220 Grit	2.7"-4.1"	68.6-104.1	Cast Iron	32 Ra	AN-300	M27-J55	HN-300S
Finishing	3.5"-5.5"	88.9-139.7	Short/Blind	32 Ra	AN-300-71	M27-J55-71	HN-302S
			Cast Iron	32 Ra	AN-301	N37-J55	HN-301S
			Short/Blind	32 Ra	AN-301-71	N37-J55-71	HN-304S
			Cast Iron	32 Ra	AN-306	W47-J55	HN-306S
Use Master Holder & Sleeve Support	4.7"-15.0"	119.4-381	Cast Iron	32 Ra	-----	-----	-----
280 Grit	2.5"-2.7"	63.5-68.6	Cast Iron	20 Ra	AN-515	G25-J65	HN-515S
Fine Finish	2.7"-4.1"	68.6-104.1	Cast Iron	20 Ra	AN-500	M27-J65	HN-500S
			Short/Blind	20 Ra	AN-500-71	M27-J65-71	HN-502S
			Hard Sleeves	12 Ra	AN-530	M27-J63	HN-530S
			Cast Iron	20 Ra	AN-501	N37-J65	HN-501S
	3.5"-5.5"	88.9-139.7	Short/Blind	20 Ra	AN-501-71	N37-J65-71	HN-504S
			Hard Sleeves	12 Ra	-----	-----	HN-531S
	4.7"-15.0"	119.4-381.0	Hard Sleeves	12 Ra	AN-536	W47-J63	HN-536S
			Cast Iron	20 Ra	AN-506	W47-J65	HN-506S
400 Grit	2.5"-2.7"	63.5-68.6	Cast Iron	8 Ra	-----	G25-J87	HN-615S
Extra Fine	2.7"-4.1"	68.6-104.1	Cast Iron	8 Ra	-----	M27-J87	HN-600S
			Hard Sleeves	5 Ra	-----	M27-J85	HN-630S
			Cast Iron	8 Ra	-----	N37-J87	HN-601S
			Hard Sleeves	5 Ra	-----	N37-J85	HN-631S
Cork	2.5"-3.3"	63.5-83.8	Cast Iron*	2-3 Ra	-----	G25-C05	-----
Polishing	3.3"-4.2"	83.8-106.7	Cast Iron*	2-3 Ra	-----	MM33-C05	-----
	4.0"-5.6"	101.6-142.2	Cast Iron*	2-3 Ra	-----	NN40-C05	-----

(*Cast Iron – 3 Ra., Hard Sleeves – 2 Ra, Steel– 3 Ra)

1Ruby Aluminum-Oxide abrasive for longer life in rough cutting use



Master Holder & Stone Supports

- Holds one 4" stone set
- Stones sold separately
- AN-365 requires use of AN-260
- Larger sizes available upon special order


Master Holder

Dia. Range	Order No.
4.7"-7.0"	AN-355
6.0"-9.0"	AN-365

Stone Supports for AN-365

6.0"-9.0"	AN-260
-----------	--------

Note: Larger sizes available by special order.



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Goodson Is Authorized To Ship Sunnen® Products Within The Americas


... another satisfied customer

"The thing I like about Goodson is you always have the correct, up-to-date tools."

— ALC Machine, Santa Rosa, CA, Goodson customer since 1990

Keyway Honing Stone Sets

- Two-stroke engines have intake and exhaust ports that interrupt the operation of your honing stone
- These stones allow the hone to pass the intake and exhaust ports while maintaining consistent pressure to remove material accurately and easily
- Use with any AN- or GH-series hone (p. 86)
- For Cast Iron



Grit	Range	mm	Finish	Type	Order No.
150 Grit	2.5" - 3.3"	63.5 - 83.8	45 Ra	Alum.	GY25-J45
Medium	3.3" - 4.2"	83.8 - 106.7	45 Ra	Alum.	MY33-J45
280 Grit	2.5" - 3.3"	63.5 - 83.8	20 Ra	Brass	GY25-J65
Fine Finish	3.3" - 4.2"	83.8 - 106.7	20 Ra	Soft	MY33-J65
400 Grit	2.5" - 3.3"	63.5 - 83.8	8 Ra	Brass	GY25-J85
Extra Fine	3.3" - 4.2"	83.8 - 106.7	8 Ra	Soft	MY33-J85

EHU type stones

GEHN type stones



C-3070K

C-3120K



Stones & Shoes for Sunnen Hone Machines

- Premium-quality replacements for all CV-616, and CK-10 hones equipped with Sunnen® Master Holder Sets
- Diameter Range: 4.125" - 5.000" (104.8 - 127.0mm)
- Use with Master Holder Set CK-3045A (sold separately)
- 2 stones per set

Stones			Goodson - 1 Pair	Sunnen - 6 Pair
Use	Grit	Finish	Order No.	Order No.
Hard Blocks	70	60 Ra	GEHN-116	EHN-116
Hard Blocks	220	22-32 Ra	GEHN-512	EHN-512
Air Cooled Cyl.	220	22-32 Ra	GEHN-518	EHN-518
Hard Blocks	70	60 Ra	GEHU-123	EHU-123
Roughing	70	60 Ra	GEHU-133	EHU-133
Hard Blocks	220	22-32 Ra	GEHU-518	EHU-518
Gen. Purp.	220	22-32 Ra	GEHU-525	EHU-525
Aluminum	220	30-36 Ra	GJHU-525	JHU-525
High Nickel	280	20-25 Ra	GJHU-623	JHU-623
Finishing	280	16-23 Ra	GJHU-625	JHU-625
High Nickel	400	7-14 Ra	GJHU-818	JHU-818
Aluminum	400	7-14 Ra	GJHU-820	JHU-820
Accessories			Qty.	Order No.
Sunnen® Master Holder Set			1	CK-3045A
Sunnen® Centering Guide (includes CK-3070)			1	CK-3090A
Sunnen® Guide Shoe & 2 Screws			1	CK-3070
Sunnen® Brass Guide Shoe & 2 Screws			1	CK-3120
Goodson Wear Shoe			1	C-3070K
Goodson Stabilizing Shoe			2	C-3120K

For Rod Honing Stones and Shoes see page 91



CK-3070NY3X

C30-A55

CK-3570

Tooling for Honing Dart Blocks & Ductile Sleeves

- Recommended for Dart™ Machinery
- Use with Sulfurated Rod Honing Oil (below)

Description	Order No.
Honing Stone Sets For Portable Tooling	
80 Grit	N37-A25
220 Grit	N37-A55
280 Grit	N37-J65
400 Grit	MM33-J85
For CK/CV Type Machines	
80 Grit Stone Set (6)	C30-A25
150 Grit Stone Set (6)	C30-A45
220 Grit Stone Set (6)	C30-A55
280 Grit Stone Set (6)	C30-J65
400 Grit Stone Set (6)	C30-J85
Hardened Steel Guide Shoe (1)	CK-3570
Delron® Guide Shoe (1)	CK-3070NY3X
Goodson Brand Shoes For CK/CV Type Machines	
Hardened Steel Guide Shoe (1)	GCK-3570
Delron® Guide Shoe (1)	GCK-3070NY3X



For CK & CV Machines, DO NOT use Bronze Shoes, use Hardened Steel and Delron shoes above (1 of each)

Ultra-Finish Plateau Hones



- Abrasive impregnated nylon bristles
- Ideal for rebuilding high-performance engines and engines with low-tension rings • Superior plateau finish so rings will seal immediately
- Reduce break-in time
- Allow closer tolerances • 1 Pair



Portable Hones

- Fit AN- or GH- style hones
- Range: 3.78" to 4.68"
- Order No. **MM-PHT-731**

CV/CK Hone Heads

- Range: 3.10" to 5.00"
- Order No. **C30-PHT-731**

Sulfurated Honing Oil

- Includes additives for high pressure cutting

Size	Order No.
1 gal./3.78L	RHO-10
5 gal./18.9L	RHO-50





82° 3" Dia. Chamfering Cones & Mandrel

- Chamfer sharp edges for safe piston and ring installation
- Handles all diameter cylinders or sleeves
- Fits 3/8" (9.53mm) or larger drill • Kit (CC-100) includes mandrel and three 50 Grit Aluminum Oxide cones (CC-15)
- Due to manufacturing process, abrasive color may vary
- Aluminum-Oxide is a good general purpose abrasive suited for ferrous and non-ferrous metals
- Zirconium is a tough abrasive well suited for heavy stock removal on most metals

Description	Order No.	Incl.
3" Top Dia. Chamfering Cone Kit	CC-100	▼
Replacement 3/8" Drill Adaptor	CC-100-1	x
Aluminum Oxide Chamfering Cones (red)		
40 Grit	CC-14	
50 Grit	CC-15	x
80 Grit	CC-20	
Premium Zirconia Chamfering Cones (blue)		
50 Grit	CCZ-15	
80 Grit	CCZ-20	



45° 5" (127mm) Dia. Chamfering Cones & Mandrel

- Large diameter cones chamfer the top of the cylinder to an exact 45° angle in one pass
- 1/2" (12.7mm) steel shank is permanently embedded in the cone base to ensure stability
- Cone height: 3 1/2" (88.9mm)
- Kit includes mandrel & one 36-grit cone (CC-30)
- Due to manufacturing processes, abrasive color may vary
- Aluminum-Oxide is a good general purpose abrasive suited for ferrous and non-ferrous metals
- Zirconium is a tough abrasive well suited for heavy stock removal on most metals

Description	Order No.	Incl.
5" Chamfering Cone Kit	CC-130	▼
Chamfering Cones	Abrasive	Grit
	Aluminum Oxide	36
	(red)	50
		80
	Premium	36
	Zirconia	50
	(blue)	80
		CC-30
		CC-50
		CC-80
		CCZ-36
		CCZ-50
		CCZ-80




Honing Stone Sets For Nicasil

- For deglazing Nicasil with a CV/CK Honing Machine
- Diameter Range:
 - 3.0" - 5.0" (76.2-127.0mm) in standard automotive head
 - 2.6" - 3.5" (66.0-88.9mm) in junior head
- 150 grit aluminum oxide abrasive
- 6 pairs per package
- Order No. EHU-412

Lisle® Honing Stone Sets

- Clip-on style mounts in seconds
- 5" / 127mm stones and wipers
- Each set contains two stones and two felt wipers
- Use dry

Replaces Lisle® No.	Grit	Order No.
15500	80	HL-80
15510	180	HL-180
15520	280	HL-280
15590	500	HL-500




Honing Stones for Nicasil


- Deglaze Nicasil cylinders with portable hones
- Aluminum-Oxide abrasive
- Resizing cylinders requires diamond abrasive
- A43 = Aluminum-Oxide, J63 = Silicon-Carbide

Stones for SNJ-10 Portable Hones			Stones for AN & GH Style Hones		
Inch	Grit	Order No.	Inch	Grit	Order No.
1.42"-1.60"	150	SNJ2-A43	2.5"-3.3"	150	GG25-A43
	280	SNJ2-J63	3.3"-4.2"	150	MM33-A43
1.58"-1.77"	150	SNJ3-A43	4.0"-5.6"	150	NN40-A43
	280	SNJ3-J63			

Standard Duty 240 Grit Aluminum Oxide Flex-Hones® For Nicasil

Inch	mm	Order No.	Inch	mm	Order No.
2 1/4"	57.2	BA-225240	3 3/4"	82.5	BA-325240
2 3/8"	60.2	BA-237240	3 1/2"	88.9	BA-350240
2 1/2"	63.5	BA-250240	3 3/4"	95.3	BA-375240
2 5/8"	66.5	BA-262240	4 1/8"	104.8	BA-418240
2 3/4"	69.8	BA-275240	4 3/8"	117.5	BA-462240
3"	76.2	BA-300240	More Flex-Hones® on page 90		





BRM

Brake Rotor
Flex-Hones
page 122

Flex-Hones® For Any Type And Size Of Cylinder

- Abrasive globules each have independent suspension • Self-centering • Self-aligning • Self-compensating for wear
- Applications are interchangeable, select bore size • Right Hand rotation only

240 Grit Silicon-Carbide Valve Guide Flex-Hones®

- Ideal for all materials including cast iron, bronze, phosphor bronze and aluminum

Size	mm	OAL	Order No.	Incl.
6 Pc. Kit			VGf-KIT	▼
1 $\frac{1}{64}$ "	4.5	6"	VGf-4.5MM	
1 $\frac{3}{64}$ "	5.0	8"	VGf-5MM	
7 $\frac{32}$ "	5.5	8"	VGf-5.5MM	
1 $\frac{1}{4}$ "	6.4	8"	VGf-6.4MM	x
9 $\frac{32}$ "	7.0	8"	VGf-7MM	x
5 $\frac{16}$ "	8.0	8"	VGf-8MM	x
1 $\frac{1}{32}$ "	9.0	8"	VGf-9MM	x
3 $\frac{8}$ "	10.0	8"	VGf-10MM	x
7 $\frac{16}$ "	11.0	8"	VGf-11MM	x
15 $\frac{32}$ "	12.0	8"	VGf-12MM	
33 $\frac{64}$ "	13.0	8"	VGf-13MM	
9 $\frac{16}$ "	14.0	8"	VGf-14MM	
19 $\frac{32}$ "	15.0	8"	VGf-15MM	

400 Grit Diamond Valve Guide Flex-Hones®

- Ideal for heat treated steel, high nickel stainless steel, chromes or plated bores, MMX aluminum alloys, ceramics and carbides

Size	mm	OAL	Order No.
1 $\frac{1}{4}$ "	6.4	8"	VGFD-6.4MM
9 $\frac{32}$ "	7.0	8"	VGFD-7MM
5 $\frac{16}$ "	8.0	8"	VGFD-8MM
1 $\frac{1}{32}$ "	9.0	8"	VGFD-9MM
3 $\frac{8}$ "	10.0	8"	VGFD-10MM

120 Grit Silicon-Carbide Flex-Hones®

- Ideal for all materials including cast iron, bronze, phosphor bronze and aluminum
- When ordering heavy-duty, order on cylinder size

Standard				Heavy-Duty	
Size	mm	OAL	Order No.	OAL	Order No.
2"	50.8	8"	BG-210	-----	-----
2 $\frac{1}{4}$ "	57.2	8"	BG-225	-----	-----
2 $\frac{1}{2}$ "	63.5	8"	BG-250	-----	-----
2 $\frac{3}{4}$ "	69.8	8"	BG-275	-----	-----
3"	76.2	8"	BG-300	13 $\frac{1}{2}$ "	BGD-300
3 $\frac{1}{4}$ "	82.6	13 $\frac{1}{2}$ "	BG-325	13 $\frac{1}{2}$ "	BGD-325
3 $\frac{1}{2}$ "	88.9	13 $\frac{1}{2}$ "	BG-350	13 $\frac{1}{2}$ "	BGD-350
3 $\frac{3}{4}$ "	95.3	13 $\frac{1}{2}$ "	BG-375	13 $\frac{1}{2}$ "	BGD-375
4"	101.6	-----	-----	13 $\frac{1}{2}$ "	BGD-400
4 $\frac{1}{8}$ "	104.8	13 $\frac{1}{2}$ "	BG-418	-----	-----
4 $\frac{1}{4}$ "	107.9	-----	-----	13 $\frac{1}{2}$ "	BGD-425
4 $\frac{3}{8}$ "	111.1	13 $\frac{1}{2}$ "	BG-438	-----	-----
4 $\frac{1}{2}$ "	114.3	-----	-----	13 $\frac{1}{2}$ "	BGD-450
4 $\frac{3}{4}$ "	117.5	13 $\frac{1}{2}$ "	BG-462	-----	-----
5 $\frac{1}{2}$ "	139.7	-----	-----	17 $\frac{1}{2}$ "	BGD-550
6"	152.4	-----	-----	17 $\frac{1}{2}$ "	BGD-600
6 $\frac{1}{2}$ "	165.1	-----	-----	17 $\frac{1}{2}$ "	BGD-650

180 Grit Silicon-Carbide Flex-Hones®

- Ideal for all materials including cast iron, bronze, phosphor bronze and aluminum
- Sizes with extra-long shanks are ideal for cam bearings

Standard				Extra-Long Shank*	
Size	mm	OAL	Order No.	OAL	Order No.
5 $\frac{16}$ "	15.9	8"	BH-625	-----	-----
3 $\frac{1}{4}$ "	19.1	8"	BH-750	-----	-----
13 $\frac{16}$ "	20.6	8"	BH-820	-----	-----
7 $\frac{16}$ "	22.2	8"	BH-875	-----	-----
1"	25.4	8"	BH-1000	-----	-----
1 $\frac{1}{8}$ "	28.6	8"	BH-1125	-----	-----
1 $\frac{1}{4}$ "	31.8	8"	BH-1250	-----	-----
1 $\frac{3}{8}$ "	34.9	8"	BH-1375	-----	-----
1 $\frac{1}{2}$ "	38.1	8"	BH-1500	-----	-----
1 $\frac{5}{8}$ "	41.3	8"	BH-1625	-----	-----
1 $\frac{3}{4}$ "	44.5	8"	BH-1750	17 $\frac{1}{2}$ "	CBF-175*
2"	50.8	8"	BH-2000	17 $\frac{1}{2}$ "	CBF-200*
2 $\frac{1}{4}$ "	57.2	8"	BH-2250	17 $\frac{1}{2}$ "	CBF-225*
2 $\frac{1}{2}$ "	63.5	8"	BH-2500	17 $\frac{1}{2}$ "	CBF-250*
2 $\frac{3}{4}$ "	69.8	8"	BH-2750	17 $\frac{1}{2}$ "	CBF-275*

*CBF flex-hones include an extender & nipple for OAL of 17 $\frac{1}{2}$ "

320 Grit Standard Duty Silicon-Carbide Flex-Hones®

- Ideal for all materials

Size	mm	OAL	Order No.
1 $\frac{1}{4}$ "	31.8	8"	BG-125320
2 $\frac{1}{4}$ "	57.2	8"	BG-225320
3"	76.2	8"	BG-300320
3 $\frac{1}{4}$ "	82.6	13 $\frac{1}{2}$ "	BG-325320
3 $\frac{1}{2}$ "	88.9	13 $\frac{1}{2}$ "	BG-350320
3 $\frac{3}{4}$ "	95.3	13 $\frac{1}{2}$ "	BG-375320
4 $\frac{1}{8}$ "	104.8	13 $\frac{1}{2}$ "	BG-418320
4 $\frac{3}{8}$ "	111.1	13 $\frac{1}{2}$ "	BG-438320
4 $\frac{3}{4}$ "	117.5	13 $\frac{1}{2}$ "	BG-462320

320 Grit Heavy Duty Silicon-Carbide Flex-Hones®

- Ideal for all materials

Size	mm	OAL	Order No.
4"	101.6	13 $\frac{1}{2}$ "	BGD-400320
4 $\frac{1}{4}$ "	107.9	13 $\frac{1}{2}$ "	BGD-425320
4 $\frac{1}{2}$ "	114.3	13 $\frac{1}{2}$ "	BGD-450320

240 Grit Aluminum-Oxide Flex-Hones®

- Ideal for hard surfaces such as Nicasil and hardened steel

Size	mm	OAL	Order No.
2 $\frac{1}{4}$ "	57.2	8"	BA-225240
2 $\frac{3}{8}$ "	60.2	8"	BA-237240
2 $\frac{1}{2}$ "	63.5	8"	BA-250240
2 $\frac{5}{8}$ "	66.8	8"	BA-262240
2 $\frac{3}{4}$ "	69.8	8"	BA-275240
3"	76.2	8"	BA-300240
3 $\frac{1}{4}$ "	82.6	13 $\frac{1}{2}$ "	BA-325240
3 $\frac{1}{2}$ "	88.9	13 $\frac{1}{2}$ "	BA-350240
3 $\frac{3}{4}$ "	95.3	13 $\frac{1}{2}$ "	BA-375240
4 $\frac{1}{8}$ "	104.8	13 $\frac{1}{2}$ "	BA-418240
4 $\frac{3}{8}$ "	117.5	13 $\frac{1}{2}$ "	BA-462240

RIGHT HAND ROTATION ONLY! For best results, always use with an ample flow of honing oil




Stones & Replacement Parts For CR-Series Mandrels

- Sunnen honing stones are sold as pairs while Goodson honing stones are sold individually

Honing Stones for Manual Honing*			
Fit Mandrels	Finish	Sunnen Order No.	Order No.
CR-1450 to 1750	Medium	CR-2	----
	Fine	CR-4	----
CR-1900 & Larger	Aluminum/		
	Titanium	CR-9	----
	Roughing	CR-10	HC-10
	Medium	CR-12	HC-12
	Fine	CR-14	HC-14
For Power Hone	Roughing	CR-10N	----
Guide Shoes (2 per box)			
CR-1450 to 1750	Die Cast	CR-40D	----
CR-1900 & larger	Die Cast	CR-50D	----
	Bronze	CR-50B	----
Wedge & Wedge Plates			
CR-1450 to 1750	Wedge	CR-70	----
	Small Plate	CR-75	----
	Large Plate	CR-85	----
CR-1900 to 2500	Wedge	CR-100	----
CR-1900 & Larger	Small Plate	CR-110	----
	Large Plate	CR-120	----
CR-2900	Wedge	CR-200	----
Sunnen® Tension Block For CR-2900 & Larger			LN-1337A
Sunnen® Shoe Clamps (4 + screws) for CR-1900 & larger			CR-45A

*Sunnen® honing stones include 2/box, Goodson include 1/box



Replacement Parts for CV-616 Honing Machine

Replacement Belts	Order No.
Timing Belt	CK-252
Flat Belt	CK-192A
Replacement Fiber Planetary Gear Set	CK-234A



Rod Honing Oil

- Includes additives for high pressure cutting
- Keeps stones clean and free-cutting during rod reconditioning, pin fitting and other honing applications
- Will mix with other honing oils (including Sunnen®)

Size	Order No.
1 gal./3.78L	RHO-10
5 gal./18.9L	RHO-50





Goodson Belts for Sunnen® Rod Honing Machines

- Top-quality belts for long life

tech tips

from the techperts™
You must measure the belt you are replacing. Ordering is based on length, not machine model. If your belt size doesn't match one in the chart, order the next size down. For example, if your belt measures 72½", order the 70" Oil Pump Belt. Belts stretch over time so the shorter belt will fit.



Size	Order No.	
Oil Pump Belts (.250" dia.)		
70"/1.78m	RHB-70	
74"/1.88m	RHB-74	
85"/2.16m	RHB-85	
109"/2.77m	RHB-109	
Flat Belts		
46½" x 5⁄8"/1181.1x15.9mm	RHFB-46	

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS


V-TWIN & METRIC
HARD PARTS

full service
...**fast**



"If you need engine building tools and supplies, you need Goodson! We're dedicated to providing you with the best quality products, the best value and the best service in the industry."

- Lea, Goodson Customer Service - 2 year of service



Hone High-Silicon Aluminum Alloy Blocks

With Ease - Honing Stones & Silicon Compound

- Stones fit both the Sunnen® **AN-112** and **AN-815** and the Goodson **GH-2555** Portable Honing Mandrels
- Use each stone set progressively until the final bore size is achieved • For Hone Diameter: 3.3" to 4.2"
- To create the final condition, coat the felt set and the honed cylinder surface with the Silicon Compound (**AN-30**) and lap the cylinders
- After completion, the cylinder will have a dull matte finish
- Piston and rings will ride on silicon instead of aluminum
- Silicon Compound 1 lb. / 450g

Description	Order No.
Roughing (280 grit)	MM33-J63
Finishing (400 grit)	MM33-J85
Polishing (600 grit)	MM33-CO5
Felt Set	MM33-FO5
Silicon Compound	AN-30

SUNNEN Based Honing Oil

- Formulated for general purpose automotive machine shop honing
- Compatible with most popular honing machines
- 5 gallons (18.1L)
- Order No. **MAN-845**



tech tips


from the techxperts™

Right Hand Rotation Only.

For best results, keep your RPM about the same as your hone RPM, use the same rate of speed and number of strokes per minute.

Ultra-Finish Plateau Soft Hones

- Remove microscopic peaks and scuffs without enlarging bores • Use with a portable drill • Abrasive impregnated nylon bristles • Ideal for high-performance engine rebuilding and for engines that use low-tension rings
- Use **after** honing
- Gives a superior plateau finish so rings seal immediately, reducing break-in time
- Allows closer tolerances for improved compression, better oil control, lower emissions
- For best results, use liberal amounts of honing oil (**HO-50**, pg. 85) • **NOT** interchangeable with Flex-Hones®




Hole Diameter Range	Hone	Head	Overall	
in	mm	Dia.	Length	Length
.875"-1.00"	22-25	1.250"	2.00"	10.00"
1.00"-1.25"	25-32	1.500"	2.00"	10.00"
1.25"-1.75"	32-45	2.000"	2.00"	10.00"
1.75"-2.25"	45-57	2.500"	2.00"	10.00"
2.25"-2.75"	57-70	3.000"	3.00"	10.00"
2.50"-3.00"	63-76	3.500"	4.00"	14.00"
3.00"-3.50"	76-89	4.000"	4.00"	14.00"
3.50"-4.00"	89-102	4.500"	4.00"	14.00"
4.00"-4.50"	102-114	5.000"	5.00"	14.00"
4.50"-5.00"	114-127	5.500"	5.00"	14.00"

Valve Guide Plateau Hones on page 36



Line Hone Stones & Shoes

- For the Sunnen® CH-100, CHV-31, CH-20 & CH-40 Line Honing Machines
- Stones for Aluminum blocks (RY24-J45) are softer than those for cast iron (RY24-J49)



Description	Order No.
Replacement Stones — 5 per box (Requires 10 stones)	
Recommended Application Cast Iron	RY24-J49
Aluminum	RY24-J45
Replacement Shoes — 10 per box (Requires 20 shoes)	
Fit 10RY-2400G & 10RY2700G	RG-D
Fit 10RY-3000H	RH-D

Goodson is
Authorized to Ship
Sunnen Automotive
Products into Canada

Rod Honing Stones & Mandrels

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS



KL-Series Connecting Rod Lifetime Honing Unit Mandrel Adaptor

- Mandrel Adaptor comes with retainer
- Order No. **AK20-A**



Rod Honing Stones, Guide Shoes & Replacement Parts

- Premium-quality • Choose Goodson or Sunnen®

SL
Stones




HP / PL
Stones




HM / ML
Stones



HK / KL
Stones



		Goodson		Sunnen®	Old		
Stones	Use	Order No.	Qty.		Order No.	Order No.	Qty.
	For Sunnen® SL720 - SL2300 Mandrel						
	Roughing				SL-5		6
	General Purpose		WorldwideShipping		SL-7		6
	Finishing			SL-13		6	
	For Sunnen® PL Series Mandrel						
	Roughing	HP-5	1		P28-J27	PL-5	12
	General Purpose	HP-7	1		P28-J47	PL-7	12
	Finishing	HP-13	1		P28-J67	PL-13	12
	For Sunnen® ML Series Mandrel						
	Roughing	HM-5	1		P20-J25	ML-5	12
	General Purpose	HM-7	1		P20-J47	ML-7	12
	Finishing	HM-13	1		P20-J67	ML-13	12
	For Sunnen® KL Series Mandrel						
	Roughing	HK-5	1		K20-J25	KL-5	12
	General Purpose	HK-7	1		K20-J47	KL-7	12
	Finishing	HK-13	1		K20-J67	KL-13	12
	Steel				K20-A69	KL-14	12
Bronze Guide Shoes		Order No.	Qty.		Order No.		Qty.

Note: Bronze guide shoes outlast die cast 6 to 1.

Bronze
Guide
Shoes



Zinc Alloy Guide Shoes		Order No.	Qty.	Order No.	Qty.
For Sunnen® PL and ML Series Mandrel					
	1.355" - 1.500"	34.4-38.1mm	----	WC-D	2
	1.480" - 1.625"	37.6- 41.3mm	----	WD-D	2
	1.730" - 2.000"	43.9- 50.8mm	----	WE-D	2



When cutting action of your honing stone slows down, a light stroke with the diamond dresser breaks the glaze and restores honing efficiency. Especially recommended for rod reconditioning. Consists of diamond stone on a sturdy metal holder with a chain for fastening it to the honing machine.



Diamond Stone Dresser

- Diamond stone on durable metal tool
- Order No. **MAN-700**

Rod & Cap Grinding Wheels

- Fits Sunnen® Rod and Cap Grinding Machines
- Recessed design
- Size: 6" x 2" x 1 1/4" (152.4 x 50.8 x 31.8mm)
- Order No. **GR-805**



Rod & Cap Grinding Wheels

- For Sunnen® and other popular brand cap grinders
- Fits CRG 700, 750, 770, 780, 805 & 920K
- Softer than GR-805 • 6" x 2" x 1 1/4"
- Order No. **F343793**



... another
satisfied
customer

"Quality tools, fast turn around time and friendly, helpful people."
- Norman, NC Machine, Rutledge, Mo, Goodson customer since 2017

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING


MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

tech tips

from the techxperts™

Standard Wrist Pin Bushing Driver sizes range from 25mm to 54mm. If we don't have the size you're looking for in the chart below, choose the next size up and turn it down on your lathe to the exact size you require.



Universal Tapered Pin Bushing Press Kit For Light & Medium Duty Diesel Engines

sized for
diesel

This press kit is specially designed to remove and replace tapered bushings in most common light to medium duty diesel applications. Don't spend time making a fixture that's dedicated to a single size. Our Tapered Pin Bushing Press Kit is ready to go when you receive it.

Description	Order No.	Includes			
Complete Wrist Pin Bushing Press Kit	TB-KIT	▼			
Wrist Pin Press Base (select drivers below)	TB-BASE	▼ x			
Press Tube - Small (27x21x120mm)	TPT-SM	x			
Press Tube - Large (30x31x110mm)	TPT-LG	x			
Wrist Pin Ring (50x5x20/26mm)	WPR-001	x			
Wrist Pin Parallels (2) 8x10x50mm	WPP-2	x			
Extended Mandrel (8 1/2" long)	TB-MANDREL	x			
Wrist Pin Bushing Drivers sold by dimension, not application					
MM	Nominal	Actual	Step		
25	1.000"	0.957"	0.063"	TBD-25	x
26	1.063"	0.990"	0.058"	TBD-26	x
27	1.060"	1.032"	0.067"	TBD-27	x
28	1.100"	1.006"	0.055"	TBD-28	x
30	1.180"	1.102"	0.075"	TBD-30	x
31	1.220"	1.158"	0.090"	TBD-31	x
31	1.220"	1.198"	0.067"	TBD-31A	x
32	1.260"	1.222"	0.078"	TBD-32	x
33	1.300"	1.268"	0.068"	TBD-33	x
34	1.340"	1.304"	0.073"	TBD-34	x
36	1.420"	1.377"	0.075"	TBD-36	x
38	1.500"	1.458"	0.076"	TBD-38	x
40	1.570"	1.554"	0.068"	TBD-40	x
42	1.650"	1.614"	0.097"	TBD-42	x
45	1.770"	1.742"	0.089"	TBD-45	x
46	1.810"	1.772"	0.108"	TBD-46	x
50	1.970"	1.940"	0.083"	TBD-50	x
52	2.050"	2.012"	0.114"	TBD-52	x
54	2.130"	2.099"	0.081"	TBD-54	x
Goodson Press Fit Lube (6 oz. Aerosol can)				PFL-200*	
Deburring Tool				DT-6	


*Hazardous Goods Fees Apply When Shipped Air



Deburring Tool

- Swivel tool chamfers sharp, machined edges, bolt holes, and much more
- DT-6 includes cutters for aluminum and cast iron

Description	Order No.
Deburring Tool	DT-6
Replacement Cutters	
Steel/Aluminum	DT-10
Cast Iron/Brass	DT-20



Gas Porting Tools for High Performance


- Virtually eliminate side ring clearance by drilling gas ports in your piston ring lands
- These tiny ports apply compression pressure directly to the back of the ring, pushing it against the cylinder wall with greater force while minimizing compression leakage
- Gas ports work best with piston-compression heights of 1.2" or less on engines running at high rpm (7,000 or higher)
- This simple tool kit take the guess-work out of gas porting and include everything you'll need to get started
- The complete kit includes: Drill Fixture, Depth Bushing and one Drill Bit

US Patent No. US D617,664 S

Description	Order No.
Gas Porting Tool Kits	GPT-043
.040" Drill Bits (5 Pack)	GPT-040-DB
Gas Porting Tool Kits	GPT-062
.0625" Drill Bits (5 Pack)	GPT-062-DB

Rod & Piston Work

CYLINDER HEAD
REBUILDING
CLEANING,
ASSEMBLY & SAFETY
SHORT BLOCK
REBUILDING
CRANKSHAFT/
FLYWHEEL GRINDING
MISCELLANEOUS
TOOLS & SUPPLIES
BRAKE SERVICE
TOOLING
MEASURING
V-TWIN & METRIC
HARD PARTS




Piston Pin Removal Fixture

- Use to remove or install interference fit piston pins
- Force of removal is against the piston pin and connecting rod – no pressure is exerted on the piston itself
- Tooled to fit most popular engines with pin diameters of 0.859" through 1.087"
- Replacement Support Inserts & Guide Pins sold separately

tech tips


For Small Block Chevy use Support Insert #1 or Offset #6, for Big Block Chevy, use Support Insert #5, Support #2 is a .275" thick blank, ready to be machined to your exact specifications.

Description	ID	Step	Order No.	Incl.
Complete Kit			PPE-7082	▼
Replacement C-Frame			PPE-302186	x
Replacement	#1	0.945" .100"	PPE-39889	x
Support Inserts	#2	1.110" .182"	PPE-39890	x
	#3	1.000" .182"	PPE-39888	x
	#4	1.110" .182"	PPE-39886	x
	#5	1.000" .100"	PPE-39887	x
	#6	0.945" .100"	PPE-39822	x
Replacement Guide Pins	0.859"		PPE-17940	x
	0.897"		PPE-17936	x
	0.926"		PPE-17937	x
	0.970"		PPE-17938	x
	0.992"		PPE-17939	x
	1.032"		PPE-17941	x
	1.055"		PPE-17942	x
	1.087"		PPE-18729	x
Replacement Parts				
J" Bolt (Rear Support)			PPE-302224	x
Wing Nut			PPE-10588	x
1 3/16" 30.2mm Stop Plug			PPE-17830D	x
Base Plate			PPE-17929	x
Receiving Tube			PPE-17931B	x
Body Guide			PPE-17932B	x
5 1/2" 139.7mm Spring			PPE-17934	x
Guide Pin Driver			PPE-17935	x
1 3/4" 41.3mm External Spiral Lock			PPE-17945	x



Universal Piston Pin Press-Out Tool

- Use with a shop press
- Top quality steel tooling
- Standard set handles most applications
- You can modify for individual needs




Description	Order No.	Incl.
Piston Pin Extractor Kit	PPE-1	▼
Piston Support Fixtures .800" hole	PPE-1A	x
.865" hole	PPE-1F	x
.950" hole	PPE-1B	x
1.010" hole	PPE-1C	x
1.010" hole	PPE-1D	x
1.110" hole	PPE-1E	x
Fixture Base Block (4" x 4" x 3/4")	PPE-1G	x
Pin Pressing Drifts .760" dia.	PPE-1H	x
.812" dia.	PPE-1J	x
.875" dia.	PPE-1K	x
1.000" dia.	PPE-1L	x
Tapped Handle	PPE-1M	x
Threaded Rod	PPE-1N	x
Threaded Adaptor	PPE-1P	x
Rod Support	PPE-1GM	x

Kit includes the rod support for tapered boss pistons

GOODSON Rod Support for Sunnen® Pin Press Tooling

- Remove late model connecting rods from tapered boss pistons
- Aluminum construction prevents connecting rod damage • Fits B-162 Pin Press Reducing Ring

Description	Order No.
Rod Support	BRS-130
Pin Press Reducing Ring	B-162



Rod & Piston Work

CYLINDER HEAD
REBUILDING
CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING


CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS



220V, Single-Phase Electric Rod Heater


- Includes a digital timer and 450° temperature crayon
- Double wall insulated heat chamber with safety screen
- Vented top for better performance
- Powder-coated heavy-gauge steel housing for long life



Toggle switches with flip-up covers to prevent accidental activation. LED lamps indicate when power is active.




Heating elements operate on separate thermostats.



Adjustable rod supports accommodate most automotive connecting rods.

Description	Order No.	Incl.
220V, 50/60 Hz Single Phase Electric Rod Heater	ERH-2220	▼
Digital Read-Out Timer (battery included)	ERH-TIMER	x
Replacement Toggle Switch (ea.)	ERH-SWITCH	
Replacement Toggle Switch Guard (ea.)	ERH-TSG	
Replacement Thermostat (ea.)	ERH-THERM	
Replacement Heater Coil (ea.)	ERH-COIL	
Replacement LED Light Assembly (ea.)	ERH-LED	
Replacement Bezel Knob (ea.)	ERH-KNOB	
Replacement Thumbscrew (ea.)	ERH-TST	
450° Melting Point Temperature Indicator Crayon	TIC-450	x
Piston Pin Installation Fixture	PIF-25	



Temperature Indicating Crayon

- Mark the workpiece before heating
- Melts when temperature is reached

Melting Point	Order
450°F / 232.22°C	TIC-450
500°F / 260.00°C	TIC-500
600°F / 315.56°C	TIC-600

Gauntlet Style Heat & Flame Resistant Gloves

- Heavy lined red terry-cloth • 13 1/2" Long
- Safe to 450°F / 232.2°C
- Order No. **HFR-300**



Band Ring Compressor Kits

- Install rings safely and easily • Hardened steel for durability
- Trigger ratchet mechanism for tight compressions

Description	Order No.	Incl.
6 Pc. Band Ring Compressor Kit	GPS-98	▼
9 Pc. Band Ring Compressor Kit	GPS-99	▼
Compressing Pliers	GPS-98A	x x
Bands	Range in. mm	
	1.875" - 2.125"	47.63-53.98 GPS-98Q
	2.125" - 2.375"	53.98-60.33 GPS-98R x
	2.375" - 2.625"	60.33-66.68 GPS-98S x
	2.625" - 2.875"	66.68-73.03 GPS-98T x
	2.875" - 3.125"	73.03-79.38 GPS-98B x x
	3.125" - 3.375"	79.38-85.73 GPS-98C x x
	3.375" - 3.625"	85.73-92.08 GPS-98D x x
	3.625" - 3.875"	92.08-98.43 GPS-98E x x
	3.875" - 4.125"	98.43-104.78 GPS-98F x x
	4.125" - 4.375"	104.78-111.13 GPS-98G x x
	4.500" - 4.750"	114.30-120.65 GPS-98H
	4.750" - 5.000"	120.65-127.00 GPS-98I
	5.000" - 5.250"	127.00-133.35 GPS-98J
	5.250" - 5.500"	133.35-139.70 GPS-98N

The Original Goodson Powered Ring Filer

- No more tedious filing and checking and filing and checking to get desired end gap; set it once and cut multiple rings
- Easy to read integral dial indicator and positive ring stop make repeatable precision quick and easy
- Fits 2½" to 5" / 63.5 to 127mm diameter rings
- Adjustable guide holds rings square to the cutting wheel
- Table pivots past cutting wheel
- No open ways to gather grinding dust that causes premature wear
- Handy knurled in-feed adjustment knob • High torque motor

Diamond Dresser is securely held in place by the ring clamping pin



made in America


Lighted Rocker Switch

Built-in deburring wheel eliminates the need to hand hone or deburr rings after filing




Also available WITHOUT deburring wheel


Description	Order No.
Powered Ring Filer 110V / 60 cycle w/o Deburring Wheel	PRF-812
Powered Ring Filer with Deburring Wheel 110V / 60 cycle	PRF-812DW
Powered Ring Filer with Deburring Wheel 220V / 50 cycle	PRF-822DW
Replacement Deburring Wheel	PRF-DW
NEW 3" Diamond Wheel	PRF-10002D
2½" Replacement Grinding Wheel (60 grit) for pre-2008 models	PRF-1001
3" Replacement Grinding Wheel (60 grit)	PRF-1002
Replacement Diamond Dresser	PRF-812D
Replacement Table Spring	PRF-SPRING
Sun-Dura® Canvas Machine Cover	GMC-PRF




1 Stainless Steel Table



2 Eccentric adjusts quickly and easily



3 Positive ring stop



4 Table pivots past grinding wheel


new



PRF-1002D


Manual Ring Grinder

- Produce end gap rings squarely
- Heavy duty aluminum casting
- Precisely machined for long life
- Aluminum-Oxide wheel holds shape and produces clean precise cuts
- Includes 1 grinding wheel (replacements available)
- Wheel measures 2" OD x ¾" ID x ⅛" thick



Built-in V-Groove for butt grinding valves

Description	Order No.
Piston Ring Grinder	PRF-250
Replacement Wheel	PRF-250W




Manual Ring Grinder

- Universal design lets you grind almost any make, type or size of piston ring • Includes diamond abrasive wheel measuring 2" OD x ¼" ID x ⅛" Thick

Description	Order No.
Universal Piston Ring Filer	PRF-500
Replacement Diamond Abrasive Wheel	PRF-870-DW

Rod Balancing Stand

- Ideal for static balancing parts
- Use to weigh rotating and reciprocating masses and record the information for dynamic balancing
- Heavy-duty steel construction
- Includes 1-2" (50.8mm) and 1-2.3" (58.4mm) support discs
- Height adjustment for different rod sizes
- Order No. BS-201



made in America

6100 Gram Balancing Scales

- Scales feature automatic tare weight correction
- 1.0 Gram / 0.100 Ounce increments
- Operates on 9V battery (not included) or 110V converter (included) • Low battery indicator
- Order No. BS-6100



Special Orders Available

full service ...fast



"Technology has provided us with more efficient ways to give you, our customers, the quality of service you deserve! Our goal is to make ordering shop supplies faster & easier for you, whether you order by phone or through our website."

- Cheryl, Goodson IT/Order Fulfillment Manager - 30 years of service

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Rod Clamping Vise

- Align rods and caps perfectly
- Smooth jaws won't damage connecting rods like an ordinary vise
- Clamp rods firmly to align parting faces while torquing rod bolts
- Clamp in a vise or bolt to a workbench
- Order No. **RCV-20**



Watch a how-to video on the product's website listing



ERBG-3T
RBSG-P

Rod Bolt Stretch Gauge

- Accurate to .001"
- Features a 1½" dial gauge
- Extra heavy-duty tension spring for repeatable accuracy
- For bolts from 1" to 2½" long
- See more information on rod bolt stretch on page 123

Description	Order No.
Rod Bolt Stretch Gauge	RBSG-3
Optional Contact Point	ERBG-3T
Replacement Pointer	RBSG-P



Rod Bolt Boots

- Plastic boots protect crank journals & rod bolts during piston installation
- Save crank journals from rod bolt damage
- Don't risk your reputation for quality
- Reusable
- Set of 16
- Order No. **RBP-16**



On the product's website listing




Heavy-Duty Rod Bolt Installing Block

- Mount universal block in a vise to support rod while installing bolts
- Hardened aluminum won't slip
- If the top wears, you can restore it with a file or belt grinder
- Ream holes larger to accommodate oversize bolts
- Order No. **RB-50**



Connecting Rod not included




Piston Pin Installing Fixture

- Adjustable stops prevent over-centering rods
- Adjust the stop once and you're ready to assemble a full set of rods
- Base is pre-drilled to mount to a workbench
- Order No. **PIF-25**

Piston Ring Expander

- Remove and install most rings
- Tapered jaws
- ⅜" to ¼" ring width
- Order No. **PRE-500**



Piston Installing Deadblow Hammer

- 1 piece design
- Specially formulated urethane compound is cut and split resistant
- Convex-faced, non-mushrooming material
- Offset head
- Ideal for fast, mar-free piston installation
- Weighs 1.7 lbs./ .77 kg
- Order No. **PK-200**

Fine Abrasive Stick

- Radiused for easier ring deburring after end gapping
- 4" L x ½" radius / 101.6mm x 12.7mm
- Works on all types of rings
- Works on ring ID radii
- Order No. **RS-103**



tech tips

from the techxperts™
Fine Abrasive
Sticks work great for deburring the ends of piston rings after filing, or any part that needs deburring. For a finer finish, soak the abrasive stick in Lapping Oil (LP-LO-4).

Oil Gallery Plug Installer / Staker

- Set depth and lock plug in a single step
- Arbor nose aligns cup plug, then follows with two 180° staker lugs to set depth and lock oil gallery plug securely in place
- Order No. **ST-SB**



Steel Oil Gallery Plugs

- Replace lost or damaged originals
- 1/4" pipe plugs
- For use at the rear of Small Block Chevy oil galleries or other engines with similar size plugs
- 25 per box
- Order No. **OP-250**



dimensional
shipping


Oil Gallery Brushes

Steel Wire			Order No.	Incl.
3-pc. Kit	Size	Length	OGB-SK	▼
	1/4" x 3"	24"	OGB-1	x
	3/8" x 3"	24"	OGB-2	x
	5/8" x 3"	24"	OGB-3	x
Nylon Bristle			Order No.	Incl.
5-pc. Kit	Size	Length	OGB-KIT	▼
	3/8" x 3"	34"	OGB-38	x
	1/2" x 2 1/2"	34"	OGB-42	x
	5/8" x 3"	34"	OGB-5	x
	3/4" x 3"	34"	OGB-7	x
	3/4" x 3"	40"	OGB-8	x



100% Natural Oil Gallery Beeswax

- Preheat the part to be removed, apply wax to its base, allow to cool and remove the part
- 100% natural beeswax
- Measures 1" x 3/4" x 3" • Weighs 1 oz.
- Order No. **BWS-1**



Oil Filter Inspection Tool

- Check for contaminants with every oil change
- Cut open the filter canister for inspection
- Fits 2 1/2" to 6 1/2" diameter filters
- Includes a single blade

Description	Order No.
Oil Filter Inspection Tool	FIT-1-G
Replacement Cutter Blade	FIT-W

Oil Pump Pickup Tube Driver

- For all GM pumps
- Replace pickup tubes easily with a light mallet
- Driver grips the pickup tube flare
- Gives control for fast alignment and installation

Application	Tube OD	Order No.
Small Block	5/8"/15.9mm	TI-25
Big Block	3/4"/19.1mm	TI-30



Oil Gallery Plug Removers

- Power plugs out with an impact wrench
- Threaded plug inside prevents bit from backing into the holder
- Hardened tool-steel holder with lifetime breakage guarantee (excludes bit)
- Tool-steel bit can be reground or replaced
- Set screw holds bit firmly in place
- 1/2" drive – fits your impact wrenches
- **Do NOT use with a breaker bar or ratchet**



Description	Size		Order No.	Incl.
Plug Remover Kit	in	mm	PPS-KIT	▼
Replacement Tool	3/16"	4.76	PPS-187	x
Tool includes	1/4"	6.35	PPS-250	x
bit (except	9/32"	7.14	PPS-281*	x
PPS-281)	5/16"	7.94	PPS-312	x
	3/8"	9.53	PPS-375	x
Replacement Bits	3/16"	4.76	PPS-187B	
	1/4"	6.35	PPS-250B	
	5/16"	7.94	PPS-312B	
	3/8"	9.53	PPS-375B	

NOTE: *No bit is needed for PPS-281 (square socket).

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

... another
satisfied
customer

"Along with the slide hammer set, the lifter bore burnishing tool fixes tight lifter bores, even on assembled bottom ends quick and easy!! My last race motor build was going great until I noticed a few of my new lifters were real tight at the bottom of the bore.

This tool resized the bores fast and accurate even with the cam still in place. Due to the method of resizing, the entire block isn't contaminated with debris like a hone would do, and saves time and money."

- Grant Farmer, Grand Island, NY, Goodson Customer since 2018




Photo courtesy Tim Wilkerson Racing

Lifter Bore Burnishing Tools

- Eliminate burrs caused by shot blasting
- Drive the burnishing tool into the bore with a soft hammer then slide-hammer it back out
- 60Rc burnishing balls deburr and correct out-of-round lifter bores quickly and easily
- Won't oversize the bore



Lifter Bore Burnishing Balls

Description	Order No.	Incl.
Standard Burnishing Tool Set	LBB-1500	▼
14" Slide Shaft	GAO-1	x
15" Slide Shaft	LBB-1	
Slide Hammer	GAO-2	x
Lifter Bore Burnishing Balls		
0.8450" dia. (General Motors)	LBB-GM1	x
0.8760" dia. (Ford)	LBB-FO1	x
0.9060" dia. (Chrysler)	LBB-CR1	x
1.0000" dia.	LBB-1.000	
1.0010" dia.	LBB-1.001	
1.0625" dia.	LBB-1.0625	
1.0635" dia.	LBB-1.0635	
Jam Nut	LBB-NUT	x
Lifter Bore Brushes.		
7/8" (.875") dia.	LBB-875	
1" (1.00") dia.	LBB-100	
1 1/8" (1.125") dia.	LBB-1125	



SUNNEN®

Sunnen® Lifter Bore Hones

- Restore bore size and finish after shot blasting
- Install oversize lifters for high-performance
- Stones work in cast iron bores or ones sleeved with brass or steel
- Wide stones contact a large area giving better stability for hand honing
- Cross oil ports without catching
- Wedge-type adjustment is a simple, positive way to expand or contract the stone to the precise size needed
- Use a 3/8" (9.5mm) or 1/2" (12.7mm) hand-held electric or air drill at approx. 200 RPM
- Use with honing oil
- **All parts MUST be ordered separately to make a complete unit**

tech tips
from the techxperts™

NOTE: Wedges may come with a tab that must be removed **BEFORE** using them with the P-180 Head



Description	Order No
Honall Head	P-180
Adaptor	PAK20-A
Roughing Stone (280 Grit) 12/box	Y20-J67
Finishing Stone (400 Grit) 12/box	Y20-J87
Standard Lifter Bore Tooling (6" Reach)	
Mandrel .838" - .869" Range	AAY20838BH6LH
.869" - .900" Range	AAY20869BH6LH
Wedge	Y20-W-6LH
Retainer	LN-3688A-6LH
Truing Sleeve .838" - .869" Range	S-838
.869" - .900" Range	S-869
Extended Reach Lifter Bore Tooling (6 3/4" Reach)	
Mandrel .838" - .869" Range	AAY20838675LH
.869" - .900" Range	AAY20869675LH
Wedge	Y20-W-675LH
Retainer	LN-3688A675LH
Truing Sleeve .838" - .869" Range	S-838
.869" - .900" Range	S-869

Goodson is authorized to ship Sunnen products only within North and South America

Rod Honing Oil

- Includes additives for high pressure cutting
- Keeps stones clean and free-cutting during rod reconditioning, pin fitting and other honing applications
- Will mix with other honing oils (including Sunnen®)



Size	Order No.
1 Gal. (3.78L)	RHO-10
5 Gal. (18.9L)	RHO-50

... another
satisfied
customer

"Goodson is such an easy company to do business with. We'll certainly order again."
— David Everitt, Milton, PA, Goodson customer since 2022



Universal Cam Bearing Tool

- Remove and install hundreds of sizes of cam bearings with just four mandrels!
- Expanding Mandrels cover a 1.370"-2.250" range
- Adjusts instantly to under-size bearings so you can remove and install them from virtually any block
- Approximately 1/4" range for each size segment
- Interchangeable with Dura-Bond



This is ... another
one of those satisfied
customer
MUST have tools for
the shop and trailer.
We have needed our
Goodson Degree wheel
at the track a few times
and in a few minutes we
were done and ready
to go! Thanks again for
great equipment.
— Dean Dubbin, DMP
Awnings (NHRA Top
Alcohol Dragster),
Goodson customer
since 2010

Degree Wheel

- Check cam timing, duration and overlap
- Degree wheel measures 11" / 279.4mm dia. with 1 1/8" / 47.6mm hole • Complete kit includes the Degree Wheel, a 3/4" ID mounting hub for mounting on cranks using 7/16" to 3/4" fasteners, a 1/2" hub and necessary fasteners • Use hubs or turning tool to mount the wheel.
- Use with 1/2" drive ratchet

Wheel / Adaptors	Order No.	Incl.
Automotive Degreasing Kit	DW-KIT-2	▼
Degree Wheel	DW-11	x

Description	Order No.	Incl.
Universal Cam Bearing Tool	CBT-300	▼
Replacement Segment with Sleeve		
Max Dia. 1.370"	CBT-5M	x
1.682"	CBT-6M	x
1.875"	CBT-7M	x
2.250"	CBT-8M	x
Replacement Backing Plate		
Max Dia. 1.375"	CBT-5W	x
1.682"	CBT-6W	x
1.885"	CBT-7W	x
2.250"	CBT-8W	x
Replacement Neoprene Sleeve		
Max Dia. 1.370"	CBT-5NS	
1.682"	CBT-6NS	
1.875"	CBT-7NS	
2.250"	CBT-8NS	
Drivers		
Length 5" (pictured at left)	CBT-1B	x
24"	CBT-2B	
36" (pictured at left)	CBT-3B	x
48"	CBT-4B	
Miscellaneous Replacement Parts		
1.200" Expander with stud	CBT-3E	x
15/8" Expander with stud	CBT-4E	x
1/2"x13 Stud	CBT-1S	
3" Guide Cone	CBT-1C	x
Steel Storage Rack	CBT-300-WR	x
INTERCHANGEABLE WITH DURA-BOND		

Bearing Scraper

- Eliminate bearing high spots after installation to ensure correct oil clearance
- Solid hardwood handle
- 4" / 101.6mm blade with 3 cutting edges
- German steel blade
- Order No. **BS-30**

Lifting Sling

- Lift up to 1800 lbs. safely and easily
- 1" x 36" looped nylon webbing sling
- Do NOT use with caustics or temperatures exceeding 190°F
- Order No. **LS-3**

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Camshaft Work

Whether you're regrinding cores for stock applications or custom grinding for diesel and high performance, you can count on Goodson Cam Grinding Wheels to deliver an excellent finish

Goodson abrasives are second to none. We work with our manufacturers to get you the most ideal grain that's bonded to be free-cutting, yet still shed before loading up. Our Premium wheels are ideal for steel high performance camshafts of 55 to 65 Rc and for Stellite overlays. Goodson finishes all Camshaft Grinding Wheels to your specifications in-house for faster turn-around and delivery. Choose from the sizes below or custom order your cam wheel today!



Cam Grinding Wheels - WAA54-L5V1 - 54 Grit				
Diameter	Width	Arbor	Order No.	
18"	3/4"	19mm 6"	152mm	E341420
457mm	7/8"	22mm 6"	152mm	E335351
	1"	25mm 6"	152mm	E335352
	1 1/8"	29mm 6"	152mm	E335353
	1 1/4"	32mm 6"	152mm	E335354

Cam Grinding Wheels - 43A602-K8-V1 - 60 Grit				
18"	3/4"	19mm 6"	152mm	E342030
457mm	7/8"	22mm 6"	152mm	E339945
	1"	25mm 6"	152mm	E342031
	1 1/4"	32mm 6"	152mm	E348558

Cam Grinding Wheels - 7BL801 - 80 Grit				
18"	3/4"	19mm 6"	152mm	E416880
457mm	7/8"	22mm 6"	152mm	E427392


Due to the manufacturing process, actual colors may vary

Cam Grinding Wheels - WAA100 - 100 Grit				
18"	3/4"	19mm 6"	152mm	E379225
457mm	7/8"	22mm 6"	152mm	E397667
	1 1/4"	32mm 6"	152mm	E416183

Standard Goodson Cam Grinding Wheels - 100 Grit				
18"	3/4"	19mm 6"	152mm	GCC 18 x 0.750 x 6
457mm	7/8"	22mm 6"	152mm	GCC 18 x 0.875 x 6
	1"	25mm 6"	152mm	GCC 18 x 1.000 x 6
	1 1/4"	32mm 6"	152mm	GCC 18 x 1.250 x 6

Due to the manufacturing process, actual colors may vary

Ask about special order sizes, grits & grains



180 Grit Cam Bearing Flex-Hones®

- Silicon-Carbide globules laminated to high density nylon
- Includes 18" drive rod

Inch	mm	OAL	Order No.
1 3/4"	45	17 1/2"	CBF-175
2"	51	17 1/2"	CBF-200
2 1/4"	57	17 1/2"	CBF-225
2 1/2"	64	17 1/2"	CBF-250
2 3/4"	70	17 1/2"	CBF-275

Order 3 or more (mix or match) to Save 10% off Jobber

Bore Washing Brushes

- Clean tunnel housing bores and full-annular grooved area
- Heavy, hand-driven shank

Bore Washing Brushes		
Dia.	Length	Order No.
2"	36"	CBB-200
2 1/4"	36"	CBB-225
2 1/2"	36"	CBB-250
2 3/4"	18 1/2"	CWB-27W
3 1/2"	18 1/2"	CWB-35
4"	18 1/2"	CWB-40
4 1/2"	18 1/2"	CWB-45
5"	18 1/2"	CWB-50



Professional Measuring & Inspection Stand For Cranks & Cams

- Length adjusts up to 23" to fit journal spacing
- Rotate work to view or measure
- Solid aluminum frame with self-lubricating, corrosion and chemical-resistant wear surfaces
- Order No.



Cam & Crank Grinding Coolant

- Semi synthetic
- Non-nitrite
- High-lubricity
- Dilute 20 parts water to 1 part coolant

Size	Order No.
1 gallon (3.78L)	CGC-10
5 gallons (18.93L)	CGC-50

full service
...fast



"We're continually improving our production department to provide more flexibility in grinding wheel shapes and profiles. Give us a call when you need something special."

- Brandon, Goodson Production, 2 year of service



Crankshaft Journal Radius Gauge

- 16 radii ... $\frac{1}{32}$ " to $\frac{1}{16}$ "
- Measure radii of reground journals quickly
- Blades are clearly marked in $\frac{1}{64}$ " increments
- Use in holder or remove to use blades separately
- Order No. RG-16

Crankshaft Straightening Peening Tool

- Designed for narrow journals on some new-style V6 crankshafts
- Peen crankshafts in the radius area of damaged journals to straighten
- Long-shank
- Offset-radius face
- 10" long • 0.0625" radius
- 0.125" diameter

Description	Order No.
Peening Tool	CPT-062
Safety Glasses	PGL-21



tech tips
from the Techexperts™
**Stay Safe In
The Workplace!**
Always wear
protective gear.

Hand-Held Dressing Sticks

- Keep your crankshaft grinding wheels cutting clean

GG-112



DS-NOR

Hard Silicon-Carbide

- 1" x 1" x 6"
- Use to deglaze wheel side
- Removes material with light pressure
- Order No. GG-112


Dense Granular Norbide

- $\frac{3}{16}$ " x $\frac{1}{2}$ " x 3" • Long lasting
- For fine tuning radius and side relieving wheels
- Order No. DS-NOR



Rockwell Hardness Tester

- Calculate Rockwell Hardness quickly and accurately
- Range: 15 to 65 Rockwell on C-Scale
- Features a steel ball of precise weight and shape which is dropped from an exact height to yield an accurate Rc reading
- Weighs just 4 oz. • 9¼" long
- Includes case & instructions
- Order No. HT-45RC



Mach-B Grinding Wheel Shaping & Resizing



From routine grinding wheel shaping and sizing to emergency work, **Mach-B Can Do That!**

Mach-B Grinding Wheel Shaping & Resizing specializes in:

- Custom Grinding Wheel Shaping
- Custom Grinding Wheel Sizing
- Reducing Outside Diameters
- Increasing Inside Diameters
- ANSI Compliant Speed Testing
- Static Balance Testing
- Standard and Custom Profiles
- Grinding Wheel Slotting



Turn to Mach-B and Goodson for Fast Turnaround.
Visit www.mach-b.com for more information.



Goodson has several videos available related to Camshaft & Crankshaft Grinding. To access them on our website, simply scan the appropriate code with your smart phone or other smart device.

Crankshaft Grinding Wheel Selection



Grinding Wheel Slotting



CYLINDER HEAD
REBUILDING

ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

full service
...fast



"The Mach-B division of Goodson offers many services such as ANSI compliant speed testing, balance testing, grinding wheel shaping, resizing and more. Find out more at Mach-B.com."

- Jon, Goodson Production Manager, 44 years of service


Goodson crankwheels are made-to-order in-house

Other sources stock finished wheels, which makes it virtually impossible to stock a full range of sizes. If they don't have what you need, they may charge more and delay your order for weeks. That's why Goodson makes every wheel to order. We always have the right wheel because we take a Type 1 straight wheel, size it, shape it, speed test it and ship it.


For future reference write down your

Crank Wheel Number (s)

Select the shape




Hub




Straight



Recessed 1 Side



Recessed 2 Sides



Tapered

Select your wheel grade:

WAA



Superior Grade - 54 grit
Excellent dimensional accuracy, corner radii and surface finish. For multiple applications including weld grinding. Ideal for grinding everything from cast iron to steel. Finishing and roughing wheel. Aluminum-oxide abrasive for light to medium stock removal.

CSS ULTRA

Premium Grade
This new abrasive formulation combines high-quality components and an innovative bonding technology to produce a long-lived, cool grinding abrasive wheel. White and sintered aluminum-oxide. Increase stock removal rates without sacrificing quality. Limited stock available.

GCH



Superior Grade - 54 grit
Better form holding ability, cuts cooler and needs less dressing. Use on crank journals with Rockwell hardness of 35 Rc or less. Use on crankshafts of cast or forged steel, Nodular iron. Ideal for large radii, thrust and plunge grinding. Great for high-performance.

GCD

Premium Grade - 60 grit
For harder materials. Good form holding ability; cuts cooler and needs less dressing. Grains yield faster, cooler grinding. Use on journals with Rockwell hardness of 35 Rc or more. Ideal for diesel, high-performance, industrial and billet steel.

Increase coolant flow with Crankwheel Slotting

Slotting facilitates the flow of coolant to the thrust and radius areas of the crankshaft to prevent journal burning. Highly recommended for high performance and diesel crankshafts. Don't waste time waiting on other suppliers who outsource their crankwheels for slotting - Goodson has a shop full of equipment, so we slot wheels in house!

Order No. **SLOTTING** Call for quote



How to order:



If you have any questions, please call 1-800-533-8010

Grade	Diameter (OD)	Face Width	Arbor Size (ID)	Machine	Shape
WAA - Superior	Diameters are	Most sizes from 3/4" to	Arbor size of your	Identify the make and	Specify the shape for
GCD - Premium	available from 18" to	2 5/8" (custom widths	grinder. Any arbor	model of your grinder.	your grinder. We will
GCH - Superior	36" in most grades.	available). Be sure	hole from 3" to 12".		need the diameter
CSS-ULTRA		to include mounting			and depth of tapers,
		surface thickness.			recesses and hubs.

Crankshaft Grinding Wheels

Due to the commodity-like nature of abrasive grinding wheels, prices may change without notice. Please call us at **1-800-533-8010** or **1-507-452-1830** to confirm current pricing and availability.
No additional discounts available!

			
		WAA	GCH GCD
Dia.	Face Width		
Fits Storm Vulcan 14, 15			
18"	3/4"-1"		
3" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
Fits Storm Vulcan 15, 15 Special, 1550, 1648			
20"	3/4"-1"		
3" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
Fits Kwik-Way / Lempco			
20"	3/4"-1"		
33/4" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
Fits Kwik-Way / Lempco 539 & Storm Vulcan 15A (early)			
22"	3/4"-1"		
5" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
Fits Peterson Berco 180			
22"	3/4"-1"		
8" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
Fits Storm Vulcan 15A (late), 15A Special; RMC/Robbi REX-1200			
Fits Kwik-Way / Lempco KGA and NKG Series			
24"	3/4"-1"		
5" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
Van Norman 438, 448, 460, 465;			
Winona Van Norman/Zanrosso CG-210 (early); Storm Vulcan Scledum 200			
24"	3/4"-1"		
8" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
Storm Vulcan 15C			
25"	3/4"-1"		
5" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
AMC K1100; Peterson Berco 180, 225; Scledum 200, 230; Van Norman 438, 448, 460, 465, 475, 476; Winona Van Norman CG-210 (late), CG-840			
26"	3/4"-1"		
8" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
	2 1/64"-2 1/4"		

			
		WAA	GCH GCD
Dia.	Face Width		
Schou 1500/270, 1600, 260			
27 1/2"	3/4"-1"		
8 55/64" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
	2 1/64"-2 1/4"		
Peterson Berco 260; SV Scledum 230, 270/280; Zanrosso Mito 250; Van Norman 400, 438, 454, 475, 476, 666; RMC/Robbi REX-1500			
28"	3/4"-1"		
8" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
	2 1/64"-2 1/4"		
	2 17/64"-2 5/8"		
Seest MC62			
30"	3/4"-1"		
6" Arbor	1 1/64"-1 1/4"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
Zanrosso Mito 280; Storm Vulcan Scledum 270/280; RMC / Robbi REX-1800, REX 2200L			
30"	3/4"-1"		
8" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
	2 1/64"-2 1/4"		
	2 17/64"-2 5/8"		
AMC 1400, K1500, K1800; Van Norman 467, 477; Zanrosso			
32"	3/4"-1"		
8" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
	2 1/64"-2 1/4"		
	2 17/64"-2 5/8"		
Peterson Berco 280, 300; RMC Robbi REX-1800RM; REX-2200, REX-2200RM, REX-2700RM, REX-3100RM			
32"	3/4"-1"		
12" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
	2 1/64"-2 1/4"		
	2 17/64"-2 5/8"		
Peterson Berco 300, 350; Storm Vulcan Scledum 250; RMC / Robbi REX-2200M, 2700M, 3100M; Winona Van Norman 111			
36"	3/4"-1"		
12" Arbor	1 1/64"-1 1/4"		
	1 17/64"-1 1/2"		
	1 33/64"-1 3/4"		
	1 49/64"-2"		
	2 1/64"-2 1/4"		
	2 17/64"-2 5/8"		

NOTE: All wheel widths are delivered up to .015" oversized to allow for side dressing when mounting the wheel

CYLINDER HEAD
REBUILDING
CLEANING,
ASSEMBLY & SAFETY
SHORT BLOCK
REBUILDING
CRANKSHAFT/
FLYWHEEL GRINDING
MISCELLANEOUS
TOOLS & SUPPLIES
BRAKE SERVICE
TOOLING
MEASURING
TOOLS
V-TWIN & METRIC
HARD PARTS

full service ...fast



"We do our best to get our inventory on the shelves; professionally and correctly packaged and ready for when you need it."

- Brandon, Goodson Receiving, 4 years of service

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Plastigage

- Accurately measure bearing clearance
- Color coded by size
- Put a piece on rod or main bearing and torque the cap
- Remove and inspect – width of crushed Plastigage shows clearance
- Use at the workbench or in the vehicle
- 10 per pack

Clearance Range	Order No.
.001" to .003" (.025 to .076mm)	PG-Green
.002" to .006" (.051 to .152mm)	PG-Red
.004" to .009" (.102 to .229mm)	PG-Blue
10pk. Assortment : 5 Green, 3 Red, 2 Blue	PG-10PK



Stroke Checker

- Accurately measure strokes up to 6"
- Works with any precision caliper to accurately measure crankshaft strokes
- Measures strokes up to 6" with an accuracy of .001"
- Rigid, hard-anodized aluminum frame is fully adjustable
- Fits almost any crankshaft
- Order No. **CSG-1**

See page 127 for our selection of calipers



Caliper
sold
separately

Heavy Duty Steel Stamps

- For hard materials
- Order in sets

Figure	Shank	Number Sets	Order No.
1/8"	5/16"		SFH-1/8
3/16"	3/8"		SFH-3/16

Special and custom orders are available, call 1-800-533-8010



Crank Welding Plug Rods

- 3 diameters available
- Each rod is 12 1/2" long and cuts off easily
- Sharpen ends with your existing pencil sharpener
- 5 Crank Welding Plug Rods per pack

Size	Order No.
.250"	CWPR-250
.312"	CWPR-312
.375"	CWPR-375




Sanding, Grinding, Polishing Belts Made to Order In-House

To provide you better service and save you money, Goodson bought an abrasive converting company in 2017. Since then, we've added equipment and personnel and we're cranking out abrasive belts for a wide range of industries. **Abrasive Industrial Supplies** is operated as a division of Goodson and our feet are still firmly placed in the automotive market.

Almost every abrasive belt shown in the Goodson catalog is manufactured by **Abrasive Industrial Supplies (AIS)** but that's just the beginning. We know you use belts on machines other than cylinder head resurfacers and crankshaft polishers and we're ready to meet those supply needs too.

Contact your Customer Service Representative today to get current pricing. Have AIS make something great for you!




Crankshaft Work



Eliptibur Tool

- Fastest, safest way to chamfer crank oil holes
- Simplify deburring and chamfering of angularly drilled holes on cylindrical surfaces
- Easily produces a chamfer of relative uniformity and depth
- Self-centering, spring loaded pilot
- Includes one replaceable blade
- For 30Rc or softer crankshafts

Description	Order No.
Eliptibur Tool (1 blade included)	EBT-15
Replacement Blade	EBT-15B
Replacement Pilot	EBT-15N



Need Steady Rest Shoes?

Email orderdesk@goodson.com or fax 1-507-452-2907 the design and dimensions for what you need

Crankshaft Grinder Steady Rest Shoes for Peterson-Berco

- Use same shoe for upper and lower replacement
- $\frac{5}{16}$ " thick
- Order No. **RBE-200**



Create a relief in the block for rod #2 at the pan rail area using your normal process.



Place the arbor in main saddles 1 & 2, keeping the flange nearest to the pointer against #2.



Rotate the arbor and adjust the pointer until the tapered end passes freely through the relief with a minimum of clearance.



Lock the pointer in position with the set screw and check the clearance.



Once satisfied, scribe a line on the pointer opposite the set screw.



A Must-Have when building a Stroker Engine!

Stroker Mimic™

- Lightweight and easy to use
- Eliminates the need to repeatedly install and remove the crankshaft, pistons, rod assembly and the necessary bearings when clearancing a block for a stroker crank
- Once the Stroker Mimic™ has been set to a particular crank, rod and piston combination, the tool can be marked or measured for future reference
- Order No. **SM-350**



Reluctor Ring Installation Tool



All steel construction features 2 indexing dowels to properly align the reluctor ring when installing it on the crankshaft. Designed to fit Generation III (LS1, LS6) and Generation IV (LS2, LS3, LS7) engines. Aligns GM sensor rings (12559353, 12586768). **US Patent No. 7,716,827.**

Goodson exclusive



The 8mm indexing dowel is attached to the fixture by an exterior tang. It can be adjusted for depth to accommodate a variety of popular flange widths. This dowel fits into the only 8mm hole on the reluctor wheel.



The internal indexing dowel pin is designed to fit into the dowel pin hole on the crankshaft. It is adjustable to fit different depths. The combination of dowel pins gives very precise alignment of the reluctor wheel and crankshaft.

Description	Order No.
Reluctor Ring Installation Tool	RRJ-350
Temperature Indicating Crayon (450° F/232°C)	TIC-450

tech tips
from the techxperts™

Heat reluctor ring to 450°F (232°C) then slide it onto the casting. Be sure to deburr all components before beginning assembly. Any sharp edges will cause the reluctor ring to catch on the casting, making assembly impossible.

Conversion Calculator

We've tried to convert as many SAE measurements to Metric (and vice versa) as possible. In some cases there hasn't been enough room.

If you need to convert a measurement, here are the formulas:

Starting Measurement	Conversion Formula	Converted Measurement
Inches (in)	Inches x 25.4	Millimeters (mm)
Feet (ft)	Feet x .3048	Meters (m)
Millimeters (mm)	Millimeters ÷ 25.4	Inches (in)
Fahrenheit (F)	(5 ÷ 9) x (F - 32)	Celsius (C)
Celsius (C)	(9/5 x C) + 32	Fahrenheit (F)

Crankshaft Polishing

CYLINDER HEAD
REBUILDING

CLEANING,
REBUILDING
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Crankshaft Polishing Starter Kit

Includes 1 each of:

- Grind Aid,
- Polishing Rouge,
- Abrasive Dresser and
- 5-Pack of our most popular 72" belts
- Order No. **CP-KIT**



Grind Aid

- Cools and lubricates
- Reduces loading-up and grain fracturing
- Belts produce a better finish and last up to twice as long
- Use only on cloth-back belts such as those shown on pages 108 & 109
- Order No. **GRA-10**




Polishing Rouge

- Produces high luster finish
- Use with light pressure, for cork or fine grit polishing to finish crank journals perfectly
- Hard, dry compound becomes viscous with heat
- White • 16 oz. / 454 g
- Order No. **CPR-16**



Natural Rubber Abrasive Belt Dresser

- Prolongs belt life
- Hold at 45° angle on moving belt to remove foreign material
- Restores cutting ability of grains
- 2" x 2" x 4" / 51 x 51 x 102mm
- Order No. **ACB-224**



Check out the Crankshaft Polisher in action! Scan the code below with the camera on your smart phone or other smart device to see the **Crankshaft Polishing** episode of **Tech Lab Tuesday**.



dimensional
shipping



Shown with flanged rollers

To keep motor operating efficiently, clean regularly with compressed air. Not recommended for use on chrome-plated items, which can damage the motor.

tech tips
from the techsavers™

Extend the life of your polishing belts by releasing the tension when not in use.

Includes a sample pack of our most popular 72" Belts (PCP-72PAK)

made in America

Adjustable 110V Crankshaft Polisher

- Adjusts to accommodate 70" to 72"L belts
- Flex resistant steel frame
- Weighs 15 lbs. (6.8 kg)
- Crowned rollers keep snug belt running true
- 1" nominal = 1.625"
- 2" nominal = 2.625"
- 1/2 HP motor designed for high RPM not heavy loads
- Specify flanged or unflanged rollers when ordering
- 110V, 60Hz Motor



Roller Width					Order No.
Nominal	Actual	HP	Max. RPM		
1 1/25mm	1.625"/41mm	1/2	10,000		PCP-1072
2 7/51mm	2.625"/67mm	1/2	10,000		PCP-1072-2
Replacement Parts and Rollers					Includes
Flanged Roller Sets					
(3 piece set)					
1"					PCP-1 ▼
2"					PCP-2 ▼
Unflanged Roller Sets					
(3 piece set)					
1"					PCP-1S ▼
2"					PCP-2S ▼
Flanged Drive Roller					
1"					PCP-1D 1 1
Fits 3/8" shaft - 1 ea.					PCP-2D 1 1
Flanged Roller Assembly					
1"					PCP-1F 2
2"					PCP-2F 2
3/8" x 16 thread - 1 ea.					
Unflanged Roller Assembly					
1"					PCP-1-1EA 2
2"					PCP-2-EA 2
3/8" x 16 thread - 1 ea.					
Bearing - 1 ea.					PCP-BRG
Replacement Switch					PCP-SWITCH-72
Replacement 110V, 60Hz Motor (round housing)					PCP-MOTOR-RS
Retrofit Motor Adaptor (round to square housing)					PCP-RFK
Retrofit Motor Adaptor (square to round housing)					PCP-RFK2
Replacement Motor Brush Set (1 Pair)					PCP-BRUSH-72

Crankshaft Polishing Belts



10 Belts
Per Box

240, 320 & 400 Grit Standard Polishing Belts

- US CAMI Grade aluminum-oxide abrasive
- 2-layer glue bond • Fast break-in
- Use with Polishing Rouge (CPR-16) for better finish
- Highly flexible J-Weight cloth backing
- Less aggressive belts for polishing

STANDARD STRAIGHT-EDGE (10 per box)				
Lgth	Width	240 grit	320 grit	400 grit
60"	¾"	60x34x240	60x34x320	60x34x400
	1"	60x1x240	60x1x320	60x1x400
	1¼"		60x1¼x320	
64"	¾"	64x34x240	64x34x320	64x34x400
	1"	64x1x240	64x1x320	64x1x400
	1¼"		64x1¼x320	
	1½"	64x1½x240	64x1½x320	
70"	1¾"		64x1¾x320	
	2"	64x2x240	64x2x320	64x2x400
	¾"		70x34x320	
	1"	70x1x240	70x1x320	70x1x400
72"	1¼"			70x1¼x400
	1½"			70x1½x400
	1¾"			
	2"	72x2x240	72x2x320	72x2x400
77"	¾"	72x34x240	72x34x320	72x34x400
	1"	72x1x240	72x1x320	72x1x400
	1¼"	72x1¼x240	72x1¼x320	
	1½"	72x1½x240	72x1½x320	72x1½x400
	1¾"	72x1¾x240		
77"	2"			
	¾"		77x34x320	77x34x400
	1"	77x1x240	77x1x320	77x1x400
	1½"		77x1½x320	
77"	1¾"			77x1¾x400
	2"	77x2x240	77x2x320	

All abrasives are guaranteed for 1 year from the original purchase date

Need a size not listed in the chart?

We can do that!

Goodson division, Abrasive Industrial Supplies, makes abrasive belts to order. Whether you're looking for other sizes of polishing belts or you need something to fit a grinder in your shop, they're available. Check out www.AbrasiveIndustrialSupplies.com or ask your customer service representative for more information.

Standard Scalloped Edge Crankshaft Polishing Belts

- 10 per box • 320 grit • 1" wide
- Ideal for radius polishing
- Double layer urea glue bond CAMI grade polishing belts

Length	Order No.
64"	S64x1x320
72"	S72x1x320



Fine Finish

- Gold Aluminum-oxide • Flexible, woven blue backing • **Very** aggressive
- Phenolic Resin-Over-Resin bond
- Sharper grains cut faster without sacrificing finish • Use with Grind Aid (GRA-10) or Polishing Rouge (CPR-16) for cooler polishing or grinding



Custom
Belt Sizes Available

Fine Finish (10 per box)

Length	Width	320 grit	400 grit
60"	1"	G-60x1x320	G-60x1x400
64"	1"	G-64x1x320	G-64x1x400
72"	1"	G-72x1x320	G-72x1x400
77"	1"	G-77x1x320	G-77x1x400

Scotch-Brite Style Micro Finish

- Rigid, 3-dimensional back • Resin bond • Aluminum-oxide abrasive • Non-directional Satin finish
- Use with Grind Aid (GRA-10)

Micro-Finish (1 per box)

Length	Width	Order No.
60"	¾"	GFB-60 x 3/4
	1"	GFB-60 x 1
64"	¾"	GFB-64 x 3/4
	1"	GFB-64 x 1
70"	¾"	GFB-70 x 3/4
	1"	GFB-70 x 1
72"	¾"	GFB-72 x 3/4
	1"	GFB-72 x 1
77"	1"	GFB-77 x 1
91"	1"	GFB-91 x 1




Scotch-Brite Style Super-Micro Finish

- Produces a mirror-like non-directional finish
- Resin bond • Silicon-Carbide abrasive
- For final Satin finish • Use with Grind Aid (GRA-10)

Super-Micro Finish (1 per box)

Length	Width	Order No.
60"	¾"	SGFB-60 x 3/4
	1"	SGFB-60 x 1
64"	¾"	SGFB-64 x 3/4
	1"	SGFB-64 x 1
70"	¾"	SGFB-70 x 3/4
	1"	SGFB-70 x 1
72"	¾"	SGFB-72 x 3/4
	1"	SGFB-72 x 1
77"	¾"	SGFB-77 x 3/4
	1"	SGFB-77 x 1



800 Grit Abrasive Cork Super-Fine Finish

- Won't disturb polished radii
- Silicon-carbide • Use with Polishing Rouge (CPR-16) for High Luster finish

Abrasive Cork (1 per box)

Length	Width	Order No.
64"	¾"	CPB-64-3/4
	1"	CPB-64-1
70"	¾"	CPB-70-3/4
	1"	CPB-70-1
72"	¾"	CPB-72-3/4
	1"	CPB-72-1
77"	¾"	CPB-77-3/4
	1"	CPB-77-1



Need A Size You Don't See? Give Us A Call; We Make Most Belts In-House!

Secure Online Ordering at www.goodson.com

109

CYLINDER HEAD
REBUILDING

ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS



Watch the Tech Lab Tuesday video in which we explain why we offer so many crank polishing belts. Scan the code below with your smart phone or other smart device for instant access to the video.



240 to 600 Grit Premium Ruby Aluminum-Oxide Crankshaft Polishing Belts

- Ruby Aluminum-Oxide abrasive specifically for use on metal
- Closed coat J-weight cloth backing with high strength joint
- Phenolic resin-over-resin bond
- Polish better and outlast other standard polishing belts
- Color may vary due to manufacturing process

STRAIGHT-EDGE (10 per box)					
L	W	240 Grit	320 Grit	400 Grit	600 Grit
60"	¾"	R60x3/4x240	R60x3/4x320	R60x3/4x400	R60x3/4x600
	1"	R60x1x240	R60x1x320	R60x1x400	R60x1x600
	2"			R60x2x400	
64"	¾"	R64x3/4x240	R64x3/4x320	R64x3/4x400	R64x3/4x600
	1"	R64x1x240	R64x1x320	R64x1x400	R64x1x600
	1¼"		R64x11/4x320	R64x11/4x400	R64x11/4x600
	1½"	R64x11/2x240		R64x11/2x400	R64x11/2x600
	1¾"	R64x13/4x240	R64x13/4x320		
72"	2"	R64x2x240	R64x2x320	R64x2x400	R64x2x600
	¾"	R72x3/4x240	R72x3/4x320	R72x3/4x400	R72x3/4x600
	1"	R72x1x240	R72x1x320	R72x1x400	R72x1x600
	1¼"	R72x11/4x240	R72x11/4x320	R72x11/4x400	R72x11/4x600
	1½"		R72x11/2x320	R72x11/2x400	R72x11/2x600
77"	1¾"	R72x13/4x240	R72x13/4x320	R72x13/4x400	R72x13/4x600
	2"	R72x2x240	R72x2x320	R72x2x400	R72x2x600
	1"		R77x1x320	R77x1x400	R77x1x600
	1¼"			R77x11/4x400	
	1½"			R77x11/2x400	
	2"		R77x2x320	R77x2x400	R77x2x600

All abrasives are guaranteed for 1 year from the original purchase date

Need a size not listed in the chart? We can do that!

Goodson division, Abrasive Industrial Supplies, makes abrasive belts to order. Whether you're looking for other sizes of polishing belts or you need something to fit a grinder in your shop, they're available. Check out www.AbrasiveIndustrialSupplies.com or ask your customer service representative for more information.



3M™ Trizact™ Crankshaft Polishing Belts

- X-Weight cloth belt • A45 micron – equivalent to 400 grit
- Structured abrasive grains are perfectly shaped pyramids bonded at equal spacing to a high-strength polyester backing • Uniform wear for better performance and long life • Produce a high-luster finish • 5 per box

Size	Order No.
64"L x 1"W	GSA-64x1
72"L x 1"W	GSA-72x1

Blue 800 Grit Crankshaft Polishing Belts With Scrum Back

- Film substrate with aluminum-oxide abrasive
- 10 belts per box
- High quality joint with scrum back
- Highly flexible and long lasting



Size	Order No.
60" x ¾"	BF-60X3/4X800
60" x 1"	BF-60X1X800
64" x ¾"	BF-64X3/4X800
64" x 1"	BF-64X1X800
72" x ¾"	BF-72X3/4X800
72" x 1"	BF-72X1X800
77" x 1"	BF-77X1X800

Micro Finish Scotch-Brite Style Abrasive Rolls



- Ideal for hand polishing of high-performance crankshafts
- Non-directional polish
- Won't remove material
- Aluminum oxide abrasive
- Measures: ¾" x 10' • 1 Per Box
- Order No. **GFR-750**

Premium Ceramic Micro Polishing Belts



- Use with Polishing rouge to achieve high luster finish
- Structured Abrasive • 5 per box

Size (LxW)	Order No.
60" x 1"	GSW-60x1
64" x 1"	GSW-64x1
72" x 1"	GSW-72x1
77" x 1"	GSW-77x1
Polishing Rouge	CPR-16



Crankshaft Polishing Belt Sample Pack

These sample packs include our most popular belts. Contents may vary.

Long	Wide	Qty.	Order No.
64"	1"	5	PCP-64PAK
72"	1"	5	PCP-72PAK
72"	2"	2	PCP-72PAK-2

... another
satisfied
customer



"Goodson was able to help me select the right grinding stones for our racing clutch and flywheel program. Their support and technical advice is always available to keep our program on the right track."


- Johnny Ahten, Johnny Ahten Racing - Goodson customers since 2005

Flywheel Radius Cutter Tip Holder

- For Winona Van Norman/
Van Norman FG-5000
- Holder measures 1.5"L with a
.312" dia. shank
- Includes 1 indexable FG-3B cutter tip


Description	Order No.
Tip Holder	FG-5011
Replacement Tip	FG-3B

FG-3B



Flywheel Cutter Tip For Winona Van Norman 570 Rotary Broach

- 3-edge carbide cutting tip for use with the special
flywheel attachment
- Order VN-FW



Flywheel Grinding Coolant

- Formula eliminates
rancid coolant
- Synthetic inhibitors
- Dilute 30:1 (water:coolant)


Size	Order No.
1 Gal. / 3.78L	FG-1101-G
5 Gal. / 18.8L	FG-1102-G



Flywheel Depth Gauge with Dial Indicator

- Measure flywheel before
and after grinding to maintain
proper depth specifications
- Gauge Assembly includes
Dial Indicator, Bar & Magnets
- Spindle Extensions sold
separately

Description	Order No.
Gauge Assembly	FGG-12
Spindle 1.5"	DIS-1.5
Extensions 2.5"	DIS-2.5
3.0"	DIS-3.0



Magnetic feet adjust to
flywheel diameter

Flywheel Grinder Bolt Adaptors

- Replace shoulder bolts with standard hardware
- Low-cost adaptor converts any 1/2" or 3/16" bolt to a 3/4" ID
- Includes countersunk adaptor with bolts for extra clearance



FG-LOCK

Fits	Size	Order No.
DCM, Peterson, KW	1/2" x 13	FG-DCP-KIT
WVN	7/16" x 14	FG-AB-KIT
WVN Table Insert	OD: 5/8" x 11, ID: 7/16" x 14	FG-LOCK

Flywheel Grinder Table Lubricant

- Extend flywheel grinder life
- High pressure oil designed to
lubricate table bearings and ways
- For all makes of flywheel grinders
- 1 Gal. (3.78L)
- Order No. FG-1131-G



FG-1165-G



FG-1070A-G




FG-1045-G



GS-17



GS-00



GS-0

Grinding Wheel Dressers & Replacement Cutters

Diamond Dresser Tools are available on pages 114-115

Cutter Assemblies				Replacement Cutters					
Applications	OD	W	Order No.	Pieces	Washers	OD	ID	Thick	Order No.
Peterson (12mm shaft)				8 Stars	3	2.375"	1.50"	.093"	GS-17
					1 w/locking tangs	1.75"	1.50"	.060"	
WVN SM2000, 4000, 5000, 6000C, 6000A, MG3000, 3850	1.250"	.978"	FG-1165-G	7 Stars	none	1.25"	0.313"	.095"	FG-1161-G
Peterson & DCM	2.375"	2.262"	FG-1070A-G	5 Stars		2.375"	1.132"	.1375"	FG-1070-G
Hand Held			FG-1045-G	1 Stone	none	1.50"	0.313"	.6250"	FG-1044-G
Desmond Dresser for wheels up to 10"			GS-0	4 Blades, 2 Spacers			0.250"		GS-00
				4 Blades, 2 Spacers			0.500"		GS-11

Flywheel Grinding Stones

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

For Best Results... Choose The Right Flywheel Stone From Goodson

Goodson stones feature 50% more usable abrasive and much stronger construction, yet sell at prices comparable to ordinary stones. With Goodson stones you'll get longer wheel life and lower-cost flywheel grinding.

Cast Iron:

Cast Iron (soft) flywheels need to be ground with harder stones. Experiment to find the best stone. A starting point is the FGW-57, our best all-around stone for Cast Iron.

Cast Steel:

Cast Steel (medium) flywheels require medium-hard stones. The FGW-65 is our best all-around stone for Cast Steel.


Billet Steel:

Billet Steel (very hard) flywheels need to be ground with softer stones. Our best all-around stone for Billet Steel is the FGW-50-2. It's our most friable and free-cutting, requiring minimal dressing.

video available Goodson carries a wide selection of flywheel grinding stones. Watch as we unpack the reasons why in our **Tech Lab Tuesday** video "Choosing the Right Flywheel Stone." Scan the code at right with your smart phone or other smart device for instant access.



Coolant on pages 74 and 110



tech tips from the techxperts™ Be sure to use ample coolant to flush away swarf and help the stones perform better.

Silicon-Carbide Abrasive

CAST IRON (Passenger cars, light trucks)

A	B	C	Arbor	Description	Order No.
6"	4½"	2⅝"	1¼"	Harder than FGW-57, lasts longer, black	FGW-67
6"	4½"	2⅝"	1¼"	Best all-around for cast iron, black	FGW-57
6"	—	2½"	1¼"	Straight-sided FGW-57, black	FGW-57S
6"	4½"	2⅝"	1¼"	Softer than FGW-57, grinds faster, black	FGW-47
6"	4¾"	2⅞"	1¼"	Silicon-carbide, ideal for top fuel, black	FGW-37
6"	4¾"	2⅞"	1¼"	Silicon-carbide, softer, finer grit than FGW-37	FGW-37F
4"	3"	2"	1¼"	Small diameter FGW-57, black	FGW-61
4"	3"	2"	1¼"	Small diameter FGW-37, black	FGW-374
3"	—	2"	1¼"	Straight-sided green silicon-carbide, premium	FGW-93

Silicon-Carbide/Aluminum-Oxide Combination

CAST STEEL (Industrial, agricultural, OTR trucks)

A	B	C	Arbor	Description	Order No.
6"	4½"	2"	1¼"	Harder than FGW-65 lasts longer, lt. gray	FGW-53
6"	4½"	2⅝"	1¼"	Best all-around for Cast Steel, speckled	FGW-65
6"	4½"	2⅝"	1¼"	Slightly softer than FGW-65, black	FGW-495
4"	3"	2"	1¼"	Small diameter FGW-65, speckled	FGW-69
6"	4½"	2⅝"	1¼"	Softer than FGW-65, grinds faster, black	FGW-49

Aluminum-Oxide Abrasive

BILLET STEEL (Import vehicles, high-performance)

A	B	C	Arbor	Description	Order No.
6"	4½"	2⅝"	1¼"	Harder, ruby stone, lasts longer	FGW-64
6"	4½"	2⅝"	1¼"	Harder, pink stone, lasts longer	FGW-62-1
6"	4½"	2½"	1¼"	Harder than FGW-50-2	FGW-50
6"	4½"	2½"	1¼"	Best all-around for Billet Steel	FGW-50-2
4"	3½"	1½"	1¼"	Harder, pink stone, lasts longer	FGW-63-1
4"	3"	2"	1¼"	Taller than FGW-56, more abrasive, white	FGW-306
4"	3½"	1½"	1¼"	Premium	FGW-56P
4"	3½"	1½"	1¼"	Small diameter, off white	FGW-56
3"	2¼"	1¼"	¾"	Small diameter, light gray	FGW-59
3"	—	2"	1¼"	Straight-sided sugar white stone	FGW-92

NOTE: Due to manufacturing process, colors may vary.

All abrasives are guaranteed for 1 year from original purchase date.

Mounting Adaptor For Small Diameter Stones



- Many flywheel grinders have lower mounting flanges that won't fit inside 3" and 4" diameter flared-cup stones
- Use this adaptor to avoid damage when mounting small stones
- Fits most small diameter stones
- Order No. **FG-FLANGE**

tech tips

from the techxperts™

Use a 3/8" Cap Screw & Washer to mount 2" & 3" Diameter CBN Flywheel Grinding Wheels to Your Flywheel Grinder



FlyMaster® CBN Super Abrasive Flywheel Grinding Wheels

• For cast iron • Light to heavy applications


A	B	C	Arbor	Shape	Grit	Order No.
2"	2"	0.4"	3/8"	Straight	100	CBN-200
3"	3"	0.4"	3/8"	Straight	100	CBN-300
2"	1 1/8"	7/8"	3/8"	Cup	100	2H0998
3"	2"	1 1/4"	1 1/4"	Cup	100	261453
3 3/4"	2 5/8"	1 1/2"	1 1/4"	Cup	100	2371052
3 3/4"	2 5/8"	1 1/2"	1 1/4"	Cup	60	34296362
5"	3 3/4"	1 3/4"	1 1/4"	Cup	100	2379270
6"	4 5/8"	1 7/8"	1 1/4"	Cup	100	2367275*
6"	4 5/8"	1 7/8"	1 1/4"	Cup	60	2G7480
CBN Dressing Stick 1/2" x 1/2" x 6"						DS-CBN

*Most popular application

tech tips

from the techxperts™

How to Measure A Flywheel Stone



tech tips

from the techxperts™

Never dress your Superabrasive with the dresser attachment on your machine. Use our CBN dressing stick for best results.

Flywheel Grinding Stones

• Four Abrasive formulas to choose from

SILICON-CARBIDE ABRASIVE

Ductile Iron, Cast Iron & Steel (Black)

A	B	C	Arbor	Hardness	Shape	Order No.
3"	2 1/2"	1 1/2"	1 1/4"	Med. Hard	Flared	U364512
4"	3"	2"	1 1/4"	Med. Soft	Flared	U335369
6"	4 1/2"	2 1/2"	1 1/4"	Med. Soft	Flared	U324495
6"	4 1/2"	2 1/2"	1 1/4"	Med. Hard	Flared	U335376
6"	4 1/2"	2 1/2"	1 1/4"	Hard	Flared	U335377
6"	4 1/2"	2 1/2"	1 1/4"	Med. Soft	Flared	U357854
6"	4 1/2"	2 1/2"	1 1/4"	Med. Hard	Flared	U343805

EXTENDED LIFE CERAMIC

Ductile Iron, Cast Iron & Steel (Black)

A	B	C	Arbor	Hardness	Shape	Order No.
6"	4 1/2"	3"	1 1/4"	Med. Hard	Flared	U370095

ALUMINUM-OXIDE ABRASIVE

Mild Steel & Hardened Steel (White)

A	B	C	Arbor	Hardness	Shape	Order No.
6"	4 1/2"	2 1/2"	1 1/4"	Soft	Flared	F342636

ALUMINUM-OXIDE ABRASIVE

Light to Medium Stock Removal on Steel, Cast Iron & Ductile Iron (Ruby)

A	B	C	Arbor	Hardness	Shape	Order No.
4"	3"	2"	1 1/4"	Medium	Flared	F348769
6"	4 1/2"	2 1/2"	1 1/4"	Soft	Flared	F372039
6"	4 1/2"	2 1/2"	1 1/4"	Med. Soft	Flared	F348771
6"	4 1/2"	2 1/2"	1 1/4"	Medium	Flared	F348772
6"	4 1/2"	2 1/2"	1 1/4"	Hard	Flared	F348773

Colors may vary due to the manufacturing process

Diamond Flywheel Grinding Wheel

• For hard, spray coated floaters and flywheels
• Not for use on cast iron or steel flywheels
• A = 6" | B = 4 5/8" | C = 1 7/8" | Arbor = 1 1/4"
• Order No. 2E5742



3/4" Thick Wall
for Faster, More
Aggressive
Grinding



Big Brute™ Flywheel Grinding Stone

• Medium-Hard Silicon Carbide abrasive formula • Extra beefy for better grinding
• Measurements: A = 6" | B = 4 3/4" | C = 3" | Arbor = 1 1/4" (see graphic above)
• Order No. U69693

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Diamond Dresser Tools

shown at approximately full size

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS




Diamond: Selected for very high point definition. A sharper diamond cuts faster and gives a superior finish.

Matrix: Matrix material is bronze or copper-based for a tight hold on the diamond & high heat transfer.

Holder: Cold rolled steel. Threaded types have precision threads over a long distance to screw easily into tool holders and support cutting point firmly to prevent vibration.

Diamonds are stamped for easy identification and re-ordering



Premium Diamond Resetting Service:

Send your worn premium diamonds to Goodson for fast resetting. Prices quoted upon request. Reset when wear facets exceed $\frac{1}{16}$ " on a $\frac{1}{2}$ to $\frac{3}{4}$ carat diamond and $\frac{1}{8}$ " on a 1 carat or larger.

Diamond Dresser Tools



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Diamond Dressers for most shop machines are in stock and ready-to-ship

A diamond tool is only as good as the diamond itself. GOODSON diamonds are furnished by the most respected supplier in the U.S. Each is subjected to a microscopic examination by experts and must meet strict standards to be accepted. This rigorous inspection and careful control during manufacturing assures consistent high quality. Our diamond tools deliver the highest levels of performance and longevity.

In addition to our standard diamond tools, GOODSON stocks a wide selection of Premium Quality Diamonds. These diamonds last longer and improve wheel performance. They stay sharp longer and have more points so they can be reset more times. Because of this quality, they will dress harder wheels and wheels will need to be dressed less frequently. If you don't see the diamond you need in a premium quality, call 1-800-533-8010 for a special order.

	Machine	Description	Carat	Standard	Premium
Valve Refacers	B&D, Skil, SiouxTM, Thor, VanDorn, WVN	3/8" x 1 7/8"	1/5	G-1	G-1P
	Kwik-Way, Tobin Arp (S&D)	5/16" x 2 1/2"	1/5	G-3	—
	Kwik-Way, Valve Master (1714)	1/2" x 3 3/4" 20NF	1/5	G-4	—
	SiouxTM (1713, 1715), IDL, WVN (CG50, CG80)	3/8" x 2 3/4" 24NF	1/5	G-5	G-5P
	IDL, WVN (CG50, CG80)	3/8" x 3 3/4" 24NF	1/5	G-80	—
	US	7/16" x 2"	1/5	G-6	—
	Skil (Talent)	5/16" x 2 1/4" 18NC	1/5	G-9	—
Valve Seat Grinders	Kwik-Way	7/16" x 2 3/4" 20NF	1/5	G-17	G-17P
	B&D, S&D, Van Dorn	3/8" x 2 1/4" 24NF	1/5	G-2	—
	Kwik-Way	1/2" x 3 3/4" 20NF	1/5	G-4	—
	SiouxTM (1715), K-W (NSG), Thor	3/8" x 2 3/4" 24NF	1/5	G-5	G-5P
	Hall HD (13-1938P), Skil, Snap-On, B&D	5/16" x 2 1/4" 24NF	1/5	G-8	G-8P
	KO Lee, Skil	5/16" x 2 1/4" 18NC	1/5	G-9	—
	SiouxTM Heavy Duty (1715B, 1719)	3/8" hex RH thread	1/5	G-11	—
	Goodson Universal Wheel Dresser	8mm x 1.25mm	1/5	—	G-13P
	SiouxTM Heavy Duty (1715A)	3/8" x 2 3/4" 24NF	1/2	G-15	—
	Kwik-Way Heavy Duty Wheel Dresser	1 1/2" x 3" 20NF	1/5	G-18	G-18P
Clutch Grinders	Lempco AC, NAC, VAC & Do-ALL	7/16" x 2"	1/5	G-6	—
Piston Grinders	Van Norman 75, 76 & Relio	3/8" x 1 5/8"	1/5	G-1	G-1P
	Storm-Vulcan D-3	7/16" x 2"	1/5	G-6	—
Drum Lathes	Van Norman (all except 302, 302H)	3/8" x 1 5/8"	1/5	G-1	G-1P
	Barret, V.N. 302, 302H	3/8" x 3"	1/5	G-1L	—
	Lempco	7/16" x 2"	1/5	G-6	—
	Ammco 5000	1 1/2" x 1 1/2"	1/5	G-19	—
Rod Grinders	Sunnen® Rod & Cap Grinder (CRG-500)	3/8" x 1 5/8"	1/5	G-1	G-1P
	Storm-Vulcan No. 65 Rod Grinder	1/2" x 3 3/4" 20NF	1/5	G-4	—
Crank & Cam Grinders	Storm-Vulcan 14, 15, 15A, 15C, 75, 75A	1 1/2" x 3"	3/4	G-25	—
		1 1/2" x 3"	1	G-25A	—
	Scledum	10mm x 1 5/8"	3/4	G-27	—
	Winona Van Norman/Zanrosso,	7/16" x 1 1/4", 5/8" head	3/4	G-30	—
	Lempco, Landis	7/16" x 1 1/4", 5/8" head	1	G-30A	—
	Berco	tapered, step type	1	G-32A	G-32AP
	Berco	tapered, step type	1 1/2	G-32B	—
	Storm-Vulcan, WVN CG210, 250, 280	1 1/2" x 2" 70° radius dress	3/4	G-33	—
Flywheel Grinder	Kwik-Way 796	7/16" x 2"	1/5	G-6	—

tech tips

from the techxperts™

- 1. Set tool at a proper angle.** Position at 10° to 15° from surface. Smaller angles blunt the diamond. Larger angles may cause the wheel to remove matrix material.
- 2. Prevent vibration in the holder.** Any looseness in the tool holder will allow vibration of the tool resulting in poor finish on the wheel.

3. Turn coolant on before dressing. Wheels used wet should be dressed wet. To keep diamond cool, turn coolant on before starting to dress. (If wheel is dressed dry, air-cool diamond between cuts but don't quench with water.)

4. Start at highest point. Wheels often wear unevenly & may have high & low spots. Set tool to dress high spots first, feed in about .001" per pass until done. This prevents overheating & damage.

5. Use steady travel. Uneven travel causes an uneven finish. The best rate is found by experiment, but whatever the rate of travel, it must be even.

6. Turn the tool in the holder. Turn the tool often to expose new diamond surface to the wheel.

7. Don't bump or drop diamond. They are hard but brittle, and can be harmed if dropped or bumped.

CAUTION: Grinding Wheel must never touch the matrix or holder.

Crankshaft & Flywheel Tools

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Petroleum Based Valve Lapping Compound

- Silicon-carbide, grease-based compound
- Petroleum based valve lapping compound facilitates precise mating between valve seats and valves
- Use with any powered or manual valve lapping tools
- The higher the number, the finer the grit



Size	Grit	Order No.
2 oz. / 56.7g	400 Grit	VLC-2-400
	600 Grit	VLC-2-600
	800 Grit	VLC-2-800
	1200 Grit	VLC-2-1200

More lapping compounds on page 17

tech tips

from the techxperts™

Put a dab of valve lapping compound on a dwell pin that just won't come out, then use your puller to extract it. The grit in the lapping compound gives you more grip so you can successfully pull stubborn dowels.

Pin Pal Puller

- Remove dowels fast
- Adjusts to pull all sizes of dowels
- Locking pliers with special hardened jaws hold firm while 4 lb. slide hammer forces dowels out
- Also pulls pressed-in hollow tubes or frozen shafts
- Rugged steel construction

Description	Order No.
Complete Tool	GA-300
Replacement Jaws	GA-300E-R



Mirrored Safety Glasses

- Wrap-around design
- Tinted lenses provide sun glare protection
- Universal bridge
- Polycarbonate lenses
- Do not use as welders helpers
- Order No. **PGL-21**

Heavy Metal

An essential component when balancing rods & pistons to crankshafts to ensure proper engine operation. Contains 90% Tungsten



HEAVY METAL - TUNGSTEN 90%

Hole	Press Fit	1.0" Long	1.2" Long
in	+ in/mm	Grams	Order No.
1/2"	.002"/.05	57	HM-57
3/4"	.002"/.05	122	HM-122
7/8"	.002"/.05	169	HM-169
1"	.002"/.05	227	HM-227

NOTE: Due to market fluctuations, heavy metal prices are subject to change without notice. Please confirm pricing when ordering.

tech tips

from the techxperts™

It is essential, when pulling a dowel, that the tightening sleeve is installed with the flared end toward the collet. This will allow the tightening sleeve to slide over the collet, locking it to the dowel you are removing. Also, be sure to select the correct collet size for the dowel you are removing.



video available

Scan the code below on your smart phone or other smart device to watch our How-To video on Dowel Pulling.




Dowel Puller and Collets

- Slide hammer action removes stubborn dowels
- Use on blocks, heads, flywheels, etc.
- Split collets grip firmly without causing damage
- A high-quality tool that lets you reuse dowel pins
- Choose from SAE or Metric kits
- All items also sold separately

Description	Order No.	Incl.
Standard Kit	GA-600	▼
Metric Kit	GA-600M	▼
Slide Shaft (14" L)	GAO-1	x x
Slide Hammer	GAO-2	x x
Tightening Sleeve	GAO-3	x x
Gripping Collets		
OD ID mm		
1" .1575" 4.00	GAO-22	x
1" .1875" 4.76	GAO-4	
1" .1969" 5.00	GAO-13	x
1" .2362" 6.00	GAO-14	x
1" .2500" 6.35	GAO-5	x
1" .2756" 7.00	GAO-26	
1" .3125" 7.94	GAO-6	x
1" .3150" 8.00	GAO-10	x
1" .3750" 9.53	GAO-7	x
1" .3937" 10.00	GAO-23	
1" .4375" 11.11	GAO-8	x
1" .4724" 12.00	GAO-24	
1" .5000" 12.70	GAO-9	
1" .6250" 15.88	GAO-20	
Removal Basin	GAO-21	x x

Parts are stamped for easy identification & reordering



14mm Spark Plug Thread Chaser/Burnisher

- Ideal for spark plug hole cleaning
- Re-forms the original material by burnishing, not cutting, and won't create new chips to clean out
- Order No. **SPB-14**

Burr Buster

- Use on air float tables, seat & guide machines, beds of crankshaft grinders and flywheel grinder tables
- Deburrs gasket surfaces on heads, blocks, manifolds, etc.
- 120 grit premium grade abrasive
- 1½" x 2½" x 9"
- Order No. **BB-9**

Premium Tapered Reamer

- Use by hand or with a powered driver to deburr or enlarge tapered holes for valve guides, bolt hole chamfering, and more • Degree of Taper: 2.86°
- Use in ½" chuck at approx. 40 RPM
- OAL: 5¾" • Flute Length: 3¾"
- Small End: ⅞" dia.
- Large End: ½" dia.
- Order No. **TR-216-1**

Maxxeon® WorkStar® 364 USB Rechargeable UV Leak Detection Pen/Inspection Light

- 3.7V Lithium battery with USB charger
- Run time: 35 min. continuous, 2 hr. intermittent operation
- Use with Goodson Glow or Magnetic Crack Detection Oil (page 53) • Dust-tight, waterproof to 3 feet
- Easily adjustable beam to suit application
- Drop tested to 6 feet
- Order No. **DFL-364**

Maxxeon® WorkStar® 360 Rechargeable LED Pen/Inspection Light

- No batteries to replace! Includes Micro USB charger
- 3X zoom provides 160 lumens on low
- 1X zoom provides 260 lumens on high
- 40 minute continuous or 2-hour intermittent operation
- Dust-tight, waterproof to 3 feet
- Drop tested to 6 feet
- Order No. **DFL-360**

Maxxeon® WorkStar® 810 CYCLOPS Rechargeable LED Work Light

- Puts the light right where you need it • Drop tested to 6 feet
- LiPo battery with USB charger
- 3 light settings
- Magnetic base attaches the light to your machine
- Water resistant, do not immerse
- Order No. **DFL-810**

Bench Grinder Wheels

- 40 and 60 grit for general grinding
- 100 grit for sharpening carbide tools
- Includes bushings to reduce arbor hole from ¾" to ½"
- PLUS a ⅝" bushing adaptor

Size	Grit	Order No.
General Purpose Wheels: For steel and cast iron		
6" x ¾"	60	GG-666
6" x 1"	60	GG-686
8" x 1"	60	GG-886
Green Grit Wheels: For sharpening carbide tools		
6" x ¾"	100	GGC-661
6" x 1"	100	GGC-681

Grinding Wheel Star Dressers

Description	Order No.
Desmond Hand Dresser for Wheels to 10" Dia.	GS-0
Replacement Cutter Sets	
4 Blades, 2 Spacers, 1¼" ID for GS-0 dresser	GS-00
4 Blades, 2 Spacers, 1½" ID for GS-1 dresser	GS-11

Deburring Wheels for Bench Grinders

- Medium-hard wheels are better suited for heat sensitive materials
- Use to clean and polish white metal
- Buff and Blend Wheels deliver the same results as a wire brush but are much safer to work with

Description	Size	Qty.	Order No.
Medium-Hard Deburring Wheel	6" x 1" x 1"	1	SCW-68M
Buff and Blend Wheels	6" x 1½" x 1"	5	BBD-65

... another
satisfied
customer

"Goodson is the most hassle-free vendor that I deal with. Everything I have ordered has always been in stock."

- Jerry Darien, Darien Racing, Goodson customer since 2012

CYLINDER HEAD
REBUILDING



Tip Holder for Drums

Fits Ammco 1000, 2002, 3000, 4000, 4100, 7500 & 7700; All Tool 747; Hoffman 660; Performance 6600, 7200, 7100 & 7600

Dimensions: 1/2" x 3/8" x 2 1/4"

Replaces OE No. 9872

Orientation: Right

Use Tips: RT-A Series (includes 1)

Order No. **TAM-41R**

CLEANING,
ASSEMBLY & SAFETY



Tip Holder for Rotors

Fits Ammco 3000, 3850, 4000, 4100, 7000 & 6900, 6950 Twin Cutters; All Tool 747; Performance 6600, 7200, 7100, 7600; Hoffman 660

Dimensions: 3/8" x 3/8" x 1 7/8"

Replaces OE No. 10701, 10702

Use Tips: RT-A Series (includes 1)

Left: Order No. **TAM-702**

Right: Order No. **TAM-701**

SHORT BLOCK
REBUILDING



Tip Holder for Rotors

Fits Ammco 3000, 3850, 4000, 4100, 7000 & 6900, 6950 Twin Cutters

Dimensions: 3/8" x 3/8" x 1 7/8"

Replaces OE No. 25968, 25969

Use Tips: RT-3A or RT-3AS (includes 1)

Left: Order No. **TAM-25969**

Right: Order No. **TAM-25968**

CRANKSHAFT/
FLYWHEEL GRINDING



Tip Holder for Drums & Rotors

Fits Kwik-Way CBL, NCL, SDL;
Snap-On Y282, Y277, Y278, 180

Dimensions: 3/8" x 3/8" x 2 1/2"


Replaces OE No. 109-1091-02,
109-1091-00

Use Tips: RT-KW Series (includes 1)

Left: Order No. **TKW-85L**

Right: Order No. **TKW-84R**

MISCELLANEOUS
TOOLS & SUPPLIES



Brazed Carbide Brake Lathe Tools

• Fit most popular brake drum lathes

Left Hand Cutting Tools

Size	Application	Order No.
3/8" sq. x 2 1/2"	Replaces Bean 43-46L; Bear 23211; Star CB-8; VN 302-7272 for 303, 304, 304H	L-1
3/8" sq. x 4"	Replaces Ammco 5725, for 5000; Star CB-30; VN "Big Brute" for 310-404 Hardspots	L-1A
3/8" sq. x 3 1/2"	Extra long L-1 for small dia. drums	L-1L
3/8" sq. x 2 1/2"	Master carbide-tipped with 7° rake angle	L-1S

Right Hand Cutting Tools

Size	Application	Order No.
3/8" sq. x 2 1/2"	Replaces Bean 43-46R; Bear 20718; Star LB-16; VN 302-7171 for 204, 300, 302, 302H, 333, 243XV; and Barrett & Lempco	R-1
3/8" sq. x 2 1/2"	Master carbide-tipped with 7° rake angle	R-1S
3/8" sq. x 4"	Replaces Bear 24034, Star CB-35	R-4

Hardspot Cutters

Left Hand		
Size	Use	Order No.
3/8" x 1/2" x 2 3/8"	Drums	L-5
Right Hand		
Size	Use	Order No.
3/8" x 1/2" x 2 3/8"	Drums	R-5



L-5 R-5

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Don't buy a new
brake lathe ...
expand your existing
one to handle rotors
up to 15"



Lead Screw Bushing

- Easy installation
- Increases lathe capacity to 15"
- Ideal for machining large rotors common on SUVs and large pick-ups
- Fits Ammco 3000 and 4000 Brake Lathes
- Order No. **LSB-78529**

Brake Shoe Grinding Sleeves

- Aluminum-Oxide abrasive



ID	Length	Grit	Order No.
3"	5 1/4"	40	AS-2
3"	6 3/4"	40	AS-4


Carbide Tipped Brake Drum Swedge Cutting Tool

- Hard-to-find tool cuts wheel stud swedges to remove and replace pressed-in wheel studs
- Use with a drill press or mill
- For 1/2" stud
- Order No. **ST-500**



Brake Lathe Replacement Tips

Tips Are Shown Actual Size



Buy 3 or More
10-Packs (mix & match), SAVE 10% off Jobber



Solid Carbide

These standard grade, solid carbide cutting tips are parallel ground for resurfacing cast iron drums and rotors.

Honed Edge Carbide

Parallel & peripheral ground. Deliver a better finish on cast iron and composite rotors.

Titanium

Premium grade titanium coated carbide. Parallel and peripheral ground for ultimate performance on cast iron & composite rotors.

10 Pack Brake Lathe Replacement Tips


Machine	Model(s)	OE No.	Edges	Rake	Screws	Order No.	Order No.	Order No.
Ammco	700, 710, OTC Lathes, 1000, 2002, 3000, 4000, 4100, 7000, 7500, 7700	6914	6	Neg	Yes	RT-A-10	RT-A-H-10	RT-A-T-10
	3850 smaller (1/4") radius	6918	3	Pos	Yes	RT-3AS-10	RT-3AS-H-10	RT-3AS-T-10
	larger (1/2") radius	7681	3	Pos	Yes	RT-3A-10	RT-3A-H-10	RT-3A-T-10
	6900, 6950 negative rake (std.)	6914	6	Neg	Yes	RT-A-10	RT-A-H-10	RT-A-T-10
Twin Cutters:	positive rake (standard) 1/4" (finer finish)	6918	3	Pos	Yes	RT-3AS-10	RT-3AS-H-10	RT-3AS-T-10
	positive rake (modified) 1/2" (more durable)	7681	3	Pos	Yes	RT-3A-10	RT-3A-H-10	RT-3A-T-10
	7900	6914	6	Neg	Yes	RT-A-10	RT-A-H-10	RT-A-T-10
Ammco HD	5000, 6000, 6002	5677	3	Pos	No	RT-373-10	—	—
Accu-Turn	All combination disc/drum lathes	433796	3	Pos	Yes	RT-AC-10	RT-AC-H-10	RT-AC-T-10
	On-The-Car Lathes	878051	6	Neg	Yes	RT-A-10	RT-A-H-10	RT-A-T-10
All-Tool	747	3331	6	Neg	Yes	RT-A-10	RT-A-H-10	RT-A-T-10
Bean	B-401, B-410, B-501, B-601	90487	3	Pos	Yes	RT-FMC-10	RT-FMC-H-10	RT-FMC-T-10
Bear	1410, 1466, 1467, 1468, 1469, 1478	2264, 72265, 772834	6	Neg	Yes	RT-B-10	—	—
	10-1430, 10-1435	W136	6	Neg	No	RT-HF-10	—	—
FMC	600, 601, 700, 701, RotoTruer	90487	3	Pos	Yes	RT-FMC-10	RT-FMC-H-10	RT-FMC-T-10
	505, On-The-Car Lathe	91212	3	Pos	Yes	RT-KW-10	RT-KW-H-10	RT-KW-T-10
Hoffman	660	3331	6	Neg	Yes	RT-A-10	RT-A-H-10	RT-A-T-10
Hunter	BL300 On-The-Car Lathe	221580-2	6	Neg	Yes	RT-A-10	RT-A-H-10	RT-A-T-10
	BL-500, BL-501, BL-505	6918	3	Pos	Yes	RT-3AS-10	RT-3AS-H-10	RT-3AS-T-10
	BL-500	221-678-3	3	Pos	Yes	RT-HNT-10	—	—
Kwik-Way	CBL, NCL, SDL Kwik-Lathe OTC Lathe	109-1092-23	3	Pos	Yes	RT-KW-10	RT-KW-H-10	RT-KW-T-10
	Lightening Lathe	109-1092-45	3	Pos	Yes	—	—	RT-KWL-T-10
Performance	6600, 7200, 7100, 7600	3331	6	Neg	Yes	RT-A-10	RT-A-H-10	RT-A-T-10
Pro-Cut	On-The-Car Lathe	50-701, 50-742	3	Pos	Yes	RT-VBG-10	RT-VBG-H-10	RT-VBG-T-10
RJ West	Perfect 400, 1115HD	W139	3	Pos	Yes	RT-AC-10	RT-AC-H-10	RT-AC-T-10
RTI	BRC35 On-The-Car Lathe	91212	3	Pos	Yes	RT-3A-10	RT-3A-H-10	RT-3A-T-10
Snap-On	YA282, YA277, YA278, YA180 OTC Lathe	109-1092-23	3	Pos	Yes	RT-KW-10	RT-KW-H-10	RT-KW-T-10
Van	204, 204D, 205, 205DC, 415, 243XV	29687	3	Pos	No	RT-VN-10	RT-VN-H-10	RT-VN-T-10
Norman and Rels	Smaller (1/4") radius		3	Pos	No	RT-VNS-10	—	—
	204, 304, 405	29005	6	Neg	No	RT-VNA-10	—	—
	303, 304, 305, 404, 405, V22	304-7167	2	Pos	No	RT-VNP-L-10	—	—
	204, 205, 205DR, 300, 302, 333, 243, 243XV	302-7167	2	Pos	No	RT-VNP-R-10	—	RT-VNP-RT-10
	Rels 2000 rotor	45016, 45021	3	Pos	Yes	RT-RL-10	—	—
VBG	On-The-Car Lathe	50-701	3	Pos	Yes	RT-VBG-10	RT-VBG-H-10	RT-VBG-T-10
Round Tips With Hole		RT-312, RT-312T	360°	Pos	Yes	RT-312	—	RT-312T
Round Solid Fits RJH and CT Holders		CT10	360°	Pos	No	RT-360-10	—	—

NOTE: The table above shows the original equipment cutting tips for Ammco machines. Most of them use negative-rake tool systems. However, some Ammco machines (especially the 4000 and 7000-series) have been modified in the field by using the TAM-25968 and TAM-25969 positive-rake tool holders (see next page).

If your machine is shown above to have 6-edge tips but has 3-edge tips, it has been modified – please order our RT-3A or RT-3AS series tips.

RT-A	RT-3A	RT-AC	RT-HNT	RT-VN	RT-B	RT-VNA
Height: .350"	Height: .343"	Height: .445"	Height: .312"	Height: .545"	Height: .343"	Height: .535"
Thick: .095"	Thick: .093"	Thick: .131"	Thick: .103"	Thick: .125"	Thick: .105"	Thick: .188"
Hole: .135"	Hole: .133"	Hole: .145"	Hole: .127"	Hole: N/A	Hole: .130"	Hole: .148"
Rake: NEG	Rake: POS	Rake: POS	Rake: POS	Rake: POS	Rake: NEG	Rake: NEG
RT-3AS	RT-373	RT-KW	RT-VBG	RT-FMC	RT-VNS	RT-RL
Height: .357"	Height: .625"	Height: .358"	Height: .344"	Height: .452"	Height: .547"	Height: .421"
Thick: .104"	Thick: .125"	Thick: .101"	Thick: .098"	Thick: .125"	Thick: .121"	Thick: .130"
Hole: .127"	Hole: .117"	Hole: .125"	Hole: .124"	Hole: .090"	Hole: N/A	Hole: .147"
Rake: POS	Rake: POS	Rake: POS	Rake: POS	Rake: POS	Rake: POS	Rake: POS
RT-VNP-L / -R		RT-360	RT-312			
Height: .902"		Diameter: .311"	Thick: .311"			
Thick: .100"		Thick: .100"	Thick: .100"			
Hole: N/A		Hole: N/A	Hole: .150"			
Rake: POS		Rake: POS	Rake: POS			

Cutting Tip Measurements



CYLINDER HEAD
REBUILDING
CLEANING,
ASSEMBLY & SAFETY
SHORT BLOCK
REBUILDING
CRANKSHAFT/
FLYWHEEL GRINDING
MISCELLANEOUS
TOOLS & SUPPLIES
BRAKE SERVICE
TOOLING
MEASURING
TOOLS
V-TWIN & METRIC
HARD PARTS

Brake Lathe Silencers

CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS




34" Neoprene Brake Lathe Silencer

- Longer lasting than rubber
- Neoprene material resists deterioration associated with standard rubber belts
- 7 sound deadening weights
- Measures: 34" L x $\frac{5}{8}$ " W x $\frac{3}{16}$ " Thick
- Order No. **GT-6030N**



34" Rubber Brake Lathe Silencer

- Live rubber strap with 7 sound deadening weights
- For vented rotors
- Measures: 34" L x $\frac{5}{8}$ " W x $\frac{3}{16}$ " thick
- Order No. **CE-8**



Rubber Brake Lathe Tube Silencers for Vented Rotors

- $\frac{9}{16}$ " OD rubber tube with internal sound dampeners
- 2 sizes to choose from

Diameter	Weights	Order No.
9"	6	CE-5
8"	4	CE-5S




Magnetic Strap Brake Lathe Silencer for Non-Vented Rotors

- Measures 48"L x $\frac{1}{4}$ " wide
- Eliminates silencer wandering on solid, non-vented rotors
- Order No. **CE-10**



Spring Silencer For Vented Rotors

- For 6" to 9" rotors
- Metal spring with internal sound dampeners
- Order No. **CE-13**



Rubber Band Brake Lathe Silencers for Non-Vented Rotors

- Neoprene rubber gasket type bands for thin solid rotors
- Both lengths measure $\frac{5}{16}$ " wide x $\frac{3}{16}$ " thick

Length	Order No.
6 $\frac{1}{2}$ "	CE-11
9"	CE-12



Replacement Pucks for Ammco Friction Rotor Silencer

- Heavy non-asbestos pucks provide the mass needed to dampen vibration
- Sold as a pair
- Fits Ammco 7075 silencer
- Order No. **CE-9**



Clamp-On Brake Lathe Silencers For Vented & Non-Vented Rotors

- Follows the cut to absorb vibrations where they start
- Outlast plastic pads, rubber straps and bands

Application	Order No.
For Bench Model Brake Lathes	CE-6
For On-The-Car Brake Lathes	CE-26



Premium Rubber Brake Lathe Silencers for Brake Drums

- Premium live rubber straps
- Two sizes to choose from

Application	Size	Order No.
Passenger Cars	62"L x 2 $\frac{1}{8}$ "W x $\frac{1}{8}$ " Thick	CE-1
Trucks	78"L x 2 $\frac{1}{8}$ "W x $\frac{1}{8}$ " Thick	CE-2

GOODTOOL
Now exclusively from Goodson



Replacement Work Light

- 30" adjustable arm
- 5/8" round mounting end
- Uses up to 100W standard base bulb (not included)
- Easily accessible switch
- Fits most Ammco models
- Order No. **GT-7963**



Replacement Switch for Ammco Brake Lathes

- Easy to install
- Fits most models
- Order No. **GT-7893**



1HP Motor for Ammco Brake Lathes

- Fits 3000, 4000, 4100, 7000, 7500 & 7700 models
- 208 / 230 / 115V • 60Hz
- 1725 RPM • Shaft: .625"
- Includes motor plate and fasteners
- Order No. **GT-2165**

Mounting Spacers

- Fit all 1" arbor brake lathes

Length	Order No.
1/2"	GT-3125

Automotive Brake Lathe Bell Clamps

- For brake lathes with 1" dia. arbors

OD Size: 4.500"
Arbor Size: 1.000"
Order No.: GT-9490



Ammco Rotor & Drum Feed Screw Bushings

Description	Order No.
Rotor Feed Bushing (early)	GT-10868
Rotor Feed Bushing (late)	GT-10868X
Lead Screw Bushing Adaptor	LSB-78529



Brass Wear Inserts for Ammco

- Sold individually

Dia. x Lgth.	Order No.
3/16" x 1/8"	GT-3141
19/64" x 1/4"	GT-3142
(most popular)	
1/4" x 19/64"	GT-9836



Replacement Feed Screw Seal for Ammco

- 1 1/4" OD
- Order No. **3163**

Replacement Screw for Twin Cutter Tool Bit Holders

- Square Head Screw
- Order No. **GT-9249**

Drive Pulleys & Belts for Ammco


- Fit Ammco 3000, 4000, 4100, 7000 & 7100
- Serpentine design runs quieter and increases arbor speed by 175RPMs • Virtually eliminates vibration

New-Style (Serpentine)

Description	Order No.
20 1/4" Belt	GT-5002
19" Belt	GT-5003

Original-Style (V-Belt) Replacements

Description	Order No.
24" Belt	GT-10241
(replaces OE 10241)	



Small Ammco Replacement Parts

Description	Order No.
Locking Knob	6854
Cross Feed Shear Gear with C-Clip	7996



Tooling Hold Down Stud Assembly

- Includes 6 1/2" Stud and Nut Assembly
- Order No. **GT-25900**

Pastelub™ Synthetic High Temp Brake Lubricant

- OE recommended • High pressure resistant
- Recommended for the backs of brake pads
- Not for use on friction surfaces
- 2400°F Ultra high-temperatures range
- Patented "real synthetic" Swiss formula won't melt, rub or wash off brake parts • Gray • Net wt. 7 oz.
- No silicone or petroleum to weaken the carrier base
- Order No. **BPL-2400**



Ceramlub-2800™ Extreme High Temperature Lubricant

- Use on brake caliper slides, etc.
- Contains ceramic pressure solids and high concentrations of anti-corrosive agents
- Specifically designed for use on caliper slides, rubber seals & O-Rings
- A great complement to Pastelub™ Hi-Temp Lubricant
- Purple • Net wt. 7 oz.
- Order No. **CBL-2800**




full service ...fast



"We pride ourselves on packaging our products carefully and professionally. We want you to receive your order quickly and in good condition."

- Brian, Goodson Receiving, 35 years of service

CYLINDER HEAD REBUILDING
CLEANING, ASSEMBLY & SAFETY
SHORT BLOCK REBUILDING
CRANKSHAFT/ FLYWHEEL GRINDING
MISCELLANEOUS TOOLS & SUPPLIES
BRAKE SERVICE TOOLING
MEASURING TOOLS
V-TWIN & METRIC HARD PARTS



GOODTOOL
Now exclusively from Goodson

Replacement Boot Packs

- Keep extra boots on hand for routine maintenance or emergency replacement
- Fits Ammco 3000, 4000, 4100, 7000, 7700



Description	Order No.
Polyethylene Spindle Boot	3085
Screw Feed Dust Boot	3086
Cross Feed Dust Boot	3087
Boot Ring	23682
C-Clip	SBR-4435
Snap Ring	SBR-3159


tech tips

from the techxperts™



Get step by step instructions on replacing brake lathe boots

Check out the blog post (with pictures) on our website. Use your smart phone or other smart device to scan the code at left for instant access to the post.




See page 83 for more Flex-Hones®

Brake Rotor Flex-Hones®

- Provide a non-directional finish
- Use with a 3/8" variable speed drill at 600-1000 RPM
- Zirconium abrasive
- Use dry




Type	Grit	Order No.
Fine	240	BRF-25F
Medium	120	BRF-25M
Coarse	60	BRF-25C



Assorted Accu-Turn Replacement Parts

Description	Order No.
Rotor Feed Screw Assembly (1/2" 20TPI)	GT-433156
Rotor Feed Bushing (fine thread)	GT-433647
Drum Feed Bushing (not shown) (coarse thread)	GT-433646



Rotor Feed Screws & Nuts For FMC & Bean

Description	Order No.
Rotor Feed Screw	GT-90071
Rotor Feed Nut	GT-90077



Brake Drum Grinding Wheels

- Aluminum-Oxide abrasive
- For Van Norman / Rels 204, 300, 302, 303, 333 & 404 Drum Grinders
- Size: 3" x 1/2" x 1"
- OE No.: 8522
- Shape: Recessed
- Order No. **GDV-304**

Measuring Tools



Precision Straight Edges

- 2 sizes to choose from
- Accuracy .005" per foot
- Precision ground one edge
- .375" thick high quality heat-treated steel construction
- Each straight edge is pre-drilled for easy wall storage

Description	Order No.
24" straightedge, 1 precision edge	DIS-24
36" straightedge, 1 precision edge	DIS-36



Rod Bolt Stretch Gauge

- Accurate to .001"
- Features a 1½" dial gauge
- Extra heavy-duty tension spring for repeatable accuracy
- For bolts from 1" to 2½" long

Description	Order No.
Rod Bolt Stretch Gauge	RBSG-3
Optional Contact Point	ERBG-3T
Replacement Pointer	RBSG-P

tech tips
from the techxperts™

Most engine rod failures aren't from faulty parts, they're from improper installation. When you're installing connecting rods, you need to

check the rod bolt stretch by performing a series of torquing and loosening and recording the readings.

Here's how:


1. Torque the bolts to 15 foot pounds and measure the stretch. Record the reading, then loosen the bolts.
2. Repeat at 15 foot pounds and record the reading.
3. Repeat, increasing to 30 foot pounds, record the reading.
4. Repeat, increasing to 60 foot pounds, record the reading.
5. Repeat at 60 foot pounds and record the reading.

Each time you loosen the bolts, measure to be sure that the rod bolts have returned to within .001" of the starting size. If you have a greater variation, get rid of the rod bolts and start with new ones.

When you're conducting final assembly, be sure you use the stretch specified by your rod manufacturer. Attach a rod bolt stretch gauge to the connecting rod bolt and zero it. Use an extra-long box wrench to tighten until the proper stretch is achieved.

Small Hole Gauge Set

- See if rebuilding or replacing is needed by checking guide wear
- Check guide bosses for proper interference fit during replacement
- Check and maintain correct stem-to-guide ID clearance
- 4-piece set has combined range of .125" to .500"
- Order No. **SHG-4**



26" Round Warp Gauge

- Use with feeler gauges (below)
- ¾" diameter tool steel
- Includes anti-roll collar and eye bolt allowing you to hang it for safe, convenient storage
- Order No. **EWG-100** Jobber \$194.99



12" Feeler Gauges

- Measure piston-to-wall clearance when honing, to find ring end gap and to check cylinder heads with a straight-edge
- Also useful for shimming while straightening heads and for machine set-ups

Complete Kit	Order No.	
Thick .0015"	FE-KIT	▼
.0020"	FE-002	x
.0030"	FE-003	x
.0040"	FE-004	x
.0050"	FE-005	x
.0060"	FE-006	x
.0070"	FE-007	x
.0080"	FE-008	x
.0090"	FE-009	x
.0100"	FE-010	x
.0150"	FE-015	x
.0200"	FE-020	x

Mitutoyo

Split Ball Bore Gauge

- Dial gauge with large contact area
- Measures quickly & accurately to .0001"
- Works in threaded or knurled guide IDs
- Range: .280"-.400" • Easy to change contacts
- Order No. **MVG-34**



6 Piece Telescoping Gauge Set

- Compress spring plunger and lock by twisting handle
- Insert into bore and release plunger – it will expand to fit
- Lock again and remove
- Measure with a micrometer
- Double plunger design for consistent measuring
- Long-lasting finish
- Size range: ⅝" - 6"
- Order No. **MTG-6**



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

full service
...**fast**



"From the time we answer the phone to when you receive your delivery, our goal is to get it right the first time and every time."
- Daniela, Goodson Advertising Department, 2 years of service



Build Your Own Valve Guide Gauge Set! Order the Valve Guide Gauge (P-300), Setting Fixture (P-610A) and the Valve Guide Probe you need.



Valve Guide Gauge Set

- The only way to be sure clearance is correct is to gauge it
- Checks all types of guides for size and roundness FAST
- Set up and measure valve guide IDs quickly and easily
- Complete set includes gauge, 3 probes (.312", .344" and .375"), hex wrench, setting fixture and metal storage case with spaces for all components
- Dial calibrated in .0002" increments

Description	Order No.	Incl.
Complete Valve Guide Gauge Set	P-310	▼
Valve Guide Gauge	P-300	x
Setting Fixture	P-610A	x
Valve Guide Probes		
Size Range in. mm		
.236" .224" to .264"	5.69 to 6.71	P-236
.250" .238" to .278"	6.05 to 7.05	P-250
.281" .269" to .309"	6.83 to 7.85	P-281
.312" .300" to .340"	7.62 to 8.64	P-312 x
.344" .332" to .372"	8.43 to 9.45	P-344 x
.375" .363" to .403"	9.22 to 10.24	P-375 x
.438" .426" to .466"	10.82 to 11.84	P-438

Additional probe sizes available by special order

⚠ WARNING: Operating, servicing and maintaining a passenger vehicle or off-road vehicle can expose you to chemicals including engine exhaust, carbon monoxide, phthalates, and lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. To minimize exposure, avoid breathing exhaust, do not idle the engine except as necessary, service your vehicle in a well-ventilated area and wear gloves or wash your hands frequently when servicing your vehicle. For more information go to www.P65Warnings.ca.gov/products/passenger-vehicle.



Sunnen® AG-Series Precision Gauge

- Dial reads directly in "tenths" (.0001")
- Checks rod journal bore for distortion
- Measures size instantly
- Wear-compensated gauge points for permanent accuracy
- Rugged construction – all moving parts are enclosed in the housing
- Includes Point Sets listed below (optional sets are available, call for information)

Description	Order No.
.375" - 3.375" (9.5 - 85.7mm) Range Gauge	AG-300
Standard Point Set (.720" - 1.530" Range)	AG-210
Medium Point Set (1.50" - 2.25" Range)	AG-620
Large Point Set (1.932" - 2.687" Range)	AG-630
Sun-Dura® Gauge Cover (8"L x 8"H x 4"D)	GMC-AG300

Point sets will only fit AG-gauges higher than Serial No. 4000



Distributor Depth Gauge

Working on a Big Block or Small Block Chevy with a distributor? Avoid problem wear and potential failure caused by a distributor that fits too deep. This easy to use gauge measures the depth of engagement allowing you to compensate to create adequate clearance. Kit comes complete with a .500" diameter adaptor. An optional .491" shaft is also available.

Description	Order No.
Distributor Depth Gauge Kit	DDG-05
.491" Shaft	DDG-491




Fig. 1
Insert depth gauge in place of distributor. Bottom out in oil pump drive.




Fig. 2.
Push down on the top collar, making contact with manifold.




Fig. 3
Remove depth gauge from engine. Install adaptor in distributor tool. Measure and record depth.




Fig. 4
Install adaptor in distributor drive. Measure as before and compare. Shim as needed to create clearance.

Sunnen® Dial Bore Gauges

Sunnen® Dial Bore Gauges



- Standard Sunnen® Dial Bore Gauges read out in tenths
- Also available in five-tenths and metric (special order)
- Diameter ranges from .495" to 6.000" (see chart for gauge ranges)
- All models below feature all-carbide gauging points, wear-proof ball crank and adjustable centralizers
- Includes molded storage case with all tools and wrenches required for setup and adjustment

Shock-Shield protects dial from hand heat and jarring to assure accurate reliable readings.

All standard Sunnen Dial Bore Gauges are TENTH READING. Metric and .0005" readouts are also available (special order). Dial can be indexed 90° for easy reading at any angle.

Adjustable centralizers for proper centering over the entire diameter range. One twist adjusts gauge tension so head goes into and out of any size hole smoothly.

Patented wear-proof ball crank assures repeatability over a long life.

Carbide indicating points are long wearing and replaceable.

Transfer Rod

Indexable Centralizer Points

Non-Retractable Dial Bore Gauges

- | | | |
|--|---|---|
| <ul style="list-style-type: none"> • Dia. Range: .495" to .750" (12.6 to 19.0mm) • Max. Gauging Depth: 7.00" (175mm) • Overall Length: 11.8125" (302mm) • .0001" Reading • Measures to within .200" of the bottom of a blind bore • Carbide balls replaceable in the indicating fingers only • Set with SCF-502 Setting Fixture • Order No. GA-4141 | <ul style="list-style-type: none"> • Dia. Range: 2.00" to 6.00" (50 to 150mm) • Max. Gauging Depth: 12.00" (300mm) • Overall Length: 17.00" (432mm) • .0001" Reading • Measures to within .500" of the bottom of a blind bore • Carbide balls replaceable in indicating fingers and extension points • Use CF-1126 Setting Fixture • Order No. GA-2121 | <ul style="list-style-type: none"> • Dia. Range: 2.00" to 6.00" (50 to 150mm) • Max. Gauging Depth: 12.00" (300mm) • Overall Length: 17.00" (432mm) • .0005" Reading • Measures to within .500" of the bottom of a blind bore • Carbide balls replaceable in indicating fingers and extension points • Use CF-1126 Setting Fixture • Order No. GA-2125 |
|--|---|---|

Retractable Dial Bore Gauges

- | | | |
|--|--|---|
| <ul style="list-style-type: none"> • Dia. Range: .740" to 1.19" (18.9 to 30.20mm) • Max. Gauging Depth: 12.00" (300mm) • Overall Length: 17.6875" (451mm) • .0001" Reading • Measures to within .270" of the bottom of a blind bore • Carbide balls replaceable in the indicating fingers only • Set with SCF-502 Setting Fixture • Order No. GR-6241 | <ul style="list-style-type: none"> • Dia. Range: 1.18" to 2.00" (30.0 to 50.8mm) • Max. Gauging Depth: 12.00" (300mm) • Overall Length: 17.75" (452mm) • .0001" Reading • Measures to within .335" of the bottom of a blind bore • Carbide balls replaceable in indicating fingers and extension points • Use SCF-502 Setting Fixture • Order No. GR-9241 | <ul style="list-style-type: none"> • Dia. Range: 2.00" to 6.00" (50 to 150mm) • Max. Gauging Depth: 12.00" (300mm) • Overall Length: 17.00" (432mm) • .0001" Reading • Measures to within .500" of the bottom of a blind bore • Carbide balls replaceable in indicating fingers and extension points • Use CF-1126 Setting Fixture • Order No. GR-2121 |
|--|--|---|

- | | |
|---|---|
| <ul style="list-style-type: none"> • Dia. Range: 2.00" to 6.00" (50 to 150mm) • Max. Gauging Depth: 24.00" (600mm) • Overall Length: 29.00" (737mm) • .0001" Reading • Measures to within .500" of the bottom of a blind bore • Carbide balls replaceable in indicating fingers and extension points • Use CF-1126 Setting Fixture • Order No. GR-2241 | <ul style="list-style-type: none"> • Dia. Range: 2.00" to 6.00" (50 to 150mm) • Max. Gauging Depth: 24.00" (600mm) • Overall Length: 29.00" (737mm) • .0005" Reading • Measures to within .500" of the bottom of a blind bore • Carbide balls replaceable in indicating fingers and extension points • Use CF-1126 Setting Fixture • Order No. GR-2245 |
|---|---|

Dial Bore Gauge Setting Fixtures

- Models combine to cover a continuous range of .054" to 8" in .0001" increments
- Heavy stress-relieved cast iron bases
- Lapped carbide micrometer anvils
- Built-in magnifier
- Each setting fixture includes a master calibrating ring
- Size Setting Adaptor centers gauge probes between parallel reference surfaces on SCF-502 Setting Fixture

Range	Order No.
.054" to 2.00"	SCF-502
2.00" to 8.00"	CF-1126
Size Setting Adaptor	CF-540

Gauges & Setting Fixtures Sold Separately



CYLINDER HEAD
REBUILDING

ASSEMBLY & SAFETY


SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING
TOOLS & SUPPLIES

MISCELLANEOUS
BRAKE SERVICE
TOOLING

MEASURING
TOOLS


V-TWIN & METRIC
HARD PARTS



Premium Micrometers

- Precision ground carbide anvil parallel to within .0001"
- .0001" graduations
- Set includes wood storage case

Description	Range	Order No.	Incl.
Micrometer Set	(wood storage case)	EMS-06	▼
Individual Micrometers	0"-1" (no standard)	EMIC-01	x
	1"-2"	EMIC-12	x
	2"-3"	EMIC-23	x
Each Micrometer includes a Standard,	3"-4"	EMIC-34	x
Spanner Wrench & Case (except EMIC-01)	4"-5"	EMIC-45	x
	5"-6"	EMIC-56	x



Round Anvil Micrometer

- Measure bearing thicknesses
- Ratchet spindle • 0-1" range • Precise to .0001"
- Order No **MIC-01-B**

Checking Standards

- Use to set up dial indicators in special application gauging and to check micrometer accuracy
- Made of hardened, ground and lapped tool steel
- Meet or exceed federal accuracy specifications



Length	Order No.
1"	MCS-1
2"	MCS-2
3"	MCS-3



Open and close the padded jaws to accommodate most micrometers and dial bore gauges

Easy to reach knob adjusts the head angle



Micrometer Stand

- Heavy cast iron construction
- Use to hold micrometers, standards or just about anything you need an extra hand for
- Swivel head and padded jaws won't damage expensive measuring tools
- Order No. **MIC-FIX**


Use a Micrometer Stand When Setting Your Dial Bore Gauge

Read more about it on our blog. Scan the code with your smart phone or other smart device for quick access.



MBR-1

Use with Goodson Dial Indicators:
EDI-0005, EDI-1 and MDI-12
(page 127)



Fine Adjustment Attachment

MBR-1F

Universal Magnetic Base Holders

- Fit any type of dial indicator with lug back
- Magnetic base features an on-off switch with magnetic pull of 110 pounds
- 5/8" diameter 7 1/4" high vertical column
- 3.45" x 1.97" x 2.187" base
- Available with or without fine adjustment feature

Description	Order No.
Universal Holder	MBR-1
With Fine Adjustment	MBR-1F



Dial Bore Gauge Set

- Rugged bore gauge with protected dial
- Carbide tipped contact points
- .0001" (.001mm) graduations • Indication stability: .00008"
- Accuracy: .0002" • Shoe can be rotated for a fresh wear surface • Sets up with a standard micrometer (see page 128)

Range	Description	Order No.
2.0"-6.0"	11 anvils and 4 spacers	MMCB-06
Replacement Spacers	.020"	MMCB-06-020
for anvils 2" & larger	.040"	MMCB-06-040
	.080"	MMCB-06-080
	.120"	MMCB-06-120
Replacement Lens		MMCB-06LENS
Replacement Dial Indicator		MMCB-06IND
Replacement Dial Cover		MMCB-06COVER



0.0005" Graduation Dial Bore Gauge

- Includes: .050" travel indicator, 3 spacers (.100", .050" and .020"), 11 anvils and storage case
- Use for precise bore measurements
- Bore depth: 6" • Range: 2" to 6"

Description	Order No.
Dial Bore Gauge	EBG-265
11 Piece Replacement Spacer Set	EBG-ANVILS


Metric Dial Bore Gauge

- Carbide anvils
- Easy-to-read gauge
- Insulated grip with chrome plated handle
- Includes: extension holder and fitted case
- Range: 35 to 160mm
- Graduations: 0.01mm
- Order No. **MCBG-160**



0.7" to 1.5" Range Cylinder Dial Bore Gauge Set

- Carbide anvils • Easy to read gauge
- Measure cylinders up to 9.5" deep
- Graduations: 0.0005" • Self-centering • Insulated grip
- Chrome plated handle • Includes extension holder and case • Order No. **FBG-7**



Internal Electronic Caliper

- Ideal for measuring mating port runners and bowl diameters
- Hardened contact surfaces
- Robust housing with large LCD display
- Range: 0.5" to 6.0" • Reading: .01" (.3mm)
- Spring loaded locking nut
- Order No. **IEC-56**



1.4" to 6" Range Cylinder Dial Bore Gauge Set

- Carbide anvils • Easy to read gauge
- Measure cylinders up to 9.5" deep • Graduations: 0.0005"
- Self-centering • Insulated grip • Chrome plated handle
- Includes extension holder and case
- Order No. **FBG-146**

Mounts on
Your Pilot



Valve Seat Height Gauge

- Confirm seat height to fire deck location
- Adjusts for all popular seat diameters
- Accurate to .001"
- Seat contact probe aligns on valve seat while gauge rides along the fire deck
- Pilot aligns in valve guide (pilot sold separately)
- Adjustable to fit popular seat diameters from .750" to 3.00"


Includes Dial
Indicator

Description	Fits Pilot	Order No.
Valve Seat Height Gauge Kit	.375"	VSHG-375
Replacement Dial Indicator		EDI-1




12" Direct Reading Dial Caliper

- .001" single revolution • Hardened measuring face
- Precision Ground • Micro-lapped for accuracy
- Adjusting slide for fine adjustment
- Take inside, outside and depth measurements
- Satin Chrome finish with engraved graduations
- Clamp for repetitive readings • Accurate to .001" per 6"
- Covered Rack • Deluxe fitted case
- Order No. **EDC-12**



6" Direct Reading Dial Caliper

- Four way measurement - outside, inside, depth and step
- Hardened stainless steel with satin chrome finish
- Precision ground and lapped measuring surfaces
- Reads direct to .001" or with .100" graduations on beam
- Adjustable bezel with lock • Thumb roll with lock
- 1 1/2" jaw length • Large easy to read dial
- Covered rack • Deluxe fitted case
- Order No. **MDC-03**




6" Digital Caliper

- Accuracy: .0008" under 4" length / .0012" over 4" length
- .0005" (.01mm) resolution • Automatic floating zero
- Used to take inside and outside measurements
- Direct inch/metric conversion
- Large, high-contrast LCD display
- On/Off Button • Deluxe fitted case


Description	Order No.
Digital Caliper	EEDC-06
Replacement Battery	EDC-06B

Use with a one or more dial indicators



Magnetic Deck Stand

- Precision manufactured with 6 to 8 pounds of magnetic pull yet slides smoothly over the piston dome and deck
- Should only be used with dial indicators (sold separately) in upright position - perpendicular to the ground
- Order No. **MDBS-2**



Revolution Counter
(included on most models)

Adjustable bezel
for zero settings

Shatter resistant crystal

3/8" stem

EDI-0005

- 1" travel
- 2" dial
- 1"L stem
- .0005" graduations

All indicators
have lug back



EDI-1

- 1" travel • 2" dial
- 1"L stem
- .001" graduations



MDI-2

- 2" travel • 3" dial
- 2"L stem
- .001" graduations




MDI-12

- .125" travel
- 2" dial
- 12"L stem
- .001" graduations



Starrett
Goodson
exclusive



Dial Indicator Flat Anvil

- Use with dial indicator (sold separately) to make full contact on surface to be measured
- Especially useful when measuring deep inside blocks in combination with our magnetic deck stand (MDBS-2 at left)
- Order No. **MDI-12A**

V-Twin On-the-Engine Valve Spring Compressor

Replace broken valve springs, install high performance valve springs, remove and replace valve guide seals all without disassembling the bike – just remove the gas tank and get to work. Use on Sportster, Evolution, Twin-Cam and most aftermarket V-Twins. Kit includes valve spring compressor, adaptor for compressing beehive springs, valve seal driver/installer and head pressurizing hose. Order No. **CF-HDIF**



CYLINDER HEAD
REBUILDING

CLEANING,
ASSEMBLY & SAFETY

SHORT BLOCK
REBUILDING

CRANKSHAFT/
FLYWHEEL GRINDING

MISCELLANEOUS
TOOLS & SUPPLIES

BRAKE SERVICE
TOOLING

MEASURING
TOOLS

V-TWIN & METRIC
HARD PARTS

Pan/Shovel Spring Seat Cutting Tool


- Convert Pan & early Shovel to late style Shovel easily to attain higher lift
- Spacer stops the cutter at the correct height for uniform spring spacing
- Use with lower spring collars or stock late style lower spring collars (1980-1984) • OD: 1.680" • ID: 0.750"



Description	Order No.
Spring Seat Cutting Tool	VSS-1680HD
.375" Spring Pad Pilot	VP-375

Guide Driver for Reduced Diameter Top Valve Guides

The guide top fits into the groove between the driver and the bushing to center and drive the guide into place. Puts pressure on the step top of the guide, not the seal area. Required for installing 20-2120 & 20-2130 series guides on page 134. Order No. **VGD-315420**



Keeper Installation Tools

Best Keeper Tool on the Market!

- Spring-loaded plunger
- For single & multi-groove keepers
- Reaches keeper grooves located farther from the valve tip • Ideal for use with **CF-500** (p. 44) or **PSB-5000** (p. 43)

Size	Order No.
5mm / .2031"	VKI-5
6mm / .2344"	VKI-6
7mm / .2812"	VKI-7
8mm / .3125"	VKI-8
Replacement Rubber Sleeve	VKI-56

One of the handiest keeper tools you'll ever find!

Keeper Magnet

- 6⁵/₁₆" long holder fits easily into deep bores
- Powerful .170" diameter earth magnet holds keepers securely when removing or installing
- Order No. **VKM-17**



.421" Valve Seal Cutter

- Evo/Twin Cam
- Will shorten and re-chamfer the guide top, increasing seal-to-retainer clearance for higher lift camshafts
- Can also be used to modify .530" guides to .421" guides
- Guide OD: .421" • Pilot Size: .312"
- Use with 71010 seal (page 133)
- Order No. **VSC-420312**



Universal Seal Pliers

- Works on OHC and in-line engines with recessed springs
- Long, serrated jaws reach into confined areas and grip seals firmly
- Heat-treated steel with easy-grip handles
- Order No. **VSP-823**





.415" Lift

Panhead™
1948 to 1965

Valve Spring Kit for 3/8" Valve Stems

- OE Replacement
- Fits Intake Valve 20-4257 and Exhaust Valve 20-4195
- Heat-treated and shot peened for long life • Kits include 4 Retainers, 4 Springs, 4 Keepers & 4 Base Washers

Max Lift	Installed Height	Seat Pressure	Open Pressure	@ Lift	Order No.
.415"	1.375"	129 lbs.	272 lbs.	.415"	20-20430

.600" Lift

Evolution™
1984 to 1999
Valve Spring Kit
For 5/16"

Valve Stems

- Heat-treated and shot peened for long life
- Lightweight Racing Kits include 4 Retainers, 4 Springs, 4 Keepers & 4 Base Washers
- Use with Intake Valve 20-4171 & Exhaust Valve 20-4170

Max Lift	Installed Height	Seat Pressure	Open Pressure	@ Lift	Order No.
.600"	1.810"	163 lbs.	361 lbs.	.600"	20-20132

.655" Lift

Evolution™
1984 to 1999
Valve Spring Kit For
5/16" Valve Stems

- Springs heat-treated and shot peened for long life
- Lightweight Racing Kits include 4 Retainers, 4 Springs, 4 Keepers and 4 Base Washers
- Use with Intake Valve 20-4171 & Exhaust Valve 20-4170

Max Lift	Installed Height	Seat Pressure	Open Pressure	@ Lift	Order No.
.655"	1.860"	190 lbs.	465 lbs.	.655"	20-20081

.600" Lift

Shovelhead™
1966 to 1977

Valve Spring Kit For 3/8" Valve Stems

- Lightweight Racing Kits include 4 Retainers, 4 Springs, 4 Keepers and 4 Base Washers • Lightweight, hard anodized 7075T-6 Retainers offset .070" for taller installed height • Base Washers counter-bored for a .665" OD seal
- Use with Intake Valve 20-4194 & Exhaust Valve 20-4195

Max Lift	Installed Height	Seat Pressure	Open Pressure	@ Lift	Order No.
.600"	1.510"	150 lbs.	385 lbs.	.600"	20-2110

.600" Lift

Shovelhead™
1966 to 1977

Valve Spring Kit For 3/8" Valve Stems

- Springs heat-treated and shot peened for long life
- Lightweight Racing Kits include 4 Steel Retainers, 4 Springs, 4 Keepers and 4 Base Washers
- Use with Intake Valve 20-4194 & Exhaust Valve 20-4195

Max Lift	Installed Height	Seat Pressure	Open Pressure	@ Lift	Order No.
.600"	1.510"	150 lbs.	385 lbs.	.600"	20-20450

.415" Lift

Shovelhead™
1966 to 1977
Valve Spring Kit
For 3/8" Valve Stems

- Springs heat-treated and shot peened for long life
- OE Replacement Kit includes 4 Steel Retainers, 4 Springs, 4 Keepers and 4 Base Washers
- Use with Intake Valve 20-4194 & Exhaust Valve 20-4195

Max Lift	Installed Height	Seat Pressure	Open Pressure	@ Lift	Order No.
.415"	1.375"	129 lbs.	272 lbs.	.415"	20-20435

**Ensure Your Valve Springs
Are Set Correctly
with a
Valve Spring Tester
from Goodson**

See page 41

**Compression
Release Valves**

- 2 per pack
- 10 x 1.0mm thread
- High temperature resistant knobs
- Shorter thread section makes installation easier with less drilling than required with OE-style



Application	Length	Thread	Order No.
Evolution	1.400"	.350"L	20-21250
Twin Cam	1.730"	.350"L	20-21255
OE Replacement	1.750"	.500"L	20-21260



.610" Max Lift Beehive Valve Spring Set for 5/16" Valves

- Advanced spring design with special attention to cam and spring harmonics, stress, mass and operating RPM
- Premium grade, super clean ground chrome silicon wire
- Kits include 4 Retainers, 4 Springs, 4 Keepers and 4 Base Washers • Supersedes HVS-6000S

Max Lift	Installed Height	Seat Pressure	Open Pressure	@ Lift	Order No.
.610"	1.860"	175 lbs.	400 lbs.	.610"	20-21300

.660" Max Lift Beehive Valve Spring Sets for 5/16" Valves

- 9° taper • Advanced spring design with special attention to cam and spring harmonics, stress, mass & operating RPM
- Premium grade, super clean ground chrome silicon wire
- Kits include 4 Retainers, 4 Springs, 4 Keepers and 4 Base Washers • Supersedes HVS-6500S

Max Lift	Installed Height	Seat Pressure	Open Pressure	@ Lift	Order No.
.660"	1.860"	178 lbs.	371 lbs.	.660"	20-21500

.610" Max Lift Beehive Valve Spring Sets for 7mm Valves

- Advanced spring design
- Premium grade, super clean ground chrome silicon wire
- Kits include 4 Retainers, 4 Springs, 4 Keepers 4 Viton Seals and 4 Base Washers • Supersedes HVS-6000-7SG

Max Lift	Installed Height	Seat Pressure	Open Pressure	@ Lift	Order No.
.610"	1.860"	175 lbs.	400 lbs.	.610"	20-21400

.660" Max Lift Beehive Valve Spring Sets for 7mm Valves

- 9° taper
- Advanced spring design
- Premium grade, super clean ground chrome silicon wire
- Kits include 4 Retainers, 4 Springs, 4 Keepers, 4 Viton Seals and 4 Base Washers • Supersedes HVS-6500-7SG

Max Lift	Installed Height	Seat Pressure	Open Pressure	@ Lift	Order No.
.660"	1.860"	178 lbs.	371 lbs.	.660"	20-21550

**Evolution™ (04-99), Evo Sportster™ 883cc (96-03)
XL™ 1100cc (86-87), Evo Sportster™ 1200cc (88-20),
Twin Cam™ 88" (99-04) & Buell™ XB9-XB-12 (03-10)**



20-21650



20-23650

Lightweight Racing Dual Spring Kits

- Exact match for installation heights and spring pressures
- Retainers designed for optimum rocker cover clearance
- Includes 4 heavy-duty 9° high-temperature steel keepers, 4 springs, 4 retainers and 4 base washers

Max Lift	Installed Height	Seat Pressure	Open Pressure	@ Lift	Order No.
Fit 5/16" Valve Stems High Temperature Steel Retainers and BaseWashers Seals Sold Separately					
.650"	1.860"	185 lbs.	440 lbs.	.650"	20-21650
.675"	1.860"	185 lbs.	450 lbs.	.675"	20-21600
Fit 7mm Valve Stems High Temperature Steel Retainers and BaseWashers Seals Included					
.650"	1.860"	185 lbs.	440 lbs.	.650"	20-23500
.675"	1.860"	185 lbs.	450 lbs.	.675"	20-23600
Fit 7mm Valve Stems Titanium Retainers and High Temperature Steel BaseWashers Seals Included					
.650"	1.860"	185 lbs.	440 lbs.	.650"	20-23550
.675"	1.860"	185 lbs.	450 lbs.	.675"	20-23650

Same Day Shipping


131

CYLINDER HEAD
REBUILDING
CLEANING,
ASSEMBLY & SAFETY
SHORT BLOCK
REBUILDING
CRANKSHAFT/
FLYWHEEL GRINDING
MISCELLANEOUS
TOOLS & SUPPLIES
BRAKE SERVICE
TOOLING
MEASURING
TOOLS
V-TWIN & METRIC
HARD PARTS

White Diamond® Hard Chrome Replacement Valves for Milwaukee-Eight™ Heads

- 1-piece forged with White Diamond® hard chrome stems for impervious wear resistance
- Inconel® 751 exhaust valves designed to outperform in the most extreme forced induction or racing applications
- Flow bench tested to optimize intake and exhaust profiles

Type	Head Dia.	Stem Dia.	Radius	Angle	OAL	Order No.	Material	Supersedes
Intake	1.614" (41.00mm)	0.2347"	0.235"	15°	4.035"	20-21060H	Chrome	-----
Intake	1.630" (41.40mm)	0.2347"	0.235"	10°	4.055"	20-21009H	Chrome	20-21009
Intake	1.654" (42.01mm)	0.2347"	0.235"	15°	4.032"	20-21061H	Chrome	20-21014
Exhaust	1.264" (32.11mm)	0.2342"	0.460"	24°	4.050"	20-21016H	Chrome	20-21016
Exhaust	1.284" (32.61mm)	0.2342"	0.460"	24°	4.050"	20-21017H	Chrome	20-21017
Exhaust	1.299" (32.99mm)	0.2342"	0.395"	0°	4.055"	20-21062K	Chrome	-----



Milwaukee-Eight™ Beehive Spring Kits

- Includes 8 progressively wound ovate wire Beehive Springs, 8 Retainers, 8 Tophat Seals and 8 Spring Bases

Max Lift	Installed Height	Seat Pressure	Open Pressure	@ Lift	Order No.
Titanium Retainers					
.625"	1.500"	85 lbs.	280 lbs.	.625"	20-21800
Heat Treated Steel Retainers					
.625"	1.500"	85 lbs.	280 lbs.	.625"	20-21850

Milwaukee-Eight™ Beehive Valve Spring Kits

- Advanced spring design with special attention to cam and spring harmonics, stress, mass and operating RPM
- Premium-grade, super clean ground chrome silicon wire • Heat-treated and shot peened for long life



.465" Max Lift Beehive Valve Spring Kit With Titanium Retainers

- Includes 8 retainers, 8 springs and 8 base washers
- Installed Height: 1.410"
- Seat Pressure: 80 lbs.
- Open Pressure: 212 lbs. at .465"
- Order No. **20-21000**



.465" Max Lift Beehive Valve Spring Kit With Heat Treated Steel Retainers

- Includes 8 retainers, 8 springs and 8 base washers
- Installed Height: 1.410"
- Seat Pressure: 80 lbs.
- Open Pressure: 212 lbs. at .465"
- Order No. **20-21050**



.550" Max Lift Beehive Valve Spring Kit With Titanium Retainers


- Supersedes #20-21200
- Includes 8 retainers, springs, base washers and viton tophat seals
- Installed Height: 1.550"
- Seat Pressure: 85 lbs.
- Open Pressure: 257 lbs. at .550"
- Order No. **20-21205**



Solid Viton Seals With Metal Jacket & Choker Spring

• 16 Per Package


Stem Dia.	OAL	Seal OD	A	D	Order No.	Supersedes
7.0mm	0.510"	0.665"	0.560"	0.375"	71028	HVS-7MM
.312"	0.412"	0.566"	0.420"	0.275"	71010	HVS-421
.312"	0.514"	0.671"	0.530"	0.330"	71045	HVS-531
.375"	0.516"	0.661"	0.562"	0.375"	71011	—



Solid Viton Seals With Metal Jacket & Integral Spring Base

• 16 Per Package
• Spring Shoulder Diameter: 0.970"

Stem Dia.	OAL	Seal OD	A	C	Order No.	Supersedes
7.0mm	0.974"	1.457"	0.560"	0.700"	71030	HV-7MMOE



Milwaukee-Eight™ Tophat Valve Seal

• 16 Per Package


Stem Dia.	OAL	Seal OD	A	C	Order No.	Supersedes
6.0mm	0.712"	1.170"	—	—	71046-16	—



OE Style Seals Solid Teflon With Metal Jacket

16 Per Package

Stem Dia.	OAL	Seal OD	A	D	Order No.	Supersedes
.312"	0.385"	0.565"	0.420"	0.315"	71032	HSS-420
.312"	0.375"	0.630"	0.530"	0.295"	71033	HSS-530312
.343"	0.375"	0.630"	0.530"	0.365"	71034	HSS-530343
.375"	0.375"	0.660"	0.562"	0.315"	71035	HSS-562
.375"	0.400"	0.720"	0.625"	0.310"	71036	HSS-625



Need something not listed here?

We can order just about anything in the Kibblewhite catalog for you.

Call us at 1-800-533-8010 for more information.



Valve Seat Inserts

- For Harley-Davidson®
- Easy to machine
- Effectively dissipate heat for consistent valve sealing
- Hardness increases during engine break-in
- Radiused for easy installation



Replacement Valve Seats For Shovel Head 1200 & 1340

Application	OD	ID	Thick	Order No.	Supersedes
Exhaust	1.944"	1.575"	.400"	10-HC493	HVS-1944
Intake	2.135"	1.750"	.400"	10-HC542	HVS-2135

Oversize Seats For Shovel, Evolution, Twin Cam & M8 – machining required

	OD	ID	Thick	Order No.	Supersedes
Fits M8	1.630"	1.180"	.385"	10-HC414	HVS-1630
	1.757"	1.410"	.430"	10-HC447	HVS-1757
	1.882"	1.520"	.410"	10-HC478	HVS-1882
	2.008"	1.610"	.440"	10-HC510	HVS-2008
	2.040"	1.700"	.425"	10-HC518	HVS-2040
	2.070"	1.610"	.460"	10-HC526	HVS-2070
	2.132"	1.800"	.460"	10-HC541	HVS-2132
	2.163"	1.750"	.455"	10-HC549	HVS-2163

For Iron Head Sportster

Application	OD	ID	Thick	Order No.	Supersedes
Exhaust	1.757"	1.371"	.315"	10-HC446	HVS-1757S
Intake	2.068"	1.750"	.315"	10-HC525	HVS-2068

Universal Repair Seat

	OD	ID	Thick	Order No.	Supersedes
Powdered	1.339"	1.024"	.375"	10-SC340	MVS-42
Metal	1.693"	1.299"	.434"	10-SC430	MVS-58
	1.819"	1.375"	.450"	10-HC462	HVS-1820
	1.945"	1.500"	.450"	10-HC494	HVS-1945
	2.257"	1.870"	.450"	10-HC573	HVS-2257

Nickel Chrome Valve Seats on Page 24



tech tips When installing seats preheat head to 400° and freeze the seat for easier installation. Press fit .006" to .008".



6061-T6 Aluminum Seal Drivers


These installation tools for OE style seals are manufactured from high strength 6061-T6 Aluminum for increased durability when compared to plastic installers.

Application	Color	Fits Seal Up To	Order No.
Evolution	Red	0.575"	20-20830
Pan/Shovelhead 74"	Black	0.673"	20-20833
Ironhead Sportster	White	0.638"	20-20832
Shovelhead 80"	Blue	0.758"	20-20831

... another
satisfied
customer

"No complaints! Been in this business 40 years. Goodson is one of the best companies I've dealt with."
- Joe James, Brighton, CT - Goodson Customer since 2002


MEASURING TOOLS
BRAKE SERVICE TOOLING
MISCELLANEOUS TOOLS & SUPPLIES
CRANKSHAFT/ FLYWHEEL GRINDING
SHORT BLOCK REBUILDING
CLEANING, ASSEMBLY & SAFETY
CYLINDER HEAD REBUILDING



Milwaukee-Eight™ Valve Guides

- Use with 6mm seals (71046 or OE)


Intake				Manganese Bronze	Cast Iron	
OD	ID	OAL	Size			
.4750"	.2347"	1.655"	Std.	20-21020M	—	
.4760"		+ .001"		20-21021M	—	
.4770"		+ .002"		20-21022M	20-21022C	
.4850"		+ .010"		20-21029M	20-21029C	
Exhaust				Manganese Bronze	Cast Iron	
OD	ID	OAL	Size			
.4750"	.2342"	1.655"	Std.	20-21030M	20-21030C	
.4760"		+ .001"		20-21031M	20-21031C	
.4770"		+ .002"		20-21032M	20-21032C	
.4850"		+ .010"		20-21039M	20-21039C	



Evolution, Twin-Cam & Evo Sportster With 5/16" Valves (.420" Guide Top)

- Use with 71010 Viton Seals or 71032 OE Style Seals


Intake				Manganese Bronze	Cast Iron	Supersedes
OD	ID	OAL	Size			
.5620"	.3098"	2.100"	Std.	20-2120M	20-2120C	
.5630"		+ .001"		20-2121M	20-2121C	HVG-5600S
.5640"		+ .002"		20-2122M	20-2122C	HVG-5601S
.5720"		+ .010"		20-2129M	—	
Exhaust				Manganese Bronze	Cast Iron	Supersedes
OD	ID	OAL	Size			
.5620"	.3098"	2.150"	Std.	20-2130M	20-2130C	
.5630"		+ .001"		20-2131M	20-2131C	HVG-5700S
.5640"		+ .002"		20-2132M	20-2132C	HVG-5701S
.5720"		+ .010"		20-2139M	—	



Evolution, Twin-Cam & Evo Sportster With 5/16" Valves (.530" Top Guides)

- Use with 71045 Viton Seals


Intake				Manganese Bronze	Cast Iron	Supersedes
OD	ID	OAL	Size			
.5625"	.3075"	2.100"	Std.	20-20860M	—	HVG-5600
.5635"		+ .001"		20-20861M	—	HVG-5601
.5645"		+ .002"		20-20862M	—	HVG-5602
Exhaust				Manganese Bronze	Cast Iron	Supersedes
OD	ID	OAL	Size			
.5625"	.3096"	2.100"	Std.	20-20870M	—	HVG-5700
.5635"		+ .001"		20-20871M	—	HVG-5701
.5645"		+ .002"		20-20872M	—	HVG-5702
.5725"		+ .010"		20-20879M	—	



Twin Cam & Evo Sportster w/ 7mm Valves

- Use with 71028 (0.562") Viton Seals

Intake				Manganese Bronze	Cast Iron	Supersedes
OD	ID	OAL	Size			
.5625"	.2760"	2.040"	Std.	20-20690M	—	HVG-6600
.5635"		+ .001"		20-20691M	—	HVG-6601
.5645"		+ .002"		20-20692M	—	HVG-6602
.5725"		+ .010"		20-20699M	—	
Exhaust				Manganese Bronze	Cast Iron	Supersedes
OD	ID	OAL	Size			
.5620"	.2755"	2.040"	Std.	20-20700M	—	HVG-6700
.5630"		+ .001"		20-20701M	—	HVG-6701
.5640"		+ .002"		20-20702M	—	HVG-6702
.5720"		+ .010"		20-20709M	—	



Sportster (1970-1983)

- Use with 71033 (intake) & 71034 (exhaust) OE-Style Seals


Intake				Manganese Bronze	Cast Iron	Supersedes
OD	ID	OAL	Size			
.5650"	.3085"	1.770"	Std.	—	20-2320C	HVG-5100C
.5660"		+ .001"		—	20-2321C	HVG-5101C
.5670"		+ .002"		—	20-2322C	HVG-5102C
Exhaust				Manganese Bronze	Cast Iron	Supersedes
OD	ID	OAL	Size			
.5650"	.3375"	1.770"	Std.	—	20-2330C	HVG-5200C
.5660"		+ .001"		—	20-2331C	HVG-5201C
.5670"		+ .002"		—	20-2332C	HVG-5202C



Shovel Head 80" (78-83)

- Use with 71036 OE Style Seals

Intake or Exhaust				Manganese Bronze	Cast Iron	Supersedes
OD	ID	OAL	Size			
.6250"	.3745"	1.910"	Std.	20-2050M	20-2050C	HVG-5400
.6260"		+ .001"		20-2051M	20-2051C	HVG-5401
.6270"		+ .002"		20-2052M	20-2052C	HVG-5402



Shovel & Pan Heads


- Use with 71011 Viton seals or 71035 OE Style Seals

Intake or Exhaust				Manganese Bronze	Cast Iron	
OD	ID	OAL	Size			
.5650"	.3760"	1.900"	Std.	20-2020M	20-2020C	
.5660"		+ .001"		20-2021M	20-2021C	
.5670"		+ .002"		20-2022M	20-2022C	
.5680"		+ .003"		20-2023M	20-2023C	
.5750"		+ .010"		20-2029M	20-2029C	

High Performance Valves



tech tips Always check and confirm running clearances when installing new valves.



CYLINDER HEAD
REBUILDING
CLEANING,
ASSEMBLY & SAFETY
SHORT BLOCK
REBUILDING
FLYWHEEL GRINDING
CRANKSHAFT/
MISCELLANEOUS
TOOLS & SUPPLIES
BRAKE SERVICE
TOOLING
MEASURING
TOOLS
V-TWIN & METRIC
HARD PARTS

Black Diamond™ & White Diamond® Valves for Harley-Davidson® Engines

- **Light and strong with optimum airflow** A combination of stress analysis and flow bench testing for optimally balanced valve mass, strength and airflow characteristics.
- **Black Diamond™ Valves** One piece forged stainless steel valves impregnated by a special German process to improve wear properties and reduce friction. Provides resistance to corrosion and superior wear.
- **Chrome Diamond® Valves** One piece forged with White Diamond® hard chrome stems. Inconel® 751 exhaust valves are designed to perform even in the most extreme conditions. Flow bench tested to optimize intake and exhaust profiles.

Application	Type	Head Diameter	Stem Diameter	Tulip Radius	Angle	Overall Length	Order No.	Supersedes
Milwaukee-Eight	Intake	1.571" (39.90mm)	0.2347"	0.235"	10°	4.015"	20-21012H	20-21012
	Intake	1.614" (41.00mm)	0.2347"	0.235"	15°	4.035"	20-21060H	-----
	Intake	1.630" (41.40mm)	0.2347"	0.235"	10°	4.055"	20-21009H	20-21009
	Intake	1.654" (42.01mm)	0.2347"	0.235"	15°	4.032"	20-21061H	20-21014
	Exhaust	1.264" (32.11mm)	0.2342"	0.460"	24°	4.050"	20-21016H	20-21016
	Exhaust	1.284" (32.61mm)	0.2342"	0.460"	24°	4.050"	20-21017H	20-21017
Pan Head 1948-1965 Black Diamond™	Exhaust	1.299" (32.99mm)	0.2342"	0.395"	0°	4.055"	20-21062K	-----
	Intake	1.750" (44.45mm)	0.3765"	0.234"	23°	3.800"	20-4257	-----
Sportster 1970-1983	Exhaust	1.750" (44.45mm)	0.3760"	0.234"	29°	3.820"	20-4195	-----
	Intake	1.935" (49.15mm)	0.3090"	0.256"	23°	3.620"	20-4196	HEV-5
	Intake	1.950" (49.53mm)	0.3090"	0.256"	23°	3.690"	20-4167	-----
Shovelhead 74" & 80" 1966-1983	Exhaust	1.570" (39.88mm)	0.3384"	0.236"	29°	3.512"	20-4197	HEV-3
	Intake	1.950" (49.53mm)	0.3765"	0.234"	23°	3.885"	20-4194	HEV-9
	Intake	2.000" (50.80mm)	0.3765"	0.234"	23°	3.885"	20-4256	-----
Shovelhead 74" & 80" 66-83 "Fat Stem"	Exhaust	1.750" (44.45mm)	0.3760"	0.234"	29°	3.810"	20-4195	HEV-7
	Intake	1.950" (49.53mm)	0.3780"	0.234"	23°	3.885"	20-4294	-----
	Exhaust	1.750" (44.45mm)	0.3775"	0.234"	29°	3.810"	20-4295	-----
Evolution 1984-1999	Intake	1.840" (46.74mm)	0.3100"	0.236"	23°	4.445"	20-4171	-----
	Intake	1.940" (49.28mm)	0.3108"	0.675"	25°	4.440"	20-20910	HBV-1940
	Intake	1.900" (48.26mm)	0.3108"	0.675"	25°	4.440"	20-20915	HBV-1900
	Intake (Racing)	1.900" (48.26mm)	0.3100"	0.344"	28°	4.420"	20-4171R	HBV-1900S
	Intake	2.150" (54.61mm)	0.3108"	0.550"	24°	4.480"	20-20900	HCV-2150
	Exhaust	1.615" (41.02mm)	0.3096"	0.236"	29°	4.525"	20-4170	HEV-10
	Exhaust (Racing)	1.630" (41.40mm)	0.3096"	0.500"	40°	4.525"	20-4170R	-----
	Exhaust	1.650" (41.91mm)	0.3106"	0.750"	25°	4.515"	20-20920	HBV-1650
	Exhaust	1.610" (40.89mm)	0.3106"	0.750"	25°	4.510"	20-20925	HBV-1610D
	Exhaust	1.585" (40.26mm)	0.3106"	0.750"	25°	4.505"	20-20930	HBV-1585
Evo Sportster 883 to 1200cc	Intake	1.715" (43.56mm)	0.3100"	0.236"	23°	4.550"	20-2010	HBV-1720
	Exhaust	1.480" (37.59mm)	0.3096"	0.500"	40°	4.625"	20-2012	-----
Twin Cam 88"-103" 2005-2017	Intake	1.805" (45.85mm)	0.2760"	0.413"	1.700°R	4.420"	20-20322	HBV-1810-TTG
	Intake	1.900" (48.26mm)	0.2760"	0.344"	28°	4.420"	20-20323R	-----
	Exhaust	1.575" (40.00mm)	0.2755"	0.354"	22°	4.520"	20-20325	-----
Buell® XB9™ 2003-2007	Exhaust	1.630" (41.40mm)	0.2755"	0.500"	34°	4.520"	20-20326R	-----
	Intake	1.805" (45.85mm)	0.2760"	0.344"	28°	4.525"	20-20260	-----
	Intake	1.900" (48.26mm)	0.2760"	0.344"	28°	4.500"	20-20262	-----
Twin Cam, Sportster & Buell® Triple Groove	Intake	1.980" (50.29mm)	0.2757"	0.290"	23°	4.455"	20-20935	HBV-1980-TTG
	Intake	1.900" (48.26mm)	0.2757"	0.475"	24°	4.445"	20-20940	HBV-1900-TTG
	Exhaust	1.610" (40.89mm)	0.2755"	0.595"	25°	4.545"	20-20945	HBV-1610-TTG
	Exhaust	1.575" (40.05mm)	0.2755"	0.595"	25°	4.560"	20-20950	HBV-1575-TTG
Evo, Big Twin & Twin Cam	Intake	2.020" (51.31mm)	0.3108"	0.670"	25°	4.440"	20-20990	HBV-2020A
	Exhaust	1.700" (43.18mm)	0.3106"	0.600"	25°	4.535"	20-20960	HBV-1700A
S&S®, Screaming	Intake	2.020" (51.31mm)	0.3108"	0.645"	25°	4.510"	20-20965	HBV-2020S
Eagle & Ultima®	Exhaust	1.610" (40.89mm)	0.3106"	0.750"	25°	4.565"	20-20970	HBV-1610S
SE® / JIMS®	Exhaust	2.100" (53.34mm)	0.3108"	0.560"	24°	4.475"	20-20955	HBV-2100
Blank Valves	Black	2.100" (53.34mm)	0.3108"	-----	24°	5.700"	20-20980	HBV-1700BC
Ready to machine	Chrome	2.200" (55.88mm)	0.3108"	-----	25°	5.700"	20-20975	HCV-2200BC

RAPIDEX

A rapid-use index of product categories

Cylinder Head Rebuilding

Pilots.....	4-6
Valve Seat Work.....	7-25
Valve Refacing.....	26-30
Reamers.....	31-32
Valve Guide Resizing.....	33-35
Valve Guide Replacement.....	36-40
Valve Seal Work.....	41
Valve Spring Work.....	42-47
Cylinder Head Resurfacing.....	49-52
Crack Detection & Repair.....	53-56
Porting & Polishing.....	58-60

Cleaning, Assembly & Safety

Parts Storage & Organizers.....	61-64
Parts Baskets.....	64
Wire Wheels & Brushes.....	65-66
Cleaning.....	67-69
Last Blast Paint & Metal Markers.....	70
Assembly Lubes.....	71
Coolants & Lubricants.....	72-73

Index.....75-82

Short Block Rebuilding

Boring Bar Tooling & Supplies.....	84-85
Cylinder Honing.....	86-89
Flex-Hones®.....	90
Rod Honing.....	92
Rod & Piston Work.....	95-98
Lifter Bore Tooling.....	100
Camshaft Work.....	101-102

Crankshaft/Flywheel Grinding

Crankshaft Grinding Wheels.....	104-105
Crankshaft Grinding & Polishing.....	108-110
Flywheel Grinding.....	111-113

Miscellaneous Tools

Diamond Dresser Tools.....	114-115
Miscellaneous.....	117

Brake Service Tooling

Brake Tips & Holders.....	118-119
Brake Lathe Silencers.....	120
Brake Lathe Replacement Parts.....	121-122

Measuring Tools

Straight Edges.....	123
Dial Bore Gauges.....	125-127
Micrometers.....	126
Calipers & Dial Indicators.....	129

V-Twin Hard Parts

Valve Springs.....	130-132
Seats & Seat Inserts.....	133
Valve Guides.....	134
Replacement Valves.....	135

© Copyright 2025, Goodson Mfg. Co., Inc. All copy and illustrations are copyrighted. Absolutely no mechanical or electronic reproduction or use of any part is allowed without our prior written permission. Goodson reserves the right to correct printing errors. Prices are subject to change without notice.



It's kind of a big year! From our catalog cover, all the way to it's last page, we're celebrating 80 years of Goodson. Let's take a trip through the last 80 years of Goodson history...

1945



Hazen Goodson (pictured with his wife) starts to sell machine shop tools and supplies in Dallas, Texas

1950



Look familiar? This is the oldest catalog we've found - and it's featured here and as the star of the 2025 cover photo!

1959

Hazen Goodson passes away, leaving the company in the hands of his son-in-law

1972

Winona Tool Company purchases all assests of Goodson Manufacturing Co. and moves the company to Winona, Minnesota

1979



Scott Biesanz purchases the Goodson Tools division from Winona Tools Company

1985



Goodson moves to current location!

1995



50 years of Goodson! And the first appearance of the Goodson Girl!

2004



Goodson purchases Mach-B Grinding Wheels Shaping & Resizing

2012



2017



Goodson purchases Abrasive Industrial Supplies

2020



Goodson becomes 100% Employee Owned!

2025..and beyond!

Goodson will continue to be your top supplier of tools and engine supplies!



Watch for this symbol throughout the catalog

We know pictures often tell the story better than words so we are making videos for many of the products in the Goodson product line. The symbol above indicates that there is a video available for that product. Where space allows we are including a QR code that will take you directly to the video. All you need to do is point your smartphone camera at the code and the link will open.



Mach-B Grinding Wheel Shaping & Resizing

From routine grinding wheel shaping and sizing to emergency work, ***Mach-B Can Do That!***

Mach-B Grinding Wheel Shaping & Resizing specializes in:

- Custom Grinding Wheel Shaping
- Custom Grinding Wheel Sizing
- Reducing Outside Diameters
- Increasing Inside Diameters
- ANSI Compliant Speed Testing
- Static Balance Testing
- Standard and Custom Profiles
- Grinding Wheel Slotting



Turn to Mach-B and Goodson for Fast Turnaround. Visit www.mach-b.com for more information.



Custom Abrasive Belts

- Any Length (up to 520")
- Any Width (up to 15")*
- Aluminum-Oxide
- Ceramic-Alumina
- Silicon-Carbide
- Zirconia-Alumina
- 36 to 600 Grit*

Abrasive Industrial Supplies Has You Covered!

Abrasive Industrial Supplies (AIS) is a division of Goodson specializing in stock and custom grinding, sanding and polishing belts. We make belts in-house and can make whatever size belt you need.

*Grit & width availability varies by abrasive grain.

Choose from a variety of abrasives in several grits and backings for a wide range of applications.

You can order directly from AIS by calling **1-800-433-8010** or visiting the website; www.abrasiveindustrialsupplies.com OR talk to your Goodson customer service rep.

Now that's ONE STOP SHOPPING!



Abrasive Industrial Supplies
A Division of Goodson Manufacturing



A TYROLIT Company

10
9
8
7
6
5
4
3
2
1

GOODSON

Tools and Supplies for Engine Builders

156 Galewski Drive
Winona, MN 55987

Easy Toll-Free Ordering by Phone
1-800-533-8010

Toll-Free Fax 24-Hours a Day
1-888-466-3909

Order Online!
www.goodson.com

Use this ruler to measure the approximate size of your parts.



fijn techniek fijnart b.v.
Machines voor motoren revisie,
honen en ultrasoonreinigen

Service makes the difference!

Blaaksedijk 30 | 4793 RN Fijnaart | Nederland
tel. +31 (0)168 46 44 61 info@ftf.nl www.ftfmachines.com

Meet the Goodson Employee Owners

We're here to serve you!



© 2025 Goodson Tools & Supplies for Engine Builders